| Applic | ant/Grantee  | Murata Manufacturing Co   | o., Ltd.  |   |              |
|--------|--|---|---|---|--------------|
| FCC II |  | VPYLB1PJ  | IC:   | 772C-LB1PJ  |              |
|        |  | Section 15.212 Modular T  | ransmitters / Sectio  | n 3.2 of RSS-Gen  | 1            |
| ]      | Request for Mo   | odular Approval   |   | ~   | Comply (Y/N) |
|        |  | Requirements  |   | Device Conditions   |              |
|        | The redice also  | Single Modula<br>ments must have the radio  | r Approval Require  |   |              |
| 1      | frequency cire<br>Physical/discr<br>may be locate  | cuitry must have the radio<br>cuitry must be shielded.<br>rete and tuning capacitors<br>ed external to the shield, but<br>he module assembly.   | Shield Can is emp<br>structure, please s<br>Photo, the emission | The module has its own RF shielding."<br>Shield Can is employed on the board<br>structure, please see exhibition External<br>Photo, the emission measurement was<br>conducted without further shielding<br>added. |              |
| 2      | modulation/d<br>provided) to e<br>comply with t<br>applicable RS   | shall have buffered<br>ata input(s) (if such inputs a<br>ensure that the module will<br>the requirements set out in t<br>SS standard under condition<br>data rates or over-modulation   | re buffered." The EU<br>inputs, it is integr<br>he              | nd data input(s) are<br>UT has buffered data<br>ated on chip QCA9377.   | Y            |
| 3      | supply regula<br>ensure that th<br>the requirement<br>standard rega<br>power supply<br>device which<br>Requirements<br>standard rega<br>design of the  | shall have its own power<br>ation on the module. This is<br>be module will comply with<br>ents set out in the applicable<br>rdless of the design of the<br>ring circuitry in the host<br>houses the module.<br>s set out in the applicable<br>rdless of the<br>power supplying circuitry in<br>ce which houses the module | regulation.   | -   | Y            |
| 4      | provisions for<br>and antennas<br>Equipment ce<br>contain a deta   | shall comply with the<br>r external power amplifiers<br>detailed in this standard. The<br>ertification submission shall<br>ailed description of the<br>of all antennas that will be<br>module.  | to the module via an ANT pin by soldering.                      |   | Y            |
| 5      | The module shall be tested for compliance<br>with the applicable standard in a stand-<br>alone configuration, i.e. the module must<br>not be inside another device during testing. The modular transmitter was tested in a<br>stand-alone configuration via a SDIO or<br>UART Interface. |   |   |   | Y            |
| 6      |  | shall comply with the<br>upment labelling   | The device is too<br>information requi<br>user manual and p     | red will be put on the  | Y            |

| 7  | The modular transmitter complies with all<br>specific rules or operating requirements<br>that ordinarily apply to a complete<br>transmitter and the manufacturer will<br>provide adequate instructions along with<br>the module to explain any such<br>requirements. A copy of these instructions<br>is included in this application for<br>equipment authorization: | Instructions in User Manual                                   | Y |
|----|--|---|---|
| 8a | Address compliance with the<br>Commission's RF exposure limits in<br>Sections 1.1310 and 2.1091.   | Please refer the Maximum Permissible<br>Exposure Information. | Y |
| 8b | The module shall comply with applicable RSS-102 exposure requirements, which are based on the intended use/configurations.   | Please refer the Maximum Permissible<br>Exposure Information. | Y |
| 9  | Is the modular device for an Industry<br>Canada licensed exempt service?   |   | Y |

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

5 Watanah

Name: Takahiro Watanabe

Title: Senior Manager

Product Development Sec. 1 IoT Module Products Dept.

Communication Modules Division

Communication & Sensor Business Unit

Company: Murata Manufacturing Co., Ltd.

Date: 2018-01-29