



Test report No: 2260325R-RF-US-P20V01

# **SAR Exemption Evaluation Report**

Product Name	WLAN+Bluetooth Module
TradeMark	Murata
Model and /or type reference	LBEE5HY2DU
FCC ID	VPYLB2DU
Applicant's name / address	Murata Manufacturing Co., Ltd.
	10-1, Higashikotari 1-chome, Nagaokakyo-shi, Kyoto 617-8555, Japan
Test method requested, standard	FCC Part1.1307
	KDB 447498 D04V01
Verdict Summary	IN COMPLIANCE
Documented By (name / position & signature)	Tim Cao/ Project Engineer
Approved by (name / position & signature)	Jack Zhang/ Manager  Zack Zhang
Date of issue	2022-07-31
Report Version	V1.0
Report template No	Template_FCC MPE-RF-V1.0

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098



# **INDEX**

		page
Com	npetences and Guarantees	3
Gen	eral conditions	3
Envi	ronmental conditions	3
Poss	sible test case verdicts	4
Abbr	reviations	4
Docu	ument History	5
Rem	narks and Comments	5
1.	RF Exposure Evaluation	6
1.1.	Limits	6
1.2.	Test Procedure	7
13	Test Result of RF Exposure Evaluation	7

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098



# **COMPETENCES AND GUARANTEES**

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

<u>IMPORTANT:</u> No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

# **GENERAL CONDITIONS**

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Jun. 20, 2022
Date (start test)	Jun. 23, 2022
Date (finish test)	Jul. 07, 2022

- 1. This report is only referred to the item that has undergone the test.
- 2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
- 3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
- 4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

# **ENVIRONMENTAL CONDITIONS**

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15°C - 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098



## POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

## **ABBREVIATIONS**

For the purposes of the present document, the following abbreviations apply:

EUT : Equipment Under Test

QP : Quasi-Peak CAV : CISPR Average

AV : Average

CDN : Coupling Decoupling NetworkSAC : Semi-Anechoic ChamberOATS : Open Area Test Site

BW: Bandwidth

AM : Amplitude Modulation
PM : Pulse Modulation

HCP : Horizontal Coupling PlaneVCP : Vertical Coupling Plane

UN: Nominal voltage

Tx : Transmitter
Rx : Receiver
N/A : Not Applicable
N/M : Not Measured

Report no.: 2260325R-RF-US-P20V01 Page 4 / 8

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098



## **DOCUMENT HISTORY**

Report No.	Version	Description	Issued Date
2260325R-RF-CA-P20V01	V1.0	Initial issue of report.	2022-07-31

## **REMARKS AND COMMENTS**

- 1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
- 2. These test results on a sample of the device are for the purpose of demonstrating Compliance with KDB 447498 and FCC Part 1.1307
- 3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, it is not necessary to account the uncertainty associated with the measurement result.
- 4. The test results presented in this report relate only to the object tested.
- 5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
- 6. This report will not be used for social proof function in China market.
- 7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
  - Chapter 1.1 Antenna information.



# 1. RF Exposure Evaluation

## 1.1. Limits

According to § 1.1307(b)(3)(i)(B)

The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold Pth (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by:

$$P_{th} \; (\text{mW}) = \begin{cases} ERP_{20\;cm} (d/20\;\text{cm})^x & d \leq 20\;\text{cm} \\ \\ ERP_{20\;cm} & 20\;\text{cm} < d \leq 40\;\text{cm} \end{cases}$$

Where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\ cm}\sqrt{f}}\right)$$
 and f is in GHz;

and

$$\mathit{ERP}_{20\;cm}\;(\mathrm{mW}) = \begin{cases} 2040f & 0.3\;\mathrm{GHz} \leq f < 1.5\;\mathrm{GHz} \\ \\ 3060 & 1.5\;\mathrm{GHz} \leq f \leq 6\;\mathrm{GHz} \end{cases}$$

d = the separation distance (cm);

Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption threshold.

Report no.: 2260325R-RF-US-P20V01

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098



## 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°Cand 78% RH.

# 1.3. Test Result of RF Exposure Evaluation

Product	:	WLAN+Bluetooth Module		
Test Item	:	RF Exposure Evaluation		
Test Site	:	AC-6		

## **Antenna information**

Antenna model / type number:	N/A			
Antenna serial number:	N/A			
Antenna Delivery	$\boxtimes$	1TX + 1RX		
		2TX + 2RX		
		Others:		
Antenna technology	$\boxtimes$	SISO		
		MIMO		Basic
				CDD
				Sectorized
				Beam-forming
Antenna Type:	$\boxtimes$	External		Dipole
				Sectorized
				PCB
		Internal		PIFA
				PCB
				Metal Antenna
Antenna Gain:	2.4GI	Hz band:0.1 dBi 50	SHz ba	nd:-0.4 dBi

Note: The antenna information for the EUT in clause 1.3 are provided and confirmed by the client.

Report no.: 2260325R-RF-US-P20V01 Page 7 / 8

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098



The tune-up power is 0.5 dB, so the maximum conducted power we used to calculate RF exposure is 26.33 dBm for Wi-Fi 2.4GHz,16.5dBm for Wi-Fi 5GHz and 9.75 dBm for Bluetooth.

Rond Exposure		Pmax	EIRP	ERP	Distance		Pth	
Band	Condition	(dBm)	(mw)	(mw)	(mm)	f(GHz)	(mW)	SAR Test
2.4G WLAN	body	26.33	439.5	267.9	56	2.462	271.35	Not required
5G WLAN	body	16.5	44.66	27.33	21	5.220	29.04	Not required
Bluetooth	body	9.75	9.44	5.75	8	2.441	6.62	Not required

Conclusion.	SAR was not required at Somm from the body.
_	The End