



RADIO TEST REPORT

Test Report No. : 10059672H-A-R1

Applicant : Murata Manufacturing Co., Ltd.
Type of Equipment : Communication Module
Model No. : LBWA1ZZYM6
FCC ID : VPYLBYM
Test regulation : FCC Part 15 Subpart C: 2013
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This report is a revised version of 10059672H-A. 10059672H-A is replaced with this report.

Date of test: August 28 to September 13, 2013

Representative test engineer:

Keisuke Kawamura
Engineer of WiSE Japan,
UL Verification Service

Approved by:

Masanori Nishiyama
Manager of WiSE Japan,
UL Verification Service



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
<http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429

CONTENTS	PAGE
SECTION 1: Customer information	4
SECTION 2: Equipment under test (E.U.T.)	4
SECTION 3: Test specification, procedures & results	5
SECTION 4: Operation of E.U.T. during testing	8
SECTION 5: Conducted Emission	10
SECTION 6: Radiated Spurious Emission	11
SECTION 7: Antenna Terminal Conducted Tests	12
APPENDIX 1: Data of EMI test	13
Conducted Emission	13
6dB Bandwidth	14
Maximum Peak Output Power	17
Average Output Power	20
Radiated Spurious Emission	21
Conducted Spurious Emission	30
Power Density	31
99% Occupied Bandwidth	34
APPENDIX 2: Test instruments	36
APPENDIX 3: Photographs of test setup	38
Conducted Emission	38
Radiated Spurious Emission	39
Worst Case Position (Horizontal: Y-axis/ Vertical:Y-axis).....	40

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 1: Customer information

Company Name : Murata Manufacturing Company, Ltd.
Address : 10-1, Higashikotari 1-chome, Nagaokakyo-shi, Kyoto 617-8555 Japan
Telephone Number : +81-75-955-6375
Facsimile Number : +81-75-955-6634
Contact Person : Takaharu Kawakatsu

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Communication Module
Model No. : LBWA1ZZYM6
Serial No. : Refer to Section 4, Clause 4.2
Rating : DC 3.3V, 2.85V
Receipt Date of Sample : August 26, 2013
Country of Mass-production : China, Japan
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No Modification by the test lab

2.2 Product Description

General Specification

The EUT is WLAN Module which is installed in Digital camera.

Specification of WLAN (IEEE802.11b/g/n)

Type of radio	Wireless LAN (IEEE802.11b/g)	Wireless LAN (IEEE802.11n) 2.4G Band SISO (20M Band)
Equipment Type	Transceiver	
Frequency of Operation	2412MHz - 2462MHz	
Bandwidth & Channel spacing	Bandwidth : 20MHz Ch spacing : 5MHz	
Type of Modulation	11b: DSSS 11g: OFDM	OFDM
Antenna Type / Antenna Gain	Monopole (pattern) Antenna: -0.3dBi (Peak)	
Power Supply (inner)	PAVDD: DC 2.85V VBAT: DC 3.3V	
Operating temperature range	-20 to +80 deg. C.	

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C: 2013, final revised on September 30, 2013 and effective October 30, 2013

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.247 Operation within the bands 902-928MHz,
2400-2483.5MHz, and 5725-5850MHz

*The revision on September 30, 2013 does not affect the test specification applied to the EUT.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.4:2003 7. AC powerline Conducted Emission measurements IC: RSS-Gen 7.2.4	FCC: Section 15.207 IC: RSS-Gen 7.2.4	QP 20.6dB, 0.15145MHz, L AV 37.3dB, 1.91724MHz, N	Complied	-
6dB Bandwidth	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" IC: RSS-Gen 4.6.2	FCC: Section 15.247(a)(2) IC: RSS-210 A8.2(a)	See data.	Complied	Conducted
Maximum Peak Output Power	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" IC: RSS-Gen 4.8	FCC: Section 15.247(b)(3) IC: RSS-210 A8.4(4)		Complied	Conducted
Power Density	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" IC: -	FCC: Section 15.247 (e) IC: RSS-210 A8.2(b)		Complied	Conducted
Spurious Emission Restricted Band Edges	FCC: "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247(issued on April 9, 2013)" IC: RSS-Gen 4.9	FCC: Section15.247(d) IC: RSS-210 A8.5 RSS-Gen 7.2.3	1.6dB 2390.000MHz, AV, Hori.	Complied	Conducted/ Radiated

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

* In case any questions arise about test procedure, ANSI C63.4: 2003 is also referred.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

FCC 15.31 (e)

The EUT has the power supply regulator. However one of the input voltages to RF part doesn't go through the regulator. The stable voltage will be supplied by the end product, which will be required to have a power supply regulator. Therefore, the EUT complies with the requirement.

FCC Part 15.203/212 Antenna requirement

It is impossible for end users to replace the antenna, because it is soldered on the circuit board. Therefore, the equipment complies with the antenna requirement of Section 15.203/212.

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	IC: RSS-Gen 4.6.1	IC: RSS-Gen 4.6.1	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room (semi-anechoic chamber)	Conducted emission (+dB)
	150kHz-30MHz
No.1	3.5dB
No.2	3.6dB
No.3	3.6dB
No.4	3.6dB

Test room (semi-anechoic chamber)	Radiated emission						
	(3m*)(+dB)				(1m*)(+dB)		(0.5m*)(+dB)
	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	1GHz -10GHz	10GHz -18GHz	18GHz -26.5GHz	26.5GHz -40GHz
No.1	4.3dB	5.0dB	5.1dB	4.9dB	5.8dB	4.4dB	4.3dB
No.2	4.3dB	5.2dB	5.1dB	5.0dB	5.7dB	4.3dB	4.2dB
No.3	4.6dB	5.0dB	5.1dB	5.0dB	5.7dB	4.5dB	4.2dB
No.4	4.8dB	5.2dB	5.0dB	5.0dB	5.7dB	5.2dB	4.2dB

*3m/1m/0.5m = Measurement distance

Power meter (+dB)	
Below 1GHz	Above 1GHz
0.7dB	1.5dB

Antenna terminal conducted emission and Power density (+dB)			Antenna terminal conducted emission (+dB)		Channel power (+dB)
Below 1GHz	1GHz-3GHz	3GHz-18GHz	18GHz-26.5GHz	26.5GHz-40GHz	
1.5dB	1.7dB	2.8dB	2.8dB	2.9dB	2.6dB

Conducted Emission test

The data listed in this test report has enough margin, more than the site margin.

Radiated emission test

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Head Office EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	655103	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	-	8.0 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	-	6.2 x 4.7 x 3.0m	2.4 x 3.4m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Data of EMI, Test instruments, and Test set up

Refer to APPENDIX.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Mode(s)

Test operating mode was determined as follows according to “Section 1 of 6 802.11 a/b/g/n testing- Managing Complex Regulatory Approvals - ” of TCB Council Workshop October 2009.

Mode	Remarks*
IEEE 802.11b (11b)	11Mbps, PN9
IEEE 802.11g (11g)	9Mbps, PN9
IEEE 802.11n SISO 20MHz BW (11n-20)	MCS 0, PN9
*The worst condition was determined based on the test result of Maximum Peak Output Power (Mid Channel)	
*Power of the EUT was set by the software as follows; Power settings: 10 Software: mfgtest 5.90.153 *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.	

*Details of Operating mode for WLAN

Test Item	Operating Mode	Tested frequency
Conducted Emission Spurious Emission (Conducted)	11g Tx *1)	2462MHz *1)
6dB Bandwidth 99% Occupied Bandwidth Maximum Peak Output Power Power Density	11b Tx 11g Tx 11n-20 Tx	2412MHz 2437MHz 2462MHz
Spurious Emission (Radiated)	11b Tx 11g Tx	2412MHz 2437MHz 2462MHz
	11n-20 Tx *2)	2412MHz 2462MHz
*1) The test was performed on the representative mode/frequency that had the highest power at antenna terminal test. *2) Only band edge was tested on this mode according to “Section 1 of 6 802.11 a/b/g/n testing- Managing Complex Regulatory Approvals - ” of TCB Council Workshop October 2009, as the 11g Tx mode had the higher power at antenna terminal test.		

UL Japan, Inc.


Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

4.2 Configuration and peripherals



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

Description of EUT

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Communication Module	LBWA1ZZYM6	001 for AT 002 for RE	MURATA	EUT
B	Jig	-	-	-	-

AT: Antenna Terminal Conducted Tests

RE: Spurious Emission (Radiated)

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	Flat Cable	0.02	Unshielded	Unshielded	-
2	DC Cable	2.0	Unshielded	Unshielded	-
3	DC Cable	2.0	Unshielded	Unshielded	-
4	DC Cable	2.0	Unshielded	Unshielded	-

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Conducted Emission

Test Procedure and conditions

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane.

The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

For the tests on EUT with other peripherals (as a whole system)

I/O cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. All unused 50ohm connectors of the LISN(AMN) were resistivity terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Detector	: QP and CISPR AV
Measurement range	: 0.15-30MHz
Test data	: APPENDIX
Test result	: Pass

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 6: Radiated Spurious Emission

Test Procedure

It was measured based on "11.0 Emissions in non-restricted frequency bands" of "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 (Issued on April 9, 2013)".

EUT was placed on a urethane platform of nominal size, 0.5m by 1.0m, raised 0.8m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

The height of the measuring antenna varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30MHz to 300MHz	300MHz to 1GHz	Above 1GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20dBc was applied to the frequency over the limit of FCC 15.209 / Table 5 of RSS-Gen 7.2.5(IC) and outside the restricted band of FCC15.205 / Table 3 of RSS-Gen 7.2.2 (IC).

Frequency	Below 1GHz	Above 1GHz		20dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV *1)	PK
IF Bandwidth	BW 120kHz(T/R)	RBW: 1MHz VBW: 3MHz	Average Power Method: <u>WLAN: 12.2.5.1</u> RBW: 1MHz VBW: 3MHz Detector: Power Averaging (RMS) Trace: Free Run	RBW: 100kHz VBW: 300kHz (S/A)
Test Distance	3m	3m (below 10GHz), 1m *2) (above 10GHz)		3m (below 10GHz), 1m *2) (above 10GHz)

*1) Average Power Measurement was performed based on 6.0 & 12.2.5 of "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 (Issued on April 9, 2013)"

*2) Distance Factor: $20 \times \log(3.0\text{m}/1.0\text{m}) = 9.5\text{dB}$

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 30M-26.5GHz
Test data : APPENDIX
Test result : Pass

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 7: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
6dB Bandwidth	20MHz	100kHz	300kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth	Enough width to display 20dB Bandwidth	1 to 3% of Span	Three times of RBW	Auto	Peak	Max Hold*1)	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak Average *2)	-	Power Meter (Sensor: 50MHz BW)
Peak Power Density	1.5 times the 6dB Bandwidth	3kHz	10kHz	Auto	Peak	Max Hold	Spectrum Analyzer *3)
Conducted Spurious Emission *4)	9kHz to 150kHz	200Hz	620Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150kHz to 30MHz	9.1kHz	27kHz				

*1) The measurement was performed with Max Hold since the duty cycle was not 100%.
*2) Reference data
*3) Section 10.2 Method PKPSD (peak PSD) of "Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 (Issued on April 9, 2013)".
*4) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents. Then, wide-band noise near the limit was checked separately, however the noise was low enough as shown in the chart. (9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=9.1kHz).

The test results and limit are rounded off to two decimals place, so some differences might be observed.

Test data : **APPENDIX**
Test result : **Pass**

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

APPENDIX 1: Data of EMI test

Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Head Office EMC Lab. No.2 Semi Anechoic Chamber

Company : Murata

Report No. : 10059672H


Model : 10059672H

Temp./num1. : 23deg. C / 00% RH

Engineer : Keisuke Kawamura

Mode / Remarks : Tx 11g 9Mbps 2412MHz

LIMIT : FCC15.207 QP
FCC15.207 AV



Frequency [MHz]	Reading Level		Corr. Factor	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.15145	31.1	5.0	13.2	44.3	18.2	65.9	55.9	21.6	37.7	N	
0.16885	27.7	2.9	13.2	40.9	16.1	65.0	55.0	24.1	38.9	N	
0.20075	20.3	-0.4	13.2	33.5	12.8	63.6	53.6	30.1	40.8	N	
0.25005	11.1	-3.1	13.2	24.3	10.1	61.8	51.8	37.5	41.7	N	
0.92430	-0.7	-5.0	13.4	12.7	8.4	56.0	46.0	43.3	37.6	N	
1.91724	-0.5	-4.8	13.5	13.0	8.7	56.0	46.0	43.0	37.3	N	
0.15145	32.1	5.2	13.2	45.3	18.4	65.9	55.9	20.6	37.5	L	
0.16885	28.9	3.4	13.2	42.1	16.6	65.0	55.0	23.0	38.4	L	
0.19930	21.8	0.0	13.2	35.0	13.2	63.6	53.6	28.6	40.4	L	
0.25005	12.2	-0.2	13.2	25.4	13.0	61.8	51.8	36.4	38.8	L	
0.92140	-0.6	-4.9	13.4	12.8	8.5	56.0	46.0	43.2	37.5	L	
1.93235	-0.5	-4.9	13.5	13.0	8.6	56.0	46.0	43.0	37.4	L	

CHART: WITH FACTOR, Peak hold data. CALCULATION: RESULT=READING+C. F (LISN LOSS+ATT LOSS +CABLE LOSS)
Except for the above table : adequate margin data below the limits.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

6dB Bandwidth

Test place Head Office EMC Lab. No.11 Measurement Room
Report No. 10059672H
Date 08/28/2013
Temperature/ Humidity 23 deg. C / 45% RH
Engineer Katsunori Okai
Mode Tx

11b

Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
2412	8.045	>500
2437	7.674	>500
2462	7.673	>500

11g

Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
2412	15.096	>500
2437	15.140	>500
2462	15.074	>500

11n-20

Frequency [MHz]	6dB Bandwidth [MHz]	Limit [kHz]
2412	15.138	>500
2437	15.135	>500
2462	15.130	>500

UL Japan, Inc.


Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


6dB Bandwidth




6dB Bandwidth

11n-20


2412MHz



2437MHz



2462MHz



UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Peak Output Power

Test place	Head Office EMC Lab. No.11 Measurement Room
Report No.	10059672H
Date	08/28/2013
Temperature/ Humidity	23 deg. C / 45% RH
Engineer	Katsunori Okai
Mode	11b Tx

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	2.25	0.50	10.08	12.83	19.19	30.00	1000	17.17
2437	2.30	0.50	10.08	12.88	19.41	30.00	1000	17.12
2462	2.17	0.50	10.08	12.75	18.84	30.00	1000	17.25

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

2437MHz

Rate [Mbps]	Reading [dBm]	Remark
1	2.11	
2	2.22	
5.5	2.19	
11	2.30	*

*: Worst Rate

All comparizon were carried out on same frequency and measurement factors.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Peak Output Power

Test place	Head Office EMC Lab. No.11 Measurement Room
Report No.	10059672H
Date	08/28/2013
Temperature/ Humidity	23 deg. C / 45% RH
Engineer	Katsunori Okai
Mode	11g Tx

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	10.11	0.50	10.08	20.69	117.22	30.00	1000	9.31
2437	9.62	0.50	10.08	20.20	104.71	30.00	1000	9.80
2462	8.93	0.50	10.08	19.51	89.33	30.00	1000	10.49

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

2437MHz

Rate [Mbps]	Reading [dBm]	Remark
6	9.54	
9	9.62	*
12	8.80	
18	9.22	
24	9.07	
36	9.59	
48	9.27	
54	8.92	

*: Worst Rate

All comparison were carried out on same frequency and measurement factors.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Peak Output Power

Test place	Head Office EMC Lab. No.11 Measurement Room
Report No.	10059672H
Date	08/28/2013
Temperature/ Humidity	23 deg. C / 45% RH
Engineer	Katsunori Okai
Mode	11n-20 Tx

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result		Limit		Margin [dB]
				[dBm]	[mW]	[dBm]	[mW]	
2412	10.03	0.50	10.08	20.61	115.08	30.00	1000	9.39
2437	9.54	0.50	10.08	20.12	102.80	30.00	1000	9.88
2462	8.91	0.50	10.08	19.49	88.92	30.00	1000	10.51

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator

2437MHz

Rate [MCS]	Reading [dBm]	Remark
0	9.54	*
1	9.31	
2	9.23	
3	9.30	
4	9.23	
5	8.96	
6	8.98	
7	8.97	

*: Worst Rate

All comparison were carried out on same frequency and measurement factors.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Average Output Power

Test place : Head Office EMC Lab. No.11 Measurement Room
 Report No. : 10059672H
 Date : 08/28/2013
 Temperature/ Humidity : 23 deg. C / 45% RH
 Engineer : Katsunori Okai
 Mode : 11b/g/n-20 Tx

[AV]

11b **5.5Mbps**

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result	
				[dBm]	[mW]
2412	-0.93	0.50	10.08	9.65	9.23
2437	-0.98	0.50	10.08	9.60	9.12
2462	-1.05	0.50	10.08	9.53	8.97

11g **6Mbps**

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result	
				[dBm]	[mW]
2412	-1.49	0.50	10.08	9.09	8.11
2437	-1.59	0.50	10.08	8.99	7.93
2462	-1.72	0.50	10.08	8.86	7.69

11n-20 **MCS0**

Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result	
				[dBm]	[mW]
2412	-1.68	0.50	10.08	8.90	7.76
2437	-1.75	0.50	10.08	8.83	7.64
2462	-1.77	0.50	10.08	8.81	7.60

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Atte

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Head Office EMC Lab. No.3 and 2 Semi Anechoic Chamber
Report No. 10059672H
Date 09/12/2013 09/12/2013
Temperature/ Humidity 23 deg. C / 61% RH 25deg. C / 52% RH
Engineer Keisuke Kawamura Satofumi Matsuyama
(1-10GHz) (10-26.5GHz)
Mode 11b Tx 2412MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2390.000	PK	55.2	28.2	2.9	32.4	-	53.9	73.9	20.0	
Hori	2491.999	PK	48.9	28.4	2.9	32.3	-	47.9	73.9	26.0	
Hori	4824.000	PK	42.4	30.5	4.9	31.4	-	46.4	73.9	27.5	
Hori	2390.000	AV	42.9	28.2	2.9	32.4	-	41.6	53.9	12.3	
Hori	2491.999	AV	39.1	28.4	2.9	32.3	-	38.1	53.9	15.8	
Hori	4824.000	AV	33.2	30.5	4.9	31.4	-	37.2	53.9	16.7	
Vert	2390.000	PK	49.2	28.2	2.9	32.4	-	47.9	73.9	26.0	
Vert	2491.999	PK	46.6	28.4	2.9	32.3	-	45.6	73.9	28.3	
Vert	4824.000	PK	44.2	30.5	4.9	31.4	-	48.2	73.9	25.7	
Vert	2390.000	AV	40.2	28.2	2.9	32.4	-	38.9	53.9	15.0	
Vert	2491.999	AV	37.3	28.4	2.9	32.3	-	36.3	53.9	17.6	
Vert	4824.000	AV	34.1	30.5	4.9	31.4	-	38.1	53.9	15.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2412.000	PK	101.1	28.2	2.9	32.4	99.8	-	-	Carrier
Hori	2400.000	PK	65.4	28.2	2.9	32.4	64.1	79.8	15.7	
Vert	2412.000	PK	97.7	28.2	2.9	32.4	96.4	-	-	Carrier
Vert	2400.000	PK	47.9	28.2	2.9	32.4	46.6	76.4	29.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Head Office EMC Lab. No.3 and 2 Semi Anechoic Chamber
Report No. 10059672H
Date 09/12/2013 09/12/2013
Temperature/ Humidity 23 deg. C / 61% RH 25deg. C / 52% RH
Engineer Keisuke Kawamura Satofumi Matsuyama
(1-10GHz) (10-26.5GHz)
Mode 11b Tx 2462MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2240.048	PK	50.6	27.7	2.8	32.4	-	48.7	73.9	25.2	
Hori	2483.500	PK	48.3	28.4	2.9	32.3	-	47.3	73.9	26.6	
Hori	4924.000	PK	42.9	30.7	4.9	31.4	-	47.1	73.9	26.8	
Hori	2240.048	AV	41.3	27.7	2.8	32.4	-	39.4	53.9	14.5	
Hori	2483.500	AV	39.0	28.4	2.9	32.3	-	38.0	53.9	15.9	
Hori	4924.000	AV	33.7	30.7	4.9	31.4	-	37.9	53.9	16.0	
Vert	2240.048	PK	51.0	27.7	2.8	32.4	-	49.1	73.9	24.8	
Vert	2483.500	PK	47.5	28.4	2.9	32.3	-	46.5	73.9	27.4	
Vert	4924.000	PK	43.9	30.7	4.9	31.4	-	48.1	73.9	25.8	
Vert	2240.048	AV	42.3	27.7	2.8	32.4	-	40.4	53.9	13.5	
Vert	2483.500	AV	38.1	28.4	2.9	32.3	-	37.1	53.9	16.8	
Vert	4924.000	AV	34.7	30.7	4.9	31.4	-	38.9	53.9	15.0	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Head Office EMC Lab. No.3 and 2 Semi Anechoic Chamber
Report No. 10059672H
Date 09/04/2013 09/12/2013 09/13/2013
Temperature/ Humidity 22 deg.C./ 61% 25deg. C / 52% RH 25deg. C / 50% RH
Engineer Keisuke Kawamura Satofumi Matsuyama Keisuke Kawamura
(1-10GHz) (10-26.5GHz) (30-1000MHz)
Mode 11g Tx 2412MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	45.300	QP	22.9	12.3	6.9	28.6	-	13.5	40.0	26.5	
Hori	76.017	QP	22.6	6.5	7.3	28.5	-	7.9	40.0	32.1	
Hori	161.849	QP	22.0	15.4	7.9	28.1	-	17.2	43.5	26.3	
Hori	232.949	QP	21.6	17.0	8.4	27.6	-	19.4	46.0	26.6	
Hori	272.099	QP	21.8	18.4	8.6	27.6	-	21.2	46.0	24.8	
Hori	856.504	QP	21.7	22.1	11.1	28.0	-	26.9	46.0	19.1	
Hori	2245.663	PK	52.6	27.8	2.8	32.4	-	50.8	73.9	23.1	
Hori	2390.000	PK	66.4	28.2	2.9	32.4	-	65.1	73.9	8.8	
Hori	4824.000	PK	42.7	30.5	4.9	31.4	-	46.7	73.9	27.2	
Hori	2245.663	AV	44.0	27.8	2.8	32.4	-	42.2	53.9	11.7	
Hori	2390.000	AV	52.8	28.2	2.9	32.4	-	51.5	53.9	2.4	
Hori	4824.000	AV	33.7	30.5	4.9	31.4	-	37.7	53.9	16.2	
Vert	44.796	QP	25.1	12.5	6.9	28.6	-	15.9	40.0	24.1	
Vert	78.600	QP	31.4	6.4	7.3	28.5	-	16.6	40.0	23.4	
Vert	160.499	QP	22.4	15.3	7.9	28.1	-	17.5	43.5	26.0	
Vert	233.399	QP	21.6	17.0	8.4	27.6	-	19.4	46.0	26.6	
Vert	271.649	QP	21.4	18.4	8.6	27.6	-	20.8	46.0	25.2	
Vert	855.338	QP	21.6	22.1	11.1	28.0	-	26.8	46.0	19.2	
Vert	2251.829	PK	52.9	27.8	2.8	32.4	-	51.1	73.9	22.8	
Vert	2390.000	PK	65.3	28.2	2.9	32.4	-	64.0	73.9	9.9	
Vert	4824.000	PK	42.0	30.5	4.9	31.4	-	46.0	73.9	27.9	
Vert	2251.829	AV	44.4	27.8	2.8	32.4	-	42.6	53.9	11.3	
Vert	2390.000	AV	52.3	28.2	2.9	32.4	-	51.0	53.9	2.9	
Vert	4824.000	AV	33.7	30.5	4.9	31.4	-	37.7	53.9	16.2	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2412.000	PK	96.4	28.2	2.9	32.4	95.1	-	-	Carrier
Hori	2400.000	PK	63.6	28.2	2.9	32.4	62.3	75.1	12.8	
Vert	2412.000	PK	95.2	28.2	2.9	32.4	93.9	-	-	Carrier
Vert	2400.000	PK	62.8	28.2	2.9	32.4	61.5	73.9	12.4	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Head Office EMC Lab. No.2 Semi Anechoic Chamber
Report No. 10059672H
Date 09/12/2013
Temperature/ Humidity 25deg. C / 52% RH
Engineer Satofumi Matsuyama
(1-26.5GHz)
Mode 11g Tx 2437MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2240.026	PK	53.2	26.9	2.9	35.7	-	47.3	73.9	26.6	
Hori	2240.026	AV	43.7	26.9	2.9	35.7	-	37.8	53.9	16.1	
Vert	2240.009	PK	53.5	26.9	2.9	35.7	-	47.6	73.9	26.3	
Vert	2240.009	AV	43.4	26.9	2.9	35.7	-	37.5	53.9	16.4	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz $20\log(3.0m/1.0m) = 9.5dB$

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place Head Office EMC Lab. No.2 Semi Anechoic Chamber
Report No. 10059672H
Date 09/12/2013
Temperature/ Humidity 25deg. C / 52% RH
Engineer Satofumi Matsuyama
(1-26.5GHz)
Mode 11g Tx 2462MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2239.994	PK	52.5	26.9	2.9	35.7	-	46.6	73.9	27.3	
Hori	2483.500	PK	65.3	26.7	3.0	35.7	-	59.3	73.9	14.6	
Hori	3693.033	PK	48.5	28.5	3.8	34.7	-	46.1	73.9	27.8	
Hori	2239.994	AV	43.1	26.9	2.9	35.7	-	37.2	53.9	16.7	
Hori	2483.500	AV	52.0	26.7	3.0	35.7	-	46.0	53.9	7.9	
Hori	3693.033	AV	42.5	28.5	3.8	34.7	-	40.1	53.9	13.8	
Vert	2240.005	PK	52.7	26.9	2.9	35.7	-	46.8	73.9	27.1	
Vert	2483.500	PK	62.8	26.7	3.0	35.7	-	56.8	73.9	17.1	
Vert	3693.033	PK	48.1	28.5	3.8	34.7	-	45.7	73.9	28.2	
Vert	2240.005	AV	44.1	26.9	2.9	35.7	-	38.2	53.9	15.7	
Vert	2483.500	AV	49.4	26.7	3.0	35.7	-	43.4	53.9	10.5	
Vert	3693.033	AV	42.0	28.5	3.8	34.7	-	39.6	53.9	14.3	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Test place : Head Office EMC Lab. No.2 Semi Anechoic Chamber
 Report No. : 10059672H
 Date : 09/12/2013
 Temperature/ Humidity : 25deg. C / 52% RH
 Engineer : Satofumi Matsuyama
 (1-10GHz)
 Mode : 11n20 Tx 2462MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2483.500	PK	64.7	26.7	3.0	35.7	-	58.7	73.9	15.2	
Hori	2483.500	AV	50.5	26.7	3.0	35.7	-	44.5	53.9	9.4	
Vert	2483.500	PK	62.5	26.7	3.0	35.7	-	56.5	73.9	17.4	
Vert	2483.500	AV	48.4	26.7	3.0	35.7	-	42.4	53.9	11.5	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter-Distance factor(above 10GHz)) - Gain(Amplifier)

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20dB).

Distance factor: 10GHz-26.5GHz 20log(3.0m/1.0m)= 9.5dB

UL Japan, Inc.



Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999


Facsimile : +81 596 24 8124

Duty rate confirmation



Conducted Spurious Emission

11g Tx 2412MHz



Frequency [kHz]	Reading [dBm]	Cable Loss [dB]	Attenuator [dB]	Antenna Gain [dBi]	EIRP [dBm]	Distance [m]	Ground bounce [dB]	E (field strength) [dBuV/m]	Limit [dBuV/m]
67.75	-88.6	0.50	9.8	-0.3	-78.6	300.0	6.0	-17.3	31.0
225	-87.5	0.51	9.8	-0.3	-77.5	300.0	6.0	-16.2	20.6

E=EIRP-20log(D)+Ground bounce +104.8[dBuV/m]

EIRP=Reading+Cable Loss+Attenuator+Antenna Gain

UL Japan, Inc.


Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


Power Density




Power Density

11n-20


2412MHz




2437MHz



2462MHz




99% Occupied Bandwidth




99% Occupied Bandwidth

11n-20


2412MHz



2437MHz



2462MHz



APPENDIX 2: Test instruments

EMI test equipment (1/2)

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAEC-03	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	RE	2013/02/28 * 12
MOS-13	Thermo-Hygrometer	Custom	CTH-180	-	RE	2013/02/26 * 12
MJM-16	Measure	KOMELON	KMC-36	-	RE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE	-
MSA-03	Spectrum Analyzer	Agilent	E4448A	MY44020357	RE	2012/11/20 * 12
MHA-20	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	258	RE	2013/05/17 * 12
MCC-133	Microwave Cable	HUBER+SUHNER	SUCOFLEX104	336164/4(1m) / 340640(5m)	RE	2012/09/05 * 12
MPA-11	MicroWave System Amplifier	Agilent	83017A	MY39500779	RE	2013/03/12 * 12
MHF-25	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	RE	2013/09/01 * 12
MAEC-02	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-06902	RE/CE	2013/06/30 * 12
MOS-22	Thermo-Hygrometer	Custom	CTH-201	0003	RE/CE	2013/02/26 * 12
MJM-14	Measure	KOMELON	KMC-36	-	RE/CE	-
MSA-04	Spectrum Analyzer	Agilent	E4448A	US44300523	RE/CE	2013/04/03 * 12
MHA-06	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	254	RE	2013/02/15 * 12
MPA-10	Pre Amplifier	Agilent	8449B	3008A02142	RE	2013/01/10 * 12
MHA-02	Horn Antenna 18-26.5GHz	EMCO	3160-09	1265	RE	2013/02/15 * 12
MCC-132	Microwave Cable	HUBER+SUHNER	SUCOFLEX104	336161/4(1m) / 340639(5m)	RE	2012/09/05 * 12
MHF-25	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	RE	2013/09/01 * 12
MTR-03	Test Receiver	Rohde & Schwarz	ESCI	100300	RE/CE	2013/06/11 * 12
MBA-02	Biconical Antenna	Schwarzbeck	BBA9106	VHA9103200 8	RE	2012/10/08 * 12
MLA-02	Logperiodic Antenna	Schwarzbeck	USLP9143	201	RE	2012/10/08 * 12
MCC-12	Coaxial Cable	Fujikura/Agilent	-	-	RE	2013/02/06 * 12
MAT-07	Attenuator(6dB)	Weinschel Corp	2	BK7970	RE	2012/11/06 * 12
MPA-09	Pre Amplifier	Agilent	8447D	2944A10845	RE	2012/09/11 * 12
MLS-06	LISN(AMN)	Schwarzbeck	NSLK8127	8127363	CE(EUT)	2013/01/07 * 12
MTA-31	Terminator	TME	CT-01	-	CE	2013/01/21 * 12
MCC-13	Coaxial Cable	Fujikura	3D-2W(12m)/5D-2W(5m)/5D-2W(0.8m)/5D-2W(1m)	-	CE	2013/02/06 * 12
MAT-65	Attenuator(13dB)	JFW Industries, Inc.	50FP-013H2 N	-	CE	2013/01/09 * 12

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

EMI test equipment (2/2)

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MOS-19	Thermo-Hygrometer	Custom	CTH-201	0001	AT	2012/12/25 * 12
MPM-08	Power Meter	Anritsu	ML2495A	6K00003338	AT	2012/10/08 * 12
MPSE-11	Power sensor	Anritsu	MA2411B	011737	AT	2012/10/08 * 12
MSA-03	Spectrum Analyzer	Agilent	E4448A	MY44020357	AT	2012/11/20 * 12
MCC-137	Microwave cable	HUBER+SUHNER	SUCOFLEX 102	37954/2	AT	2012/10/19 * 12
MCC-64	Coaxial Cable	UL Japan	-	-	AT	2013/03/22 * 12
MAT-23	Attenuator(10dB) 1-18GHz	Orient Microwave	BX10-0476-00	-	AT	2013/03/21 * 12
MAT-10	Attenuator(10dB)	Weinschel Corp	2	BL1173	AT	2012/11/06 * 12

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

**Test Item: CE: Conducted Emission
RE: Radiated Emission
AT: Antenna Terminal Conducted test**

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124