



InterLab®

Final Report on

F-022

SW:v1.01(GSM) / v1.01(Bluetooth)

HW:v2.1(GSM) / v2.1(Bluetooth)

Report Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

Date: April 12, 2011

Test Laboratory:

7 layers AG
Borsigstr. 11
40880 Ratingen
Germany



DGA-PL-192/99-02

Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7 layers AG
Borsigstrasse 11
40880 Ratingen, Germany
Phone: +49 (0) 2102 749 0
Fax: +49 (0) 2102 749 350
www.7Layers.com

Aufsichtsratsvorsitzender•
Chairman of the Supervisory Board:
Markus Becker
Vorstand• Board:
Dr. H.-J. Meckelburg
Wilfried Klassmann

Registergericht• registered in:
Düsseldorf, HRB 44096
UST-IdNr • VAT No.:
DE 203159652
TAX No. 147/5869/0385



Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

1 Administrative Data

1.1 Project Data

Project Responsible: Patrick Lomax
Date Of Test Report: 2011/04/12
Date of first test: 2011/03/16
Date of last test: 2011/03/18

1.2 Applicant Data

Company Name: Fujitsu Limited.
Street: 1-1,Kamikodanaka 4-chome,
Nakahara-ku, Kawasaki,
211-8588, Japan
Contact Person: Mr. Tsuji Masato
Phone: +81-44-874-2447
Fax: +81-44-754-3547
E-Mail: tsuji.masato@jp.fujitsu.com

1.3 Test Laboratory Data

The following list shows all places and laboratories involved for test result generation:

7 layers DE

<i>Company Name :</i>	7 layers AG
<i>Street :</i>	Borsigstrasse 11
<i>City :</i>	40880 Ratingen
<i>Country :</i>	Germany
<i>Contact Person :</i>	Mr. Michael Albert
<i>Phone :</i>	+49 2102 749 201
<i>Fax :</i>	+49 2102 749 444
<i>E Mail :</i>	michael.albert@7Layers.de

Laboratory Details

Lab ID	Identification	Responsible	Accreditation Info
Lab 1	Conducted Emissions	Mr. Robert Machulec Mr. Andreas Petz	DAR-Registration no. DGA-PL-192/99-02
Lab 2	Radiated Emissions	Mr. Robert Machulec Mr. Andreas Petz	DAR-Registration no. DGA-PL-192/99-02

1.4 Signature of the Testing Responsible

Robert Machulec

responsible for tests performed in: Lab 1, Lab 2



Reference: ODE_MJP_FJT_1019_FCCB

acc. Title 47 CFR Chapter I part 15, subpart b

1.5 Signature of the Accreditation Responsible

Accreditation scope responsible person **RETHKA**
responsible for Lab 1, Lab 2

2 Test Object Data

2.1 General OUT Description

The following section lists all OUTs (Object's Under Test) involved during testing.

OUT: F-022

Type / Model / Family:	F-022
	SW:v1.01(GSM) / v1.01(Bluetooth)
	HW:v2.1(GSM) / v2.1(Bluetooth)

Product Category:	Mobile Phone
-------------------	--------------

Manufacturer:	
Company Name:	please see applicant

Contact Person:	please see applicant
-----------------	----------------------

Parameter List:

Parameter name	Value
----------------	-------

Ancillary Equipment: ACDC Adapter

Ancillary Equipment: USB Cable charging

Ancillary Equipment: USB Cable data



2.2 Detailed Description of OUT Samples

Sample : J01

<i>OUT Identifier</i>	F-022		
<i>Sample Description</i>	Standard sample		
<i>Serial No.</i>	354224040002246 (IMEI)		
<i>HW Status</i>	V2.1		
<i>SW Status</i>	V1.01		
<i>Date of Receipt</i>	2011/01/03		
<i>Low Voltage</i>	3.3 V	<i>Low Temp.</i>	-10 °C
<i>High Voltage</i>	4.2 V	<i>High Temp.</i>	55 °C
<i>Nominal Voltage</i>	3.7 V	<i>Normal Temp.</i>	23 °C

Parameter List:

Parameter Description	Value	
Parameter for Scope FCC_v2		
Antenna Gain (Bluetooth Antenna)	2.14	(dBi)
Antenna Gain 1900 Band	-0.85	(dBi)
Antenna Gain 850 Band	-0.85	(dBi)
Frequency_high	2480	(MHz)
Frequency_low	2402	(MHz)
Frequency_mid	2441	(MHz)

Sample : ACDC01

<i>OUT Identifier</i>	ACDC Adapter	
<i>Sample Description</i>	TS04-500680	
<i>Serial No.</i>	0009	

Sample : USBdata

<i>OUT Identifier</i>	USB Cable data
<i>Sample Description</i>	

Sample : USBpower

<i>OUT Identifier</i>	USB Cable charging
<i>Sample Description</i>	

2.3 OUT Features

Features for OUT: F-022

Designation	Description	Allowed Values	Supported Value(s)
Features for scope: FCC_v2			
AC	The OUT is powered by or connected to AC Mains		
BT	EUT supports Bluetooth data rate of 1 Mbps with GFSK modulation in the band 2400 MHz - 2483.5 MHz		
DC	The OUT is powered by or connected to DC Mains		
EDGE1900	EUT supports EDGE in the band 1850 MHz - 1910 MHz		
EDR2	EUT supports Bluetooth using data rate of 2 Mbps with PI/4 DQPSK modulation in the band 2400 MHz - 2483.5 MHz		
EDR3	EUT supports Bluetooth using data rate of 3 Mbps with 8DPSK modulation in the band 2400 MHz - 2483.5 MHz		
FDD5	EUT supports UMTS FDD5 in the band 824 MHz - 849 MHz		
HSDPA-FDD5	EUT supports UMTS FDD5 HSDPA in the band 824 MHz - 849 MHz		
HSUPA-FDD5	EUT supports UMTS FDD5 HSUPA in the band 824 MHz - 849 MHz		
Iant	Integral Antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment		
PCS1900	EUT supports PCS1900 band 1850MHz - 1910MHz		

2.4 Auxiliary Equipment

AE No.	Type Designation	Serial No.	HW Status	SW Status	Description
AE 05	Cherry RS 6000	G 0000273 2P28			Keyboard 1
AE 01	LG Flatron L1740BQ	509WANF1W607			TFT 1
AE 04	Logitech M-BB48	LZC90505478			Computer Mouse
AE 02	Toshiba TECRA M9	87060248H		WinXP Prof. Ger.	Laptop 1
AE 03	Toshiba PA3378E-3AC3	G71C0006R310			AC Adapter 1

2.5 Operating Mode(s)

Ref.-No.	Description
001	GSM1900 TCH661, Bluetooth standby mode, charging via Laptop
002	GSM1900 TCH661, Bluetooth standby mode, charging via AC/DC adapter

2.6 Setups used for Testing

For each setup a relation is given to determine if and which samples and auxiliary equipment is used. The left side list all OUT samples and the right side lists all auxiliary equipment for the given setup.

Setup No.	<i>List of OUT samples</i>	<i>List of auxiliary equipment</i>	
Sample No.	Sample Description	AE No.	AE Description
ACDC_J01			
Sample:	ACDC01	TS04-500680	
Sample:	USBpower		
Sample:	J01	Standard sample	
PC_J01			
Sample:	USBdata	AE 05	Keyboard 1
Sample:	J01	AE 01	TFT 1
		AE 04	Computer Mouse
		AE 02	Laptop 1
		AE 03	AC Adapter 1

3 Results

3.1 General

Documentation of tested devices:	Available at the test laboratory.
Interpretation of the test results:	The results of the inspection are described on the following pages, where 'Conformity' or 'Passed' means that the certification criteria were verified and that the tested device is conform to the applied standard.
	In cases where 'Declaration' is printed, the required documents are available in the manufacturers product documentation.
	In cases where 'not applicable' is printed, the test case requirements are not relevant to the specific equipment implementation.

3.2 List of the Applicable Body

(Body for Scope: FCC_v2)

<i>Designation</i>	<i>Description</i>
FCC47CFRChIPART15bRADIO FREQUENCY DEVICES	Part 15, Subpart B - Unintentional Radiators



Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

3.3 List of Test Specification

Test Specification: **FCC part 2 and 15**

Version 10-1-10 Edition

Title: PART 2 - GENERAL RULES AND REGULATIONS
PART 15 - RADIO FREQUENCY DEVICES

<i>Applicable Errata</i>	<i>Activate Date</i>	<i>Comment</i>
ANSI C63.4-2003	04/1/30	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and electronic Equipment in the Range of 9 kHz to 40 GHz
DA 00-705 considerd	00/3/1	Public Notice: Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems



Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

3.4 Summary

Test Case Identifier / Name

<i>Test (condition)</i>	<i>Result</i>	<i>Date of Test</i>	<i>Lab Ref.</i>	<i>Setup</i>
15b.1 Conducted Emissions (AC Power Line) §15.107				
15b.1; Mode = transmit	Passed operating mode: 002	2011/03/18	Lab 1	ACDC_J01
	Passed operating mode: 001	2011/03/18	Lab 1	PC_J01
15b.2 Spurious Radiated Emissions §15.109				
15b.2; Mode = transmit	Passed operating mode: 001	2011/03/16	Lab 2	PC_J01
	Passed operating mode: 002	2011/03/16	Lab 2	ACDC_J01



Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

3.5 Detailed Results

3.5.1 15b.1 Conducted Emissions (AC Power Line) §15.107

Test1: 15b.1; Mode = transmit


<i>Result:</i>	Passed
<i>Setup No.:</i>	PC_J01
<i>Date of Test:</i>	2011/03/18 7:40
<i>Body:</i>	FCC47CFRChIPART15bRADIO FREQUENCY DEVICES
<i>Test Specification:</i>	FCC part 2 and 15

Detailed Results:
AC MAINS CONDUCTED

EUT: (Y7040j01) / 18.03.2011
 Manufacturer: Fujitsu
 Operating Condition: GSM1900 TCH661, Bluetooth standby mode, charging via Laptop
 Test Site: 7 layers Ratingen
 Operator: Doe
 Test Specification: ANSI C63.4; FCC 15.107 / 15.207
 Comment: computer periperal setup
 Start of Test: 18.03.2011 / 13:51:50

SCAN TABLE: "FCC Voltage"

Short Description:		FCC Voltage				
Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
150.0 kHz	30.0 MHz	5.0 kHz	MaxPeak	20.0 ms	9 kHz	ESH3-Z5
						Average


MEASUREMENT RESULT: "FJT_1019_027_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dB μ V	dB	dB μ V	dB		
0.365000	44.10	9.9	59	14.5	N	GND
0.520000	51.50	10.0	56	4.5	N	GND

MEASUREMENT RESULT: "FJT_1019_027_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dB μ V	dB	dB μ V	dB		
0.300000	39.60	9.9	50	10.6	N	GND
0.520000	36.00	10.0	46	10.0	L1	FLO
1.040000	39.40	10.0	46	6.6	L1	GND
1.555000	40.10	10.0	46	5.9	N	GND
2.075000	41.20	10.1	46	4.8	L1	GND
2.595000	38.30	10.1	46	7.7	L1	GND
3.115000	32.70	10.2	46	13.3	N	GND



Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

Test1: 15b.1; Mode = transmit


<i>Result:</i>	Passed
<i>Setup No.:</i>	ACDC_J01
<i>Date of Test:</i>	2011/03/18 7:42
<i>Body:</i>	FCC47CFRChIPART15bRADIO FREQUENCY DEVICES
<i>Test Specification:</i>	FCC part 2 and 15

Detailed Results:
AC MAINS CONDUCTED

EUT: (Y7040j01) / 18.03.2011
 Manufacturer: Fujitsu
 Operating Condition: GSM1900 TCH661, Bluetooth standby mode, charging via AC/DC adapter
 Test Site: 7 layers Ratingen
 Operator: Doe
 Test Specification: ANSI C63.4; FCC 15.107 / 15.207
 Comment:
 Start of Test: 18.03.2011 / 13:33:09

SCAN TABLE: "FCC Voltage"

Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width			Time	Bandw.
150.0 kHz	30.0 MHz	5.0 kHz		MaxPeak	20.0 ms	9 kHz
					Average	ESH3-Z5





Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

3.5.2 15b.2 Spurious Radiated Emissions §15.109

Test1: 15b.2; Mode = transmit


<i>Result:</i>	Passed
<i>Setup No.:</i>	ACDC_J01
<i>Date of Test:</i>	2011/03/16 10:45
<i>Body:</i>	FCC47CFRChIPART15bRADIO FREQUENCY DEVICES
<i>Test Specification:</i>	FCC part 2 and 15

Detailed Results:
EMI RADIATED TEST

EUT: Y7040j01
 Manufacturer: Fujitsu
 Operating Condition: GSM1900 TCH661, Bluetooth standby mode, charging via Laptop AC/DC adapter
 Test Site: 7 layers, Ratingen
 Operator: mac
 Test Specification: FCC part 15 b
 Comment: Horizontal EUT position
 Start of Test: 16.03.2011 / 09:14:05

SCAN TABLE: "FCC part 15 b"

Short Description:		FCC part 15 b				
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
30.0 MHz	1.0 GHz	60.0 kHz	MaxPeak	1.0 ms	120 kHz	HL562


MEASUREMENT RESULT: "FJT_1bradAC_fin QP"

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Height cm	Azimuth deg	Polarisation
40.380000	28.70	14.7	40.0	11.3	100.0	278.00	VERTICAL
40.740000	31.60	14.6	40.0	8.4	101.0	292.00	VERTICAL
40.980000	33.90	14.4	40.0	6.1	100.0	247.00	VERTICAL
41.100000	32.30	14.4	40.0	7.7	100.0	257.00	VERTICAL
41.520000	31.10	14.1	40.0	8.9	101.0	247.00	VERTICAL
41.700000	31.00	14.0	40.0	9.0	106.0	225.00	VERTICAL
41.940000	29.80	13.8	40.0	10.2	100.0	137.00	VERTICAL
45.000000	32.60	12.0	40.0	7.4	101.0	320.00	VERTICAL
49.860000	34.80	8.9	40.0	5.2	100.0	233.00	VERTICAL
51.900000	37.30	7.5	40.0	2.7	100.0	202.00	VERTICAL



Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

Test1: 15b.2; Mode = transmit


<i>Result:</i>	Passed
<i>Setup No.:</i>	PC_J01
<i>Date of Test:</i>	2011/03/16 10:49
<i>Body:</i>	FCC47CFRChIPART15bRADIO FREQUENCY DEVICES
<i>Test Specification:</i>	FCC part 2 and 15

Detailed Results:
EMI RADIATED TEST

EUT: Y7040j01
 Manufacturer: Fujitsu
 Operating Condition: GSM1900 TCH661, Bluetooth standby mode, charging via Laptop
 Test Site: 7 layers, Ratingen
 Operator: mac
 Test Specification: FCC part 15 b
 Comment: Horizontal EUT position
 Start of Test: 16.03.2011 / 10:35:47

SCAN TABLE: "FCC part 15 b"

Short Description:		FCC part 15 b				
Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
30.0 MHz	1.0 GHz	60.0 kHz	MaxPeak	1.0 ms	120 kHz	HL562


MEASUREMENT RESULT: "FJT_1bradcom_fin_QP"

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Height cm	Azimuth deg	Polarisation
32.820000	33.10	19.0	40.0	6.9	100.0	247.00	VERTICAL
41.040000	32.10	14.4	40.0	7.9	101.0	119.00	VERTICAL
80.820000	34.40	9.5	40.0	5.6	125.0	67.00	VERTICAL
84.960000	37.20	9.7	40.0	2.8	125.0	112.00	VERTICAL
87.960000	34.50	9.8	40.0	5.5	101.0	113.00	VERTICAL
165.960000	32.60	8.6	43.5	10.9	175.0	67.00	HORIZONTAL
170.640000	23.20	8.6	43.5	20.3	179.0	53.00	HORIZONTAL
696.840000	32.90	21.2	46.0	13.1	100.0	67.00	VERTICAL
699.720000	32.70	21.2	46.0	13.3	100.0	67.00	VERTICAL
762.480000	40.00	22.1	46.0	6.0	145.0	202.00	VERTICAL

4 Test Equipment Details

4.1 List of Used Test Equipment

The calibration, hardware and software states are shown for the testing period.

Test Equipment Anechoic Chamber

Lab ID:	Lab 2
Manufacturer:	Frankonia
Description:	Anechoic Chamber for radiated testing
Type:	10.58x6.38x6 m ³

Single Devices for Anechoic Chamber

Single Device Name	Type	Serial Number	Manufacturer
Air compressor	none	-	Atlas Copco
Anechoic Chamber	10.58 x 6.38 x 6.00 m ³	none	Frankonia
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	FCC listing 96716 3m Part15/18		2011/01/11 2014/01/10
Controller Maturo	MCU	961208	Maturo GmbH
EMC camera	CE-CAM/1	-	CE-SYS
EMC camera Nr.2	CCD-400E	0005033	Mitsubishi
Filter ISDN	B84312-C110-E1		Siemens&Matsushita
Filter Universal 1A	BB4312-C30-H3	-	Siemens&Matsushita

Test Equipment Auxiliary Equipment for Conducted emissions

Lab ID:	Lab 1
Manufacturer:	Rohde & Schwarz GmbH & Co.KG
Description:	EMI Conducted Auxiliary Equipment

Single Devices for Auxiliary Equipment for Conducted emissions

Single Device Name	Type	Serial Number	Manufacturer
Cable "LISN to ESI"	RG214	W18.03+W48.03	Huber&Suhner
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06 2011/11/05
Two-Line V-Network	ESH 3-Z5	828304/029	Rohde & Schwarz GmbH & Co. KG
Two-Line V-Network	ESH 3-Z5	829996/002	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	DKD calibration		2008/10/13 2011/10/12
	DKD calibration		2011/01/20 2013/01/19

Test Equipment Auxiliary Equipment for Radiated emissions

Lab ID: Lab 2
Description: Equipment for emission measurements
Serial Number: see single devices

Single Devices for Auxiliary Equipment for Radiated emissions

Single Device Name	Type	Serial Number	Manufacturer	
Antenna mast	AS 620 P	620/37	HD GmbH	
Biconical dipole	VUBA 9117 <i>Calibration Details</i>	9117-108	Schwarzbeck	<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2008/10/27	2013/10/26
Broadband Amplifier 18MHz-26GHz	JS4-18002600-32-5P <i>Calibration Details</i>	849785	Miteq	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
Broadband Amplifier 1GHz-4GHz	AFS4-01000400-1Q-10P-4 <i>Calibration Details</i>	-	Miteq	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
Broadband Amplifier 30MHz-18GHz	JS4-00101800-35-5P <i>Calibration Details</i>	896037	Miteq	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
Cable "ESI to EMI Antenna"	EcoFlex10 <i>Calibration Details</i>	W18.01- 2+W38.01-2	Kabel Kusch	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
Cable "ESI to Horn Antenna"	UFB311A+UFB293C <i>Calibration Details</i>	W18.02- 2+W38.02-2	Rosenberger Micro-Coax	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
Double-ridged horn	HF 906 <i>Calibration Details</i>	357357/001	Rohde & Schwarz GmbH & Co. KG	<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/04/16	2012/04/15
Double-ridged horn	HF 906 <i>Calibration Details</i>	357357/002	Rohde & Schwarz GmbH & Co. KG	<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/04/28	2012/04/27
High Pass Filter	4HC1600/12750-1.5-KK <i>Calibration Details</i>	9942011	Trilithic	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
High Pass Filter	5HC2700/12750-1.5-KK <i>Calibration Details</i>	9942012	Trilithic	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
High Pass Filter	5HC3500/12750-1.2-KK <i>Calibration Details</i>	200035008	Trilithic	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05
High Pass Filter	WHKX 7.0/18G-8SS <i>Calibration Details</i>	09	Wainwright	<i>Last Execution</i> <i>Next Exec.</i>
	Path Calibration		2010/11/06	2011/05/05

Single Devices for Auxiliary Equipment for Radiated emissions (continued)

Single Device Name	Type	Serial Number	Manufacturer
Log.-per. Antenna	HL 562 Ultralog	830547/003	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/05/27 2012/05/26
Loop Antenna	HFH2-ZZ	829324/006	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	DKD calibration		2008/10/07 2011/10/06
Network Analyzer	E5071B	MY42200813	Agilent
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2010/11/09 2011/11/09
Pyramidal Horn Antenna 26,5 GHz	3160-09	00083069	EMCO Elektronik GmbH
Pyramidal Horn Antenna 40 GHz	3160-10	00086675	EMCO Elektronik GmbH
Tilt device Maturo (Rohacell)	Antrieb TD1.5-10kg	TD1.5-10kg/024/3790709	Maturo GmbH

Test Equipment Auxiliary Test Equipment

Lab ID:	Lab 2
Manufacturer:	see single devices
Description:	Single Devices for various Test Equipment
Type:	various
Serial Number:	none

Single Devices for Auxiliary Test Equipment

Single Device Name	Type	Serial Number	Manufacturer
AC Power Source	Chroma 6404	64040001304	Chroma ATE INC.
Broadband Power Divider N (Aux)	1506A / 93459	LM390	Weinschel Associates
Broadband Power Divider SMA	WA1515	A855	Weinschel Associates
Digital Multimeter 03 (Multimeter)	Fluke 177	86670383	Fluke Europe B.V.
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2009/10/07 2011/10/06
Fibre optic link Satellite (Aux)	FO RS232 Link	181-018	Pontis
Fibre optic link Transceiver (Aux)	FO RS232 Link	182-018	Pontis
Isolating Transformer	LTS 604	1888	Thalheimer Transformatorenwerke GmbH
Notch Filter Ultra Stable (Aux)	WRCA800/960-6EEK	24	Wainwright
Vector Signal Generator	SMIQ 03B	832492/061	Rohde & Schwarz GmbH & Co.KG

Test Equipment Digital Signalling Devices

Lab ID: **Lab 1, Lab 2**
Description: Signalling equipment for various wireless technologies.

Single Devices for Digital Signalling Devices

Single Device Name	Type	Serial Number	Manufacturer
Bluetooth Signalling Unit CBT	CBT	100589	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2008/08/14 2011/08/13
Universal Radio Communication Tester	CMU 200	102366	Rohde & Schwarz GmbH & Co. KG
	<i>HW/SW Status</i>		<i>Date of Start</i> <i>Date of End</i>
	Hardware: B11, B21V14, B21-2, B41, B52V14, B52-2, B53-2, B56V14, B68 3v04, PCMCIA, U65V04		2007/07/16
	Software: K21 4v21, K22 4v21, K23 4v21, K24 4v21, K42 4v21, K43 4v21, K53 4v21, K56 4v22, K57 4v22, K58 4v22, K59 4v22, K61 4v22, K62 4v22, K63 4v22, K64 4v22, K65 4v22, K66 4v22, K67 4v22, K68 4v22, K69 4v22		
	Firmware: μP1 8v50 02.05.06		

Test Equipment Emission measurement devices

Lab ID: **Lab 1, Lab 2**
Description: Equipment for emission measurements
Serial Number: see single devices

Single Devices for Emission measurement devices

Single Device Name	Type	Serial Number	Manufacturer
Personal Computer	Dell	30304832059	Dell
Power Sensor	NRV-Z1	836219/005	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/10/20 2011/10/19
Powermeter	NRVS	836333/064	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard calibration		2009/10/15 2011/10/14
Signal Generator	SMR 20	846834/008	Rohde & Schwarz GmbH & Co. KG
Spectrum Analyzer	ESIB 26	830482/004	Rohde & Schwarz GmbH & Co. KG
	<i>Calibration Details</i>		<i>Last Execution</i> <i>Next Exec.</i>
	Standard Calibration		2009/12/03 2011/12/02

Test Equipment Shielded Room 02

Lab ID: **Lab 1**
Manufacturer: Frankonia
Description: Shielded Room for conducted testing
Type: 12 qm
Serial Number: none



Reference: ODE_MJP_FJT_1019_FCCb

acc. Title 47 CFR Chapter I part 15, subpart b

5 Annex

5.1 Additional Information for Report

**Test Description**

Conducted emissions (AC power line)

Standard FCC Part 15
Subpart B

The test was performed according to: ANSI C 63.4, 2003

Test Description

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2003. The Equipment Under Test (EUT) was setup in a shielded room to perform the conducted emissions measurements in a typical installation configuration. The EUT was powered from 50µH || 50 Ohm Line Impedance Stabilization Network (LISN). The LISN's unused connections were terminated with 50 Ohm loads.

The measurement procedure consists of two steps. It is implemented into the EMI test software ES-K1 from R&S.

Step 1: Preliminary scan

Intention of this step is, to determine the conducted EMI-profile of the EUT.

EMI receiver settings:

- Detector: Peak - Maxhold
- Frequency range: 150 kHz – 30 MHz
- Frequency steps: 5 kHz
- IF-Bandwidth: 9 kHz
- Measuring time / Frequency step: 20 ms
- Measurement on phase + neutral lines of the power cords

On basis of this preliminary scan the highest amplitudes and the corresponding frequencies relative to the limit are identified. Emissions above the limit and emissions which are in the 10 dB range below the limit are considered.

Step 2: Final measurement

Intention of this step is, to determine the highest emissions with the settings defined in the test specification for the frequencies identified in step 1.

EMI receiver settings:

- Detector: Quasi-Peak
- IF - Bandwidth: 9 kHz
- Measuring time: 1 s / frequency

At each frequency determined in step 1, four measurements are performed in the following combinations:

- 1) Neutral lead - reference ground (PE grounded)
- 2) Phase lead - reference ground (PE grounded)
- 3) Neutral lead - reference ground (PE floating)
- 4) Phase lead - reference ground (PE floating)

The highest value is reported.

Test Requirements / Limits

If not stated within the measurement plot and/or test result, class B limits are applied.

FCC Part 15, Subpart B, §15.107, Class B Limit

Frequency Range (MHz)	QP Limit (dB μ V)	AV Limit (dB μ V)
0.15 – 0.5	66 to 56	56 to 46
0.5 – 5	56	46
5 – 30	60	50

FCC Part 15, Subpart B, §15.107, Class A Limit

Frequency Range (MHz)	QP Limit (dB μ V)	AV Limit (dB μ V)
0.15 - 0.5	79	66
0.5 - 30	73	60

Used conversion factor: Limit (dB μ V) = 20 log (Limit (μ V)/1 μ V).

NOTE: a missing result table in the corresponding test report section means, that no final measurement was performed because no relevant frequencies (peaks) were found in the preliminary scan.

 Spurious radiated emissions

Standard FCC Part 15, Subpart B

The test was performed according to: ANSI C 63.4, 2003

Test Description

Measurement below 1 GHz:

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2003.

The Equipment Under Test (EUT) was set up on a non-conductive table 1.0 x 2.0 m in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The radiated emissions measurements were made in a typical installation configuration.

The measurement procedure is implemented into the EMI test software ES-K1 from R&S.

Step 1: Preliminary scan (test to identify the highest amplitudes relative to the limit)

Intention of this step is, to determine the radiated EMI-profile of the EUT.

Settings for step 1:

- Detector: Peak-Maxhold
- Frequency range: 30 – 1000 MHz
- Frequency steps: 60 kHz
- IF-Bandwidth: 120 kHz
- Measuring time / Frequency step: 100 μ s
- Turntable angle range: -180° to 180°
- Turntable step size: 90°
- Height variation range: 1 – 3 m
- Height variation step size: 2 m
- Polarisation: Horizontal + Vertical

On basis of this preliminary scan the highest amplitudes and the corresponding frequencies relative to the limit are identified. Emissions above the limit and emissions which are in the 10 dB range below the limit are considered.

Step 2:

A further measurement will be performed on the frequencies determined in step 1. Intention of this step is, to find out the approximate turntable angle and antenna height for each frequency.

Settings for step 2:

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: -180° to 180°
- Turntable step size: 45°
- Height variation range: 1 – 4 m
- Height variation step size: 0.5 m
- Polarisation: horizontal + vertical

After this step the EMI test system has determined the following values for each frequency (of step 1):

- Frequency
- Azimuth value (of turntable)
- Antenna height

The last two values have now the following accuracy:

- Azimuth value (of turntable): 45°
- Antenna height: 0.5 m

Step 3: final measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved. This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will be slowly varied by +/- 22.5° around this value. During this action the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position the antenna height is also slowly varied by +/- 25 cm around the antenna height determined. During this action the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100ms
- Turntable angle range: -22.5° to + 22.5 ° around the determined value
- Height variation range: -0.25m to + 0.25m around the determined value

Step 4: Final measurement (with QP detector)

With the settings determined in step 3, the final measurement will be performed:

EMI receiver settings for step 4:

- Detector: Quasi-Peak(< 1GHz)
- Measured frequencies: in step 3 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s

Measurement above 1 GHz:

The following modifications apply to the measurement procedure for the frequency range above 1 GHz:
 The measurement distance was reduced to 1 m. The results were extrapolated by the extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements, inverse-linear-distance-squared for the power density measurements). Due to the fact that in this frequency range a double ridged wave guided horn antenna (up to 18 GHz) and a horn antenna (18–25 GHz) are used, the steps 2-4 as described before, are omitted. Step 1 was performed at one height of the receiving antenna only.

Detector: Peak, Average (simultaneously)

RBW = VBW = 1 MHz; above 7 GHz 100 kHz

Test Requirements / Limits

If not stated within the measurement plot and/or test result, class B limits are applied.

FCC Part 15, Subpart B, §15.109, Radiated Emission Limits

Frequency Range (MHz): Class B Limit (dB μ V/m)

Frequency Range (MHz)	Class B Limit (dB μ V/m)
30 – 88	40.0
88 – 216	43.5
216 – 960	46.0
above 960	54.0

Frequency Range (MHz)	Class A Limit (dB μ V/m) / @ 3m !
30 - 88	49.5
88 - 216	54.0
216 - 960	56.9
above 960	60.0


§15.35(b)

..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dB μ V/m) = 20 log (Limit (μ V/m)/1 μ V/m)

NOTE: a missing result table in the corresponding test report section means, that no final measurement was performed because no relevant frequencies (peaks) were found in the preliminary scan.

Setup Drawings



Remark: Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

Setup in the Anechoic chamber. For measurements below 1 GHz the ground was replaced by a conducting ground plane.

6 Index

1	Administrative Data	2
1.1	Project Data	2
1.2	Applicant Data	2
1.3	Test Laboratory Data	2
1.4	Signature of the Testing Responsible	2
1.5	Signature of the Accreditation Responsible	3
2	Test Object Data	3
2.1	General OUT Description	3
2.2	Detailed Description of OUT Samples	4
2.3	OUT Features	5
2.4	Auxiliary Equipment	5
2.5	Operating Mode(s)	5
2.6	Setups used for Testing	6
3	Results	6
3.1	General	6
3.2	List of the Applicable Body	6
3.3	List of Test Specification	7
3.4	Summary	8
3.5	Detailed Results	9
3.5.1	15b.1 Conducted Emissions (AC Power Line) §15.107	9
3.5.2	15b.2 Spurious Radiated Emissions §15.109	13
4	Test Equipment Details	17
4.1	List of Used Test Equipment	17
5	Annex	21
5.1	Additional Information for Report	21
6	Index	26