



A D T

FCC TEST REPORT

(PART 22)

REPORT NO.: RF120823C14

MODEL NO.: F-03E

FCC ID: VQK-F03E

RECEIVED: Aug. 23, 2012

TESTED: Oct. 01 ~ Oct. 04, 2012

ISSUED: Oct. 09, 2012

APPLICANT: FUJITSU LIMITED

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,
Kawasaki 211-8588, Japan

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by TAF or
any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 SUMMARY OF TEST RESULTS	5
2.1 MEASUREMENT UNCERTAINTY	5
2.2 TEST SITE AND INSTRUMENTS	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 CONFIGURATION OF SYSTEM UNDER TEST	8
3.3 DESCRIPTION OF SUPPORT UNITS	9
3.4 TEST ITEM AND TEST CONFIGURATION	10
3.5 EUT OPERATING CONDITIONS	12
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	12
4 TEST TYPES AND RESULTS	13
4.1 OUTPUT POWER MEASUREMENT	13
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	13
4.1.2 TEST PROCEDURES	13
4.1.3 TEST SETUP	14
4.1.4 TEST RESULTS	15
4.2 FREQUENCY STABILITY MEASUREMENT	17
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	17
4.2.2 TEST PROCEDURE	17
4.2.3 TEST SETUP	17
4.2.4 TEST RESULTS	18
4.3 OCCUPIED BANDWIDTH MEASUREMENT	19
4.3.1 TEST PROCEDURES	19
4.3.2 TEST SETUP	19
4.3.3 TEST RESULTS	20
4.4 BAND EDGE MEASUREMENT	21
4.4.1 LIMITS OF BAND EDGE MEASUREMENT	21
4.4.2 TEST SETUP	21
4.4.3 TEST PROCEDURES	21
4.4.4 TEST RESULTS	22
4.5 CONDUCTED SPURIOUS EMISSIONS	23
4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	23
4.5.2 TEST PROCEDURE	23
4.5.3 TEST SETUP	23
4.5.4 TEST RESULTS	24
4.6 RADIATED EMISSION MEASUREMENT	25
4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	25
4.6.2 TEST PROCEDURES	25
4.6.3 DEVIATION FROM TEST STANDARD	25
4.6.4 TEST SETUP	26
4.6.5 TEST RESULTS	27
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	33
6 INFORMATION ON THE TESTING LABORATORIES	34
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	35



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120823C14	Original release	Oct. 09, 2012



A D T

1 CERTIFICATION

PRODUCT: Mobile Phone

MODEL: F-03E

BRAND: NTT DOCOMO

APPLICANT: FUJITSU LIMITED

TESTED: Oct. 01 ~ Oct. 04, 2012

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC PART 22, Subpart H

The above equipment (model: F-03E) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : , DATE : Oct. 09, 2012
Pettie Chen / Senior Specialist

APPROVED BY : , DATE : Oct. 09, 2012
James Lee / Manager



A D T

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 22.913 (a)	Effective radiated power	PASS	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	PASS	Meet the requirement of limit.
2.1049	Occupied Bandwidth	PASS	Meet the requirement of limit.
22.917	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -13.67dB at 2509.20MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



A D T

2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Dec. 22, 2011	Dec. 21, 2012
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2011	Dec. 20, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Dec. 20, 2011	Dec. 19, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 20, 2011	Dec. 19, 2012
Preamplifier EMCI	EMC 012645	980115	Dec. 30, 2011	Dec. 29, 2012
Preamplifier EMCI	EMC 330H	980112	Dec. 30, 2011	Dec. 29, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 21, 2011	Oct. 20, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Jan. 02, 2012	Jan. 01, 2013
RF signal cable Worken	RG-213	NA	Jan. 02, 2012	Jan. 01, 2013
Software	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless	E5515C	MY50266630	Sep. 29, 2011	Sep. 27, 2013
Radio Communication Analyzer	MT8820C	6201127458	May 25, 2012	May 24, 2013

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The calibration interval of the Communications Tester-Wireless is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 9.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 460141.
6. The IC Site Registration No. is IC 7450F-4.



A D T

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Mobile Phone		
MODEL NO.	F-03E		
POWER SUPPLY	5.1Vdc (adapter or host equipment) 3.8Vdc (battery)		
MODULATION TYPE	GSM	GMSK	
	WCDMA	BPSK	
FREQUENCY RANGE	GSM	824.2MHz ~ 848.8MHz	
	WCDMA	826.4MHz ~ 846.6MHz	
MAX. ERP POWER	GSM	616.60mW	
	WCDMA	73.96mW	
EMISSION DESIGNATOR	GSM	246KGXW	
	WCDMA	4M19F9W	
MULTI-SLOTS CLASS	12		
WCDMA RELEASE VERSION	8		
ANTENNA TYPE	GSM	Fixed Internal antenna with -2.6dBi gain	
	WCDMA		
I/O PORTS	Refer to users' manual		
DATA CABLE	Refer to NOTE as below		
ACCESSORY DEVICES	Refer to NOTE as below		

NOTE:

1. The EUT contains following accessory and components.

ITEM	BRAND	MODEL	SPECIFICATION
Battery	FUJITSU	F29	Rating: 3.8Vdc, 1810mAh Type: Li-ion
LCD Panel	JDI	GCX162BLP-7	--
Photo Camera	ALTEK	AOA0803	--
Video Camera	ALTEK	ASF0104	--

2. The following accessories are for support units only.


ITEM	BRAND	MODEL	SPECIFICATION
Adapter	Motorola	DC4050US0301	Input: 100-240Vac, 50/60Hz, 0.2A Output: 5.1Vdc, 850mA
USB cable	Motorola	NA	1.0m

3. SW version is LYDV01R13Ge
4. HW version is DVT2.
5. IMEI code: 353737050010461
6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.


3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST

Test Mode A




Test Mode B





A D T

FOR E.R.P. TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Earphone	DONGMEI	D-D606	NA	NA
2	Wireless charger Cradle	NTT docomo	AAF39571	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.32m non-shielded cable without core
2	NA

NOTE:

1. All power cords of the above support units are non-shielded (1.8 m).
2. Item 1, 2 were provided by client.



A D T

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y-plane for ERP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	Normal link
B	Wireless charge

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	128 to 251	128, 189, 251	GSM
A	FREQUENCY STABILITY	128 to 251	189	GSM
A	OCCUPIED BANDWIDTH	128 to 251	128, 189, 251	GSM
A	BAND EDGE	128 to 251	128, 251	GSM
A	CONDUCED EMISSION	128 to 251	189	GSM
A, B	RADIATED EMISSION	128 to 251	189	GSM

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
A	FREQUENCY STABILITY	4132 to 4233	4182	WCDMA
A	OCCUPIED BANDWIDTH	4132 to 4233	4132, 4182, 4233	WCDMA
A	BAND EDGE	4132 to 4233	4132, 4233	WCDMA
A	CONDUCED EMISSION	4132 to 4233	4182	WCDMA
A, B	RADIATED EMISSION	4132 to 4233	4182	WCDMA



A D T

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	26deg. C, 58%RH	3.8Vdc	Phoenix Chen
FREQUENCY STABILITY	26deg. C, 58%RH	3.8Vdc	Phoenix Chen
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.8Vdc	Phoenix Chen
BAND EDGE	26deg. C, 58%RH	3.8Vdc	Phoenix Chen
CONDUCED EMISSION	26deg. C, 58%RH	3.8Vdc	Phoenix Chen
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Kay Wu



A D T

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.



A D T

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS and 5MHz for WCDMA mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dB.

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS & WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).



A D T

4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GPRS850		
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
GSM (GMSK, 1 Uplink)	32.90	33.13	33.15
GPRS 8 (GMSK, 1 Uplink)	32.86	33.10	33.10
GPRS 10 (GMSK, 2 Uplink)	30.57	30.92	30.81
GPRS 11 (GMSK, 3 Uplink)	28.56	29.26	28.85
GPRS 12 (GMSK, 4 Uplink)	27.23	27.47	27.41

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.16	22.85	23.62
HSDPA Subtest-1	22.16	21.90	22.56
HSDPA Subtest-2	22.19	22.02	22.71
HSDPA Subtest-3	22.22	21.94	22.48
HSDPA Subtest-4	22.09	21.84	22.59
HSUPA Subtest-1	22.20	21.95	22.47
HSUPA Subtest-2	20.06	19.90	20.56
HSUPA Subtest-3	21.25	20.93	21.44
HSUPA Subtest-4	20.11	19.89	20.59
HSUPA Subtest-5	22.12	21.91	22.51



A D T

ERP POWER (dBm)

GSM

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	128	824.2	-2.89	32.62	27.58	572.80	H
	189	836.4	-2.81	32.52	27.56	570.16	H
	251	848.8	-2.60	32.65	27.90	616.60	H
	128	824.2	-9.77	32.76	20.84	121.34	V
	189	836.4	-9.55	32.39	20.69	117.22	V
	251	848.8	-9.92	32.54	20.47	111.43	V

WCDMA

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
Y	4132	826.4	-11.78	32.62	18.69	73.96	H
	4182	836.4	-12.01	32.52	18.36	68.55	H
	4233	846.6	-12.04	32.65	18.46	70.15	H
	4132	826.4	-19.23	32.76	11.38	13.74	V
	4182	836.4	-18.57	32.39	11.67	14.69	V
	4233	846.6	-18.89	32.54	11.50	14.13	V

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP





A D T

4.2.4 TEST RESULTS

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	GSM	WCDMA	
3.8	-0.009	0.001	2.5
3.42	0.006	-0.002	2.5
4.12	-0.008	-0.002	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.42Vdc to 4.12Vdc.

FREQUENCY ERROR vs. TEMPERATURE.


TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	GSM	WCDMA	
-30	0.007	0.003	2.5
-20	0.009	0.004	2.5
-10	-0.012	0.003	2.5
0	0.007	0.003	2.5
10	-0.008	0.002	2.5
20	-0.008	0.002	2.5
30	-0.010	0.002	2.5
40	0.008	-0.002	2.5
50	-0.008	-0.003	2.5
55	-0.008	-0.005	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 TEST SETUP






A D T

4.3.3 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz)	CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)
		GSM			WCDMA
128	824.2	245.53	4132	826.4	4.1860
189	836.4	245.28	4182	836.4	4.1754
251	848.8	244.93	4233	846.6	4.1816




4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.


4.4.2 TEST SETUP



4.4.3 TEST PROCEDURES

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz (GSM/GPRS).
- c. The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
- d. Record the max trace plot into the test report.

4.4.4 TEST RESULTS



4.5 CONDUCTED SPURIOUS EMISSIONS


4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30 MHz to 9GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.


4.5.3 TEST SETUP





A D T

4.5.4 TEST RESULTS





A D T

4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.

4.6.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.3 DEVIATION FROM TEST STANDARD

No deviation

4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).



A D T

4.6.5 TEST RESULTS

Test Mode A


GSM:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 Chamber 5
Condition : PART22/24 3m EIRP_RSE_1G~19G_3 HORIZONTAL
Brand/Model: F-03E
Remark : GSM850 Link
Tested by : Kay Wu
Temperature : 25°C
Humidity : 65%
Plane : X

	Read Freq	Level MHz	Limit dBm	Over Line dBm/m	Over dB	Over dB/m	Factor	Remark
1	32.16	-47.76	-47.37	-13.00	-34.76	-0.39	Peak	
2	108.03	-51.48	-40.91	-13.00	-38.48	-10.57	Peak	
3	186.33	-54.81	-48.46	-13.00	-41.81	-6.35	Peak	
4	307.00	-56.63	-50.31	-13.00	-43.63	-6.32	Peak	
5	538.00	-62.47	-60.42	-13.00	-49.47	-2.05	Peak	
6	748.70	-62.08	-63.86	-13.00	-49.08	1.78	Peak	
7	1672.80	-56.78	-43.96	-13.00	-43.78	-12.82	Peak	
8 pp	2509.20	-42.93	-33.76	-13.00	-29.93	-9.17	Peak	




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 Chamber 5
Condition : PART22/24 3m EIRP_RSE_1G~19G_3 VERTICAL
Brand/Model: F-03E
Remark : GSM850 Link
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X

Freq	Level	Read	Limit	Over	Factor	Remark
		MHz	dBm/m	dBm	dBm/m	dB
1 pp	31.89	-35.06	-34.67	-13.00	-22.06	-0.39 Peak
2	106.41	-55.84	-45.29	-13.00	-42.84	-10.55 Peak
3	153.39	-57.70	-51.29	-13.00	-44.70	-6.41 Peak
4	307.70	-66.39	-60.07	-13.00	-53.39	-6.32 Peak
5	479.90	-65.62	-62.02	-13.00	-52.62	-3.60 Peak
6	700.40	-62.89	-64.34	-13.00	-49.89	1.45 Peak
7	1672.80	-57.44	-44.62	-13.00	-44.44	-12.82 Peak
8	2509.20	-56.17	-47.00	-13.00	-43.17	-9.17 Peak



A D T


WCDMA:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 Chamber 5
Condition : PART22/24 3m EIRP_RSE_1G~19G_3 HORIZONTAL
Brand/Model: F-03E
Remark : Band V Link
Tested by : Kay Wu
Temperature : 25°C
Humidity : 65%
Plane : X

Freq	Read Level	Limit	Over	Factor	Remark
		Line	Limit		
MHz	dBm/m	dBm	dBm/m	dB	dB/m
1 pp	32.16	-47.29	-46.90	-13.00	-34.29
2	107.22	-51.52	-40.95	-13.00	-38.52
3	185.79	-56.03	-49.68	-13.00	-43.03
4	305.60	-58.90	-52.56	-13.00	-45.90
5	551.30	-65.64	-63.93	-13.00	-52.64
6	773.90	-62.81	-64.76	-13.00	-49.81
7	1672.80	-59.55	-46.73	-13.00	-46.55
8	2509.20	-54.15	-44.98	-13.00	-41.15




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 Chamber 5
Condition : PART22/24 3m EIRP_RSE_1G~19G_3 VERTICAL
Brand/Model: F-03E
Remark : Band V Link
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : X

Freq	Level	Read	Limit	Over	Factor	Remark
		MHz	dBm/m	dBm	dBm/m	dB
1 pp	31.89	-34.92	-34.53	-13.00	-21.92	-0.39 Peak
2	106.95	-56.14	-45.59	-13.00	-43.14	-10.55 Peak
3	219.27	-59.16	-52.08	-13.00	-46.16	-7.08 Peak
4	302.10	-65.23	-58.87	-13.00	-52.23	-6.36 Peak
5	507.90	-67.58	-64.70	-13.00	-54.58	-2.88 Peak
6	738.90	-62.74	-64.45	-13.00	-49.74	1.71 Peak
7	1672.80	-60.36	-47.54	-13.00	-47.36	-12.82 Peak



A D T


Test Mode B



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 Chamber 5
Condition : PART22/24 3m EIRP_RSE_1G~19G_3 HORIZONTAL
Brand/Model: F-03E
Remark : GSM850 Link
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : Wireless charger

Freq	Read		Limit	Over	Factor	Remark
	MHz	dBm/m	Level	Line	dBm/m	
1	76.44	-51.97	-42.04	-13.00	-38.97	-9.93 Peak
2	137.19	-63.06	-56.87	-13.00	-50.06	-6.19 Peak
3	233.58	-56.66	-50.24	-13.00	-43.66	-6.42 Peak
4	422.50	-62.97	-57.92	-13.00	-49.97	-5.05 Peak
5	552.70	-65.59	-63.94	-13.00	-52.59	-1.65 Peak
6	699.70	-63.60	-65.03	-13.00	-50.60	1.43 Peak
7	1672.80	-26.75	-13.93	-13.00	-13.75	-12.82 Peak
8 pp	2509.20	-26.67	-17.50	-13.00	-13.67	-9.17 Peak
9	3345.60	-47.57	-39.76	-13.00	-34.57	-7.81 Peak
10	4182.00	-50.79	-45.21	-13.00	-37.79	-5.58 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 Chamber 5
Condition : PART22/24 3m EIRP_RSE_1G~19G_3 VERTICAL
Brand/Model: F-03E
Remark : GSM850 Link
Tested by : Kay Wu
Temprature : 25°C
Humidity : 65%
Plane : Wireless charger

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor
	MHz	dBm/m	dBm	dBm/m	dB	dB/m
1	44.58	-43.02	-41.83	-13.00	-30.02	-1.19 Peak
2	152.04	-68.76	-62.37	-13.00	-55.76	-6.39 Peak
3	269.22	-63.64	-57.69	-13.00	-50.64	-5.95 Peak
4	301.40	-68.47	-62.10	-13.00	-55.47	-6.37 Peak
5	547.80	-66.54	-64.75	-13.00	-53.54	-1.79 Peak
6	748.00	-62.82	-64.59	-13.00	-49.82	1.77 Peak
7	1672.80	-33.05	-20.23	-13.00	-20.05	-12.82 Peak
8 pp	2509.20	-29.43	-20.26	-13.00	-16.43	-9.17 Peak
9	3345.60	-50.96	-43.15	-13.00	-37.96	-7.81 Peak
10	4182.00	-50.77	-45.19	-13.00	-37.77	-5.58 Peak
11	5018.40	-47.24	-45.52	-13.00	-34.24	-1.72 Peak



A D T

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---