

# FCC Test Report

**FCC ID** : VQK-F04G  
**Equipment** : Mobile Phone  
**Model No.** : F-04G  
**Brand Name** : FUJITSU  
**Applicant** : FUJITSU LIMITED  
**Address** : 1-1, Kamikodanaka 4-chome, Nakahara-ku,  
Kawasaki 211-8588, Japan  
**Standard** : 47 CFR FCC Part 15.225  
**Received Date** : Dec. 17, 2014  
**Tested Date** : Feb. 24, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

  
\_\_\_\_\_  
Gary Chang / Manager



## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information .....	5
1.2	Local Support Equipment List .....	6
1.3	Test Setup Chart .....	6
1.4	The Equipment List .....	7
1.5	Test Standards .....	8
1.6	Measurement Uncertainty .....	8
<b>2</b>	<b>TEST CONFIGURATION.....</b>	<b>9</b>
2.1	Testing Condition .....	9
2.2	The Worst Test Modes and Channel Details .....	9
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>10</b>
3.1	20dB and Occupied Bandwidth .....	10
3.2	Field Strength of Fundamental Emissions and Spectrum Mask .....	12
3.3	Unwanted Emissions into Restricted Frequency Bands .....	15
3.4	Frequency Stability .....	21
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>23</b>

## Release Record

Report No.	Version	Description	Issued Date
FR4D1701NF	Rev. 01	Initial issue	Apr. 01, 2015

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	Note	N/A
15.225(a)~(c)	Field strength of fundamental emissions and spectrum mask	[dBuV/m at 3m]: 13.56 MHz 52.15 (Margin -71.85dB)	Pass
15.225(d)	Field strength of any emissions appearing outside of the 13.110-14.010 MHz band	Meet the requirement of limit	Pass
15.225(e)	Frequency tolerance	Meet the requirement of limit	Pass
15.215 (c)	20dB bandwidth	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Note: The EUT consumes DC power from battery, so the test is not required.

## 1 General Description

### 1.1 Information

#### 1.1.1 Product Details

<b>Product Name</b>	Mobile Phone
<b>Brand Name</b>	FUJITSU
<b>Model Name</b>	F-04G
<b>IMEI Code</b>	357241060021606
<b>H/W Version</b>	v2.1.0
<b>S/W Version</b>	R21.5e

#### 1.1.2 Specification of the Equipment under Test (EUT)

RF General Information			
Frequency Range (MHz)	Modulation	Ch. Frequency (MHz)	Channel Number
13.553 – 13.567	NFC-ASK	13.56	1

#### 1.1.3 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	Loop antenna	---	---	---

#### 1.1.4 EUT Operational Condition

<b>Supply Voltage</b>	AC adapter: (normal output rating) 5.0Vdc, 1.8A (quick charge output rating) 9.0Vdc, 1.8A Battery: 3.75Vdc		
<b>Operational Voltage</b>	<input checked="" type="checkbox"/> Vnom (3.9 V)	<input checked="" type="checkbox"/> Vmax (4.29 V)	<input checked="" type="checkbox"/> Vmin (3.51 V)
<b>Operational Climatic</b>	<input checked="" type="checkbox"/> Tnom (20°C)	<input checked="" type="checkbox"/> Tmax (55°C)	<input checked="" type="checkbox"/> Tmin (-30°C)

#### 1.1.5 Accessories

No.	Equipment	Description
1	Cradle	Brand Name: Fujitsu Limited Model Name: F50 Input rating: (quick charge) 9.0Vdc, 1.5A Output rating: (quick charge) 9.0Vdc, 1.5A
2	Battery (Unremovable)	Brand Name: NTT Docomo Model Name: CA54310-0061 Power Rating: 3.75Vdc, 3120mAh, 12Wh


### 1.1.6 Test Tool and Power Setting

Test tool	NFC Rw Test	
Modulation Mode	NFC	RFID
Setting	Default	Default

### 1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	NFC Tag	Easy Card Corp.	Easy Card	---	---	---

### 1.3 Test Setup Chart



## 1.4 The Equipment List

<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Dec. 03, 2014	Dec. 02, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.

<b>Test Item</b>	Radiated Emission				
<b>Test Site</b>	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 09, 2014	Dec. 08, 2015
Receiver	R&S	ESR3	101658	Nov. 10, 2014	Nov. 09, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Sep. 05, 2014	Sep. 04, 2015
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 10, 2014	Nov. 09, 2015
Preamplifier	Burgeon	BPA-530	SN:100219	Sep. 09, 2014	Sep. 08, 2015
Preamplifier	Agilent	83017A	MY39501308	Oct. 09, 2014	Oct. 08, 2015
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 15, 2014	Dec. 14, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 15, 2014	Dec. 14, 2015
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 15, 2014	Dec. 14, 2015
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 15, 2014	Dec. 14, 2015
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 15, 2014	Dec. 14, 2015
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.225

ANSI C63.10-2013

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Radiated emission ≤ 1GHz	±3.72 dB
Radiated emission > 1GHz	±5.65 dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH01-WS	22°C / 67%	Haru Yang
RF Conducted	TH01-WS	20°C / 63%	Anderson Hung

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

### 2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)
Field strength of fundamental emissions and spectrum mask	NFC	13.56
Field strength of any emissions appearing outside of the 13.110-14.010 MHz band	NFC	13.56
Frequency tolerance	NFC	13.56
20dB bandwidth	NFC	13.56

**NOTE:**

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.

## 3 Transmitter Test Results

### 3.1 20dB and Occupied Bandwidth


#### 3.1.1 Limit of 20dB Bandwidth

The upper and lower frequency of the 20dB bandwidth shall within 13.553~13.567 MHz

#### 3.1.2 Test Procedures

1. Set resolution bandwidth (RBW) = 1 kHz, Video bandwidth = 3 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20dB relative to the maximum level measured in the fundamental emission.

#### 3.1.3 Test Setup




Note: Test distance is 3m

### 3.1.4 Test Result of 20dB and Occupied Bandwidth

Modulation Mode	Freq. (MHz)	20dB Bandwidth (kHz)	F <sub>L</sub> at 20dB BW (MHz)	F <sub>H</sub> at 20dB BW (MHz)	99% Bandwidth (kHz)
NFC	13.56	5.282	13.557641	13.562923	7.235890014
Limit		N/A	13.553	13.567	N/A

#### 20dB Bandwidth



## 3.2 Field Strength of Fundamental Emissions and Spectrum Mask

### 3.2.1 Field Strength of Fundamental Emissions and Spectrum Mask Limit


Field Strength of Fundamental Emissions					
Emissions	(uV/m)@30m	(dBuV/m)@30m	(dBuV/m)@10m	(dBuV/m)@3m	(dBuV/m)@1m
<b>Fundamental</b>	15848	84.0	103.1	124.0	143.1
Quasi peak measurement of the fundamental.					

Spectrum Mask					
Freq. of Emission (MHz)	(uV/m)@30m	(dBuV/m)@30m	(dBuV/m)@10m	(dBuV/m)@3m	(dBuV/m)@1m
1.705~13.110	30	29.5	48.6	69.5	88.6
13.110~13.410	106	40.5	59.6	80.5	99.6
13.410~13.553	334	50.5	69.6	90.5	109.6
13.553~13.567	15848	84.0	103.1	124.0	143.1
13.567~13.710	334	50.5	69.6	90.5	109.6
13.710~14.010	106	40.5	59.6	80.5	99.6
14.010~30.000	30	29.5	48.6	69.5	88.6

### 3.2.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the open and close planes of polarization. . Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, and the antenna rotated to repeat the measurements for both the open and close antenna polarizations.


### 3.2.3 Test Setup



Note: Test distance is 3m

### 3.2.4 Test Result of Field Strength of Fundamental Emissions and Spectrum Mask

Field Strength of Fundamental Emissions Result					
Modulation Mode	Frequency (MHz)	Fundamental (dBuV/m)@3m	Polarization	Margin (dB)	Limit (dBuV/m)@3m
NFC	13.56	52.15	Open	-71.85	124.0



### 3.3 Unwanted Emissions into Restricted Frequency Bands

#### 3.3.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.3.2 Test Procedures


- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

- 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.


### 3.3.3 Test Setup

#### Radiated Emissions below 30 MHz





Note: Test distance is 3m

#### Radiated Emissions 30 ~ 1 GHz





### 3.3.4 Transmitter Radiated Unwanted Emissions (Below 30GHz)





### 3.3.5 Transmitter Radiated Unwanted Emissions (Above 30MHz)

<b>Polarization</b>	Horizontal	<b>Test Freq. (MHz)</b>	13.56																																																																						
<b>Test Mode</b>	NFC																																																																								
																																																																									
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission Limit</th> <th>Margin</th> <th>SA</th> <th>Factor</th> <th>Remark</th> <th>ANT</th> <th>Turn</th> </tr> <tr> <th>MHz</th> <th>level</th> <th>dBuV/m</th> <th>dB</th> <th>reading</th> <th></th> <th>High</th> <th>Table</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>40.67</td> <td>27.91</td> <td>40.00</td> <td>-12.09</td> <td>44.49</td> <td>-16.58</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>2</td> <td>230.79</td> <td>28.20</td> <td>46.00</td> <td>-17.80</td> <td>46.18</td> <td>-17.98</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>569.32</td> <td>37.93</td> <td>46.00</td> <td>-8.07</td> <td>48.03</td> <td>-10.10</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>4</td> <td>705.12</td> <td>37.51</td> <td>46.00</td> <td>-8.49</td> <td>45.46</td> <td>-7.95</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>732.28</td> <td>42.42</td> <td>46.00</td> <td>-3.58</td> <td>49.85</td> <td>-7.43</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>6</td> <td>786.60</td> <td>37.04</td> <td>46.00</td> <td>-8.96</td> <td>43.84</td> <td>-6.80</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>				Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn	MHz	level	dBuV/m	dB	reading		High	Table	1	40.67	27.91	40.00	-12.09	44.49	-16.58	Peak	---	2	230.79	28.20	46.00	-17.80	46.18	-17.98	Peak	---	3	569.32	37.93	46.00	-8.07	48.03	-10.10	Peak	---	4	705.12	37.51	46.00	-8.49	45.46	-7.95	Peak	---	5	732.28	42.42	46.00	-3.58	49.85	-7.43	Peak	---	6	786.60	37.04	46.00	-8.96	43.84	-6.80	Peak	---
Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																		
MHz	level	dBuV/m	dB	reading		High	Table																																																																		
1	40.67	27.91	40.00	-12.09	44.49	-16.58	Peak	---																																																																	
2	230.79	28.20	46.00	-17.80	46.18	-17.98	Peak	---																																																																	
3	569.32	37.93	46.00	-8.07	48.03	-10.10	Peak	---																																																																	
4	705.12	37.51	46.00	-8.49	45.46	-7.95	Peak	---																																																																	
5	732.28	42.42	46.00	-3.58	49.85	-7.43	Peak	---																																																																	
6	786.60	37.04	46.00	-8.96	43.84	-6.80	Peak	---																																																																	
Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit. Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition. Note 3: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.																																																																									

<b>Polarization</b>	Vertical	<b>Test Freq. (MHz)</b>	13.56																																																																						
<b>Test Mode</b>	NFC																																																																								
																																																																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">Freq. MHz</th> <th style="text-align: center;">Emission level dBuV/m</th> <th style="text-align: center;">Limit dBuV/m</th> <th style="text-align: center;">Margin dB</th> <th style="text-align: center;">SA reading dBuV</th> <th style="text-align: center;">Factor dB</th> <th style="text-align: center;">Remark</th> <th style="text-align: center;">ANT High cm</th> <th style="text-align: center;">Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td style="text-align: center;">40.67</td> <td style="text-align: center;">35.00</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-5.00</td> <td style="text-align: center;">51.58</td> <td style="text-align: center;">-16.58</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>2</td> <td style="text-align: center;">67.83</td> <td style="text-align: center;">26.16</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-13.84</td> <td style="text-align: center;">44.88</td> <td style="text-align: center;">-18.72</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>3</td> <td style="text-align: center;">94.99</td> <td style="text-align: center;">20.80</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-22.70</td> <td style="text-align: center;">43.03</td> <td style="text-align: center;">-22.23</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>4</td> <td style="text-align: center;">149.31</td> <td style="text-align: center;">19.87</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-23.63</td> <td style="text-align: center;">36.52</td> <td style="text-align: center;">-16.65</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>5</td> <td style="text-align: center;">230.79</td> <td style="text-align: center;">22.14</td> <td style="text-align: center;">46.00</td> <td style="text-align: center;">-23.86</td> <td style="text-align: center;">40.12</td> <td style="text-align: center;">-17.98</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>6</td> <td style="text-align: center;">732.28</td> <td style="text-align: center;">31.84</td> <td style="text-align: center;">46.00</td> <td style="text-align: center;">-14.16</td> <td style="text-align: center;">39.27</td> <td style="text-align: center;">-7.43</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> </tbody> </table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	40.67	35.00	40.00	-5.00	51.58	-16.58	Peak	---	---	2	67.83	26.16	40.00	-13.84	44.88	-18.72	Peak	---	---	3	94.99	20.80	43.50	-22.70	43.03	-22.23	Peak	---	---	4	149.31	19.87	43.50	-23.63	36.52	-16.65	Peak	---	---	5	230.79	22.14	46.00	-23.86	40.12	-17.98	Peak	---	---	6	732.28	31.84	46.00	-14.16	39.27	-7.43	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	40.67	35.00	40.00	-5.00	51.58	-16.58	Peak	---	---																																																																
2	67.83	26.16	40.00	-13.84	44.88	-18.72	Peak	---	---																																																																
3	94.99	20.80	43.50	-22.70	43.03	-22.23	Peak	---	---																																																																
4	149.31	19.87	43.50	-23.63	36.52	-16.65	Peak	---	---																																																																
5	230.79	22.14	46.00	-23.86	40.12	-17.98	Peak	---	---																																																																
6	732.28	31.84	46.00	-14.16	39.27	-7.43	Peak	---	---																																																																

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 3: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.

## 3.4 Frequency Stability


### 3.4.1 Frequency Stability Limit

Carrier frequency stability shall be maintained to  $\pm 0.01\%$  ( $\pm 100$  ppm).

### 3.4.2 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.8 for frequency stability tests
<input checked="" type="checkbox"/> Frequency stability with respect to ambient temperature
<input checked="" type="checkbox"/> Frequency stability when varying supply voltage
<input type="checkbox"/> For conducted measurement.
<input checked="" type="checkbox"/> For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.

### 3.4.3 Test Setup



### 3.4.4 Test Result of Frequency Stability

Frequency Stability Result									
Condition	Ch. Freq. (MHz)	Frequency Stability (ppm)							
		0 Min	2 Min	5Min	10Min				
T <sub>20°C</sub> Vmax	13.56	23.60	20.65	23.60	24.34				
T <sub>20°C</sub> Vmin	13.56	24.34	26.55	24.34	24.34				
T <sub>50°C</sub> Vnom	13.56	22.12	22.86	20.65	24.34				
T <sub>40°C</sub> Vnom	13.56	22.12	23.60	22.12	25.07				
T <sub>30°C</sub> Vnom	13.56	23.60	22.12	19.17	21.39				
T <sub>20°C</sub> Vnom	13.56	23.45	22.12	22.86	25.81				
T <sub>10°C</sub> Vnom	13.56	21.39	21.39	28.76	24.34				
T <sub>0°C</sub> Vnom	13.56	27.29	20.65	22.12	22.12				
T <sub>-10°C</sub> Vnom	13.56	22.86	20.65	24.34	27.29				
T <sub>-20°C</sub> Vnom	13.56	19.91	26.55	25.07	24.34				
T <sub>-30°C</sub> Vnom	13.56	24.34	25.81	28.76	25.81				
Limit (ppm)		100							
Note 1: Measure at 85 % [Vmin] and 115 % [Vmax] of the nominal voltage [Vnom]. The nominal voltage refer test report clause 1.1.4 for EUT operational condition.									
Note 2: Measure maximum deviation frequency at operating frequency at startup and two, five, and ten min.									

## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

### Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan,  
R.O.C.

### Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

### Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: [ICC\\_Service@icertifi.com.tw](mailto:ICC_Service@icertifi.com.tw)

==END==