

RF EXPOSURE REPORT (FOR BLUETOOTH)

REPORT NO.: SA110509C01-2

MODEL NO.: F-12C

FCC ID: VQK-F12C

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: FUJITSU LIMITED

ADDRESS: 1-1, Kamikodanaka 4-chome, Nakahara-ku,
Kawasaki 211-8588, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Jun. 08, 2011

CERTIFICATION

PRODUCT: Mobile Phone
MODEL NO.: F-12C
BRAND: FOMA
APPLICANT: FUJITSU LIMITED
TESTED: May 26 ~ Jun. 01, 2011
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Guidelines for Human Exposure**
IEEE C95.1

The above equipment (model: F-12C) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Andrea Hsia , DATE: Jun. 08, 2011
Andrea Hsia / Specialist

APPROVED BY : Gary Chang , DATE: Jun. 08, 2011
Gary Chang / Assistant Manager

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	-2.6	0.6
EIRP Power	-10.8	0.1

***Note:** The antenna is $\lambda/4$ Monopole with -8.2dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 0.1mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold