Issue Date: 18 March 2008 Report No.: RY0803Z18R1

Model: F906i

Test setup photographs Definition of the EUT axis 3

3.1





The following configuration is defined as Y-Plane



RF Technologies Ltd.472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45- 534-0645, FAX: +81+(0)45- 534-0646, Web: http://www.rft.jp



The following configuration is defined as ${\bf Z}\text{-Plane}$



RF Technologies Ltd.472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45-534-0645, FAX: +81+(0)45-534-0646, Web: http://www.rft.jp



Radiated spurious emissions 3.2

Below 30 MHz





RF Technologies Ltd.472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45- 534-0645, FAX: +81+(0)45- 534-0646, Web: http://www.rft.jp







RF Technologies Ltd.472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45-534-0645, FAX: +81+(0)45-534-0646, Web: http://www.rft.jp



AC power line conducted emissions



RF Technologies Ltd.472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45-534-0645, FAX: +81+(0)45-534-0646, Web: http://www.rft.jp