



TEST REPORT

No. I14N00955-EMC

for

ShenZhen Sang Fei Consumer Communications Co.,Ltd.

WCDMA digital mobile phone

Model Name: Philips I908

Marketing Name: Philips I908

FCC ID: VQRCTI908

with

Hardware Version: I908_V01

Software Version: Philips_I908_V01

Issued Date: 2014-10-21

Test Laboratory:

FCC 2.948 Listed: No.310359

IC O.A.T.S listed: No.6629C-1

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633-2678 , Fax:+86(0)10-62304633-2504 Email:welcme@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE.....	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
3.4. EUT SET-UPS	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS	9
7. TEST EQUIPMENTS UTILIZED	10
ANNEX A: MEASUREMENT RESULTS.....	11

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Shenzhen, Telecommunication Metrology Center of MIIT
Address: No. 12 Building, Shangsha Innovation and Technology Park, Futian District
Postal Code: 518048
Telephone: +86(0)755-33322000
Fax: +86(0)755-33322001

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2014-08-22
Testing End Date: 2014-09-22

1.4. Signature



Du Zhaoxuan

(Prepared this test report)



Zhang Bojun

(Reviewed this test report)



Lu Minniu

Director of the laboratory

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: ShenZhen Sang Fei Consumer Communications Co.,Ltd.
Address /Post: 11 Science and Technology Road, Shenzhen Hi-tech industrial Park
Nanshan District, Shenzhen 518057,PRC
City: ShenZhen
Postal Code: 518000
Country: China

2.2. Manufacturer Information

Company Name: ShenZhen Sang Fei Consumer Communications Co.,Ltd.
Address /Post: 11 Science and Technology Road, Shenzhen Hi-tech industrial Park
Nanshan District, Shenzhen 518057,PRC
City: ShenZhen
Postal Code: 518000
Country: China

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	WCDMA digital mobile phone
Model Name	Philips I908
Marketing Name	Philips I908
FCC ID	VQRCTI908

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	/	I908_V01	Philips_I908_V01

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	/
AE2	Travel charger	/
AE3	USB cable	/

AE1

Model	AB3000CWMC
Manufacturer	Shenzhen Sang Fei Consumer Communications Co., Ltd.
Capacitance	3000mAh
Nominal voltage	3.8V

AE2

Model	A31-501000
Manufacturer	DONGGUAN AOHAI POWER TECHNOLOGY CO,LTS.
Length of cable	98cm

AE3

Model	/
Manufacturer	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1 + AE2	Charging mode
Set.2	EUT1+ AE1 + AE3	USB mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-2013 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (11.20 meters×6.10meters×5.60meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. =35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (11.20 meters×6.10 meters×6.60 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 6 GHz, 3 m distance

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Radiated Emission	15.109(a)	A.1	P
2	Conducted Emission	15.107(a)	A.2	P

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CAL PERIOD
1	Test Receiver	ESCI	100701	R&S	2015.07.30	1 year
2	Test Receiver	ESCI	100702	R&S	2015.07.30	1 year
3	Spectrum Analyzer	FSP 40	100378	R&S	2014.12.20	1 year
4	BiLog Antenna	VULB9163	9163 329	Schwarzbeck	2017.01.20	3 years
5	LISN	ESH2-Z5	100196	R&S	2015.01.14	1 year
6	Dual-Ridge Waveguide Horn Antenna	3117	00066577	ETS-Lindgren	2016.04.01	3 years
7	Universal Radio Communication Tester	E5515C	GB44051324	Agilent	2015.05.20	1 year

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission (§15.109(a))

Reference

FCC: CFR Part 15.109(a)

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.1.3 Measurement Limit

Limit from CFR Part 15.109(a)

Frequency range (MHz)	Field strength limit ($\mu\text{V}/\text{m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

*Note: The original limit is defined at 10m test distance. This limit is calculated according to CISPR requirements.

A.1.4 Test Condition

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz (IF bandwidth)	5
Above 1000	1MHz/3MHz	15

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Note: the result contains vertical part and Horizontal part

Set.1 Charging mode / Peak detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A_{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
8259.000000	49.0	V	8.0	25.0	74.0
8568.000000	50.0	V	8.0	24.0	74.0
8811.000000	49.5	V	8.9	24.5	74.0
9261.000000	50.5	H	9.2	23.5	74.0
9457.000000	50.6	V	9.5	23.4	74.0
9748.000000	50.8	V	9.7	23.2	74.0

Set.1 Charging mode / Average detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A_{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
8302.000000	36.8	H	8.0	17.2	54.0
8719.000000	37.7	V	8.5	16.3	54.0
8770.000000	37.7	H	8.7	16.3	54.0
9335.000000	38.4	H	9.4	15.6	54.0
9592.000000	38.6	V	9.7	15.4	54.0
9962.000000	39.0	V	10.4	15.0	54.0

Set.2 USB mode / Peak detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
8168.625000	48.2	H	7.9	25.8	74.0
8607.000000	50.3	V	8.1	23.7	74.0
8889.625000	49.5	V	8.9	24.5	74.0
9323.625000	50.3	H	9.4	23.7	74.0
9534.500000	51.2	H	9.7	22.8	74.0
9967.625000	51.6	H	10.4	22.4	74.0

Set.2 USB mode / Average detector

Frequency(MHz)	Result(dBuV/m)	Polarity	A _{Rpl} (dB)	Margin(dB)	Limit (dB μ V/m)
8170.375000	39.4	V	7.9	14.6	54.0
8719.000000	40.8	H	8.5	13.2	54.0
8984.125000	40.5	V	9.0	13.5	54.0
9298.250000	40.9	V	9.4	13.1	54.0
9424.250000	41.3	H	9.5	12.7	54.0
9765.500000	41.8	H	9.7	12.2	54.0




Figure A.1 Radiated Emission from 30MHz to 1GHz (Set.1, Charging mode)




Figure A.2 Radiated Emission from 1GHz to 18GHz (Set.1, Charging mode)




Figure A.3 Radiated Emission from 30MHz to 1GHz (Set.2, USB mode)




Figure A.4 Radiated Emission from 1GHz to 18GHz (Set.2, USB mode)

A.2 Conducted Emission (§15.107(a))

Reference

FCC: CFR Part 15.107(a)

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 7.2.

A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results




Figure A.5 Conducted Emission (Set.1, Charging mode)

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.618000	35.5	FLO	L1	10.0	20.5	56.0
0.662000	48.1	FLO	L1	10.0	7.9	56.0
0.718000	40.3	FLO	L1	10.0	15.7	56.0
0.762000	51.8	FLO	L1	10.1	4.2	56.0
0.810000	52.0	FLO	L1	10.1	4.0	56.0
0.866000	46.6	FLO	L1	10.1	9.4	56.0

Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.410000	34.3	FLO	L1	10.0	13.4	47.6
0.454000	40.6	FLO	L1	10.0	6.2	46.8
0.654000	39.1	FLO	L1	10.0	6.9	46.0
0.706000	42.7	FLO	L1	10.0	3.3	46.0
0.758000	44.7	FLO	L1	10.1	1.3	46.0
0.810000	44.6	FLO	L1	10.1	1.4	46.0

ESH2-Z5 Scan-FCC




Figure A.6 Conducted Emission (Set.2, USB mode)

Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.726000	47.7	FLO	L1	10.0	8.3	56.0
0.754000	44.4	FLO	L1	10.1	11.6	56.0
0.782000	43.7	FLO	L1	10.1	12.3	56.0
0.830000	46.2	FLO	L1	10.0	9.8	56.0
0.858000	44.5	FLO	L1	10.0	11.5	56.0
0.886000	41.6	FLO	L1	10.1	14.4	56.0

Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.414000	37.6	FLO	L1	10.0	10.0	47.6
0.622000	35.4	FLO	L1	10.0	10.6	46.0
0.674000	36.4	FLO	L1	10.0	9.6	46.0
0.726000	37.7	FLO	L1	10.0	8.3	46.0
0.778000	37.3	FLO	L1	10.1	8.7	46.0
0.830000	36.3	FLO	L1	10.0	9.7	46.0

END OF REPORT