



# TEST REPORT

No. 2008TAR017

for

**Shenzhen Sang Fei Consumer Communications Co., Ltd.**

**GSM/GPRS 900/1800/1900 digital mobile phone**

**Type: Xenium X500**

with

**Hardware Version: PR1**

**Software Version: C6033\_PR1\_V06\_080429CN**

**Issued Date: Jun 20th, 2008**



**No. DAT-P-114/01-01**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

TMC Beijing, Telecommunication Metrology Center of Ministry of Information Industry

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100083.

Tel:+86(0)10-62303288-2105, Fax:+86(0)10-62304793 Email:welcme@emcite.com. [www.emcite.com](http://www.emcite.com)

©Copyright. All rights reserved by TMC Beijing.

## **CONTENTS**

<b>1. TEST LABORATORY.....</b>	<b>3</b>
1.1. TESTING LOCATION.....	3
1.2. TESTING ENVIRONMENT.....	3
1.3. PROJECT DATA.....	3
1.4. SIGNATURE.....	3
<b>2. CLIENT INFORMATION.....</b>	<b>4</b>
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
3.1. ABOUT EUT.....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. GENERAL DESCRIPTION.....	6
<b>4. REFERENCE DOCUMENTS .....</b>	<b>6</b>
4.1. REFERENCE DOCUMENTS FOR TESTING.....	6
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>6</b>
<b>6. SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>7. TEST EQUIPMENTS UTILIZED.....</b>	<b>7</b>
<b>ANNEX A: EUT PHOTOGRAPH.....</b>	<b>8</b>
<b>ANNEX B: MEASUREMENT RESULTS.....</b>	<b>14</b>
B.1 OUTPUT POWER (§22.913(A)/§24.232(B)) .....	14
B.2 EMISSION LIMIT (§2.1051/§24.238).....	16
B.3 CONDUCTED EMISSION.....	23
B.4 FREQUENCY STABILITY (§2.1055/§24.235).....	26
B.5 OCCUPIED BANDWIDTH (§2.1049(H)(I)) .....	28
B.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B)) .....	34
B.7 BAND EDGE COMPLIANCE.....	40
B.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238).....	43
<b>ANNEX C: TEST LAYOUT .....</b>	<b>48</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MII  
Address: No 52, Huayuan beilu, Haidian District, Beijing,P.R.China  
Postal Code: 100083  
Telephone: 00861062303288  
Fax: 00861062304793

### 1.2. Testing Environment

Normal Temperature: 15-35℃  
Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: May 18th, 2008  
Testing End Date: May 25th, 2008


### 1.4. Signature



---

Zi Xiaogang


(Prepared this test report)



---

Sun Xiangqian

(Reviewed this test report)



---

Lu Bingsong

Deputy Director of the laboratory

(Approved this test report)

## **2. Client Information**

### **2.1. Applicant Information**

Company Name: Shenzhen Sang Fei Consumer Communications Co., Ltd.  
Address /Post: 11 Science and Technology Road, Shenzhen Hi-tech Industrial Park  
Nanshan District, Shenzhen, PRC  
City: Shenzhen  
Postal Code: 518057  
Country: China  
Telephone: +86-755-26633217  
Fax: +86-755-26635272

### **2.2. Manufacturer Information**

Company Name: Shenzhen Sang Fei Consumer Communications Co., Ltd.  
Address /Post: 11 Science and Technology Road, Shenzhen Hi-tech Industrial Park  
Nanshan District, Shenzhen, PRC  
City: Shenzhen  
Postal Code: 518057  
Country: China  
Telephone: +86-755-26633217  
Fax: +86-755-26635272

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	GSM/GPRS 900/1800/1900 digital mobile phone
Model	Xenium X500
FCC ID	VQRCTX500
Frequency	PCS 1900 MHz
Antenna	Internal
Power supply	Battery or Charger (AC Adaptor)
Output power	25.39 dBm maximum EIRP measured for PCS1900
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7 VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Photographs of EUT are shown in ANNEX A of this test report. Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MII of People's Republic of China.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
EUT1	354453020001361	PR1	C6033_PR1_V06_080429CN

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>	<b>SN</b>
AE1	Battery	XWCH0434680
AE2	Travel Adapter	433900875011

##### AE1

Model	AB1720AWM
Manufacturer	Shenzhen Xwoda Group.Co.Ltd.
Capacitance	1720mAh
Nominal Voltage	3.7V

##### AE2

Model	DSA-5W-05 FUS 050065
Manufacturer	DeeVan Electronics(Shenzhen) Co.,Ltd
Length of DC line	120cm

\*AE ID: is used to identify the test sample in the lab internally.

### 3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/GPRS Phone with integrated antenna. It consists of Hand Telephone Set and normal options: lithium battery, charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.06

## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber** (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

**Control room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber** (6.8 meters×3.08 meters×3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB

Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

## 6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Conducted Emission	15.107/207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P

## 7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESS	847151/015	R&S	2008-10-30
2	Test Receiver	ESI40	831564/002	R&S	2009-2-11
3	BiLog Antenna	3142B	9908-1403	EMCO	2009-1-16
4	BiLog Antenna	3142B	9908-1405	EMCO	2009-9-19
5	Signal Generator	SMT06	831285/005	R&S	2008-12-26
6	Signal Generator	SMP04	100070	R&S	2009-4-20
7	LISN	ESH2-Z5	829991/012	R&S	2008-8
8	Spectrum Analyzer	FSU26	200030	R&S	2009-6-18
9	Universal Radio Communication Tester	CMU200	100680	R&S	2008-8-23
10	Dual-Ridge Waveguide Horn Antenna	3115	9906-5827	EMCO	2009-3
11	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2009-3
12	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2009-3
13	Climatic chamber	PL-2G	343074	ESPEC	2009-5-15

**ANNEX A: EUT photograph**

**External Photo**



**Mobile Phone**



**Mobile Phone**






Charger (AC/DC Adapter)



Label of Charger (AC/DC Adapter)



Battery



Battery

**Internal Photo**




**Mobile phone Disassembly**




**Mobile phone Disassembly**



Mobile phone Disassembly



Mobile phone Disassembly



Mobile phone Disassembly

## **ANNEX B: MEASUREMENT RESULTS**

### **B.1 OUTPUT POWER** (§22.913(a)/§24.232(b))

#### **B.1.1 Summary**

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation.

This result contains peak output power and EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

#### **B.1.2 Conducted**

##### **B.1.2.1 Method of Measurements**

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0 MHz and 1909.8 MHz for PCS1900 band (bottom, middle and top of operational frequency range).

#### **PCS1900**

##### **Limit**

Power step	Nominal Peak output power (dBm)	Tolerance (dB)
0	30dBm(1W)*	± 2

\*GSM Specification – ETSI EN 300 910 V8.5.1 (2000-11) Section 4.1

#### **Measurement result**

##### **PCS**

Frequency(MHz)	Conducted Output Power(dBm)
1850.2	29.44
1880.0	29.14
1909.8	28.59

##### **GPRS**

Frequency(MHz)	Conducted Output Power(dBm)
1850.2	29.37
1880.0	28.96
1909.8	28.64

##### **EGPRS**

Frequency(MHz)	Conducted Output Power(dBm)
1850.2	29.22
1880.0	28.82
1909.8	28.40

**B.1.3 Radiated**

**B.1.3.1 Description**

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

**B.1.3.2 Method of Measurement**

1. In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (Pin) is applied to the input of the dipole, and the power received (Pr) at the chamber's probe antenna is recorded.
2. A "reference path loss" is established as  $Pin + 2.15 - Pr$ .
3. The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
4. From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
5. The EUT is then put into pulse mode at its maximum power level (Power Step 0 for PCS1900, 5 for GSM 850).
6. "Gated mode" power measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
7. This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (Pin).
8. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15dBi$ .

**PCS1900-EIRP 24.232(b)**

**Limits**

Power Step	Burst Peak EIRP (dBm)
0	≤33dBm (2W)

**Measurement result**

**PCS**

Frequency(MHz)	Peak EIRP(dBm)
1850.2	24.06
1880.0	24.83
1909.8	25.39

**GPRS**

Frequency(MHz)	Peak EIRP(dBm)
1850.2	23.15
1880.0	23.97
1909.8	24.63

**EGPRS**

Frequency(MHz)	Peak EIRP(dBm)
1850.2	18.32
1880.0	17.23
1909.8	16.19

**B.2 EMISSION LIMIT (§2.1051/§24.238)**

**B.2.1 Measurement Method**

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the PCS1900.


**The procedure of radiated spurious emissions is as follows:**

a) Pre-calibration

With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as,

$$RSE = R_x \text{ (dBuV)} + CL \text{ (dB)} + SA \text{ (dB)} + Gain \text{ (dBi)} - 107 \text{ (dBuV to dBm)}$$

The SA is calibrated using following setup.




b) EUT test

EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all



non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



### B.2.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power ( $P$ , in Watts) by at least  $43 + 10 \log(P)$  dB. The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### B.2.3 Measurement Results


Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

**NOTE: The spurious emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels.**

**PCS 1900**


**B.2.3.9 RADIATED SPURIOUS EMISSIONS-Channel 512: 30MHz – 2GHz**

**NOTE: peak above the limit line is the Carrier frequency @ ch-512**




**B.2.3.10 RADIATED SPURIOUS EMISSIONS-Channel 661: 30MHz – 2GHz**

**NOTE: peak above the limit line is the Carrier frequency @ ch-661**




**B.2.3.11 RADIATED SPURIOUS EMISSIONS-Channel 810: 30MHz – 2GHz**

**NOTE: peak above the limit line is the Carrier frequency @ ch-810**




**B.2.3.12 RADIATED SPURIOUS EMISSIONS-Channel 512: 2GHz – 18GHz**




— FCC -13dBm — Preview Measurement Detector 1

**B.2.3.13 RADIATED SPURIOUS EMISSIONS-Channel 661: 2GHz – 18GHz**



— FCC -13dBm      — Preview Measurement Detector 1


**B.2.3.14 RADIATED SPURIOUS EMISSIONS-Channel 810: 2GHz – 18GHz**




— FCC -13dBm      — Preview Measurement Detector 1

**B.2.3.15 Radiated spurious emission (18GHz-20GHz)**


**Note: This plot is valid for low, mid & high channels. It is same as the floor noise.**



**B.2.3.16 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 30MHz – 2GHz**




**B.2.3.17 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 2GHz – 18GHz**



— FCC -13dBm      — Preview Measurement Detector 1

**B.2.3.18 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 18GHz – 20GHz**

**Note: It is same as the floor noise.**



### **B.3 CONDUCTED EMISSION** (§15.107§15.207)

The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.


#### **B.3.1 Limit**

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50


\* Decreases with logarithm of the frequency

#### **B.3.2 Measurement result**


##### **PCS 1900MHz**



### Bluetooth




### Camera





MP3



## **B.4 FREQUENCY STABILITY (§2.1055/§24.235)**

### **B.4.1 Method of Measurement**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 and channel 190 for GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 (centre channel), measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

### **B.4.2 Measurement Limit**

#### **B.4.2.1 For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.6VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

#### **B.4.2.2 For equipment powered by primary supply voltage**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

#### B.4.3 Measurement results

##### PCS 1900

##### Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	25	0.013
3.7	21	0.011
4.2	27	0.014

##### Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	35	0.019
-20	33	0.018
-10	30	0.016
0	30	0.016
10	26	0.014
20	22	0.012
30	25	0.013
40	29	0.015
50	34	0.018

## **B.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))**

### **B.5.1 Occupied Bandwidth Results**

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the USPCS frequency band. The table below lists the measured -20dBc BW (99%). Spectrum analyzer plots are included on the following pages.


#### **PCS 1900(-20dBc)**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( kHz)
1850.2	277.242
1880.0	275.640
1909.8	274.038

**ANALYZER SETTINGS: RBW=VBW=3kHz**


#### **PCS**

#### **Channel 512-Occupied Bandwidth (-20dBc BW)**




Date: 20.MAY.2008 07:31:22

### Channel 661-Occupied Bandwidth (-20dBc BW)



Date: 20.MAY.2008 07:33:52

### Channel 810-Occupied Bandwidth (-20dBc BW)



Date: 20.MAY.2008 07:36:16


**GPRS**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( kHz)
1850.2	267.627
1880.0	280.448
1909.8	274.037

**ANALYZER SETTINGS: RBW=VBW=3kHz**


**GPRS**

**Channel 512-Occupied Bandwidth (-20dBc BW)**




Date: 20.MAY.2008 07:58:21

### Channel 661-Occupied Bandwidth (-20dBc BW)



Date: 20.MAY.2008 08:00:58

### Channel 810-Occupied Bandwidth (-20dBc BW)



Date: 20.MAY.2008 08:03:20


**EGPRS**

Frequency(MHz)	Occupied Bandwidth (-20dBc BW)( kHz)
1850.2	253.204
1880.0	264.422
1909.8	262.820

**ANALYZER SETTINGS: RBW=VBW=3kHz**

**EGPRS**


**Channel 512-Occupied Bandwidth (-20dBc BW)**



Date: 20.MAY.2008 08:17:32




### Channel 661-Occupied Bandwidth (-20dBc BW)



Date: 20.MAY.2008 08:20:10

### Channel 810-Occupied Bandwidth (-20dBc BW)



Date: 20.MAY.2008 08:22:26

**B.6 EMISSION BANDWIDTH** (§22.917(b)/§24.238(b))

**B.6.1 Emission Bandwidth Results**

Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the PCS1900 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.


**PCS 1900(-26dBc)**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
1850.2	315.704
1880.0	314.101
1909.8	315.705

**ANALYZER SETTINGS: RBW=VBW=3kHz;**


**PCS 1900**

**Channel 512-Occupied Bandwidth (-26dBc BW)**




Date: 20.MAY.2008 07:31:46

### Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 20.MAY.2008 07:34:19

### Channel 810-Occupied Bandwidth (-26dBc BW)



Date: 20.MAY.2008 07:36:54


**GPRS**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
1850.2	315.706
1880.0	320.512
1909.8	315.704

**ANALYZER SETTINGS: RBW=VBW=3kHz;**


**GPRS**

**Channel 512-Occupied Bandwidth (-26dBc BW)**




Date: 20.MAY.2008 07:58:58

### Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 20.MAY.2008 08:01:31

### Channel 810-Occupied Bandwidth (-26dBc BW)



Date: 20.MAY.2008 08:03:50


**EGPRS**

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)( kHz)
1850.2	304.487
1880.0	312.500
1909.8	312.499

**ANALYZER SETTINGS: RBW=VBW=3kHz;**


**EGPRS**

**Channel 512-Occupied Bandwidth (-26dBc BW)**




Date: 20.MAY.2008 08:18:01

### Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 20.MAY.2008 08:20:43

### Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 20.MAY.2008 08:22:55


**B.7 BAND EDGE COMPLIANCE**      (**§22.917(b)/§24.238(b)**)

**PCS 1900**

**LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512**




**HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810**






**GPRS**  
**LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512**




Date: 20.MAY.2008 08:05:45

**HIGH BAND EDGE BLOCK-C (PCS-1900) -Channel 810**




Date: 20.MAY.2008 08:06:31

**EGPRS**  
**LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512**



Date: 20.MAY.2008 08:24:06

**LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 810**



Date: 20.MAY.2008 08:24:49

**B.8 CONDUCTED SPURIOUS EMISSION** (§2.1057/§22.917/§24.238)

**B.8.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

**PCS1900 Transmitter**

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

**B. 8.2 Measurement Limit**

Sec. 24.238 Emission Limits.

(a) On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least  $43+10\log(P)$  dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

**B. 8.3 Measurement result**

**PCS1900**


Harmonic	Tx ch. 512 Freq. (MHz)	Level (dBm)	Tx ch. 661 Freq. (MHz)	Level (dBm)	Tx ch. 810 Freq. (MHz)	Level (dBm)
2	3700.4	nf	3760	nf	3819.6	nf
3	5550.6	nf	5640	nf	5729.4	nf
4	7400.8	nf	7520	nf	7639.2	nf
5	9251.0	nf	9400	nf	9549.0	nf
6	11101.2	nf	11280	nf	11458.8	nf
7	12951.4	nf	13160	nf	13368.6	nf
8	14801.6	nf	15040	nf	15278.4	nf
9	16651.8	nf	16920	nf	17188.2	nf
10	18502.0	nf	18800	nf	19098.0	nf

nf: Noise floor

### A. 8.3.1 Channel 512: 30MHz – 4GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 20.MAY.2008 07:43:20

### A. 8.3.2 Channel 512: 4GHz – 20GHz

Spurious emission limit –13dBm.




Date: 20.MAY.2008 07:41:06

### A. 8.3.3 Channel 661: 30MHz – 4GHz

Spurious emission limit –13dBm


**NOTE: peak above the limit line is the carrier frequency.**



Date: 20.MAY.2008 07:42:39

### A. 8.3.4 Channel 661: 4GHz –20GHz

Spurious emission limit –13dBm




Date: 20.MAY.2008 07:41:56

### A. 8.3.5 Channel 810: 30MHz – 4GHz

Spurious emission limit –13dBm.


**NOTE: peak above the limit line is the carrier frequency.**



Date: 20.MAY.2008 07:44:10

### A. 8.3.6 Channel 810: 4GHz – 20GHz


Spurious emission limit –13dBm.



Date: 20.MAY.2008 07:44:51

**A. 8.3.7 Idle mode: 30MHz – 4GHz**


Spurious emission limit -13dBm.



Date: 20.MAY.2008 07:46:42

**A. 8.3.8 Idle mode: 4GHz – 20GHz**

Spurious emission limit -13dBm.



Date: 20.MAY.2008 07:46:02

**ANNEX C: TEST LAYOUT**



**Pic C-1 Conducted Emission**



**Pic C-2 Radiated Spurious Emission**

**\*\*\*END OF REPORT\*\*\***