Rhein Tech Laboratories, Inc. 360 Herndon Parkway Suite 1400 Herndon, VA 20170 http://www.rheintech.com Client: Medeco Security Locks, Inc. Model: EA-150092 Standards: FCC 15.247/IC RSS-247 ID's: VR3-92/7465A-92 Report #: 2016160

## Appendix A: FCC Part 1.1307, 1.1310, 2.1091, 2.1093; IC RSS-Gen: RF Exposure

According to KDB 447498 D01 General RF Exposure Guidance v05 4.3.1. Standalone SAR test exclusion considerations, unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

## Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] [ $\sqrt{f(GHz)}$ ]  $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before the calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is <5 mm, a distance of 5 mm is applied to determine SAR test exclusion

## **EUT RF Exposure**

The max conducted peak output power is 0.05 mW at 2402 MHz.

The maximum gain of the antenna is 1 dBi / 1.3 numeric (from antenna specification)

EIRP =  $0.05 \text{ mW} \times 1.3 = 0.07 \text{ mW}$  (rounding to the nearest mW = 0.1 mW)

General RF Exposure = (0.1 mW / 5 mm ) x  $\sqrt{2.402}$  GHz = 0.03

Therefore, SAR test is not required since the result is below the ≤3.0 1-g SAR limit.

## IC RSS-102 Issue 5 Technical Brief

Per section 2.5.1 Table 1, this device is exempt from SAR as the output power is less than the Exemption Limits at a separation distance of less than or equal to 5 mm.