

# Electromagnetic Compatibility Test Report

*Prepared in accordance with*

**Product Standard:**

**FCC Part 15: 2007, RSS-210: 2007**

on

## **Lighting Control System**

## **Radio Bridge**

Prepared for:

Sensor Switch, Inc.

900 Northrop Road

Wallingford, CT 06492

Prepared by:

**TUV Rheinland of North America, Inc.**

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

<b>Auftraggeber:</b> <i>Client:</i>		Sensor Switch, Inc. 900 Northrop Road Wallingford, CT 06492			
<b>Bezeichnung:</b> <i>Identification:</i>	Lighting Control System	<b>Serien-Nr.:</b> <i>Serial No.</i>	PROTOYPE		
<b>Gegenstand der Prüfung:</b> <i>Test item:</i>	Radio Bridge	<b>Prüfdatum:</b> <i>Date tested:</i>	October 8th -10th 2007		
<b>Prüfört:</b> <i>Testing location:</i>	TUV Rheinland of North America 12 Commerce Road Newtown, CT 06470-1607 NVLAP # 200111-0				
<b>Prüfgrundlage:</b> <i>Test specification:</i>	FCC Part 15: FCC Part 15C Section 15.247 FCC Part 15.247 (a)(2), FCC Par 15.247 (b)(3), FCC Part 15.247 (b)(5) and 1.1310, FCC Part 15.247 (c), 15.205, 15.209, FCC Part 15, FCC Part 15.247 (d), FCC Part 15.215 (b), FCC Part 15.215 (c), RSS-210				
<b>Prüfergebnis:</b> <i>Test Result</i>	<b>Der vorstehend beschriebene Prüfgegenstand wurde geprüft und entspricht oben genannter Prüfgrundlage. The above product was found to be Compliant to the above test standard(s)</b>				
<b>geprüft / tested by:</b> Dieter Baldamus		<b>kontrolliert / reviewed by:</b> Bruce Fagley			
16 July 2008		16 July 2008			
<b>Datum</b> <i>Date</i>	<b>Name</b> <i>Name</i>	<b>Unterschrift</b> <i>Signature</i>	<b>Datum</b> <i>Date</i>	<b>Name</b> <i>Name</i>	<b>Unterschrift</b> <i>Signature</i>
<b>Sonstiges :</b> <i>Other Aspects:</i>	None				
Abkürzungen: OK, Pass, Compliant, Complies = entspricht Prüfgrundlage Fail, Not Compliant, Does not Comply = entspricht nicht Prüfgrundlage N/A = nicht anwendbar	Abbreviations: OK, Pass, Compliant, Complies = passed Fail, Not Compliant, Does Not Comply = failed N/A = not applicable				
			Industry Canada		
US5112	200111-0		3466D-1		

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

## TABLE OF CONTENTS

<b>1 GENERAL INFORMATION .....</b>	<b>5</b>
1.1 SCOPE .....	5
1.2 PURPOSE .....	5
1.3 SUMMARY OF TEST RESULTS .....	6
<b>2 LABORATORY INFORMATION .....</b>	<b>7</b>
2.1 ACCREDITATIONS & ENDORSEMENTS.....	7
2.2 MEASUREMENT UNCERTAINTY.....	7
2.3 CALIBRATION TRACEABILITY .....	7
<b>3 PRODUCT INFORMATION .....</b>	<b>8</b>
3.1 PRODUCT DESCRIPTION.....	8
3.2 EQUIPMENT MODIFICATIONS .....	8
3.3 TEST PLAN.....	8
<b>4 EMISSIONS.....</b>	<b>11</b>
4.1 SPECTRUM BANDWIDTH.....	11
4.2 MAXIMUM OUTPUT POWER .....	17
4.3 RF HUMAN EXPOSURE LIMITS .....	25
4.4 RADIATED SPURIOUS EMISSIONS .....	27
4.5 TRANSMITTER POWER DENSITY SPECTRUM.....	40
4.6 CONDUCTED EMISSIONS.....	45
4.7 FREQUENCY STABILITY.....	49
4.8 BAND EDGE MEASUREMENT.....	53
<b>APPENDIX A .....</b>	<b>58</b>
<b>5 TEST PLAN.....</b>	<b>58</b>
5.1 GENERAL INFORMATION .....	58
5.2 MODEL(S) NAME .....	58
5.3 TYPE OF PRODUCT.....	58
5.4 EQUIPMENT UNDER TEST (EUT) DESCRIPTION .....	59
5.5 MODIFICATIONS .....	59
5.6 PRODUCT ENVIRONMENT .....	59
5.7 COUNTRIES .....	59
5.8 APPLICABLE DOCUMENTS.....	60
5.9 GENERAL PRODUCT INFORMATION.....	61
5.10 EUT POWERED INFORMATION .....	61
5.11 EUT MODES OF OPERATION .....	61
5.12 EUT CONFIGURATIONS .....	62
5.13 EUT CLOCK/OSCILLATOR FREQUENCIES .....	62
5.14 ELECTRICAL SUPPORT EQUIPMENT .....	62
5.15 NON - ELECTRICAL SUPPORT EQUIPMENT .....	63
5.16 EUT EQUIPMENT/CABLING INFORMATION .....	63

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

5.17	EUT DOORS.....	63
5.18	EUT GROUNDING.....	63
5.19	EUT TEST PROGRAM.....	64
5.20	MONITORING OF EUT DURING TESTING .....	64
5.21	EUT CONFIGURATION BLOCK DIAGRAM.....	64
5.22	CONSTRUCTIONAL DATA FORM.....	65

---

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

## 1 General Information

### 1.1 Scope

This report is intended to document the status of conformance with the requirements of the FCC Part 15C, based on the results of testing performed on October 8th -10th 2007 on the Lighting Control System, Model No. Radio Bridge, manufactured by Sensor Switch, Inc.. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

### 1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT (Equipment Under Test) in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report.

### 1.3 Summary of Test Results

<b>Applicant</b>	Sensor Switch, Inc. 900 Northrop Road Wallingford, CT 06492	<b>Tel</b>	(203) 265-2842	<b>Contact</b>	William J Fassbender
		<b>Fax</b>	(203) 265-1565	<b>email</b>	fozzy@sensorswitch.com
<b>Type of Equipment</b>	Lighting Control System	<b>Model Number</b>	Radio Bridge		
<b>Standards</b>		<b>Description</b>	<b>Severity Level or Limit</b>		<b>Criteria</b>
FCC Part 15		Radio Frequency Devices -Part C	See called out basic standards below		See Below
FCC Part 15.247 (a) (2)		Spectrum Bandwith of a Direct Sequence Spread Spectrum System	500kHz on a 6dB Bandwith, 2.405 GHz - 2.480 GHz		Limit
FCC Part 15.247 (b) (3)		Maximum Output Power	1 Watt (30dBm)		Limit
FCC Part 15.247 (b)(5) and 1.1310		RF Human Exposure Limit	1.0 (mW/cm2)		Limit
FCC Part 15.247 (c), 15.205, 15.209		Radiated Spurious Emissions	-20dBc, 15.205 (a), 15.209 (a)		Limit
FCC Part 15.247 (d)		Transmitter Power Density	8 dBm/3kHz		Limit
FCC Part 15.207		Conducted Emissions	15.207 (a)		Limit
FCC Part 15.215 (b)		Frequency Stability	Containment of 20dB,		Limit
FCC Part 15.215 (c) RSS-210		20dB Bandwith	20dB Contained within the Frequency Band		Within Limit
					Complies

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

## 2 Laboratory Information

### 2.1 Accreditations & Endorsements

#### 2.1.1 US Federal Communications Commission

TUV Rheinland of North America located at 12 Commerce Road, Newtown CT is accredited by the commission for performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (Registration No US5112). The laboratory scope of accreditation includes: Title 47 CFR Part 15, and 18. The accreditation is updated every 3 years.

#### 2.1.2 NIST / NVLAP

Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Standard 17025:2005 (Lab code: 200111-0). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

#### 2.1.3 Industry Canada

Registration No.: 3466D-1. The OATS has been accepted by Industry Canada to perform testing to 3 and to 10m, based on the test procedures described in ANSI C63.4-2003.

### 2.2 Measurement Uncertainty

#### General

The estimated combined standard uncertainty for conducted immunity measurements is  $\pm 1.4\text{dB}$ .

The estimated combined standard uncertainty for radiated emissions measurements is  $\pm 1.6\text{ dB}$ .

The estimated combined standard uncertainty for conducted emissions measurements is  $\pm 1.2\text{dB}$ .

### 2.3 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2005. Equipment calibration records are kept on file at the test facility.

## 3 Product Information

### 3.1 Product Description

The radio bridge is only one component that is part of a new lighting control system being designed by Sensor Switch, Inc. The name for the newly designed system is called 'nLight'. nLight will typically consist of the following components: SensorView software, at least one gateway, at least one bridge (or two radio bridges), devices for switching lighting loads (nPP-16, nWSD, nCMR, ...), devices for detecting occupancy, light levels (nCM, nWV, nCM-ADC, ...) and devices for user control (nPOD, nPOD-D, ...). SensorView software is a browser based application which will allow clients to customize their buildings lighting needs. The software will have the ability to change device parameters, load profiles, update device firmware, respond to load shedding, and many more selectable options. The gateway provides a method of translating Ethernet packets from SensorView to RS-485 where all nLight devices can communicate. The bridge (or radio bridges) contains eight RS-485 ports. Each port typically represents a lighting zone to which devices can be connected. For example, a private office will typically require one nCMR and one nPOD. An open office area could potentially use five nPP-16 and seven nCM-PDT depending on the overall size and lighting load.

### 3.2 Equipment Modifications

No modifications were needed to bring product into compliance.

### 3.3 Test Plan

The EUT product information, test configuration, mode of operation, test types, test procedures, test levels, pass/failure criteria, in this report were carried out per the product test plan located in appendix A of this report

FCC ID: VR8-SSIEXTR001  
IC: 7791-SSIEXTR001



Report No.:

307625324.001

Page 9 of 65



Figure 1 – Photo of EUT (Transmitter)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

FCC ID: VR8-SSIEXTR001  
IC: 7791-SSIEXTR001



Report No.:

307625324.001

Page 10 of 65



Figure 2 – Photo of EUT (Receiver)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

QF0904400

TÜV Rheinland Inc., North American Headquarters, 12 Commerce Road, Newtown, CT 06470 - Tel (203)426-0888 - Fax (203)426-4009

Rev. 1.0

## 4 Emissions

### 4.1 Spectrum Bandwidth

This test measures the spectrum bandwidth of the intentional radiator signal generated by the EUT.

#### 4.1.1 Over View of Test

<b>Results</b>	<b>Complies</b> (as tested per this report)						<b>Date</b>	11/07/2007
<b>Standard</b>	FCC Part 15.247 (a) (2)							
<b>Product Model</b>	Radio Bridge			<b>Serial#</b>	Protoype			
<b>Configuration</b>	See test plan for details							
<b>Test Set-up</b>	Tested @ 3m on O.A.T.S. placed on turn-table, see test plans for details							
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22°C	<b>Humidity</b>	45%	<b>Pressure</b>	998mbar	
<b>Frequency Range</b>	2.405 GHz - 2.480 GHz @ 3m							
<b>Perf. Criteria</b>	500kHz. (Below Limit)		<b>Perf. Verification</b>	Readings Under Limit				
<b>Mod. to EUT</b>	None		<b>Test Performed By</b>	Dieter Baldamus				

#### 4.1.2 Test Procedure

Spectrum Bandwidth was performed using the Conducted method. The photos included with the report show the EUT in its maximized configuration.

The frequency range from 2.405-2.480 GHz was investigated for Spectrum Bandwidth testing the lowest middle and highest channels.

The transmitter output was connected to the spectrum analyzer. The bandwidth of the fundamental was measured using 100kHz RBW and a VBW=100kHz. The 6dB bandwidth was measured and recorded.

#### 4.1.3 Deviations

There were no deviations from the test methodology listed in the test plan.


#### 4.1.4 Final Test

All final radiated emissions measurements were below (in compliance) the limits.

#### 4.1.5 Summary of Final Data

NOTES:	Spectrum Bandwidth Low Frequency
--------	-------------------------------------

13:56:31 NOV 07, 2007 1  
 MFR: SENSOR SWITCH MODEL: RADIO BRIDGE  
 MARKER  $\Delta$   
 -1.65 MHz  
 .86 dB      ACTV DET: PEAK  
 MEAS DET: PEAK QP AVG  
 MKR $\Delta$  -1.65 MHz  
 .86 dB



ANTENNA/COUPLER:			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
<u>MEAS TYPE:</u>			
<input checked="" type="checkbox"/> Radiated Prescan	<input checked="" type="checkbox"/> Vertical	<input checked="" type="checkbox"/> 3 Meter	<input type="checkbox"/> OATS
<input type="checkbox"/> Radiated Final	<input checked="" type="checkbox"/> Horizontal	<input type="checkbox"/> 10 Meter	<input type="checkbox"/> Semi-Anechoic
<input type="checkbox"/> Conducted	<input type="checkbox"/> Line	<input type="checkbox"/> _____ Meter	<input checked="" type="checkbox"/> Shielded Room
<input type="checkbox"/> Disturbance Power	<input type="checkbox"/> Neutral	<input type="checkbox"/> NA	<input type="checkbox"/> Factory Floor
<input type="checkbox"/> Other _____	<input type="checkbox"/> NA		<input type="checkbox"/> Other _____

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

**Spectrum Bandwidth  
Middle Frequency**

② 14:34:41 NOV 07, 2007

MFR: SENS0R SW1TCH MODEL: RADIO BRIDGE

MARKER  $\Delta$   
-1.80 MHz  
-.02 dB

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR $\Delta$  -1.80 MHz  
-.02 dB

LOG REF 13.0 dBm

PREAMP ON


10  
dB/  
ATTN  
50 dB

MA  
SB  
SC  
FC  
CORR

CENTER 2.46050 GHz  
#IF BW 100 kHz

#AVG BW 100 kHz

SPAN 20.00 MHz  
SWP 20.0 msec



ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

MEAS TYPE:

- Radiated Prescan
- Radiated Final
- Conducted
- Disturbance Power
- Other

POLARIZATION:

- Vertical
- Horizontal
- Line
- Neutral
- NA

DISTANCE:

- 3 Meter
- 10 Meter
- \_\_\_\_\_ Meter
- NA

LOCATION:

- OATS
- Semi-Anechoic
- Shielded Room
- Factory Floor
- Other

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

**Spectrum Bandwidth  
High Frequency**

② 14:50:24 NOV 07, 2007

MARKER  
2.46135 GHz  
83.46 dB $\mu$ V

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.46135 GHz  
83.46 dB $\mu$ V

LOG REF 122.0 dB $\mu$ V


10  
dB/  
ATTN  
40 dB

MA SB  
SC FC  
CORR

CENTER 2.46000 GHz  
#IF BW 100 kHz

#AUG BW 100 kHz

SPAN 10.00 MHz  
SWP 20.0 msec



ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

MEAS TYPE:

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other

POLARIZATION:

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

DISTANCE:

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA

LOCATION:

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

#### 4.1.6 Tabulated Test Data

<b>Radiated Emissions Measurements</b>						
Standard:	47 CFR 15.247 (a) (2)				Date:	11/7/2007
Device Tested:	Sensor Switch - Radio Bridge				File:	07110701- 6dB Bandwith.xls
Meas #	Freq (MHz)	6dB Bandwith (MHz)	Minimum Limit (MHz)	Minimum Limit (Average + Correction Factors - Limit)	Result	Comment
Channel 1 (2410GHz)	2404.43	1.6500	0.5000	-1.15	Complied	
Channel 8 (2450GHz)	2444.60	1.8500	0.5000	-1.35	Complied	
Channel 15 (2480GHz)	2480.50	1.8000	0.5000	-1.30	Complied	
Tested by:	Dieter Baldamus					
TUV Rheinland of North America, Inc. 12 Commerce Road Newtown, CT 06470 Tel:(203) 426-0888 Fax: (203) 426-4009						

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

#### 4.1.7 Photos




Figure 3 – Spectrum Bandwidth Test Setup

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

## 4.2 Maximum Output Power

This test measures the radiated electromagnetic levels of the intentional radiator generated by the EUT through the antenna port.

### 4.2.1 Over View of Test

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	07/0/2007		
<b>Standard</b>	FCC Part 15.247 (a) (2)						
<b>Product Model</b>	Radio Bridge			<b>Serial#</b>	Protoype		
<b>Configuration</b>	See test plan for details						
<b>Test Set-up</b>	Tested in shielded room		EUT placed on table		see test plans for details		
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22°C	<b>Humidity</b>	45%	<b>Pressure</b>	998mbar
<b>Frequency Range</b>	2.405GHz - 2.480GHz @ 3m						
<b>Perf. Criteria</b>	1 Watt (30dBm) (Below Limit )	<b>Perf. Verification</b>		Readings Under Limit			
<b>Mod. to EUT</b>	None	<b>Test Performed By</b>		Dieter Baldamus			

### 4.2.2 Test Procedure

Maximum output power test was performed using the conducted method. The measurement was made using a direct connection between the RF transmitter output of the EUT and the spectrum analyzer. The cable loss and antenna factor were added to the measurement. Measurement of the duty cycle were also made and used to calculate the average level. The photos included with the report show the EUT in its maximized configuration.

The frequency range from 2.405-2.480 GHz was investigated for radiated emissions, testing the lowest middle and highest channels.

### 4.2.3 Deviations


There were no deviations from the test methodology listed in the test plan.

### 4.2.4 Final Test

All final radiated emissions measurements were below (in compliance) the limits.

#### 4.2.5 Summary of Final Data

NOTES:	<b>Duty Cycle Measurement</b>
--------	-------------------------------



ANTENNA/COUPLER:			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
MEAS TYPE:	POLARIZATION:	DISTANCE:	LOCATION:
<input checked="" type="checkbox"/> Radiated Prescan	<input checked="" type="checkbox"/> Vertical	<input checked="" type="checkbox"/> 3 Meter	<input type="checkbox"/> OATS
<input type="checkbox"/> Radiated Final	<input checked="" type="checkbox"/> Horizontal	<input type="checkbox"/> 10 Meter	<input type="checkbox"/> Semi-Anechoic
<input type="checkbox"/> Conducted	<input type="checkbox"/> Line	<input type="checkbox"/> _____ Meter	<input checked="" type="checkbox"/> Shielded Room
<input type="checkbox"/> Disturbance	<input type="checkbox"/> Neutral	<input type="checkbox"/> NA	<input type="checkbox"/> Factory Floor
Power			
<input type="checkbox"/>			<input type="checkbox"/> Other _____
Other			


The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.



NOTES:

**Maximum Output Power  
 Low Frequency**

[60] 14:24:49 NDV 07, 2007  
 MFR: SENSOR SWITCH MODEL: RADIO BRIDGE  
 MARKER 2.40446 GHz ACTV DET: PEAK  
 3.77 dBm MEAS DET: PEAK QP AVG  
 MKR 2.40446 GHz 3.77 dBm



<u>ANTENNA/COUPLER:</u>			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
<u>MEAS TYPE:</u>	<u>POLARIZATION:</u>	<u>DISTANCE:</u>	<u>LOCATION:</u>
<input checked="" type="checkbox"/> Radiated Prescan	<input checked="" type="checkbox"/> Vertical	<input checked="" type="checkbox"/> 3 Meter	<input type="checkbox"/> OATS
<input type="checkbox"/> Radiated Final	<input checked="" type="checkbox"/> Horizontal	<input type="checkbox"/> 10 Meter	<input type="checkbox"/> Semi-Anechoic
<input type="checkbox"/> Conducted	<input type="checkbox"/> Line	<input type="checkbox"/> _____ Meter	<input checked="" type="checkbox"/> Shielded Room
<input type="checkbox"/> Disturbance Power	<input type="checkbox"/> Neutral	<input type="checkbox"/> NA	<input type="checkbox"/> Factory Floor
<input type="checkbox"/> Other _____	<input type="checkbox"/> NA		<input type="checkbox"/> Other _____

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

## NOTES:

## Maximum Output Power Middle Frequency

15:06:35 NOV 07, 2007

MARKER  
2.44448 GHz  
2.66 dBm

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.44446 GHz  
2.86 dBm

LOG-BFF 13.0 dBm

PREFAMP ON



## ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

**MEAS TYPE:**

- Radiated Prescan**
- Radiated Final**
- Conducted**
- Disturbance Power**
- Other**

## POLARIZATION:

- Vertical
- Horizontal
- Line
- Neutral
- NA

## **DISTANCE:**

- 3 Meter
- 10 Meter
- \_\_\_\_\_ Meter
- NA

**LOCATION:**


- OATS
- Semi-Anechoic
- Shielded Room
- Factory Floor
- Other

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, N.V., AP, or any agency of the United States Government.

NOTES:

**Maximum Output Power  
High Frequency**

14:29:56 NOV 07, 2007  
MFR: SENSOR SWITCH MODEL: RADIO BRIDGE  
MARKER ACTV DET: PEAK  
2.48050 GHz MEAS DET: PEAK QP AVG  
2.75 dBm MKR 2.48050 GHz  
2.75 dBm



<u>ANTENNA/COUPLER:</u>			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLX 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
<u>MEAS TYPE:</u>	<u>POLARIZATION:</u>	<u>DISTANCE:</u>	<u>LOCATION:</u>
<input checked="" type="checkbox"/> Radiated Prescan <input type="checkbox"/> Radiated Final <input type="checkbox"/> Conducted <input type="checkbox"/> Disturbance Power <input type="checkbox"/> Other _____	<input checked="" type="checkbox"/> Vertical <input checked="" type="checkbox"/> Horizontal <input type="checkbox"/> Line <input type="checkbox"/> Neutral <input type="checkbox"/> NA	<input checked="" type="checkbox"/> 3 Meter <input type="checkbox"/> 10 Meter <input type="checkbox"/> _____ Meter <input type="checkbox"/> NA	<input type="checkbox"/> OATS <input type="checkbox"/> Semi-Anechoic <input checked="" type="checkbox"/> Shielded Room <input type="checkbox"/> Factory Floor <input type="checkbox"/> Other _____

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

#### 4.2.6 Tabulated Test Data

Radiated Emissions Measurements										Date:
Standard:	47 CFR 15.247(b) (3)			Prescan/Final:		Final			11/7/2007	
Device Tested:	Sensor Switch - Radio Bridge				Distance:		0m, Direct Measurement			File:
Meas #	Freq (MHz)	Measured Peak (dBm)	Cable Correction Factor	Duty Cycle	Antenna Gain	Corrected Measured Average (dBm)	Peak Limit 1 Watt (30dBm)	Peak (dB) <input type="checkbox"/>	e.i.r.p. Peak Power (dBm)	Comment
Channel 1 (2.405GHz)	2404.48	3.60	1.00	-5.51	2.14	1.23	30.00	-28.77	Complied	
Channel 8 (2.444GHz)	2445.48	2.73	1.00	-5.51	2.14	0.36	30.00	-29.64	Complied	
Channel 15 (2.480GHz)	2480.24	2.86	1.00	-5.51	2.14	0.49	30.00	-29.51	Complied	
Tested by:	Dieter Baldamus									
TUV Rheinland of North America, Inc. 12 Commerce Road Newtown, CT 06470 Tel:(203) 426-0888 Fax: (203) 426-4009										

Average Values were calculated based on the duty cycle of the transmission frequency

Measured Duty Cycle is 2.025ms + 0.787ms in 10ms

Duty Cycle = Tx ON/(TxON+TxOFF)

Duty Cycle 28.12%  
 in dB -5.509847

Average Value = Peak Value (in dBm) - Duty Cycle

Duty Cycle =  $10\log(0.2812) = -5.509847$

Corrected Measured Peak (dBm) = Measured Peak + Correction Factor+ Duty Cycle+ Antenna Gain

FCC ID: VR8-SSIEXTR001  
IC: 7791-SSIEXTR001

 TÜVRheinland®  
Precisely Right.

Report No.:

307625324.001

Page 24 of 65




Figure 4 – Maximum Output Power (Semi-Anechoic Chamber 2)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

QF0904400

TÜV Rheinland Inc., North American Headquarters, 12 Commerce Road, Newtown, CT 06470 - Tel (203)426-0888 - Fax (203)426-4009

Rev. 1.0

### 4.3 RF Human Exposure Limits

This test evaluates the RF Human Exposure to prove the safety of radiation harmfulness to human body.

#### 4.3.1 Test Over View

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	08/10/207					
<b>Standard</b>	FCC Part 15.247 (b)(5) and 1.1310									
<b>Product Model</b>	Radio Bridge			<b>Serial#</b>	Protoype					
<b>Configuration</b>	See test plan for details									
<b>Test Set-up</b>	Tested in shielded room      EUT placed on table									
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22°C	<b>Humidity</b>	45%	<b>Pressure</b>	998mbar			
<b>Frequency Range</b>	2.405GHz - 2.480GHz @ 3m									
<b>Perf. Criteria</b>	1.0 (mW/cm2) (Below Limit)		<b>Perf. Verification</b>	Readings under Limit						
<b>Mod to EUT</b>	None		<b>Test Performed By</b>	Dieter Baldamus						

#### 4.3.2 Test Procedure

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Semi-Anechoic Chamber, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula (see section 4.9.6) and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

#### 4.3.3 RF Exposure Limit

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
<b>(A) Limits For Occupational / Control Exposures</b>				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
<b>(B) Limits For General Population / Uncontrolled Exposure</b>				
300-1500	...	...	F/1500	6
1500-100,000	...	...	1.0	30

F = Frequency in MHz

#### 4.3.4 Deviations

There were no deviations from the test methodology listed in the test plan

#### 4.3.5 Antenna Gain

The maximum Gain measured in Semi-Anechoic Chamber is 2.14 dBi or 1.637 (numeric).

#### 4.3.6 Test Results

##### ***Output Power into Antenna & RF Exposure value at distance 20cm:***

Calculations for this report are based on highest power measurement and the highest gain of the antenna. Limit for MPE (from FCC part 1.1310 table 1) is 1.0 mW/cm<sup>2</sup> for 2.4-2.483.5 GHz.

Highest Pout is 1.327 mW (1.23dBm), highest antenna gain (in linear scale) is 1.637, and R is 20cm.

$P_d = (1.327 * 1.637) / (4 * \pi * 20^2) = 0.00432 \text{ mW/cm}^2$ , which is 0.99568 mW/cm<sup>2</sup> below to the limit.

#### Sample Calculation

The Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where;

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi \approx 3.1416$

$R$  = distance between observation point and center of the radiator in cm

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition, Page 640, Eq. (11-133).

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

## 4.4 Radiated Spurious Emissions

This test measures the radiated electromagnetic levels of the intentional and unintentional radiator generated by the EUT.

### 4.4.1 Test Over View

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	10/09/2007									
<b>Standard</b>	FCC Part 15.247 (c), 15.205, 15.209													
<b>Product Model</b>	Radio Bridge		<b>Serial#</b>	Protoype										
<b>Configuration</b>	See test plan for details													
<b>Test Set-up</b>	Tested in shielded room EUT placed on table													
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22°C	<b>Humidity</b>	45%	<b>Pressure</b>	998mbar							
<b>Frequency Range</b>	2.405GHz - 2.480GHz @ 3m													
<b>Perf. Criteria</b>	-20dBc, 15.205 (a), 15.209 (a)		<b>Perf. Verification</b>	Readings under Limit										
<b>Mod to EUT</b>	None		<b>Test Performed By</b>	Dieter Baldamus										

### 4.4.2 Test Procedure

Radiated emissions tests were performed using the procedures of ANSI C63.4 including methods for signal maximizations and EUT configuration. The photos included with the report show the EUT in its maximized configuration.

The frequency range from 2.405-2.480 GHz was investigated for radiated emissions, testing the lowest middle and highest channels.

Radiated emission testing was first performed at a distance of 3 meters in the semi-anechoic chamber in order to identify the specific frequencies for which these measurements will be made on the 3m OATS.

### 4.4.3 Deviations

There were no deviations from the test methodology listed in the test plan.

### 4.4.4 Final Test


The Radiated Spurious Emissions of the EUT were below the limits specified in the standard.

#### 4.4.5 Summary of Final Data

NOTES:

##### Radiated Emissions Prescan

09:44:59 NOV 07, 2007  
MFR: SENSOR SWITCH MODEL: RADIO BRIDGE  
**MARKER**  
**125.4 MHz** ACTV DET: PEAK  
**39.20 dB $\mu$ V/m** MEAS DET: PEAK QP AVG  
**39.20 dB $\mu$ V/m** MKR 125.4 MHz  
**39.20 dB $\mu$ V/m**



#### ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

#### MEAS TYPE:

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

#### POLARIZATION:

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

#### DISTANCE:

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA

#### LOCATION:


OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

Radiated Spurious Emissions Prescan

09:49:11 NOV 07, 2007  
MFR: SENSDR SWITCH MODEL: RADIO BRIDGE  
MARKER ACTV DET: PEAK  
301.2 MHz MEAS DET: PEAK QP AVG  
50.52 dB $\mu$ V/m MKR 301.2 MHz  
50.52 dB $\mu$ V/m



ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

MEAS TYPE:

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

POLARIZATION:

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

DISTANCE:

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA

LOCATION:


OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

Radiated Spurious Emissions Prescan

09:55:54 NOV 07, 2007  
MFR: SENSDR SWITCH MODEL: RADIO BRIDGE  
**MARKER** ACTV DET: PEAK  
1.078 GHz MEAS DET: PEAK QP AVG  
35.60 dB $\mu$ V/m MKR 1.078 GHz  
35.60 dB $\mu$ V/m



ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

MEAS TYPE:

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

POLARIZATION:

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

DISTANCE:

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA


LOCATION:

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

Radiated Spurious Emissions Prescan



ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

MEAS TYPE:

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

POLARIZATION:

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

DISTANCE:

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA


LOCATION:

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

**Radiated Spurious Emissions Prescan**



ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLX 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

MEAS TYPE:

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

POLARIZATION:

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

DISTANCE:

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA


LOCATION:

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

Radiated Spurious Emissions Prescan




ANTENNA/COUPLER:			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
MEAS TYPE:	POLARIZATION:	DISTANCE:	LOCATION:
<input checked="" type="checkbox"/> Radiated Prescan	<input checked="" type="checkbox"/> Vertical	<input checked="" type="checkbox"/> 3 Meter	<input type="checkbox"/> OATS
<input type="checkbox"/> Radiated Final	<input checked="" type="checkbox"/> Horizontal	<input type="checkbox"/> 10 Meter	<input type="checkbox"/> Semi-Anechoic
<input type="checkbox"/> Conducted	<input type="checkbox"/> Line	<input type="checkbox"/> _____ Meter	<input checked="" type="checkbox"/> Shielded Room
<input type="checkbox"/> Disturbance Power	<input type="checkbox"/> Neutral	<input type="checkbox"/> NA	<input type="checkbox"/> Factory Floor
<input type="checkbox"/> Other _____	<input type="checkbox"/> NA		<input type="checkbox"/> Other _____

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

Radiated Spurious Emissions Prescan



ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

MEAS TYPE:

- Radiated Prescan
- Radiated Final
- Conducted
- Disturbance Power
- Other \_\_\_\_\_

POLARIZATION:

- Vertical
- Horizontal
- Line
- Neutral
- NA

DISTANCE:

- 3 Meter
- 10 Meter
- \_\_\_\_\_ Meter
- NA


LOCATION:

- OATS
- Semi-Anechoic
- Shielded Room
- Factory Floor
- Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

Radiated Spurious Emissions Prescan




ANTENNA/COUPLER:			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
MEAS TYPE:	POLARIZATION:	DISTANCE:	LOCATION:
<input checked="" type="checkbox"/> Radiated Prescan	<input checked="" type="checkbox"/> Vertical	<input checked="" type="checkbox"/> 3 Meter	<input type="checkbox"/> OATS
<input type="checkbox"/> Radiated Final	<input checked="" type="checkbox"/> Horizontal	<input type="checkbox"/> 10 Meter	<input type="checkbox"/> Semi-Anechoic
<input type="checkbox"/> Conducted	<input type="checkbox"/> Line	<input type="checkbox"/> _____ Meter	<input checked="" type="checkbox"/> Shielded Room
<input type="checkbox"/> Disturbance Power	<input type="checkbox"/> Neutral	<input type="checkbox"/> NA	<input type="checkbox"/> Factory Floor
<input type="checkbox"/> Other _____	<input type="checkbox"/> NA		<input type="checkbox"/> Other _____

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

Radiated Spurious Emissions Prescan



ANTENNA/COUPLER:			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
MEAS TYPE:	POLARIZATION:	DISTANCE:	LOCATION:
<input checked="" type="checkbox"/> Radiated Prescan	<input checked="" type="checkbox"/> Vertical	<input checked="" type="checkbox"/> 3 Meter	<input type="checkbox"/> OATS
<input type="checkbox"/> Radiated Final	<input checked="" type="checkbox"/> Horizontal	<input type="checkbox"/> 10 Meter	<input type="checkbox"/> Semi-Anechoic
<input type="checkbox"/> Conducted	<input type="checkbox"/> Line	<input type="checkbox"/> _____ Meter	<input checked="" type="checkbox"/> Shielded Room
<input type="checkbox"/> Disturbance Power	<input type="checkbox"/> Neutral	<input type="checkbox"/> NA	<input type="checkbox"/> Factory Floor
<input type="checkbox"/> Other _____	<input type="checkbox"/> NA		<input type="checkbox"/> Other _____

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

#### 4.4.6 Tabulated Test Data

Radiated Spurious Emissions Measurements															
Standard: 47 CFR 15.35, 15.209(b) and 15.205 (a)(b), Device Tested: Sensor Switch, Radio Bridge with Cables, 120 VAC / 60 Hz										PRESCAN or FINAL: Final		Date: 7/5/2008			
										Distance: 3.0m		File: 08060702.xls			
Measured Level															
Meas #	Freq (MHz)	Peak	Quasi-Peak	Average	Quasi-Peak Limit	Peak Limit (-20dBc)	Average Limit	Minimum Delta	Antenna + Cable Correction Factor (included in measured levels)	Result	Antenna Polarization	Angle (degrees)	Antenna Height (m)		
RBW=120kHz, VBW=300kHz															
1	53.8711	44.10	25.65	17.87	39.10			-13.45	7.55	Complied	Vertical	356	1.54		
2	63.5000	44.17	33.96	3.98	39.10			-5.14	6.27	Complied	Vertical	2	1.25		
3	72.0000	33.08	27.74	21.03	39.10			-11.36	6.56	Complied	Vertical	203	1.87		
4	75.0000	31.14	26.67	20.48	39.10			-12.43	6.81	Complied	Vertical	357	1.00		
5	275.0497	31.03	26.50	25.15	46.40			-19.90	13.22	Complied	Vertical	214	2.24		
6	300.0545	48.77	45.70	42.45	46.40			-0.70	14.22	Complied	Vertical	248	2.47		
7	638.3527	25.32	18.89	12.11	46.40			-27.51	19.23	Complied	Vertical	NA	NA		
8	725.0000	24.82	18.65	12.13	46.40			-27.75	18.8	Complied	Vertical	182	1.85		
Radiated Spurious Emissions Measurements															
Standard: 47 CFR 15.35, 15.209(b) and 15.205 (a)(b), Device Tested: Sensor Switch, Radio Bridge with Cables, 120 VAC / 60 Hz										PRESCAN or FINAL: Final		Date: 7/5/2008			
										Distance: 3.0m		File: 08060702.xls			
Measured Level															
Meas #	Freq (MHz)	Peak	Quasi-Peak	Average	Quasi-Peak Limit	Peak Limit (-20dBc)	Average Limit	Minimum Delta	Antenna + Cable Correction Factor (included in measured levels)	Result	Antenna Polarization	Angle (degrees)	Antenna Height (m)		
RBW=1MHz, VBW=1MHz															
1	2405.2177	81.58	80.73	63.08				27.6	Fundamental	Vertical	15	1.00			
2	2400.0000	50.86	47.55	36.44		61.58	53.98	-17.54	27.6	Complied	Vertical	10	1.00		
3	4809.1000	40.64	38.45	35.11		61.58	53.98	-18.87	12.7*	Complied	Vertical	10	1.10		
4	7214.0000	40.45	38.44	35.12		61.58	53.98	-18.86	14.5*	Complied	Vertical	25	1.00		
5	2444.5000	82.44	81.55	62.55					27.6	Fundamental	Vertical	32	1.00		
6	4891.0000	41.50	38.45	35.44		62.44	53.98	-18.54	12.7*	Complied	Vertical	18	1.00		
7	7336.9000	40.80	38.78	34.98		62.44	53.98	-19.00	14.5*	Complied	Vertical	26	1.00		
8	2480.4800	82.05	81.54	63.44				27.6	Fundamental	Vertical	355	1.10			
9	2485.3000	51.25	48.45	45.55		62.05	53.98	-8.43	12.7*	Complied	Vertical	5	1.00		
10	4959.3000	40.89	38.47	35.04		62.05	53.98	-18.94	12.7*	Complied	Vertical	5	1.12		
11	7441.4400	41.05	39.05	34.96		62.05	53.98	-19.02	14.5*	Complied	Vertical	356	1.00		
Tested by:	Dieter Baldamus														
TUV Rheinland of North America, Inc.	12 Commerce Road	Newtown, CT	06470	Tel:(203) 426-0888	Fax: (203) 426-4009										

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

#### 4.4.7 Photos



Figure 5 - Radiated Spurious Emissions Test Setup (Radiated Prescan- Semi Anechoic Chamber)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

FCC ID: VR8-SSIEXTR001  
IC: 7791-SSIEXTR001



Report No.:

307625324.001

Page 39 of 65



Figure 6 - Radiated Spurious Emissions Test Setup (Radiated Final Test - OATS)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

QF0904400

TÜV Rheinland Inc., North American Headquarters, 12 Commerce Road, Newtown, CT 06470 - Tel (203)426-0888 - Fax (203)426-4009

Rev. 1.0

## 4.5 Transmitter Power Density Spectrum

This test is to evaluate

### 4.5.1 Test Over View

<b>Results</b>	<b>Complies</b> (as tested per this report)				<b>Date</b>	07/0/2007						
<b>Standard</b>	FCC Part 15.215 (b)											
<b>Product Model</b>	Radio Bridge			<b>Serial#</b>	Protoype							
<b>Configuration</b>	See test plan for details											
<b>Test Set-up</b>	Tested in 3m chamber EUT placed on table See test plan for details											
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22°C	<b>Humidity</b>	45%	<b>Pressure</b>	998mbar					
<b>Frequency Range</b>	2.405GHz - 2.480GHz @ 3m											
<b>Perf. Criteria</b>	8dBm in a 3kHz BW		<b>Perf. Verification</b>	Readings under Limit								
<b>Mod to EUT</b>	None		<b>Test Performed By</b>	Dieter Baldamus								

### 4.5.2 Test Procedure

The Radiated Power Density was performed using a 1 second interval over a 3kHz bandwidth within each band.

The frequency range from 2.405-2.480 GHz was investigated for radiated emissions, testing the lowest middle and highest channels

Radiated emission testing was first performed at a distance of 3 meters in the semi-anechoic chamber in order to identify the specific frequencies for which these measurements will be made on the 3m OATS

### 4.5.3 Deviations

There were no deviations from the test methodology listed in the test plan for the Radiated Immunity test.

### 4.5.4 Final Test


The EUT met the performance criteria requirement as specified in the test plan of this report and in the standards.

#### 4.5.5 Summary of Final Data

NOTES:

##### Transmitter Power Density Measurement

② 14:23:49 NOV 07, 2007  
MFR: SENSOR SWITCH MODEL: RADIO BRIDGE  
MARKER ACTV DET: PEAK  
2.405124 GHz MEAS DET: PEAK QP AVG  
-9.86 dBm MKR 2.405124 GHz  
-9.86 dBm



##### ANTENNA/COUPLER:

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

##### MEAS TYPE:

- Radiated Prescan
- Radiated Final
- Conducted
- Disturbance Power
- Other \_\_\_\_\_

##### POLARIZATION:

- Vertical
- Horizontal
- Line
- Neutral
- NA

##### DISTANCE:

- 3 Meter
- 10 Meter
- \_\_\_\_\_ Meter
- NA

##### LOCATION:

- OATS
- Semi-Anechoic
- Shielded Room
- Factory Floor
- Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.


NOTES:

**Transmitter Power Density Measurement**

15:07:36 NOV 07, 2007

MARKER  
2.444501 GHz  
-10.12 dBm

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.444501 GHz  
-10.12 dBm



**ANTENNA/COUPLER:**

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

**MEAS TYPE:**

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

**POLARIZATION:**

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

**DISTANCE:**

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA

**LOCATION:**

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

**Transmitter Power Density Measurement**

14:46:34 NOV 07, 2007

MARKER  
2.479494 GHz  
-9.25 dBm

ACTV DET: PEAK  
MEAS DET: PEAK QP AVG  
MKR 2.479494 GHz  
-9.25 dBm

LOG REF 15.0 dBm


10  
dB/  
ATTN  
40 dB

VA SB  
SC FC  
CORR

CENTER 2.480000 GHz  
#IF BW 3.0 kHz

#AUG BW 3 kHz

SPAN 1.500 MHz  
SWP 500 msec



**ANTENNA/COUPLER:**

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

**MEAS TYPE:**

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

**POLARIZATION:**

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

**DISTANCE:**

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA

**LOCATION:**

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

#### 4.5.6 Photos




Figure 7 – Transmitter Power Density Spectrum (Semi-Anechoic Chamber 2)

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

## 4.6 Conducted Emissions

This test measures the electromagnet levels of spurious signals generated by the EUT on the AC power line that may affect the performance of other near by electronic equipment.

### 4.6.1 Test Over View

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	07/0/2007					
<b>Standard</b>	FCC Part 15.207									
<b>Product Model</b>	Radio Bridge			<b>Serial#</b>	Protoype					
<b>Configuration</b>	See test plan for details									
<b>Test Set-up</b>	Tested in shielded room      EUT placed on table									
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22°C	<b>Humidity</b>	45%	<b>Pressure</b>	998mbar			
<b>Frequency Range</b>	120V/60Hz, 0150-30MHz									
<b>Perf. Criteria</b>	FCC Part 15.207 (a)	<b>Perf. Verification</b>			Readings Under Limit for L1 and L2					
<b>Mod. to EUT</b>	None	<b>Test Performed By</b>			Dieter Baldamus					

### 4.6.2 Test Procedure

Conducted and FCC emissions tests were performed using the procedures of ANSI C63.4 including methods for signal maximizations and EUT configuration. The photos included with the report show the EUT in its maximized configuration.

The frequency range from 0.15 to 30 MHz was investigated for conducted emissions.

Conducted Emissions measurements were performed in the shielded room using procedures specified in the test plan and standard.

### 4.6.3 Deviations

There were no deviations from the test methodology listed in the test plan for the conducted emission test.

### 4.6.4 Final Test

All final conducted emissions measurements were below (in compliance) the limits.

#### 4.6.5 Final Graph

NOTES:

Conducted Emissions @ 120V/60Hz



<u>ANTENNA/COUPLER:</u>			
<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp
MEAS TYPE:	POLARIZATION:	DISTANCE:	LOCATION:
<input type="checkbox"/> Radiated Prescan	<input type="checkbox"/> Vertical	<input type="checkbox"/> 3 Meter	<input type="checkbox"/> OATS
<input type="checkbox"/> Radiated Final	<input type="checkbox"/> Horizontal	<input type="checkbox"/> 10 Meter	<input type="checkbox"/> Semi-Anechoic
<input checked="" type="checkbox"/> Conducted	<input checked="" type="checkbox"/> Line	<input type="checkbox"/> _____ Meter	<input checked="" type="checkbox"/> Shielded Room
<input type="checkbox"/> Disturbance Power	<input checked="" type="checkbox"/> Neutral	<input type="checkbox"/> NA	<input type="checkbox"/> Factory Floor
<input type="checkbox"/> Other _____	<input type="checkbox"/> NA		<input type="checkbox"/> Other _____

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

#### 4.6.6 Final Tabulated Data at 120V/60Hz

Conducted Emissions Measurements											Date:	11/9/2007	
Standard:	EN55022:1998, Class B/FCC Part 15.107 (a)										File:	.xls	
Device Tested:	Sensor Switch - Radio Bridge												
Voltage:	120V/60Hz												
Signal Num	Freq	Peak Amp	QP Amp	Avg Amp	QP Limit	Avg Limit	Conductor	QP $\cup$	QP Result	Avg $\cup$	Average Result	Mode	
	MHz	dBuV	dBuV	dBuV	dBuV	dBuV		dB		dB			
1	0.1633	43.45	36.71	23.77	65.29	55.29	Line	-28.58	Complied	-31.52	Complied		
2	0.2858	37.09	31.35	4.51	60.64	50.64	Line	-29.29	Complied	-46.13	Complied		
3	0.5039	17.19	9.77	2.53	56.00	46.00	Line	-46.23	Complied	-43.47	Complied		
4	25.0133	44.17	43.75	43.28	60.00	50.00	Line	-16.25	Complied	-6.72	Complied		
5	0.1615	40.73	33.93	23.61	65.39	55.39	Neutral	-31.46	Complied	-31.78	Complied		
6	0.2720	33.87	26.69	8.77	61.06	51.06	Neutral	-34.37	Complied	-42.29	Complied		
7	13.8424	13.28	8.74	2.33	60.00	50.00	Neutral	-51.26	Complied	-47.67	Complied		
8	17.8317	13.95	9.02	2.75	60.00	50.00	Neutral	-50.98	Complied	-47.25	Complied		
9	25.0134	43.54	43.16	42.71	60.00	50.00	Neutral	-16.84	Complied	-7.29	Complied		

Tested by: Dieter Baldamus

TUV Rheinland of North America, Inc. 12 Commerce Road Newtown, CT 06470 Tel:(203) 426-0888 Fax: (203) 426-4009

CE22\_B.xls Revised 13APR05

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

#### 4.6.7 Photos



Figure 8 –Conducted Emissions Test Setup

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

## 4.7 Frequency Stability

This test is to evaluate the performance of the EUT when subjected to temperature and voltage changes

### 4.7.1 Test Over View

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	10/09/2007			
<b>Standard</b>	FCC Part 15.215							
<b>Product Model</b>	Radio Bridge			<b>Serial#</b>	Protoype			
<b>Configuration</b>	See test plan for details							
<b>Test Set-up</b>	Tested in shielded room. See test plans for details							
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22°C	<b>Humidity</b>	45%	<b>Pressure</b>		
<b>Frequency Range</b>	2.405 GHZ – 2.480GHz		<b>Temperature Range</b>		0°C – 70°C			
<b>Perf. Criteria</b>	Containment of 20dB of frequency range		<b>Perf. Verification</b>	Readings under Limit				
<b>Mod to EUT</b>	See section 5.5		<b>Test Performed By</b>	Dieter Baldamus				

### 4.7.2 Test Procedure

EUT was place in a temperature chamber. Frequency and output power level were measured at room temperature. Temperature in the chamber was increased to 70°C and maintained till the EUT reached that temperature. Frequency and level was measured again. EUT was placed into a humidity chamber and temperature was set to 0 °C. Temperature was maintained till the EUT reached that temperature. Frequency and level were measured again.

### 4.7.3 Deviations

There were no deviations from the test methodology listed in the test plan for the Surge Immunity test.

### 4.7.4 Final Test

The EUT met the performance criteria requirement as specified in the test plan of this report and in the standards.

#### 4.7.5 Summary of Final Test Results

---

ECC TempStab.xls Revised 24APR03

Frequency Stability Test - Voltage Variations					
Standard:	FCC Part 15.225 e)			Date:	6/11/2008
Device Tested:	DSVII+Turbo			File:	08061101 FreqVar.xls
Customer:	Datastrip				
Temperature	Start-up (GHz)	2min (GHz)	5min (GHz)	10min (GHz)	Permitted Band Edge in MHz (+/-0.01%)
Low					
102V(85%)	2.4047	2.4047	2.4048	2.4048	2.4000GHz-2.4835GHz
120V (100%)	2.4048	2.4047	2.4048	2.4048	2.4000GHz-2.4835GHz
138V (115%)	2.4047	2.4047	2.4047	2.4047	2.4000GHz-2.4835GHz
Middle					
102V(85%)	2.4445	2.4445	2.4445	2.4445	2.4000GHz-2.4835GHz
120V (100%)	2.4444	2.4444	2.4444	2.4444	2.4000GHz-2.4835GHz
138V (115%)	2.4445	2.4445	2.4445	2.4445	2.4000GHz-2.4835GHz
High					
102V(85%)	2.4806	2.4805	2.4804	2.4805	2.4000GHz-2.4835GHz
120V (100%)	2.4805	2.4805	2.4805	2.4805	2.4000GHz-2.4835GHz
138V (115%)	2.4806	2.4805	2.4806	2.4805	2.4000GHz-2.4835GHz
Tested by:	Dieter Baldamus				
TUV Rheinland of North America, Inc. 12 Commerce Road Newtown, CT 06470 Tel:(203) 426-0888 Fax: (203) 426-4009					
FCC TempStab.xls Revised 24APR08					

---

ECC TempStab.xls Revised 24APR01

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

#### 4.7.6 Photos



Figure 9 –Frequency Stability Test Setup – Temperature Chamber at +50°C

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.



Figure 10 –Frequency Stability Test Setup – Humidity Chamber at 0°C

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

## 4.8 Band Edge Measurement

This test evaluates the band edge of the fundamental signal in each of the lowest, middle and highest transmission frequency.

### 4.8.1 Test Over View

<b>Results</b>	<b>Complies</b> (as tested per this report)			<b>Date</b>	05/13/2008			
<b>Standard</b>	FCC Part 215 c)/RSS-210							
<b>Product Model</b>	Radio Bridge			<b>Serial#</b>	Protoype			
<b>Configuration</b>	See test plan for details							
<b>Test Set-up</b>	Tested in OATS EUT placed on table			See test plan for details				
<b>EUT Powered By</b>	AC/DC Adapter & Batteries	<b>Temp</b>	22° C	<b>Humidity</b>	45%	<b>Pressure</b>	1001mbar	
<b>Perf. Criteria</b>	6dB and 99% Band Edge		<b>Perf. Verification</b>	Readings within Limit				
<b>Mod to EUT</b>	None		<b>Test Performed By</b>	Dieter Baldamus				

### 4.8.2 Test Procedure

Radiated field strength emissions tests were performed using the procedures of ANSI C63.4 including methods for signal maximizations and EUT configuration. The photos included with the report show the EUT in its maximized configuration. Testing was performed at a distance of 10 meters on the OATS Deviations. Readings were made at 6dB and 99% of the fundamental signal.

### 4.8.3 Deviations

There were no deviations from the test methodology listed in the test plan for the band edge measurement test.


### 4.8.4 Final Test

The Band Edge Measurements were within the limits specified in the standard.

#### 4.8.5 Graphs

NOTES:

**Band Edge Measurement**  
(Radiated)



**ANTENNA/COUPLER:**

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

**MEAS TYPE:**

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

**POLARIZATION:**

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

**DISTANCE:**

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA

**LOCATION:**

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

NOTES:

**Band Edge Measurement**  
(Radiated)

12:24:00 JUL 08, 2008

REF 97.0 dB $\mu$ V


#AT 0 dB

MKR 2.40000 GHz

5086 dB $\mu$ V

PEAK  
LOG  
10  
dB/

MA SB  
SC FC  
CORR



START 2.39950 GHz

#RES BW 1.0MHz

STOP 2.40786 GHz

VBW 1 MHz

SWP 200 msec

**ANTENNA/COUPLER:**

<input type="checkbox"/> 9124 Bicon	<input type="checkbox"/> 3109 Bicon	<input type="checkbox"/> CBL6140 X-Wing	<input type="checkbox"/> NNB-4/63TL LISN
<input type="checkbox"/> 3146 Log Per	<input checked="" type="checkbox"/> 3115 Horn	<input type="checkbox"/> JB3 Bilog	<input type="checkbox"/> NNB-4/200X LISN
<input type="checkbox"/> 3106 Horn	<input type="checkbox"/> CBL6112B Bilog	<input type="checkbox"/> NSLK 8126 LISN	<input type="checkbox"/> MDS-21 Clamp

**MEAS TYPE:**

Radiated Prescan  
 Radiated Final  
 Conducted  
 Disturbance Power  
 Other \_\_\_\_\_

**POLARIZATION:**

Vertical  
 Horizontal  
 Line  
 Neutral  
 NA

**DISTANCE:**

3 Meter  
 10 Meter  
 \_\_\_\_\_ Meter  
 NA

**LOCATION:**

OATS  
 Semi-Anechoic  
 Shielded Room  
 Factory Floor  
 Other \_\_\_\_\_

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

#### 4.8.6 Tabulated Test Data

<b>Radiated Emissions Measurements</b>								
<b>Standard:</b>	47 CFR FCC Part 15.215 c)/RSS-210		<b>PRESCAN or FINAL:</b>	Final		<b>Date:</b>	5/13/2008	
<b>Device Tested:</b>	Sensor Switch - Radio Bridge				<b>Distance:</b>	10m	<b>File Name:</b>	0805301Bandedge.xls
<b>Mode:</b>	Normal Operation							
<b>Mount:</b>	Table Top							
<b>Modifications:</b>	NA		Measured Level					
Meas #	TX Band	Peak	-20dB High End (MHz)	+20dB High End (MHz)	99% Measured Bandwidth (MHz)	Band (MHz)	Result	Comment
RBW = 9kHz VBW=30kHz								
1	2404.48	3.60	2403.53	2405.31	1.7800	2400-2483.5	Complied	
2	2445.48	2.73	2444.52	2446.33	1.8100	2400-2483.6	Complied	
3	2480.24	2.86	2479.49	2481.36	1.8700	2400-2483.7	Complied	
Tested by:	Dieter Baldamus							
TUV Rheinland of North America, Inc. 12 Commerce Road Newtown, CT 06470 Tel:(203) 426-0888 Fax: (203) 426-4009								

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.

#### 4.8.7 Photos




Figure 11 –Bandedge Measurement Test Set-up

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TÜV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TÜV Rheinland, NVLAP or any agency of the United States Government.

## Appendix A

### 5 Test Plan

This test report is intended to follow this test plan outlined here in unless other wise stated in this here report. The following test plan will give details on product information, standards to be used, test set ups and refer to TUV test procedures. The test procedures will give the steps to be taken when performing the stated test. The product information below came via client, product manual, product itself and or the internet.

#### 5.1 General Information

<b>Client</b>	Sensor Switch, Inc.
<b>Address</b>	900 Northrop Road
<b>Address</b>	Wallingford, CT 06492
<b>Contact Person</b>	William J Fassbender
<b>Telephone</b>	(203) 265-2842
<b>Fax</b>	(203) 265-1565
<b>email</b>	fozzy@sensorswitch.com

#### 5.2 Model(s) Name

Radio Bridge

#### 5.3 Type of Product

Lighting Control System

## 5.4 Equipment Under Test (EUT) Description

The EUT is a wireless foot pedal used for various applications in the industrial environment. The wireless system eliminates the nuisance of wires under foot while invisible waves fill a room with 360° of signal. The EUT consist of a wireless foot pedal transmitter and a receiver; one (the transmitter) used with batteries and one (the receiver) used with an AC/DC adapter. The receiver also sends a signal every second to control de antenna output power of the transmitter.

## 5.5 Modifications

Software Change to comply with the frequency stability test.

## 5.6 Product Environment

<input type="checkbox"/>	<b>Residential</b>	<input type="checkbox"/>	<b>Hospital</b>
<input checked="" type="checkbox"/>	<b>Light Industrial</b>	<input type="checkbox"/>	<b>Small Clinic</b>
<input type="checkbox"/>	<b>Industrial</b>	<input type="checkbox"/>	<b>Doctor's office</b>
<input type="checkbox"/>	<b>Other</b>		

\*Check all that apply

## 5.7 Countries

<input checked="" type="checkbox"/>	<b>USA</b>
<input type="checkbox"/>	<b>Taiwan</b>
<input type="checkbox"/>	<b>Japan</b>
<input type="checkbox"/>	<b>Europe</b>

\*Check all that apply

## 5.8 Applicable Documents

Standard	Description
FCC Part 15	Rado Frquency Devices -Part C
FCC Part 15.247 (a) (2) RSS-210	Spectrum Bandwith of a Direct Sequence Spread Spectrum System
FCC Part 15.247 (b)	Maximum Output Power
FCC Part 1.1310	RF Human Exposure Limit
FCC Part 15.247 (c), 15.205, 15.209	Radiated Spurious Emissions
FCC Part 15.247 (d)	Transmitter Power Density of a Direct Sequence Spread Spectrum System
FCC Part 15.207	Conducted Emissions
FCC Part 15.215 (b)	Frequency Stability
FCC part 15.215 c), RSS-210	Band Edge Measurement

## 5.9 General Product Information

Size (Transmitter)	<b>H</b>	5cm	<b>W</b>	15cm	<b>L</b>	15cm
Weight (Transmitter)	0.5		<b>Fork-Lift Needed</b>		No	
Notes	None					

## 5.10 EUT Powered Information

### 5.10.1 Power Type

<input checked="" type="checkbox"/>	AC	<input checked="" type="checkbox"/>	DC (From AC./DC Block)	<input type="checkbox"/>	Batteries	<input type="checkbox"/>	Host -
-------------------------------------	----	-------------------------------------	------------------------	--------------------------	-----------	--------------------------	--------

### 5.10.2 Power Information

Name	Type	Voltage		Frequency	Current	Notes
		min	max			
24VDC AC/DC Adapter	Class 1	120VAC	120VAC	60Hz	500mA	
Notes						

## 5.11 EUT Modes Of operation

The EUT footswitch transmitter has 2 modes of operation. Switch ON or Switch OFF. Both modes were in operation during the test. The receiver was constantly on receiving signals from the footswitch transmitter.

## 5.12 EUT Configurations

Configuration	Description
Configuration 1	Transmitter was on all the time

**Note:** all configurations are the same except as noted above

## 5.13 EUT Clock/Oscillator Frequencies

<input type="checkbox"/>	Less than 108MHz	FCC – scan up to 1GHz
<input type="checkbox"/>	Less than 500MHz	FCC – scan up to 2GHz
<input type="checkbox"/>	Less than 1000MHz	FCC – scan up to 5GHz
<input checked="" type="checkbox"/>	Greater then 1000MHz	FCC – scan up to 5 <sup>th</sup> Harmonic or 40GHz (2.4GHz)

## 5.14 Electrical Support Equipment

Type	Manufacture	Model	Connected To
NA	NA	NA	NA

### 5.15 Non - Electrical Support Equipment

Item	Notes
NA	NA

### 5.16 EUT Equipment/Cabling Information

EUT Port	Connected To	Location	Cable Type		
			Length	Shielded	Bead
15-24VDC Input	AC/ DC Terminal Block	Tx/ Rx	1.5m	No	No

### 5.17 EUT Doors

<input checked="" type="checkbox"/>	<b>None</b>
<input type="checkbox"/>	<b>For service personnel only</b>
<input type="checkbox"/>	<b>Operator will wear ESD strap</b>
<input type="checkbox"/>	<b>Other</b>

### 5.18 EUT Grounding

<input checked="" type="checkbox"/>	<b>None</b>
<input type="checkbox"/>	<b>AC line cord – third wire</b>
<input type="checkbox"/>	<b>Via host I/O cable</b>
<input type="checkbox"/>	<b>Other</b>

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.


## 5.19 EUT Test Program

None

## 5.20 Monitoring of EUT during Testing

During the test a LED in the receiver indicates that the switch of the transmitter is ON. If the LED is off the foot switch is OFF as well.

## 5.21 EUT Configuration Block Diagram



## **5.22 Constructional Data Form**

The test results contained in this report refer exclusively to the product(s) presented for testing. No liability may be assumed for models or products not referred to herein. This test report may not be published or duplicated in part without permission of the testing body. This test report by itself does not constitute authorization for the use of any TUV Rheinland test mark. This report must not be used by the applicant to claim product endorsement by TUV Rheinland, NVLAP or any agency of the United States Government.