

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the  
Federal Communications Commission****By:****Telefication B.V.  
Edisonstraat 12a  
Zevenaar, NL-6902 PK  
Netherlands****Date of Grant: 05/17/2016****Application Dated: 05/13/2016****Fibocom Wireless Inc.  
5/F, Tower A, Technology Building II,  
1057# Nanhai Blvd,  
Shenzhen, 518067  
China****Attention: Tao Zhu , Marketing Director****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is  
VALID ONLY for the equipment identified hereon for use under the Commission's  
Rules and Regulations listed below.

**FCC IDENTIFIER:** ZMOH380GL**Name of Grantee:** Fibocom Wireless Inc.**Equipment Class:** PCS Licensed Transmitter**Notes:** WCDMA module with GSM,GPRS,EDGE**Modular Type:** Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	22H	824.2 - 848.8	0.912	0.0121 PM	243KGXW
	22H	824.2 - 848.8	0.45	0.0123 PM	248KG7W
	22H	826.4 - 846.6	0.217	0.0115 PM	4M09F9W
	24E	1850.2 - 1909.8	1.047	0.0059 PM	248KGXW
	24E	1850.2 - 1909.8	0.339	0.006 PM	248KG7W
	24E	1852.4 - 1907.6	0.261	0.0061 PM	4M08F9W

Single modular approval: This module may only be installed by the OEM or an OEM integrator in the products as specified in this filing. Output power is ERP for Part 22 and EIRP for Part 24. The antenna(s) used for this transmitter must be used to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. End-users must be provided with antenna installation instructions and transmitter operating conditions for satisfying RF exposure compliance.

The maximum antenna gain allowed for use with this device is 5 dBi.

This device contains functions that are not operational in U.S. Territories. This filing is only applicable for U.S. operations.