

FCC and ISED Test Report

Jotron AS
EPIRB, Model: Tron 40VDR AIS

In accordance with FCC 47 CFR Part 80,
FCC 47 CFR Part 2, ISED RSS-182 and ISED
RSS-GEN (AIS)

Prepared for: Jotron AS
Ringdalskogen 8,
3270 Larvik,
Norway



Add value.
Inspire trust.

FCC ID: VRV40VDRAIS IC: 2131A-40VDRAIS

COMMERCIAL-IN-CONFIDENCE

Document 75950873-04 Issue 02

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Simon Bennett	Director of Test Operations	Authorised Signatory	21 January 2022

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 80, FCC 47 CFR Part 2, ISED RSS-182 and ISED RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Neil Rousell	21 January 2022	
Testing	Graeme Lawler	21 January 2022	

FCC Accreditation
90987 Octagon House, Fareham Test Laboratory

ISED Accreditation
12669A Octagon House, Fareham Test Laboratory

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 80: 2019, FCC 47 CFR Part 2: 2019, ISED RSS-182: Issue 5 (2012-01) and ISED RSS-GEN: Issue 5 (2018-04) for the tests detailed in section 1.3.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2022 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

TÜV SÜD
is a trading name of TÜV SÜD Ltd
Registered in Scotland at East Kilbride,
Glasgow G75 0QF, United Kingdom
Registered number: SC215164

TÜV SÜD Ltd is a
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100
Fax: +44 (0) 1489 558101
www.tuvsud.com/en

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire PO15 5RL
United Kingdom



Contents

1	Report Summary	2
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summary of Results	3
1.4	Manufacturer Declared Variant	4
1.5	Application Form	5
1.6	Product Information	7
1.7	Deviations from the Standard.....	7
1.8	EUT Modification Record	7
1.9	Test Location	8
2	Test Details	9
2.1	Bandwidths	9
2.2	Transmitter Frequency Tolerances	12
2.3	Spurious Emissions at Antenna Terminals	15
2.4	Radiated Spurious Emissions	22
2.5	Modulation Requirements	26
2.6	Transmitter Power	31
3	Photographs	33
3.1	Test Setup Photographs	33
4	Measurement Uncertainty	35



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	12 January 2022
2	Second Issue to include section reference for Manufacturer Declared Model and amend note in the test results for Section 2.1 Bandwidths	21 January 2022

Table 1

1.2 Introduction

Applicant	Jotron AS
Manufacturer	Jotron AS
Model Number(s)	Tron 40VDR AIS
Serial Number(s)	00039 and 00041
Hardware Version(s)	Rev: 2020
Software Version(s)	Rev 1.2
Number of Samples Tested	2
Manufacturer Declared Variant	Tron 40AIS (Refer to Section 1.4)
Test Specification/Issue/Date	FCC 47 CFR Part 80: 2019 FCC 47 CFR Part 2: 2019 ISED RSS-182: Issue 5 (2012-01) ISED RSS-GEN: Issue 5 (2018-04)
Order Number	P42335
Date	22-December-2020
Date of Receipt of EUT	23-February-2021
Start of Test	13-May-2021
Finish of Test	01-July-2021
Name of Engineer(s)	Neil Rousell and Graeme Lawler
Related Documents	ANSI C63.26: 2015 FCC KDB 971168 D01 v03r01



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 80, FCC 47 CFR Part 2, ISED RSS-182 and ISED RSS-GEN is shown below.

Section	Specification Clause				Test Description	Result	Comments/Base Standard
	Part 80	Part 2	RSS-182	RSS-GEN			
Configuration and Mode: AIS Transceiver							
2.1	80.205	2.1049	7.7 and 7.9.1	6.7	Bandwidths	Pass	
2.2	80.209	2.1055	7.4	6.11	Transmitter Frequency Tolerances	Pass	
2.3	80.211	2.1051	7.9	6.13	Spurious Emissions at Antenna Terminals	Pass	
2.4	80.211	2.1053	7.9	6.13	Radiated Spurious Emissions	Pass	
2.5	80.213	2.1047	7.7	-	Modulation Requirements	Pass	
2.6	80.215	2.1046	7.5	6.12	Transmitter Power	Pass	

Table 2



1.4 Manufacturer Declared Variant



Larvik: 07.12.2021

Statement of Conformity

Jotron AS hereby states that the Tron 40AIS is a variant of the Tron 40VDR AIS.
Testing performed on the Tron 40VDR AIS should in most cases cover Tron 40AIS testing.

On behalf of Jotron AS:

A handwritten signature in blue ink that reads 'Frank Løke'.

Frank Løke
Certification Manager
Jotron AS



1.5 Application Form

Equipment Description

Technical Description: <i>(Please provide a brief description of the intended use of the equipment including the technologies the product supports)</i>	COSPAS-SARSAT 406 MHz Satellite Emergency Position-Indication Radio Beacon	
Manufacturer:	Jotron AS	
Model:	Tron 40VDR AIS	
Part Number:	103171	
Hardware Version:	Rev: 2020	
Software Version:	Rev 1.2	
FCC ID of the product under test – see guidance here	VRV40VDRAIS	
IC ID of the product under test – see guidance here	2131A-40VDRAIS	

Intentional Radiators

Technology	EPIRB				
Frequency Range (MHz to MHz)	406.031 MHz, 161.975 - 162.025 MHz, 121.5 MHz				
Conducted Declared Output Power (dBm)	35.5 dBm (406 MHz) 31.4 dBm (162 MHz) 19.2 dBm (121.5 MHz)				
Antenna Gain (dBi)	-				
Supported Bandwidth(s) (MHz) (e.g 1 MHz, 20 MHz, 40 MHz)	25 KHz (406 MHz) 25 KHz (162 MHz) 25 KHz (121.5 MHz)				
Modulation Scheme(s) (e.g GFSK, QPSK etc)	Phase modulation 1.1 rad (406 MHz) GMSK/FM (162 MHz) AM Homing (121.5 MHz)				
ITU Emission Designator (see guidance here) (not mandatory for Part 15 devices)	16K0G1D (406.031 MHz) 16K0GXW (162 MHz) 3K20A3X (121.5 MHz)				
Bottom Frequency (MHz)	121.5 MHz				
Middle Frequency (MHz)	-				
Top Frequency (MHz)	406.031 MHz				

Un-intentional Radiators

Highest frequency generated or used in the device or on which the device operates or tunes	406.031 MHz
Lowest frequency generated or used in the device or on which the device operates or tunes	121.5 MHz
Class A Digital Device (Use in commercial, industrial or business environment) <input checked="" type="checkbox"/>	
Class B Digital Device (Use in residential environment only) <input type="checkbox"/>	

AC Power Source

AC supply frequency:	-	Hz
----------------------	---	----



Voltage	-	V
Max current:	-	A
Single Phase <input type="checkbox"/> Three Phase <input type="checkbox"/>		

DC Power Source

Nominal voltage:	-	V
Extreme upper voltage:	-	V
Extreme lower voltage:	-	V
Max current:	-	A

Battery Power Source

Voltage:	7.2	V
End-point voltage:	5	V (Point at which the battery will terminate)
Alkaline <input type="checkbox"/> Leclanche <input type="checkbox"/> Lithium <input checked="" type="checkbox"/> Nickel Cadmium <input type="checkbox"/> Lead Acid* <input type="checkbox"/> *(Vehicle regulated)		
Other <input type="checkbox"/>	Please detail:	

Charging

Can the EUT transmit whilst being charged	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
---	---

Temperature

Minimum temperature:	-20	°C
Maximum temperature:	+55	°C

Cable Loss

Adapter Cable Loss (Conducted sample)	-	dB
---------------------------------------	---	----

Antenna Characteristics

Antenna connector <input type="checkbox"/>	State impedance		Ohm
Temporary antenna connector <input type="checkbox"/>	State impedance		Ohm
Integral antenna <input checked="" type="checkbox"/>	Type:		Gain
External antenna <input type="checkbox"/>	Type:		Gain
For external antenna only: Standard Antenna Jack <input type="checkbox"/> If yes, describe how user is prohibited from changing antenna (if not professional installed): Equipment is only ever professionally installed <input type="checkbox"/> Non-standard Antenna Jack <input type="checkbox"/>			

Ancillaries (if applicable)



Manufacturer:		Part Number:	
Model:		Country of Origin:	

I hereby declare that the information supplied is correct and complete.

Name: Frank Løke
 Position held: Certification Manager Jotron AS
 Date: 2021-07-07

1.6 Product Information

1.6.1 Technical Description

The Equipment under test (EUT) was a Jotron AS Tron 40VDR AIS EPIRB with Float Free capsule.

The primary function of the EUT is an Emergency Position Indication Radio Beacon (EPIRB) within capsule.

Additionally, the EUT has functionality for Automatic Identification System (AIS), GNSS Rx (GPS/Galileo/Glonass), Transmitting 406 MHz, 121.5 MHz Home, RLS and VDR

1.7 Deviations from the Standard

No deviations from the applicable test standard were made during testing.

1.8 EUT Modification Record

The table below details modifications made to the EUT during the test programme.

The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Model: Tron 40VDR AIS, Serial Number: 00039 and 00041			
0	As supplied by the customer	Not Applicable	Not Applicable
1	GNSS LED changed to blink before or after 406MHz to reduce noise on modulation	Manufacturer at TUV SUD site	31-March 2021
2	Addition of a LDO (Low Dropout Regulator) to the TCXO, to reduce the noise coming from the power supply. A resistor of 0 ohm (added to the design for current measurement) was replaced by the three-legged regulator.	Manufacturer	27-April 2021
3	SW update to reduce image AIS frequencies. Parameter in the synthesizer was adjusted to reduce the signal level from the clock.	Manufacturer	21-May 2021

Note: Repair was carried out on sample with Serial Number 00041 on 25-May-2021 to resolve an issue with low power output.

Table 3



1.9 Test Location

TÜV SÜD conducted the following tests at our Fareham Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Configuration and Mode: AIS Transceiver		
Bandwidths	Neil Rousell	UKAS
Transmitter Frequency Tolerances	Neil Rousell	UKAS
Spurious Emissions at Antenna Terminals	Neil Rousell	UKAS
Radiated Spurious Emissions	Graeme Lawler	UKAS
Modulation Requirements	Neil Rousell	UKAS
Transmitter Power	Neil Rousell	UKAS

Table 4

Office Address:

TÜV SÜD
Octagon House
Concorde Way
Fareham
Hampshire
PO15 5RL
United Kingdom



2 Test Details

2.1 Bandwidths

2.1.1 Specification Reference

FCC 47 CFR Part 80, Clause 80.205
FCC 47 CFR Part 2, Clause 2.1049
ISED RSS-GEN, Clause 6.7

2.1.2 Equipment Under Test and Modification State

Tron 40VDR AIS, S/N: 00039 - Modification State 2

2.1.3 Date of Test

13-May-2021

2.1.4 Test Method

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 80.205, Part 2.1049, ISED RSS-GEN Clause 6.7 and KDB 971168.

The EUT was transmitting at maximum power, modulated by the standard AIS test signals using PRBS packet payloads. The EUT was connected to a spectrum analyser via a cable and attenuator, the RBW of the spectrum analyser was set to at least 1% of the emission bandwidth, the occupied bandwidth measurement function of the analyser was used and the 99% bandwidth recorded.

2.1.5 Environmental Conditions

Ambient Temperature 23.4 °C
Relative Humidity 44.3 %

2.1.6 Test Results

AIS Transceiver

161.975 MHz	162.025 MHz
9.53 kHz	9.45 kHz

Table 5 - Occupied Bandwidth Results




Figure 1 - 161.975 MHz Occupied Bandwidth




Figure 2 - 162.025 MHz Occupied Bandwidth

FCC 47 CFR Part 80, Limit Clause 80.205

Emission Designator: 16K0GXW (Note: Emission Designator for AIS not specified in Part 80.205)
 Authorised Bandwidth: < 20 kHz

ISED RSS-182, Limit Clause 7.9.1

Equipment with a 25 kHz channel spacing, an authorised bandwidth of 16 kHz for voice and 20 kHz for data.



2.1.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Rubidium Standard	Rohde & Schwarz	XSRM	1316	6	17-May-2021
Network Analyser	Rohde & Schwarz	ZVA 40	3548	12	29-Jan-2022
Calibration Unit	Rohde & Schwarz	ZV-Z54	4368	12	30-Dec-2021
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	17-May-2021
1 metre K-Type Cable	Florida Labs	KMS-180SP-39.4-KMS	4520	12	16-Nov-2021
PXA Signal Analyser	Keysight Technologies	N9030A	4654	12	06-Nov-2021
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5475	12	06-Apr-2022
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5504	12	14-Apr-2022
Attenuator 2W 10dB DC-10GHz	Telegartner	J01156A0031	5577	-	O/P Mon
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB 40	5605	12	08-Sep-2021

Table 6

O/P Mon – Output Monitored using calibrated equipment



2.2 Transmitter Frequency Tolerances

2.2.1 Specification Reference

FCC 47 CFR Part 80, Clause 80.209
FCC 47 CFR Part 2, Clause 2.1055
ISED RSS-182, Clause 7.4
ISED RSS-GEN, Clause 6.11

2.2.2 Equipment Under Test and Modification State

Tron 40VDR AIS, S/N: 00039 - Modification State 3

2.2.3 Date of Test

15-June-2021 to 16-June-2021

2.2.4 Test Method

The EUT was modulated using the standard AIS test signal with PRBS packet payload and was transmitting in turn on either AIS channel. The EUT was connected to a spectrum analyser via a cable and attenuator. The external frequency reference of the spectrum analyser was locked to a 10 MHz rubidium frequency standard reference. The 99 % OBW function of the spectrum analyser was used to record the carrier frequency error. The temperature was varied from -30°C to +55° in 10° steps. At 20°C the voltage was also reduced to the manufacturer declared battery endpoint voltage and the carrier frequency measured.

2.2.5 Environmental Conditions

Ambient Temperature 24.7 - 24.9 °C
Relative Humidity 48.7 - 50.9 %

2.2.6 Test Results

AIS Transceiver

Voltage	Frequency Error (ppm)	
	161.975 MHz	162.025 MHz
4.5 V DC	0.13	0.08
7.2 V DC	0.14	0.09

Table 7 - Frequency Stability Under Voltage Variations



Temperature	Frequency Error (ppm)	
	161.975 MHz	162.025 MHz
+55.0 °C	0.04	0.02
+50.0 °C	0.07	0.02
+40.0 °C	0.10	0.07
+30.0 °C	0.08	0.06
+20.0 °C	0.14	0.09
+10.0 °C	0.10	0.16
0 °C	0.23	0.35
-10.0 °C	0.24	0.30
-20.0 °C	0.35	0.14
-30.0 °C	0.22	0.29

Table 8 - Frequency Stability Under Temperature Variations

FCC 47 CFR Part 80, Limit Clause 80.209

± 10 ppm.

ISED RSS-182, Limit Clause 7.4

± 10 ppm



2.2.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 3.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Rubidium Standard	Rohde & Schwarz	XSRM	1316	6	03-Dec-2021
Hygrometer	Rotronic	I-1000	2891	12	16-Oct-2021
Multimeter	Fluke	79 Series II	3057	12	21-Aug-2021
Thermocouple Data Logger	Pico Technology Ltd	TC-08	3783	12	22-Jun-2021
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	03-Dec-2021
1 metre K-Type Cable	Florida Labs	KMS-180SP-39.4-KMS	4519	12	16-Nov-2021
PXA Signal Analyser	Keysight Technologies	N9030A	4654	12	06-Nov-2021
Quad Power Supply	Rohde & Schwarz	HMP4040	4954	-	O/P Mon
Thermo-Hygro-Barometer	PCE Instruments	OCE-THB-40	5470	12	31-Mar-2022
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5504	12	14-Apr-2022
Attenuator 2W 10dB DC-10GHz	Telegartner	J01156A0031	5577	-	O/P Mon
Environmental Chamber	ACS	DY110TC	5589	-	O/P Mon

Table 9

O/P Mon – Output Monitored using calibrated equipment



2.3 Spurious Emissions at Antenna Terminals

2.3.1 Specification Reference

FCC 47 CFR Part 80, Clause 80.211
FCC 47 CFR Part 2, Clause 2.1051
ISED RSS-182, Clause 7.9
ISED RSS-GEN, Clause 6.13

2.3.2 Equipment Under Test and Modification State

Tron 40VDR AIS, S/N: 00039 - Modification State 3

2.3.3 Date of Test

11-June-2021 to 01-July-2021

2.3.4 Test Method

For emissions where the frequency is removed less than 250 % of the authorized bandwidth measurements were performed conducted as follows:

The EUT was connected to a spectrum analyser via a cable and attenuator. The path loss between the EUT and analyser was calibrated using a network analyser and entered into the spectrum analyser as a reference level offset. The spectrum analyser was configured with an RBW of 300 Hz with the trace set to max hold using a peak detector. The mask as per FCC CFR 47 Part 80, clause 80.211 (f) was applied.

For emissions where the frequency is removed more than 250 % of the authorized bandwidth measurements were performed both conducted and radiated. Conducted measurements were performed as follows:

A network analyser was used to measure the path loss and the worst case was entered as a reference level offset into the spectrum analyser. The EUT was connected to a spectrum analyser via an attenuator, filter and cable. Between 300 MHz and 2 GHz a 300 MHz high pass filter was used. The spectrum analyser was configured with an RBW of 30 kHz with the trace set to max hold using a peak detector

2.3.5 Environmental Conditions

Ambient Temperature	23.4 - 23.5 °C
Relative Humidity	49.6 - 60.6 %



2.3.6 Test Results

AIS Transceiver




Figure 3 - 161.975 MHz - Transmitter Spectrum Mask




Figure 4 - 162.025 MHz - Transmitter Spectrum Mask




Figure 5 - 161.975 MHz - 9 kHz to 300 MHz




Figure 6 - 162.025 MHz - 9 kHz to 300 MHz




Figure 7 - 161.975 MHz - 300 MHz to 1 GHz




Figure 8 - 162.025 MHz - 300 MHz to 1 GHz




Figure 9 - 161.975 MHz - 1 GHz to 2 GHz




Figure 10 - 162.025 MHz - 1 GHz to 2 GHz



FCC 47 CFR Part 80, Limit Clause 80.211

Within 250 % of the Authorised Bandwidth:

On any frequency removed from the assigned frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: At least 25 dB;

On any frequency removed from the assigned frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: At least 35 dB

More than 250 % of the Authorised Bandwidth:

On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 plus $10\log_{10}$ (mean power in watts) dB.

ISED RSS-182, Limit Clause 7.9.1

On any frequency removed from the carrier frequency by more than 50 %, but not more than 100 % of the authorized bandwidth: at least 25 dB, measured with a bandwidth of 300 Hz.

On any frequency removed from the carrier frequency by more than 100 %, but not more than 250 % of the authorized bandwidth: at least 35 dB, measured with a bandwidth of 300 Hz.

On any frequency removed from the carrier frequency by more than 250 % of the authorized bandwidth: at least $43 + 10 \log_{10} P(\text{watts})$ dB, measured with a bandwidth of 30 kHz.



2.3.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Rubidium Standard	Rohde & Schwarz	XSRM	1316	6	03-Dec-2021
Network Analyser	Rohde & Schwarz	ZVA 40	3548	12	29-Jan-2022
Calibration Unit	Rohde & Schwarz	ZV-Z54	4368	12	30-Dec-2021
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	03-Dec-2021
1 metre K-Type Cable	Florida Labs	KMS-180SP-39.4-KMS	4520	12	16-Nov-2021
PXA Signal Analyser	Keysight Technologies	N9030A	4654	12	06-Nov-2021
Cable (18 GHz)	Rosenberger	LU7-071-1000	5099	12	12-Oct-2021
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5475	12	06-Apr-2022
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5504	12	14-Apr-2022
300 MHz High Pass Filter	Mini-Circuits	NHP-300	5532	12	25-Mar-2022
Attenuator 2W 10dB DC-10GHz	Telegartner	J01156A0031	5577	-	O/P Mon

Table 10

O/P Mon – Output Monitored using calibrated equipment



2.4 Radiated Spurious Emissions

2.4.1 Specification Reference

FCC 47 CFR Part 80, Clause 80.211
FCC 47 CFR Part 2, Clause 2.1053
ISED RSS-182, Clause 7.9
ISED RSS-GEN, Clause 6.13

2.4.2 Equipment Under Test and Modification State

Tron 40VDR AIS, S/N: 00041 - Modification State 3

2.4.3 Date of Test

08-June-2021

2.4.4 Test Method

Testing was performed in accordance with ANSI C63.26, clause 5.5.4.

A preliminary profile of the Spurious Radiated Emissions was obtained up to the 10th harmonic by operating the EUT on a remotely controlled turntable within a semi-anechoic chamber.

Measurements of emissions from the EUT were obtained with the Measurement Antenna in both Horizontal and Vertical Polarisations. The profiling produced a list of the worst-case emissions together with the EUT azimuth and antenna polarisation.

Using the information from the preliminary profiling of the EUT, the list of emissions was then confirmed or updated under Alternative Open Site conditions. Emission levels were maximised by adjusting the antenna height, antenna polarisation and turntable azimuth.

The EUT was set to transmit on maximum power with each channel tested in turn.

2.4.5 Environmental Conditions

Ambient Temperature 20.1 °C
Relative Humidity 53.2 %

2.4.6 Test Results

AIS Transceiver

Frequency (MHz)	Level (dBm)
323.973	-15.81

Table 11 - 161.975 MHz - Emissions Results

No other emissions were detected within 10 dB of the limit.




Figure 11 - 161.975 MHz - 30 MHz to 2 GHz - Vertical Polarisation




Figure 12 - 161.975 MHz - 30 MHz to 2 GHz - Horizontal Polarisation



Frequency (MHz)	Level (dBm)
324.012	-16.65

Table 12 - 162.025 MHz - Emissions Results

No other emissions were detected within 10 dB of the limit.




Figure 13 - 162.025 MHz - 30 MHz to 2 GHz - Vertical Polarisation




Figure 14 - 162.025 MHz - 30 MHz to 2 GHz - Horizontal Polarisation



FCC 47 CFR Part 80, Limit Clause 80.211

More than 250% of the Authorised Bandwidth:

On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 plus $10\log_{10} P$ (mean power in watts) dB.

ISED RSS-182, Limit Clause 7.9.1

On any frequency removed from the carrier frequency by more than 250 % of the authorized bandwidth: at least 43 + 10 log₁₀ P(watts) dB, measured with a bandwidth of 30 kHz.

2.4.7 Test Location and Test Equipment Used

This test was carried out in EMC Chamber 12.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Antenna with permanent attenuator (Bilog)	Schaffner	CBL6143	287	24	14-Oct-2022
Comb Generator	Schaffner	RSG1000	3034	-	TU
EMI Test Receiver	Rohde & Schwarz	ESU40	3506	12	18-Mar-2022
EmX Emissions Software	TUV SUD	V2.1.9	5125	-	Software
Cable 2.92m	Junkosha	MWX241/B	5411	12	22-Jun-2021
3.5 mm 2m Cable	Junkosha	MWX221-02000DMS	5428	12	15-Oct-2021
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5481	12	31-Mar-2022
Broadband Horn Antenna (1-10 GHz)	Schwarzbeck	BBHA 9120 B	5611	12	22-Sep-2021
Turntable & Mast Controller	Maturo Gmbh	NCD/498/2799.01	5612	-	TU
Tilt Antenna Mast TAM 4.0-P	Maturo Gmbh	TAM 4.0-P	5613	-	TU
Turntable	Maturo Gmbh	Turntable 1.5 SI-2t	5614	-	TU
3m Semi Anechoic Chamber	MVG	EMC-3	5621	36	11-Aug-2023
Cable Assembly - 18GHz 8m	Junkosha	MWX221-08000NMSNMS/B	5732	6	05-Aug-2021

Table 13

TU - Traceability Unscheduled



2.5 Modulation Requirements

2.5.1 Specification Reference

FCC 47 CFR Part 80, Clause 80.213
FCC 47 CFR Part 2, Clause 2.1047
ISED RSS-182, Clause 7.7

2.5.2 Equipment Under Test and Modification State

Tron 40VDR AIS, S/N: 00039 - Modification State 3

2.5.3 Date of Test

14-June-2021

2.5.4 Test Method

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 80, clause 80.213 (d).

The EUT was transmitting at maximum power, modulated by the standard AIS test signals using either PRBS, 01010101 or 00001111 packet payloads. The EUT was connected to a spectrum analyser via a cable and attenuator, using the FM demodulation function of the spectrum analyser, the peak frequency deviation was observed.

2.5.5 Environmental Conditions

Ambient Temperature 23.8 °C
Relative Humidity 57.3 %

2.5.6 Test Results

AIS Transceiver




Figure 15 - 161.975 MHz - 01010101




Figure 16- 161.975 MHz - 00001111




Figure 17- 161.975 MHz - PRBS




Figure 18 - 162.025 MHz - 01010101




Figure 19- 162.025 MHz - 00001111




Figure 20- 162.025 MHz - PRBS

FCC 47 CFR Part 80, Limit Clause 80.213

Ship and coast station transmitters operating in the 156-162 MHz and 216-220 bands must be capable of proper operation with a frequency deviation that does not exceed ± 5 kHz when using any emission authorized by 80.207.

ISED RSS-182, Limit Clause 7.7

The VHF AIS equipment shall comply with the following characteristics.

- | | |
|------------------------|---|
| Transmitter frequency: | 161.975 MHz (channel 87B)
162.025 MHz (channel 88B) |
| Channel spacing: | 25 kHz or 12.5 kHz |
| Modulation scheme: | GMSK/FM |
| Modulation index: | 0.5 max. for 25 kHz channel spacing
0.25 max. for 12.5 kHz channel spacing |
| Transmission rate: | 9600 bps |



2.5.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Rubidium Standard	Rohde & Schwarz	XSRM	1316	6	03-Dec-2021
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	03-Dec-2021
PXA Signal Analyser	Keysight Technologies	N9030A	4654	12	06-Nov-2021
Cable (18 GHz)	Rosenberger	LU7-071-1000	5099	12	12-Oct-2021
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5475	12	06-Apr-2022
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5504	12	14-Apr-2022

Table 14



2.6 Transmitter Power

2.6.1 Specification Reference

FCC 47 CFR Part 80, Clause 80.215
 FCC 47 CFR Part 2, Clause 2.1046
 ISED RSS-182, Clause 7.5
 ISED RSS-GEN, Clause 6.12

2.6.2 Equipment Under Test and Modification State

Tron 40VDR AIS, S/N: 00039 - Modification State 2

2.6.3 Date of Test

13-May-2021

2.6.4 Test Method

The test was applied in accordance with the test method requirements of FCC CFR 47 Part 80, clause 80.215 (e) and KDB 971168.

The EUT was set to transmit on maximum power in turn on either AIS channel. The EUT was modulated using the standard AIS test signal with PRBS packet payload. The EUT was connected to a spectrum analyser via a cable and attenuator. The path loss was measured using a network analyser and entered as a reference level offset in the spectrum analyser. The RBW of the spectrum analyser was set to 100 kHz and the video bandwidth to 300 kHz with the trace set to max hold using a peak detector and the result was recorded

2.6.5 Environmental Conditions

Ambient Temperature 23.5 °C
 Relative Humidity 43.7 %

2.6.6 Test Results

AIS Transceiver

161.975 MHz		162.025 MHz	
Result (dBm)	Result (W)	Result (dBm)	Result (W)
33.9	2.5	33.9	2.5

Table 15 - Transmitter Power Results

FCC 47 CFR Part 80, Limit Clause 80.215 (d)

Ship station frequencies above 27500 kHz. The maximum power must not exceed the values listed below:

- Ships Stations: 156 to 162 MHz - 25 W
- Marine Utility Stations and Handheld Portable Transmitters: 156 to 162 MHz - 10 W



ISED RSS-182, Limit Clause 7.5

The output power shall be within ± 1.0 dB of the manufacturer's rated power and not exceed the limits listed in the table below, unless indicated otherwise.

Stations	Typical Power
Coast Station	50 W
Ship Stations Minimum Maximum	6 W 25 W
Hand-held portable transmitters	5 W
Survival two-way radiotelephones	Should have a minimum e.i.r.p of 0.25 W

Table 16

2.6.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Rubidium Standard	Rohde & Schwarz	XSRM	1316	6	17-May-2021
Network Analyser	Rohde & Schwarz	ZVA 40	3548	12	29-Jan-2022
Calibration Unit	Rohde & Schwarz	ZV-Z54	4368	12	30-Dec-2021
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	17-May-2021
1 metre K-Type Cable	Florida Labs	KMS-180SP-39.4-KMS	4520	12	16-Nov-2021
PXA Signal Analyser	Keysight Technologies	N9030A	4654	12	06-Nov-2021
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB-40	5475	12	06-Apr-2022
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5504	12	14-Apr-2022
Attenuator 2W 10dB DC-10GHz	Telegartner	J01156A0031	5577	-	O/P Mon
Thermo-Hygro-Barometer	PCE Instruments	PCE-THB 40	5605	12	08-Sep-2021

Table 17

O/P Mon – Output Monitored using calibrated equipment

3 Photographs

3.1 Test Setup Photographs



Figure 21 - Test Setup - 30 MHz to 1 GHz



Figure 22 - Test Setup - 1 GHz to 2 GHz



4 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

Test Name	Measurement Uncertainty
Bandwidths	± 58.05 Hz
Transmitter Frequency Tolerances	± 11 Hz
Spurious Emissions at Antenna Terminals	± 3.45 dB
Radiated Spurious Emissions	30 MHz to 1 GHz: ± 5.2 dB 1 GHz to 18 GHz: ± 6.3 dB
Modulation Requirements	-
Transmitter Power	± 3.2 dB

Table 18

Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2007, clause 4.4.3 and 4.5.1.