



Tron 40VDR

VDR	
Local Recording Medium	
VDR Number	
Serial No.	01006
MMSI Code, URN	
Vessel Name	
MMSI Call Sign	
Country	

PUSH

Manual Operating
Remove the CPMB from the Device



Activation

- 1) Remove seal
- 2) Push
- 3) The switch goes to ON position

Deactivation
Reverse operation

Test
Only after test of each test
1) Push and hold down
2) Release the test
3) Repeat test only

Complete safety distance: 0.5m
Minimum distance to vessels: 0.5m

Weight: 1000g

In the event of false activation in the USA, call toll free: 1-855-406-USCG (8724)

Jotron AS cannot be held responsible for any damage caused due to incorrect use of equipment or breach of laid down procedures.



www.jotron.com



0470/14

WARNING
FOR EMERGENCY USE ONLY

Keep EPRM with a clear view to the sky without obstructions at all times

WARRANTY VOID
IF SEAL IS BROKEN



WARNING: The EPIRB can drop out of the bracket when releasing front cover of the bracket.

OPERATION

Pull pin from release rail above to remove cover, detach cover with caution. For manual activation, deactivation, self-test and inspection of EPIRB please follow instructions on EPIRB. Category 1 EPIRB will automatically be released from bracket and float free if vessel sinks.

WARNING: THE EPIRB SHALL NOT BE OPERATED EXCEPT IN AN EMERGENCY.

THIS EPIRB IS CATEGORY 1



406/121.5 MHz
SATELLITE
EPIRB

Tron 40VDR

visit www.jotron.com for Recording Medium

EPI Number	
Serial No.	010006
NET Code, USA	
Manufacturer	
EMR Call Sign	
Country	

Compass safety distance: 0.8m
 Maximum distance to vessel: 0.8m

Weight: 1000g

In the event of false activation in the USA, call toll free 1-800-406-USCG (8724)

Jotron will not be held responsible for any damage caused due to incorrect use of equipment or breach of laid down procedures.

JOTRON
www.jotron.com

5478/14



Activation:
 1) Remove seal
 2) Push
 3) The switch go ON position.
 Deactivate:
 Reverse operation

WARRANTY IF SEAL IS BROKEN

JOTRON Tron 40VDR Docking Module 87921

Power	Data
On	Link

87945



Tron 40VDR

VDR	
Initial Recording Medium	
USP Number	
Serial No.	01008
NET Code, USN	
Brand Name	
Manufacturer Sign	
Capacity	

ON READY

PUSH

Check safety distance: 0.8m
 Maximum pressure or vacuum: 0.8m

Weight: 100 kg

In the event of false activation in the USA, call toll free 1-800-408-USCG (8724)

Jotron AG cannot be held responsible for any damage caused due to incorrect use of equipment or breach of laid down procedures.

JOTRON
www.jotron.com

0470/14

Manual Operating
 Remove the EPDR from its holder

Activation: 1) Remove seal 2) Push 3) The switch goes to ON position. Deactivate: Reverse operation	Tip: Check indicator light of push button If push button not lit, test power cable and signal line only

WARNING
 FOR EMERGENCY USE ONLY
 Keep EPDR unit in close view to the fire without touching any part of it.

WARRANTY VOID
 IF SEAL IS BROKEN

JOTRON Tron 40VDR Docking Module 87921

Power	Data
On	Link

87945



JOTRON
HYDROSTATIC RELEASE
Stock No. 8-91820
Part No. 87945
MADE IN SWEDEN

JOTRON Tron 40VDR
Docking Module 87921

Power	Data
On	Link

87945