





Folie: ORACAL 751 TRANSPARENT  
 Colour: Orange  
 Colour: Ligth grey (edge)  
 Colour: Black (text)

E	31.03.14	BJ	Changed character	
D	14.03.12	BJ	Changed from wessel to vessel.	
A	08.12.10	AD	First version.	
Rev.	Date	Sign.	Description/Change	
Material:			This drawing is a property of Jotron AS and must not be duplicated or used for manufacture of the parts disclosed herein without permission from Jotron AS.	
Surface Treatment:			Scale:	
			1 : 1	
Approved:	Draft:	Date:		
	AD	08.12.10		
LABEL			Replaces draft:	Repl. by draft:
OPERATION				
FB-60/Simrad FB-70			X-86212	
			Sheet:	1 / 1
			Rev:	E



**406/121.5 MHz**  
**S A T E L L I T E**  
**EPIRB**

Foliotype: FASCAL TRANSP FOLIE  
 Color: GREY

A				10.12.10	AD	First version
Rev.	Date	Sign	Description/Change			
Material:				This drawing is a property of Jotron AS and must not be duplicated or used for manufacture of the parts disclosed herein without permission from Jotron AS		
Surface Treatment:				Scale:		
				1:1		
Approved:	Draft:	AD	Date:	10.12.10		
LABEL				Replaces draft:	Repl. by draft:	
406/121,5 MHz				<b>X-86216</b>		Sheet: 1 / 1
FB-60/Simrad FB-70						Rev: <b>A</b>

WARRANTY VOID  
IF SEAL IS BROKEN

Folie type: SCS500-500 (sølvgrå)  
Colour text: BLACK

A	17.09.12	AD	First version.		
Rev.	Date	Sign.	Description/Change		
Material:				This drawing is a property of Jotron AS and must not be duplicated or used for manufacture of the parts disclosed herein without permission from Jotron AS	
Surface Treatment:				Scale: 1 : 1	
Approved:	Draft:	Date:			
	AD	17.09.12			
SEAL LABEL				Replaces draft:	Repl. by draft:
WARRANTY VOID IF SEAL IS BROKEN				X-87256	Sheet: 1 / 1 Rev: A

Note: The EPIRB will automatically activated when it's in water.

### Manual Operating


Remove the EPIRB from the Bracket

Compass safety distance: 0,8m  
безопасное расстояние до компаса : 0,8m



Weight: 1900g

In the event of false activation in the USA,  
call toll free 1-855-406-USCG (8724)



Jotron AS cannot be held responsible for any  
damage caused due to incorrect use of  
equipment or breach of laid down  
procedures.



www.jotron.com

0470/15

**Activation:**  
1) Remove seal  
2) Push  
3) The switch goes to ON position.


**Deactivate:**  
Reverse operation

**Test:**  
(Only within first 5 min. of each hour)  
1) Push and hold >15 sec.  
Test passed after one single flash only.


**WARNING!**  
FOR EMERGENCY USE ONLY!  
Keep EPIRB with a clear view to the sky without obstructions of GPS antenna.

Colour: BLACK

Material: ORACAL 751 00 transparent  
This drawing is property of Jotron AS and must not be duplicated or used for manufacturing of any parts disclosed

Surface Treatment: 

Approved: \_\_\_\_\_ Draft: TN Date: 20.09.13



LABEL OPERATION TRON 40VDR



Size: A4 Scale: 1:1 Sheet: 1 / 1

X-87555 Rev: D

D	20.11.14	BJ	wheelmark change from 2014 to 2015	nnnn
C	09.04.14	BJ	Change from signal to single	nnnn
B	16.01.14	BJ	Updated	nnnn
A	20.10.13	TN	First version	nnnn
Rev.	Date	Sign.	Description	EM No.



2017	2018	2019	2020	2021	2022						
Battery type: 87459 (Class 2) Lithium metal 7.2V / 18Ah Service or SMI shall be performed within battery expire date: Operation: > 168 hrs. -20°C to +55°C (4°F to +130°F) Storage: > 70% (22°F to +150°F) -30°C to +70% (22°F to +150°F)											
Expire date year/month											
1	2	3	4	5	6	7	8	9	10	11	12

Colour: BLACK

B	29.01.14	BJ	New design	nnnn
A	20.09.13	TN	First version	nnnn
Rev.	Date	Sign.	Description	EM No.
Material:			This drawing is property of Jotron AS and must not be duplicated or used for manufacturing of any parts disclosed	
ORACAL 751 00 transparent				
Surface Treatment:				
Approved:	Draft:	Date:		
	TN	20.09.13		
LABEL			Size:	Sheet:
BATTERY EXPIRE DATE			A4	1 / 1
TRON 40VDR			Scale:	Rev:
			1 : 1	B
			X-87556	



**Bracket type: 87920, FB-40VDR**  
**Category 1, Automatic release**  
**Replace hydrostatic release:**

Folie: ORACAL 751 TRANSPARENT  
 Colour: Light grey (edge)  
 Colour: Black (text)

A	20.06.13	BJ		
Rev.	Date	Sign	Description/Change	
Material:			This drawing is a property of Jotron AS and must not be duplicated or used for manufacture of the parts disclosed herein without permission from Jotron AS	
Surface Treatment:			Scale:	
			1 : 1	
Approved:	Draft:	Date:		
	AD	08.12.10		
LABEL			Replaces draft:	Repl. by draft:
BRACKET TYPE			X-87759	Sheet: 1 / 1
FB-40VDR				Rev: A

**EPIRB type: Tron 40VDR 406/121.5 MHz**  
**Class 2 (-20°C to +55°C/-4°F to +131°F)**  
**Jotron AS, Norway, [www.jotron.com](http://www.jotron.com)**

Folie: ORACAL 751 TRANSPARENT  
 Colour: Light grey (edge)  
 Colour: Black (text)

C	17.06.14	BJ	Update temp. operating	
B	20.01.14	BJ		
A	01.10.13	BJ		
Rev.	Date	Sign	Description/Change	
Material:			This drawing is a property of Jotron AS and must not be duplicated or used for manufacture of the parts disclosed herein without permission from Jotron Electronics	
Surface Treatment:			Scale: <b>1 : 1</b>	
Approved:	Draft: <b>AD</b>	Date: -----		
LABEL			Replaces draft:	Repl. by draft:
EPIRB TYPE			<b>X-87760</b>	Sheet: 1 / 1
FB-40VDR				Rev: <b>C</b>




Colour: BLACK

Material: Murfolie, hvit		This drawing is property of Jotron AS and must not be duplicated or used for manufacturing of any parts disclosed	
Surface Treatment:			
Approved:	Draft: TN	Date: 21.09.13	
LABEL		Size: A4	Scale: 1:1
VOYAGE DATA RECORDER		Sheet: 1 / 1	
TRON 40VDR		Rev: B	
		<b>X-87944</b>	

Rev.	Date	Sign.	Description	EM No.
B	18.03.14	BJ	New text	n n n n
A	21009.13	TN	First version	n n n n







Colour: BLACK

Rev.	Date	Sign.	Description	EM No.
				nnnn
				nnnn
A	20.09.13	TN	First version	nnnn

Material: ORACAL 751 00 transparent		This drawing is property of Jotron AS and must not be duplicated or used for manufacturing of any parts disclosed herein without permission from Jotron AS.		
Surface Treatment:				
Approved:	Draft: TN	Date: 20.09.13		
LABEL VDR DOCKING MODULE TRON 40S VDR			Size: A4	Scale: 1 : 1
			Sheet: 1 / 1	
			Rev: A	
			X-87945	



**Lithium battery type: 87459**  
**Compass safe distance 0,8m**  
**FCC ID:**

Folie: ORACAL 751 TRANSPARENT  
 Colour: Light grey (edge)  
 Colour: Black (text)

C	17.06.14	BJ	Change safety distance	
B	01.01.14	BJ	Change safety distance	
A	01.10.13	BJ	First version.	
Rev.	Date	Sign	Description/Change	
Material:			This drawing is a property of Jotron El. and must not be duplicated or used for manufacture of the parts disclosed herein without permission from Jotron Electronics	
Surface Treatment:			Scale:	
			1 : 1	
Approved:	Draft:	Date:		Replaces draft:      Repl. by draft:
	TN	?		
LABEL			X-87968	
BATTERY TYPE				
FB-40VDR			Rev: C	



Print: Black

D	16.06.14	BJ	Updated "installation"	
C	30.01.14	BJ	Updated the address	
B	10.09.12	TN	Size reduced to half.	
A	10.03.11	BJ	First version	
Rev.	Date	Sign.	Description	EM No.
Material: Multicolour (yellow)			This drawing is property of Jotron AS and must not be duplicated or used for manufacturing of any parts disclosed	
Surface Treatment:				
Approved:	Draft: TN	Date: 10.03.11		
LABEL WARNING WEPIRB w/hole			Size: A4	Scale: 1 : 1
			X-91933	Sheet: 1 / 1 Rev: D



## Arkivsystem for etiketter i pdf-format.

Dato: 17.12.2001

**Etikettens x-nummer: X - 97997**

Etikettens navn: LABEL ON-OFF-SWITCH, T-40S/GPS USA

Etikettens format bredde 70 mm høyde 16 mm

Folietype: TRANSPARENT

Trykkfarge: SORT





## Arkivsystem for etiketter i pdf-format.

Dato: 17.02.2004

**Etikettens x-nummer: X - X-97998**

Etikettens navn: PUSH LABEL T-40S/GPS USA/STD

Etikettens format bredde 30 mm høyde 9 mm

Folietype: FASCAL TRANSP FOLIE

Trykkfarge: SORT

Ferdiggjøring: SLISSES

# PUSH