► INCREASE YOUR
SAFETY ON BOARD
WITH INNOVATIVE
TECHNOLOGY









www.jotron.com

## ► AIS-SART

## GMDSS SEARCH AND RESCUE TRANSMITTER



• Adopted by IMO RES MSC. 256 (84) as an alternative to 9GHz SART

Proved performance:

- Up to 10 nm from a SOLAS ship with AIS class A transponder
- Up to 40 nm from a SAR helicopter (altitude 1000 ft)
- Up to 130 nm from a SAR aircraft (altitude 20000 ft)
- Unique AIS technology contribute to a more effective and less time consuming SAR operation, due to superior position accuracy
- The AIS-SART is detected on both AIS Class A and B
- Small and compact
- Jotron Tron AIS-SART use the same acessories as the Tron SART20 (Bulkhead bracket, pole, life-boat bracket and neoprene protection bag)

## **SPECIFICATIONS**

Weight: 450g (16 oz) Height: 251 mm (9 1/6')

Material housing: Glass fiber filled Polycarbonate

Frequency: 161.975 and 162.025 MHz (AIS 1 and 2)

Radiated power: Minimum 1W ERP (+30 dBm)

Time to GPS fix: Typically less than 2 min when operated in an area with

good satellite coverage.

Signaling: Broadcasts position message, one burst every minute.

Broadcast safety message; "SART ACTIVE"

Position update: Every minute
Antenna pattern: Vertical polarization

Antenna height: Place at least 1m (3.3 ft) above sea/ground level

Indicators: Transmitter and GPS system operating Temperature range: Operating:  $-20^{\circ}\text{C}$  to  $+55^{\circ}\text{C}$  ( $-4^{\circ}\text{F}$  to  $+131^{\circ}\text{F}$ ) Storage:  $-30^{\circ}\text{C}$  to  $+65^{\circ}\text{C}$  ( $-22^{\circ}\text{F}$  to  $+149^{\circ}\text{F}$ )

Battery: Lithium, non hazardous battery for safe and unrestricted

transportation

Operating life: Minimum 96 hours

Standards: MSC.246(83), ITU-R M.1371, IEC 61097-14, IEC 60945,

SOLAS convention

**ACCESSORIES** 

Brackets: Bulkhead bracket

Lifeboat bracket

For life raft: Life raft mounting pole

Neoprene bag and strengthened lanyard

**WARRANTY** 5 years





Agent/Distributor:

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

www.jotron.com

## **CONTACT INFORMATION**

Jotron AS P.O.Box 54 3281 Tjodalyng Norway Tel: +47 33 13 97 00 Fax: +47 33 12 67 80 sales@jotron.com Jotron UK Ltd.
Crosland Park
Cramlington
NE23 1LA
United Kingdom
Tel: +44 (0) 1670 712000
Fax: +44 (0) 1670 590265
sales@jotron.com

Jotron Asia Pte. Ltd. 19 Loyang Way Changi Logistics Centre Rear Office Block 04-26 Singapore 508724 Tel: +65 65426350 Fax: +65 65429415 sales@jotron.com Jotron USA, Inc. 10645 Richmond Avenue Suite 140 Houston, TX 77042 USA Tel: +1 713 268 1061 Fax: +1 713 268 1062 sales@jotron.com