FCC ID: VS9G320 Report No.:SZSTS090803F1

5.9Radio Frequency Exposure

5.9.1 limit

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

5.9.2 EUT Specification

EUT	Bluekite
Frequency band (Operating)	 □ WLAN: 2.412GHz ~ 2.462GHz □ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz □ WLAN: 5.745GHz ~ 5825GHz □ Others Bluetooth: 2402GHz ~ 2480GHz
Device category	✓ Portable (<20cm separation)✓ Mobile (>20cm separation)✓ Others
Exposure classification	 ☐ Occupational/Controlled exposure (S = 5mW/cm²) ☐ General Population/Uncontrolled exposure (S=1mW/cm²)
Antenna diversity	 Single antenna Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	-4.55dBm (0.35mW)
Antenna gain (Max)	1.0 dBi
Evaluation applied	
Note: 1. The maximum output power is <u>-4.55dBm (0.35mW)</u> at <u>2402MHz.</u> 2. DSS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.	

For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.

5.9.3 Test Results

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: 60/f (GHz)=60/2.441=24.58mW)

5.9.4 MPE evaluation

Not applicable.