

3F, Yukyong B/D, 544-6, Gasan-dong, Geumcheon-gu, Seoul, Korea 153-803

# §1.1307 and §2.1093-RF EXPOSURE EVULATION

# 1.1 Limit

§ 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

| Frequency Range<br>(MHz)                                | Electric Field Strength<br>(V/m) | Magnetic Field Strength<br>(A/m) | Power Density<br>(mW/cm2) | Average Time<br>(minutes) |
|---|----------------------------------|----------------------------------|---------------------------|---------------------------|
| (A) Limits for Occupational/Control Exposures           |                                  |                                  |                           |                           |
| 30 - 300  | 61.4                             | 0.163                            | 1.0                       | 6                         |
| 300 - 1500  |                                  |                                  | f/300                     | 6                         |
| (B) Limits for General Population/Uncontrolled Exposure |                                  |                                  |                           |                           |
| 30 - 300  | 27.5                             | 0.073                            | 0.2                       | 30                        |
| 300 - 1500  |                                  |                                  | f/1500                    | 30                        |

# LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Note: f is frequency in MHz

#### **1.2 Method of Measurements**

**Calculation Method of RF Safety Distance:** 

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,

P: power input to the antenna in mWEIRP: Equivalent (effective) isotropic radiated power.S: power density mW/cm2G: numeric gain of antenna relative to isotropic radiatorr: distance to centre of radiation in cm

$$r = \sqrt{\frac{PG}{4\pi \cdot S}} = \sqrt{\frac{EIRP}{4\pi \cdot S}}$$

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device.

### **1.3 Evaluation of RF Exposure Compliance Requirements**

Maximum RF Power conducted, P [dBm] = 46.04Maximum Antenna Gain, G[dBi] = 0 Maximum EIRP, P [dBm] = 46.04User-based time-average for PTT = 50%Peak EIRP = 46.04 dBm + 0 dBi = 46.04 dBm = 40,170 mWatts (worst case) Average EIRP = 50% \* EIRP = 20,085 mWatts

MPE Limit for Occupational/Controlled Exposure, S [mW/cm2] = 1.0MPE Limit for General Population/Uncontrolled Exposure, S [mW/cm2] = 0.2

## **Calculation of Minimum RF Safety Distance Limits:**

Calculated RF Safety Distance for Occupational/Controlled Exposure, r [cm] = 39.98 Calculated RF Safety Distance for General Population/Uncontrolled Exposure, r [cm] = 89.40 **Results:** Manufacturer declares RF Safety Distance of 40 cm for Occupational/Controlled

Exposure and 90 cm for General Population/Uncontrolled Exposure which met the FCC Limits. Please refer to Users Manual for details of RF Exposure Information.