



**ANSI/IEEE Std. C95.1-1992**

in accordance with the requirements of  
FCC Report and Order: ET Docket 93-62



**FCC TEST REPORT**

**For**

**Notebook Computer**

**Trade Name: TOSHIBA**

**Model:**

**Satellite L4\*\*\*\*\*-C\*\*\*\*\*,**

**Satellite Radius L4\*\*\*\*\*-C\*\*\*\*\*,**

**Satellite Radius E4\*\*\*\*\*-C\*\*\*\*\***

(\* means 0-9; a-z; A-Z; / ; - ; no symbol, or blank for marketing purpose)

Issued to

**Pegatron Corporation**

**5F, NO. 76, LIGONG ST., BEITOU DISTRICT, TAIPEI CITY 112, TAIWAN (R.O.C.)**

Issued by

**Compliance Certification Services Inc.**

**No.11, Wugong 6th Rd., Wugu Dist.,**

**New Taipei City 24891,**

**Taiwan. (R.O.C.)**

**<http://www.ccsrf.com>**

**[service@ccsrf.com](mailto:service@ccsrf.com)**

**Issued Date: 2015/04/08**



*Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2015/04/08	Initial Issue	ALL	Peter Chen



## Table of Contents

<b>1</b>	<b>Certificate of Compliance (SAR Evaluation)</b> .....	<b>5</b>
<b>2</b>	<b>Description of Equipment Under Test</b> .....	<b>6</b>
2.1	Summary of Highest SAR Values .....	7
<b>3</b>	<b>Requirements for Compliance Testing Defined</b> .....	<b>8</b>
3.1	Requirements for Compliance Testing Defined by the FCC .....	8
<b>4</b>	<b>Dosimetric Assessment System</b> .....	<b>9</b>
4.1	Measurement System Diagram .....	10
4.2	System Components .....	11
<b>5</b>	<b>Evaluation Procedures</b> .....	<b>14</b>
<b>6</b>	<b>SAR Measurement Procedures</b> .....	<b>16</b>
6.1	Normal SAR Test Procedure .....	16
<b>7</b>	<b>Device Under Test</b> .....	<b>18</b>
7.1	Wireless Technologies .....	18
7.2	Maximum Tune-up Power .....	19
7.3	Simultaneous Transmission .....	20
<b>8</b>	<b>RF Output Power Measurement</b> .....	<b>21</b>
8.1	Wi-Fi (2.4GHz Band) .....	21
8.2	Wi-Fi (5GHz Band) .....	22
8.3	Bluetooth .....	29
<b>9</b>	<b>Summary of SAR Test Exclusion Configurations</b> .....	<b>30</b>
9.1	Standalone SAR Test Exclusion Calculations .....	30
9.1.1	SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User .....	31
9.1.2	SAR Exclusion Calculations for Wi-Fi Antenna > 50mm from the User .....	33
9.1.3	SAR Required Test Configuration .....	35
<b>10</b>	<b>Exposure Limit</b> .....	<b>36</b>
<b>11</b>	<b>Tissue Dielectric Properties</b> .....	<b>37</b>
11.1	Test Liquid Confirmation .....	37
11.2	Typical Composition of Ingredients for Liquid Tissue Phantoms .....	38
11.3	Simulating Liquids Parameter Check Results .....	39
<b>12</b>	<b>Measurement Uncertainty</b> .....	<b>40</b>
<b>13</b>	<b>System Performance Check</b> .....	<b>41</b>
13.1	System Performance Check Results .....	42
<b>14</b>	<b>SAR Measurements Results</b> .....	<b>43</b>
<b>15</b>	<b>Equipment List &amp; Calibration Status</b> .....	<b>45</b>
<b>16</b>	<b>Facilities</b> .....	<b>46</b>



**17 Reference.....46**  
**18 Attachments.....47**



# 1 Certificate of Compliance (SAR Evaluation)

**Applicant** Pegatron Corporation  
 5F, NO. 76, LIGONG ST., BEITOU DISTRICT, TAIPEI CITY 112,  
 TAIWAN (R.O.C.)

**Equipment Under Test:** Notebook Computer

**Trade Name:** TOSHIBA

**Model Number:** Satellite L4\*\*\*\*\*-C\*\*\*\*\*,  
 Satellite Radius L4\*\*\*\*\*-C\*\*\*\*\*,  
 Satellite Radius E4\*\*\*\*\*-C\*\*\*\*\*  
 (\* means 0-9; a-z; A-Z; / ; - ; no symbol, or blank for marketing purpose)

**Date of Test:** March 31~April 02, 2015

**Device Category:** PORTABLE DEVICES

**Exposure Category:** GENERAL POPULATION/UNCONTROLLED EXPOSURE

Applicable Standards	
FCC	<ul style="list-style-type: none"> <li>● IEEE 1528 2013</li> <li>● KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03</li> <li>● KDB 447498 D01 General RF Exposure Guidance v05r02</li> <li>● KDB 616217 D04 SAR for laptop and tablets v01r01</li> <li>● KDB 248227 D01 SAR measurement for 802 11 a b g v01r02</li> </ul>
Limit	
1.6 W/kg	
Test Result	
Pass	

The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Tested by:

Alex Wu  
Section Manager  
Compliance Certification Services Inc.

Peter Chen  
SAR Engineer  
Compliance Certification Services Inc.



## 2 Description of Equipment Under Test

Product	Notebook Computer		
Trade Name	TOSHIBA		
Model Number	Satellite L4*****-C***** , Satellite Radius L4*****-C***** , Satellite Radius E4*****-C***** (* means 0-9; a-z; A-Z; / ; - ; no symbol, or blank for marketing purpose)		
RF Module	Realtek	Model:	RTL8821AE
Transmitters	Wi-Fi & Bluetooth		
Modulation Technique	Bluetooth:GFSK for 1Mbps; $\pi$ /4-DQPSK for 2Mbps;8DPSK for 3Mbps		
	802.11a: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11b: Direct Sequence Spread Spectrum(DSSS)		
	802.11g: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11n: Orthogonal Frequency Division Multiplexing (OFDM)		
Antenna Specification	Ant 1	Brand name	ACON
		Parts Number	ANP6Y-100012
			ANP6Y-100013
	Type	PIFA	
	Ant 2	Brand name	INPAQ
		Parts Number	WA-P-LB-01-126
WA-P-LB-02-257			
Type	PIFA		
Rechargeable Li-polymer Battery–alternate	Brand :TOSHIBA(Sanyo, LG, Samsung, BYD) Model: PA5208U-1BRS Rating 10.8Vdc, 45Wh, 3860mAh  Test is using battery by TOSHIBA(Sanyo).		

**Remark:**

1. The sample selected for test was prototype that approximated to production product and was provided by manufacturer
2. The platform have Notebook mode, Stand mode, Tablet mode and Tent mode. We Performed SAR test in tablet mode, because the EUT can fold 360 degrees. Thus, testing under tablet mode would meet the testing criteria for Stand mode and Tent mode.



## 2.1 Summary of Highest SAR Values

Results for highest reported SAR values for each frequency band and mode

Technology/Band	Test configuration	Mode	Highest Reported 1g-SAR (W/kg)
Wi-Fi 2.4 GHz	Tablet@Edge 3	802.11b	0.374
Wi-Fi 5.2 GHz	Tablet@Edge 3	802.11a	1.110
Wi-Fi 5.3 GHz	Tablet@Edge 3	802.11a	1.120
Wi-Fi 5.5 GHz	Tablet@Edge 3	802.11a	0.983
Wi-Fi 5.8 GHz	Tablet@Edge 3	802.11a	1.020



### **3 Requirements for Compliance Testing Defined**

#### **3.1 Requirements for Compliance Testing Defined by the FCC**

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/kg for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6].






## **4 Dosimetric Assessment System**

These measurements were performed with the automated near-field scanning system DASY4/DASY5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3554 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure and found to be better than  $\pm 0.25$  dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE 1528 2013.

#### 4.1 Measurement System Diagram






**The DASY5 system for performing compliance tests consists of the following items:**

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4/DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.



## 4.2 System Components

DASY4/DASY5 Measurement Server	
	<p>The DASY4/DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4/DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.</p> <p>The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.</p>
	<p>The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.</p>
Data Acquisition Electronics (DAE)	
	<p>The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.</p>



**EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements**



**Construction:** Symmetrical design with triangular core  
Built-in shielding against static charges  
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)

**Calibration:** Basic Broad Band Calibration in air: 10-3000 MHz.  
Conversion Factors (CF) for HSL 900 and HSL 1800  
CF-Calibration for other liquids and frequencies upon request.

**Frequency:** 10 MHz to > 6 GHz; Linearity:  $\pm 0.2$  dB (30 MHz to 3 GHz)

**Directivity:**  $\pm 0.3$  dB in HSL (rotation around probe axis)  
 $\pm 0.5$  dB in HSL (rotation normal to probe axis)

**Dynamic Range:** 10  $\mu$ W/g to > 100 mW/g; Linearity:  $\pm 0.2$  dB  
(noise: typically < 1  $\mu$ W/g)

**Dimensions:** Overall length: 330 mm (Tip: 20 mm)  
Tip diameter: 2.5 mm (Body: 12 mm)  
Distance from probe tip to dipole centers: 1 mm

**Application:** High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

**SAM Phantom (V4.0)**



**Construction:** The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 2013, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

**Shell Thickness:** 2  $\pm 0.2$  mm

**Filling Volume:** Approx. 25 liters

**Dimensions:** Height: 810mm; Length: 1000mm; Width: 500mm

**SAM Phantom (ELI4)**



**Construction:** Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles

**Shell Thickness:** 2.0  $\pm 0.2$  mm (sagging: <1%)

**Filling Volume:** Approx. 25 liters

**Dimensions:** Major ellipse axis: 600 mm  
**Minor axis:** 400 mm 500mm




### Device Holder for SAM Twin Phantom



**Construction:** In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).

### System Validation Kits for SAM Phantom (V4.0)



**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.


**Frequency:** 2450, 5200, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:** D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm

### System Validation Kits for ELI4 phantom



**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 2450, 5200, 5300, 5600, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:** D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm



## 5 Evaluation Procedures

### Data Evaluation

The DASYS4/DASYS5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	$dcp_i$
Device parameters:	- Frequency	$f$
	- Crest factor	$cf$
Media parameters:	- Conductivity	$\sigma$
	- Density	$\rho$

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASYS components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$U_i$	= Input signal of channel i	(i = x, y, z)
	$cf$	= Crest factor of exciting field	(DASY parameter)
	$dcp_i$	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: 
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes: 
$$H_i = \sqrt{V_i} \cdot \frac{a_{i10} + a_{i11}f + a_{i12}f^2}{f}$$

with	$V_i$	= Compensated signal of channel i	(i = x, y, z)
	$Norm_i$	= Sensor sensitivity of channel i	(i = x, y, z)

$\mu V/(V/m)^2$  for E0field Probes

$ConvF$	= Sensitivity enhancement in solution
$a_{ij}$	= Sensor sensitivity factors for H-field probes
$f$	= Carrier frequency (GHz)
$E_i$	= Electric field strength of channel i in V/m
$H_i$	= Magnetic field strength of channel i in A/m



The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

- $SAR$  = local specific absorption rate in W/kg
- $E_{tot}$  = total field strength in V/m
- $\sigma$  = conductivity in [mho/m] or [Siemens/m]
- $\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{377} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with

- $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>
- $E_{tot}$  = total electric field strength in V/m
- $H_{tot}$  = total magnetic field strength in A/m



## 6 SAR Measurement Procedures

### 6.1 Normal SAR Test Procedure

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section’s grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4/DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan’s property sheet is brought-up, the grid resolution has to less than 15 mm by 15 mm at frequency ≤2GHz; the grid resolution has to less than 12mm by 12 mm at frequency between 2GHz to 4GHz; grid resolution has to less than 10 mm by 10 mm at frequency between 4GHz to 6GHz.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	½·δ·ln(2) ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx <sub>Zoom</sub> , Δy <sub>Zoom</sub>	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	





• **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures points in accordance with the frequency can be divided into three parts. (1)The zoom scan volume was set to 5x5x7 points at frequency  $\leq 2$ GHz. (2) The zoom scan volume was set to 7x7x7 points at frequency between 2GHz to 4GHz (3) The zoom scan volume was set to 7x7x12 points at frequency between 4GHz to 6GHz. The measures points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01

			$\leq 3$ GHz	$> 3$ GHz
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$			$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm	3 – 4 GHz: $\leq 5$ mm 4 – 6 GHz: $\leq 4$ mm
Maximum zoom scan spatial resolution, normal to phantom surface	Uniform grid: $\Delta z_{Zoom}(n)$		$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm
	graded grid	$\Delta z_{Zoom}(1)$ :between 1 <sup>st</sup> two points losest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Maximum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm	

• **Power Drift Measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4/DASY5 software stop the measurements if this limit is exceeded.

• **Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.



## 7 Device Under Test

### 7.1 Wireless Technologies

Wireless technologies	Tx Frequency Bands	Operating mode	Duty Cycle used for testing
Wi-Fi	2.4GHz Band	802.11b 802.11g 802.11n(HT20) 802.11n(HT40)	100%
	5GHz Band	802.11a 802.11n(HT20) 802.11n(HT40) 802.11ac(VHT20) 802.11ac(VHT40) 802.11ac(VHT80)	100%
Bluetooth	2.4GHz	2.1 4.0 LE	N/A



### 7.2 Maximum Tune-up Power

Tolerance (dB): ± 1.5 for Wi-Fi		RF Output Power (dBm)	
Tolerance (dB): ± 1.0 for BT			
Band	Mode	Target	Max. tune-up power
2.4GHz	802.11b	15.5	17.0
	802.11g	15.5	17.0
	802.11n HT20	15.5	17.0
	802.11n HT40	15.5	17.0
5.2GHz Band	802.11a	15.5	17.0
	802.11n HT20	15.5	17.0
	802.11n HT40	15.0	16.5
	802.11ac VHT20	15.5	17.0
	802.11ac VHT40	15.0	16.5
	802.11ac VHT80	9.5	11.0
5.3GHz Band	802.11a	13.0	14.5
	802.11n HT20	13.0	14.5
	802.11n HT40	12.5	14.0
	802.11ac VHT20	13.0	14.5
	802.11ac VHT40	12.5	14.0
	802.11ac VHT80	9.5	11.0
5.6GHz Band	802.11a	13.0	14.5
	802.11n HT20	13.0	14.5
	802.11n HT40	12.5	14.0
	802.11ac VHT20	13.0	14.5
	802.11ac VHT40	12.5	14.0
	802.11ac VHT80	9.5	11.0
5.8GHz Band	802.11a	13.0	14.5
	802.11n HT20	13.0	14.5
	802.11n HT40	12.5	14.0
	802.11ac VHT20	13.0	14.5
	802.11ac VHT40	12.5	14.0
	802.11ac VHT80	12.5	14.0
Bluetooth	DH5	1.0	2.0
	3DH5	0.0	1.0
	BLE	1.0	2.0



### 7.3 Simultaneous Transmission

RF Exposure Condition	Transmit Configurations
Wi-Fi	2.4GHz(Chain 0) 2.4GHz(Chain 1) 5GHz(Chain 0) 5GHz(Chain 1) Bluetooth (Chain 1)

**Note:**

1. Both of Chain 0 and Chain 1 can be used as transmitting or receiving antennas, but only one antenna can be used as transmitting or receiving antenna at same time. Chain 0 generated the worst case than Chain 1, so it is tested and recorded in the report.



## 8 RF Output Power Measurement

### 8.1 Wi-Fi (2.4GHz Band)

Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)							
				Data Rate (Mbps)							
				1	2	5.5	11				
802.11b 1TX	1	2412	0	16.9							
	6	2437	0	<b>17.0</b>	16.9	16.9	16.9				
	11	2462	0	16.8							
	1	2412	1	16.7							
	6	2437	1	<b>16.7</b>	16.2	16.1	16.2				
	11	2462	1	16.5							
Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)							
				Data Rate (Mbps)							
				6	9	12	18	24	36	48	54
802.11g 1TX	1	2412	0	15.4							
	6	2437	0	<b>16.3</b>	16.1	16.1	16.2	16.1	16.1	16.1	16.1
	11	2462	0	15.4							
	1	2412	1	15.0							
	6	2437	1	<b>16.2</b>	16.1	16.0	16.1	16.0	16.0	16.0	16.1
	11	2462	1	15.3							
Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)							
				Data Rate (Mbps)							
				6.5	13	19.5	26	39	52	58.5	65
802.11n HT20 1TX	1	2412	0	13.4							
	6	2437	0	<b>16.3</b>	16.0	16.1	16.2	16.2	16.2	16.2	16.2
	11	2462	0	13.3							
	1	2412	1	13.1							
	6	2437	1	<b>16.3</b>	16.0	16.0	16.1	16.1	16.0	16.2	16.2
	11	2462	1	13.8							
Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)							
				Data Rate (Mbps)							
				6.5	13	19.5	26	39	52	58.5	65
802.11n HT40 1TX	3	2422	0	13.5							
	6	2437	0	<b>16.4</b>	16.3	16.3	16.2	16.3	16.1	16.3	16.3
	9	2452	0	13.4							
	3	2422	1	13.2							
	6	2437	1	<b>16.1</b>	16.0	16.0	15.8	15.8	15.9	15.9	16.0
	9	2452	1	13.1							



### 8.2 Wi-Fi (5GHz Band)

Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)								
				Data Rate (Mbps)								
				6	9	12	18	24	36	48	54	
802.11a 1TX	36	5180	0	16.6								
	40	5200	0	16.6								
	44	5220	0	<u>16.9</u>	16.1	16.1	16.8	16.7	16.6	16.6	16.5	
	48	5240	0	16.8								
	52	5260	0	14.3								
	56	5280	0	14.4								
	60	5300	0	<u>14.5</u>	14.3	14.3	14.4	14.4	14.4	14.1	14.2	
	64	5320	0	14.5								
	100	5500	0	14.1								
	104	5520	0	14.3								
	108	5540	0	14.4								
	112	5560	0	<u>14.5</u>	14.4	14.3	14.4	14.4	14.1	14.3	14.4	
	116	5580	0	14.4								
	120	5600	0	14.4								
	124	5620	0	14.1								
	128	5640	0	14.3								
	132	5660	0	14.4								
	136	5680	0	14.4								
	140	5700	0	14.1								
	149	5745	0	14.5								
153	5765	0	14.3									
157	5785	0	<u>14.5</u>	14.3	14.2	14.2	14.2	14.1	14.2	14.4		
161	5805	0	14.3									
165	5825	0	14.4									



Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)								
				Data Rate (Mbps)								
				6	9	12	18	24	36	48	54	
802.11a 1TX	36	5180	1	16.4								
	40	5200	1	16.5								
	44	5220	1	<b>16.8</b>	16.2	16.1	16.5	16.6	16.7	16.7	16.7	
	48	5240	1	16.7								
	52	5260	1	14.0								
	56	5280	1	14.3								
	60	5300	1	<b>14.4</b>	14.3	14.3	14.2	14.2	14.2	14.1	14.3	
	64	5320	1	14.1								
	100	5500	1	14								
	104	5520	1	13.2								
	108	5540	1	14.4								
	112	5560	1	<b>14.5</b>	14.3	14.1	14.2	14.4	14.2	14.3	14.3	
	116	5580	1	14.3								
	120	5600	1	14.4								
	124	5620	1	14.0								
	128	5640	1	14.2								
	132	5660	1	14.1								
	136	5680	1	14.2								
	140	5700	1	14.1								
	149	5745	1	14.0								
153	5765	1	14.2									
157	5785	1	<b>14.3</b>	14.2	14.1	14.2	14.2	14.1	14.2	14.2		
161	5805	1	14.1									
165	5825	1	14.3									



Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)								
				Data Rate (Mbps)								
				6	9	12	18	24	36	48	54	
802.11n HT20 1TX	36	5180	0	16.5								
	40	5200	0	16.5								
	44	5220	0	<u>17.0</u>	16.9	16.1	16.8	16.8	16.6	16.6	16.5	
	48	5240	0	16.8								
	52	5260	0	14.2								
	56	5280	0	14								
	60	5300	0	<u>14.5</u>	14.4	14.3	14.4	14.4	14.4	14.1	14.2	
	64	5320	0	14.5								
	100	5500	0	14.5								
	104	5520	0	14.3								
	108	5540	0	14.4								
	112	5560	0	<u>14.5</u>	14.4	14.3	14.3	14.4	14.2	14.3	14.4	
	116	5580	0	14.4								
	120	5600	0	14.4								
	124	5620	0	14.5								
	128	5640	0	14.3								
	132	5660	0	14.4								
	136	5680	0	14.4								
	140	5700	0	14.1								
	149	5745	0	14.3								
153	5765	0	14.3									
157	5785	0	<u>14.5</u>	14.4	14.1	14.2	14.2	14.1	14.2	14.4		
161	5805	0	14.5									
165	5825	0	14.4									





Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)								
				Data Rate (Mbps)								
				6	9	12	18	24	36	48	54	
802.11n HT20 1TX	36	5180	1	16.2								
	40	5200	1	16.4								
	44	5220	1	<u>16.9</u>	16.7	16.1	16.8	16.8	16.6	16.6	16.5	
	48	5240	1	16.8								
	52	5260	1	14.0								
	56	5280	1	14.0								
	60	5300	1	<u>14.3</u>	14.2	14.2	14.1	14.1	14.1	14.1	14.2	
	64	5320	1	14.2								
	100	5500	1	14.4								
	104	5520	1	14.3								
	108	5540	1	14.4								
	112	5560	1	<u>14.4</u>	14.3	14.3	14.3	14.2	14.2	14.3	14.3	
	116	5580	1	14.3								
	120	5600	1	14.3								
	124	5620	1	14.2								
	128	5640	1	14.3								
	132	5660	1	14.1								
	136	5680	1	14.2								
	140	5700	1	14.1								
	149	5745	1	14.3								
153	5765	1	14.3									
157	5785	1	<u>14.5</u>	14.4	14.1	14.2	14.2	14.1	14.2	14.4		
161	5805	1	14.5									
165	5825	1	14.4									

Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)								
				Data Rate (Mbps)								
				13.5	27	40.5	54	81	108	121.5	135	
802.11n HT40 1TX	38	5190	0	14.0								
	46	5230	0	<u>16.4</u>	16.1	16.1	16.1	16.0	16.0	16.0	16.0	
	54	5270	0	13.9								
	62	5310	0	<u>14.0</u>	13.9	13.9	13.9	13.9	13.9	13.8	13.7	
	102	5510	0	<u>14.0</u>	13.9	13.9	13.8	13.8	13.7	13.7	13.7	
	110	5550	0	13.9								
	118	5590	0	14.0								
	126	5630	0	14.0								
	134	5670	0	13.8								
	142	5710	0	14.0								
	151	5755	0	<u>13.8</u>	13.1	13.1	13.0	13.0	13.0	13.0	13.7	
	159	5795	0	13.7								



Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)							
				Data Rate (Mbps)							
				13.5	27	40.5	54	81	108	121.5	
802.11n HT40 1TX	38	5190	1	13.8							
	46	5230	1	<u>16.3</u>	16.1	16.1	16.1	16.2	16.0	16.0	
	54	5270	1	13.9							
	62	5310	1	<u>13.9</u>	13.7	13.7	13.7	13.7	13.6	16.3	
	102	5510	1	<u>13.6</u>	13.5	13.4	13.4	13.1	13.5	13.2	
	110	5550	1	13.9							
	118	5590	1	14.0							
	126	5630	1	13.8							
	134	5670	1	13.8							
	142	5710	1	14.0							
	151	5755	1	<u>13.8</u>	13.1	13.1	13.0	13.0	13.0	13.0	
159	5795	1	13.7								

Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)								
				Data Rate (Mbps)								
				6.5	13	19.5	26	39	52	58.5	65	
802.11ac VHT20 1TX	36	5180	0	16.5								
	40	5200	0	16.5								
	44	5220	0	<u>17.0</u>	16.4	16.4	16.4	16.3	16.3	16.3	16.3	
	48	5240	0	16.8								
	52	5260	0	14.2								
	56	5280	0	14.0								
	60	5300	0	<u>14.5</u>	13.8	13.8	13.8	13.8	13.7	13.7	13.6	
	64	5320	0	14.5								
	100	5500	0	14.5								
	104	5520	0	14.3								
	108	5540	0	14.4								
	112	5560	0	<u>14.5</u>	14.1	14.3	14.4	14.4	14.4	14.4	14.4	
	116	5580	0	14.4								
	120	5600	0	14.4								
	124	5620	0	14.5								
	128	5640	0	14.3								
	132	5660	0	14.4								
	136	5680	0	14.4								
	140	5700	0	14.1								
	149	5745	0	14.3								
153	5765	0	14.3									
157	5785	0	<u>14.5</u>	13.9	13.9	14.4	14.3	14.4	14.3	14.4		
161	5805	0	14.5									
165	5825	0	14.4									



Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)									
				Data Rate (Mbps)									
				6.5	13	19.5	26	39	52	58.5	65		
802.11ac VHT20 1TX	36	5180	1	16.4									
	40	5200	1	16.4									
	44	5220	1	<u>16.9</u>	16.3	16.3	16.3	16.5	16.4	16.3	16.1		
	48	5240	1	16.8									
	52	5260	1	14.2									
	56	5280	1	14.0									
	60	5300	1	<u>14.4</u>	13.8	13.8	13.8	13.8	13.7	13.7	13.6		
	64	5320	1	14.4									
	100	5500	1	14.4									
	104	5520	1	14.3									
	108	5540	1	14.4									
	112	5560	1	<u>14.5</u>	14.1	14.3	14.4	14.4	14.4	14.4	14.4	14.4	
	116	5580	1	14.3									
	120	5600	1	14.4									
	124	5620	1	14.5									
	128	5640	1	14.3									
	132	5660	1	14.4									
	136	5680	1	14.4									
	140	5700	1	14.1									
	149	5745	1	14.3									
153	5765	1	14.3										
157	5785	1	<u>14.4</u>	14.3	14.0	14.1	14.3	14.2	14.3	14.2			
161	5805	1	14.2										
165	5825	1	14.4										



Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)									
				Data Rate (Mbps)									
				13.5	27	40.5	54	81	108	121.5	135		
802.11ac VHT40 1TX	38	5190	0	14.0									
	46	5230	0	<u>16.4</u>	16.1	16.1	16.1	16.0	16.0	16.0	16.0	16.0	16.0
	54	5270	0	13.9									
	62	5310	0	<u>14.0</u>	13.9	13.9	13.9	13.9	13.9	13.9	13.8	13.7	13.7
	102	5510	0	<u>14.0</u>	13.9	13.9	13.8	13.8	13.7	13.7	13.7	13.7	13.7
	110	5550	0	13.9									
	118	5590	0	14.0									
	126	5630	0	14.0									
	134	5670	0	13.8									
	142	5710	0	14.0									
	151	5755	0	<u>13.8</u>	13.1	13.1	13.0	13.0	13.0	13.0	13.0	13.0	13.7
	159	5795	0	13.7									

Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)									
				Data Rate (Mbps)									
				13.5	27	40.5	54	81	108	121.5	135		
802.11ac VHT40 1TX	38	5190	1	13.8									
	46	5230	1	<u>16.2</u>	16.1	16.0	16.1	16.0	16.1	16.0	16.0	16.0	16.1
	54	5270	1	13.9									
	62	5310	1	<u>14.0</u>	13.9	13.9	13.9	13.9	13.9	13.9	13.8	13.7	13.7
	102	5510	1	<u>14.0</u>	13.9	13.9	13.8	13.8	13.7	13.7	13.7	13.7	13.7
	110	5550	1	13.9									
	118	5590	1	13.7									
	126	5630	1	13.8									
	134	5670	1	13.8									
	142	5710	1	14.0									
	151	5755	1	<u>13.7</u>	13.1	13.2	13.4	13.3	13.2	13.2	13.2	13.2	13.6
	159	5795	1	13.7									

Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)									
				Data Rate (Mbps)									
				29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
802.11ac VHT80 1TX	42	5210	0	<u>11.0</u>	10.1	10.1	10.0	10.9	10.9	10.9	10.8	10.8	10.8
	58	5290	0	<u>11.0</u>	10.9	10.9	10.8	10.8	10.8	10.8	10.7	10.7	10.7
	106	5530	0	10.8									
	155	5775	0	<u>13.9</u>	13.8	13.8	13.7	13.7	13.7	13.7	13.7	13.7	13.8

Mode	Channel	Frequency (MHz)	Chain	Avg. Pwr (dBm)									
				Data Rate (Mbps)									
				29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
802.11ac VHT80 1TX	42	5210	1	<u>10.8</u>	10.1	10.1	10.0	10.9	10.6	10.6	10.0	10.6	10.7
	58	5290	1	<u>11.0</u>	10.9	10.9	10.7	10.7	10.8	10.7	10.8	10.8	10.7
	106	5530	1	10.8									
	155	5775	1	<u>13.8</u>	13.5	13.5	13.6	13.6	13.7	13.6	13.7	13.7	13.7



### 8.3 Bluetooth

#### Output power table

Band (GHz)	Mode	Ch #	Freq. (MHz)	Measured Avg. Pwr (dBm)
Bluetooth	DH5	0	2402	1.5
		39	2441	1.3
		78	2480	0.7
	3DH5	0	2402	0.8
		39	2441	0.5
		78	2480	-0.1
	BLE	0	2402	1.7
		19	2440	1.4
		39	2480	0.6



## 9 Summary of SAR Test Exclusion Configurations

### 9.1 Standalone SAR Test Exclusion Calculations

Since the Dedicated Host Approach is applied, the standalone SAR test exclusion procedure in KDB 447498 section 4.3.1 is applied in conjunction with KDB 616217 section 4.3 to determine the minimum test separation distance:

1. According to KDB 447498 Section 4.1.5) if the antenna is at close proximity to user then the outer surface of the DUT should be treated as the radiating surface. The test separation distance is then determined by the smallest distance between the outer surface of the device and the user. For the purposes of this report close proximity has been defined as closer than 50 mm. For antennas <50 mm from the rear or edge the separation distance used for the estimated SAR calculations is 0 mm.
2. When the minimum test separation distance is < 5mm, a distance of 5mm is applied to determine SAR test exclusion.
3. When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.
4. If the antenna to DUT adjacent edge or bottom separation distance >50mm the actual antenna to user separation distance is used to determine SAR exclusion and estimated SAR value.

Refer to Appendix for the specific details on the antenna-to-antenna and antenna-to-edge distances used for test exclusion calculations.



**9.1.1 SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User**

According to KDB 447498 v05 r02 in section 4.3.1, if the calculated **threshold value is > 3** then SAR testing is required.

**NB Mode**

Antenna	Band	Mode	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
				dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	802.11b	2412	17	50	13.6					5.7				
	2.4GHz	802.11g	2412	17	50	13.6					5.7				
	2.4GHz	802.11n HT20	2437	17	50	13.6					5.7				
	2.4GHz	802.11n HT40	2442	17	50	13.6					5.7				
	5.2GHz	802.11a	5180	17	50	13.6					8.4				
	5.3GHz		5260	14.5	28	13.6					4.7				
	5.5GHz		5500	14.5	28	13.6					4.8				
	5.8GHz		5745	14.5	28	13.6					4.9				
	5.2GHz	802.11n HT20	5180	17	50	13.6					8.4				
	5.3GHz		5260	14.5	28	13.6					4.7				
	5.5GHz		5500	14.5	28	13.6					4.8				
	5.8GHz		5745	14.5	28	13.6					4.9				
	5.2GHz	802.11n HT40	5190	16.5	45	13.6					7.5				
	5.3GHz		5270	14	25	13.6					4.2				
	5.5GHz		5510	14	25	13.6					4.3				
	5.8GHz		5755	14	25	13.6					4.4				
	5.2GHz	802.11 ac VHT20	5180	17	50	13.6					8.4				
	5.3GHz		5260	14.5	28	13.6					4.7				
	5.5GHz		5500	14.5	28	13.6					4.8				
	5.8GHz		5745	14.5	28	13.6					4.9				
	5.2GHz	802.11 ac VHT40	5190	16.5	45	13.6					7.5				
	5.3GHz		5270	14	25	13.6					4.2				
	5.5GHz		5510	14	25	13.6					4.3				
	5.8GHz		5755	14	25	13.6					4.4				
	5.2GHz	802.11 ac VHT80	5210	11	13	13.6					2.2				
	5.3GHz		5290	11	13	13.6					2.2				
	5.5GHz		5530	11	13	13.6					2.2				
	5.8GHz		5775	14	25	13.6					4.4				
Wi-Fi Aux	Bluetooth	DH5	2402	8.5	7	13.6					0.8				



Tablet Mode

Antenna	Band	Mode	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value					
				dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4	
Wi-Fi Main	2.4GHz	802.11b	2412	17	50	19.80	222.7	169.2	8.1	137.2	3.9	>200mm	>50mm	9.6	>50mm	
	2.4GHz	802.11g	2412	17	50	19.80	222.7	169.2	8.1	137.2	3.9	>200mm	>50mm	9.6	>50mm	
	2.4GHz	802.11n HT20	2437	17	50	19.80	222.7	169.2	8.1	137.2	3.9	>200mm	>50mm	9.6	>50mm	
	2.4GHz	802.11n HT40	2442	17	50	19.80	222.7	169.2	8.1	137.2	3.9	>200mm	>50mm	9.6	>50mm	
	5.2GHz	802.11a	5180	17	50	19.80	222.7	169.2	8.1	137.2	5.7	>200mm	>50mm	14.0	>50mm	
	5.3GHz		5260	14.5	28	19.80	222.7	169.2	8.1	137.2	3.2	>200mm	>50mm	7.9	>50mm	
	5.5GHz		5500	14.5	28	19.80	222.7	169.2	8.1	137.2	3.3	>200mm	>50mm	8.1	>50mm	
	5.8GHz		5745	14.5	28	19.80	222.7	169.2	8.1	137.2	3.4	>200mm	>50mm	8.3	>50mm	
	5.2GHz	802.11n HT20	5180	17	50	19.80	222.7	169.2	8.1	137.2	5.7	>200mm	>50mm	14.0	>50mm	
	5.3GHz		5260	14.5	28	19.80	222.7	169.2	8.1	137.2	3.2	>200mm	>50mm	7.9	>50mm	
	5.5GHz		5500	14.5	28	19.80	222.7	169.2	8.1	137.2	3.3	>200mm	>50mm	8.1	>50mm	
	5.8GHz		5745	14.5	28	19.80	222.7	169.2	8.1	137.2	3.4	>200mm	>50mm	8.3	>50mm	
	5.2GHz	802.11n HT40	5190	16.5	45	19.80	222.7	169.2	8.1	137.2	5.2	>200mm	>50mm	12.7	>50mm	
	5.3GHz		5270	14	25	19.80	222.7	169.2	8.1	137.2	2.9	>200mm	>50mm	7.1	>50mm	
	5.5GHz		5510	14	25	19.80	222.7	169.2	8.1	137.2	3.0	>200mm	>50mm	7.2	>50mm	
	5.8GHz		5755	14	25	19.80	222.7	169.2	8.1	137.2	3.0	>200mm	>50mm	7.4	>50mm	
	5.2GHz	802.11 ac VHT20	5180	17	50	19.80	222.7	169.2	8.1	137.2	5.7	>200mm	>50mm	14.0	>50mm	
	5.3GHz		5260	14.5	28	19.80	222.7	169.2	8.1	137.2	3.2	>200mm	>50mm	7.9	>50mm	
	5.5GHz		5500	14.5	28	19.80	222.7	169.2	8.1	137.2	3.3	>200mm	>50mm	8.1	>50mm	
	5.8GHz		5745	14.5	28	19.80	222.7	169.2	8.1	137.2	3.4	>200mm	>50mm	8.3	>50mm	
	5.2GHz	802.11 ac VHT40	5190	16.5	45	19.80	222.7	169.2	8.1	137.2	5.2	>200mm	>50mm	12.7	>50mm	
	5.3GHz		5270	14	25	19.80	222.7	169.2	8.1	137.2	2.9	>200mm	>50mm	7.1	>50mm	
	5.5GHz		5510	14	25	19.80	222.7	169.2	8.1	137.2	3.0	>200mm	>50mm	7.2	>50mm	
	5.8GHz		5755	14	25	19.80	222.7	169.2	8.1	137.2	3.0	>200mm	>50mm	7.4	>50mm	
	5.2GHz	802.11 ac VHT80	5210	11	13	19.80	222.7	169.2	8.1	137.2	1.5	>200mm	>50mm	3.7	>50mm	
	5.3GHz		5290	11	13	19.80	222.7	169.2	8.1	137.2	1.5	>200mm	>50mm	3.7	>50mm	
	5.5GHz		5530	11	13	19.80	222.7	169.2	8.1	137.2	1.5	>200mm	>50mm	3.8	>50mm	
	5.8GHz		5775	14	25	19.80	222.7	169.2	8.1	137.2	3.0	>200mm	>50mm	7.4	>50mm	
	Wi-Fi Aux	Bluetooth	DH5	2402	8.5	7	19.80	222.7	86.5	8.1	220.7	0.5	>200mm	>50mm	1.3	>200mm





**9.1.2 SAR Exclusion Calculations for Wi-Fi Antenna > 50mm from the User**

According to KDB 447498 v05 r02, if the calculated Power threshold is less than the output power then SAR testing is required.

**NB Mode**

Antenna	Band	Mode	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
				dBm	mW	Bottom	Edge1	Edge2	Edge3	Edge4	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	802.11b	2412	17	50	13.6					<50mm				
	2.4GHz	802.11g	2412	17	50	13.6					<50mm				
	2.4GHz	802.11n HT20	2437	17	50	13.6					<50mm				
	2.4GHz	802.11n HT40	2442	17	50	13.6					<50mm				
	5.2GHz	802.11a	5180	17	50	13.6					<50mm				
	5.3GHz		5260	14.5	28	13.6					<50mm				
	5.5GHz		5500	14.5	28	13.6					<50mm				
	5.8GHz		5745	14.5	28	13.6					<50mm				
	5.2GHz	802.11n HT20	5180	17	50	13.6					<50mm				
	5.3GHz		5260	14.5	28	13.6					<50mm				
	5.5GHz		5500	14.5	28	13.6					<50mm				
	5.8GHz		5745	14.5	28	13.6					<50mm				
	5.2GHz	802.11n HT40	5190	16.5	45	13.6					<50mm				
	5.3GHz		5270	14	25	13.6					<50mm				
	5.5GHz		5510	14	25	13.6					<50mm				
	5.8GHz		5755	14	25	13.6					<50mm				
	5.2GHz	802.11 ac VHT20	5180	17	50	13.6					<50mm				
	5.3GHz		5260	14.5	28	13.6					<50mm				
	5.5GHz		5500	14.5	28	13.6					<50mm				
	5.8GHz		5745	14.5	28	13.6					<50mm				
	5.2GHz	802.11 ac VHT40	5190	16.5	45	13.6					<50mm				
	5.3GHz		5270	14	25	13.6					<50mm				
	5.5GHz		5510	14	25	13.6					<50mm				
	5.8GHz		5755	14	25	13.6					<50mm				
	5.2GHz	802.11 ac VHT80	5210	11	13	13.6					<50mm				
	5.3GHz		5290	11	13	13.6					<50mm				
	5.5GHz		5530	11	13	13.6					<50mm				
	5.8GHz		5775	14	25	13.6					<50mm				
Wi-Fi Aux	Bluetooth	DH5	2402	8.5	7	13.6					<50mm				



Tablet Mode

Antenna	Band	Mode	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
				dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	802.11b	2412	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1292.6	<50mm	968.6
	2.4GHz	802.11g	2412	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1292.6	<50mm	968.6
	2.4GHz	802.11n HT20	2437	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1292.1	<50mm	968.1
	2.4GHz	802.11n HT40	2442	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1292.0	<50mm	968.0
	5.2GHz	802.11a	5180	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.9	<50mm	937.9
	5.3GHz		5260	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.4	<50mm	937.4
	5.5GHz		5500	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1260.0	<50mm	936.0
	5.8GHz		5745	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1258.6	<50mm	934.6
	5.2GHz	802.11n HT20	5180	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.9	<50mm	937.9
	5.3GHz		5260	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.4	<50mm	937.4
	5.5GHz		5500	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1260.0	<50mm	936.0
	5.8GHz		5745	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1258.6	<50mm	934.6
	5.2GHz	802.11n HT40	5190	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.8	<50mm	937.8
	5.3GHz		5270	16.5	45	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.3	<50mm	937.3
	5.5GHz		5510	14	25	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1259.9	<50mm	935.9
	5.8GHz		5755	14	25	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1258.5	<50mm	934.5
	5.2GHz	802.11 ac VHT20	5180	14	25	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.9	<50mm	937.9
	5.3GHz		5260	17	50	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.4	<50mm	937.4
	5.5GHz		5500	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1260.0	<50mm	936.0
	5.8GHz		5745	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1258.6	<50mm	934.6
	5.2GHz	802.11 ac VHT40	5190	14.5	28	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.8	<50mm	937.8
	5.3GHz		5270	16.5	45	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.3	<50mm	937.3
	5.5GHz		5510	14	25	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1259.9	<50mm	935.9
	5.8GHz		5755	14	25	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1258.5	<50mm	934.5
	5.2GHz	802.11 ac VHT80	5210	14	25	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.7	<50mm	937.7
	5.3GHz		5290	11	13	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1261.2	<50mm	937.2
	5.5GHz		5530	11	13	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1259.8	<50mm	935.8
	5.8GHz		5775	11	13	19.8	222.7	169.6	8.1	137.2	<50mm	>200mm	1258.4	<50mm	934.4
Wi-Fi Aux	Bluetooth	DH5	2402	8.5	7	19.8	222.7	86.5	8.1	220.7	<50mm	>200mm	461.8	<50mm	>200mm



### 9.1.3 SAR Required Test Configuration For Wi-Fi and Bluetooth

#### NB Mode

Test Configurations	Bottom	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main 802.11 b	YES				
Wi-Fi Main 802.11 g	YES				
Wi-Fi Main 802.11 n HT20	YES				
Wi-Fi Main 802.11 n HT40	YES				
Bluetooth	No				

#### Tablet Mode

Test Configurations	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main 802.11 b	YES	No	No	YES	No
Wi-Fi Main 802.11 g	YES	No	No	YES	No
Wi-Fi Main 802.11 n HT20	YES	No	No	YES	No
Wi-Fi Main 802.11 n HT40	YES	No	No	YES	No
Bluetooth	No	No	No	No	No

#### Note(s):

1. Yes = SAR is required.  
No = SAR is not required.



## 10 Exposure Limit

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

### **Population/Uncontrolled Environments:**

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

### **Occupational/Controlled Environments:**

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

<p style="text-align: center;"><b>NOTE</b> <b>GENERAL POPULATION/UNCONTROLLED EXPOSURE</b> <b>PARTIAL BODY LIMIT</b> <b>1.6 W/kg</b></p>
--



## 11 Tissue Dielectric Properties

### 11.1 Test Liquid Confirmation

#### Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below.  $\pm 5\%$  may not be easily achieved at certain frequencies.

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE 1528 2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 2013 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE 1528 2013

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00



### 11.2 Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99<sup>+</sup>% Pure Sodium Chloride

Sugar: 98<sup>+</sup>% Pure Sucrose

Water: De-ionized, 16 MΩ<sup>+</sup> resistivity

HEC: Hydroxy thyl Cellulose

DGBE: 99<sup>+</sup>% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

#### Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2



11.3 Simulating Liquids Parameter Check Results

Date	Band	Freq(MHz)	Measured			Standard		Δ		Limit(%)
			e' (εr)	e''	σ	e' (εr)	σ	e' (εr)	σ	±5
2015/3/31	Body 2450	2412	52.77	13.88	1.86	52.75	1.91	0.03%	-2.78%	±5
		2437	52.67	14.11	1.91	52.72	1.94	-0.10%	-1.43%	±5
		2442	52.66	14.14	1.92	52.71	1.94	-0.09%	-1.27%	±5
		2450	52.67	14.21	1.93	52.70	1.95	-0.06%	-0.82%	±5
		2462	52.71	14.28	1.95	52.68	1.97	0.05%	-0.68%	±5
		2472	52.73	14.33	1.97	52.67	1.98	0.11%	-0.66%	±5
2015/4/2	Body 5000	5180	49.34	18.70	5.38	49.02	5.28	0.65%	2.00%	±5
		5200	49.41	18.73	5.41	49.00	5.30	0.83%	2.07%	±5
		5220	49.39	18.60	5.39	48.98	5.32	0.84%	1.33%	±5
		5240	49.29	18.58	5.41	48.96	5.35	0.68%	1.15%	±5
		5260	49.15	18.68	5.46	48.94	5.37	0.43%	1.62%	±5
		5280	49.13	18.81	5.52	48.92	5.40	0.42%	2.25%	±5
		5300	49.15	18.81	5.54	48.90	5.42	0.51%	2.20%	±5
		5320	49.15	18.76	5.54	48.86	5.44	0.59%	1.89%	±5
		5500	48.73	19.11	5.84	48.60	5.65	0.26%	3.34%	±5
		5520	48.82	19.09	5.85	48.58	5.67	0.49%	3.18%	±5
		5540	48.74	18.96	5.83	48.56	5.70	0.38%	2.39%	±5
		5560	48.59	18.90	5.84	48.54	5.72	0.11%	2.02%	±5
		5580	48.46	19.01	5.89	48.52	5.75	-0.12%	2.57%	±5
		5600	48.45	19.20	5.97	48.50	5.77	-0.11%	3.53%	±5
		5620	48.56	19.27	6.02	48.46	5.79	0.21%	3.86%	±5
		5640	48.64	19.19	6.01	48.42	5.81	0.45%	3.40%	±5
		5660	48.56	19.04	5.99	48.38	5.84	0.36%	2.57%	±5
		5680	48.35	19.08	6.02	48.34	5.86	0.02%	2.77%	±5
		5700	48.24	19.27	6.10	48.30	5.88	-0.13%	3.79%	±5
		5745	48.43	19.33	6.17	48.26	5.93	0.37%	3.95%	±5
5765	48.36	19.18	6.14	48.24	5.96	0.26%	3.08%	±5		
5785	48.16	19.17	6.16	48.22	5.98	-0.12%	3.01%	±5		
5805	47.99	19.31	6.23	48.19	6.01	-0.41%	3.67%	±5		
5825	48.01	19.48	6.31	48.15	6.03	-0.28%	4.56%	±5		



## **12 Measurement Uncertainty**

According to KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz section 2.8.2, SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is  $\geq 1.5$  W/kg for 1-g SAR, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.





### 13 System Performance Check

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

#### System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The DASY4/DASY5 system with an E-field probe EX3DV4 SN: 3554 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration (dx=dy= 5 mm, dz= 5 mm).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was 100 mW±3%.
- The results are normalized to 1 W input power.

#### Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D2450V2	728	2014/5/20	2450	1g	52.6	50.2
				10g	24.5	23.4
D5GHzV2	1004	2014/11/20	5200	1g	80.5	74.7
				10g	22.9	20.7
D5GHzV2	1004	2014/11/20	5300	1g	85.7	77.7
				10g	24.4	21.6
D5GHzV2	1004	2014/11/20	5600	1g	84.1	81.2
				10g	23.9	22.4
D5GHzV2	1004	2014/11/20	5800	1g	80.3	74.2
				10g	22.8	20.3



### 13.1 System Performance Check Results

Date	System Dipole			Parameters	Target	Measured	Deviation[%]	Limited[%]
	Type	Serial No.	Liquid					
2015/3/31	D2450V2	728	Body	1g SAR:	50.2	50.10	-0.20	± 5
				10g SAR:	23.4	23.50	0.43	± 5
2015/4/2	D5GHzV2 (5.2GHz)	1004	Body	1g SAR:	74.7	75.70	1.34	± 5
				10g SAR:	20.7	21.00	1.45	± 5
2015/4/2	D5GHzV2 (5.3GHz)	1004	Body	1g SAR:	77.7	74.40	-4.25	± 5
				10g SAR:	21.6	20.80	-3.70	± 5
2015/4/2	D5GHzV2 (5.6GHz)	1004	Body	1g SAR:	81.2	79.00	-2.71	± 5
				10g SAR:	22.4	21.90	-2.23	± 5
2015/4/2	D5GHzV2 (5.8GHz)	1004	Body	1g SAR:	74.2	73.60	-0.81	± 5
				10g SAR:	20.3	21.20	4.43	± 5



### 14 SAR Measurements Results

Wi-Fi (2.4GHz Band):

Test Mode	Test Position	Mode	Channel	Freq. (MHz)	Chain	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
							Tune up limit	Measured			
Tablet	Rear	802.11b	6	2437	0	0	17.0	17.0	0.203	0.203	
	Edge3		6	2437	0	0	17.0	17.0	0.374	0.374	
			6	2437	0	0	17.0	17.0	0.324	0.324	1

Note(s):

1. Ant 1 was performed the SAR testing. Ant 2 was performed the spot check of SAR only.
2. According to RF output power measurement the chain 0 average output power larger chain 1, so chain 0 was performed the SAR testing.



Wi-Fi (5GHz Band):

Test Mode	Test Position	Mode	Channel	Freq. (MHz)	Chain	Dist. (mm)	Power (dBm)		Measured 1g SAR (W/kg)	Reported SAR(W/kg)	Note
							Tune up limit	Measured			
Tablet	Edge3	802.11a	44	5220	0	0	17.0	16.9	0.924	0.946	
			48	5240	0	0	17.0	16.8	1.060	1.110	
			60	5300	0	0	14.5	14.5	1.080	1.080	
			64	5320	0	0	14.5	14.5	0.875	0.875	
			112	5560	0	0	14.5	14.5	0.983	0.983	
			116	5580	0	0	14.5	14.4	0.741	0.758	
			157	5785	0	0	14.5	14.5	1.020	1.020	
			149	5745	0	0	14.5	14.5	0.845	0.845	
		802.11ac	42	5210	0	0	11.0	11.0	0.348	0.348	
			58	5290	0	0	11.0	11.0	0.625	0.625	
			106	5530	0	0	11.0	10.8	0.607	0.636	
			155	5775	0	0	14.0	13.9	0.546	0.559	
		802.11a	60	5300	0	0	14.5	14.5	1.100	1.100	1
			64	5320	0	0	14.5	14.5	1.110	1.110	1
			64	5320	0	0	14.5	14.5	1.120	1.120	3

Note(s):

1. Ant 1 was performed the SAR testing. Ant 2 was performed the spot check of SAR only.
2. According to RF output power measurement the chain 0 average output power larger chain 1, so chain 0 was performed the SAR testing.
3. Repeated measurements are required only when the measured SAR is  $\geq 0.80$  W/kg. If the measured SAR values are  $< 1.45$  W/kg with  $\leq 20\%$  variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
  - 3.1 Original SAR = 1.110 W/kg, therefore two times repeat SAR is required.
  - 3.2 Repeat SAR = 1.120 W/kg  $< 1.45$ W/kg
  - 3.3 SAR variation= 0.9 %  $< 20\%$



## 15 Equipment List & Calibration Status

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Cycle(year)	Calibration Due
S-Parameter Network Analyzer	Agilent	E5071C	MY46213916	1	2015/6/25
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A	N/A
Power Meter	Agilent	4416	GB41291611	1	2015/9/4
Power Sensor	Agilent	8481H	MY41091956	1	2015/9/4
Data Acquisition Electronics (DAE)	SPEAG	DAE4	558	1	2015/7/21
Dosimetric E-Field Probe	SPEAG	EX3DV4	3554	1	2015/9/23
2450 MHz System Validation Dipole	SPEAG	D2450V2	728	1	2015/5/19
5GHz System Validation Dipole	SPEAG	D5GHzV2	1004	1	2015/11/19
Robot	Staubli	RX90L	F02/5T69A1/A/01	N/A	N/A
Amplifier	Mini-Circuit	ZVE-8G	665500309	N/A	N/A
Amplifier	Mini-Circuit	ZHL-1724HLN	D072602#2	N/A	N/A



## 16 Facilities

All measurement facilities used to collect the measurement data are located at

- No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
- No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

## 17 Reference

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEEE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM '97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10



## 18 Attachments

Exhibit	Content
1	System Performance Check Plots
2	SAR test plots for Wi-Fi
3	SAR Equipment calibration report
4	T150331W02-SF PHOTOS

**END OF REPORT**