

## TEST REPORT



Applicant	PEGATRON CORPORATION
Address	5F., NO. 76, LIGONG ST., BEITOU DISTRICT, TAIPEI CITY, Taiwan

Manufacturer or Supplier	PEGATRON CORPORATION
Address	5F., NO. 76, LIGONG ST., BEITOU DISTRICT, TAIPEI CITY, Taiwan
Product	Tablet PC
Brand Name	Q00Q/SQ00L
Model	MT10UWA116
Additional Model & Model Difference	N/A
Date of tests	Oct. 23, 2015 ~ Nov. 3, 2015 Apr 10, 2016 ~ May 17, 2016

The tests have been carried out according to the requirements of the following standard:

**FCC Part 15, Subpart C, Section 15.247**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Chris Chen Manager / EMC Department
	  Date: May 17, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD .....</b>	<b>5</b>
<b>1 SUMMARY OF TEST RESULTS.....</b>	<b>6</b>
<b>2 MEASUREMENT UNCERTAINTY .....</b>	<b>6</b>
<b>3 GENERAL INFORMATION.....</b>	<b>7</b>
3.1 GENERAL DESCRIPTION OF EUT.....	7
3.2 DESCRIPTION OF TEST MODES.....	7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST .....	9
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	11
3.4 DESCRIPTION OF SUPPORT UNITS.....	11
<b>4 TEST TYPES AND RESULTS .....</b>	<b>12</b>
4.1. CONDUCTED EMISSION MEASUREMENT .....	12
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	12
4.1.2 TEST INSTRUMENTS.....	12
4.1.3 TEST PROCEDURES .....	13
4.1.4 DEVIATION FROM TEST STANDARD .....	13
4.1.5 TEST SETUP .....	14
4.1.6 EUT OPERATING CONDITIONS .....	14
4.1.7 TEST RESULTS.....	15
4.2. RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	15
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	19
4.2.2 TEST INSTRUMENTS.....	20
4.2.3 TEST PROCEDURES.....	21
4.2.4 DEVIATION FROM TEST STANDARD.....	23
4.2.5 TEST SETUP .....	23
4.2.6 EUT OPERATING CONDITIONS .....	23
4.2.7 TEST RESULTS.....	24
4.3. NUMBER OF HOPPING FREQUENCY USED.....	24
4.3.1. LIMIT OF HOPPING FREQUENCY USED .....	34
4.3.2. TEST SETUP .....	34
4.3.3. TEST INSTRUMENTS.....	34
4.3.4. TEST PROCEDURES .....	35
4.3.5. DEVIATION FROM TEST STANDARD .....	35
4.3.6. TEST RESULTS.....	35
4.4. DWELL TIME ON EACH CHANNEL .....	38



4.4.1	LIMIT OF DWELL TIME USED .....	38
4.4.2	TEST SETUP .....	38
4.4.3	TEST INSTRUMENTS .....	38
4.4.4	TEST PROCEDURES.....	38
4.4.5	DEVIATION FROM TEST STANDARD.....	39
4.4.6	TEST RESULTS.....	39
4.5.	CHANNEL BANDWIDTH.....	42
4.5.1	LIMITS OF CHANNEL BANDWIDTH.....	42
4.5.2	TEST SETUP .....	42
4.5.3	TEST INSTRUMENTS .....	42
4.5.4	TEST PROCEDURE .....	42
4.5.5	DEVIATION FROM TEST STANDARD.....	42
4.5.6	EUT OPERATING CONDITION.....	42
4.5.7	TEST RESULTS.....	43
4.6.	HOPPING CHANNEL SEPARATION .....	47
4.6.1.	LIMIT OF HOPPING CHANNEL SEPARATION .....	47
4.6.2.	TEST SETUP .....	47
4.6.3.	TEST INSTRUMENTS.....	47
4.6.4.	TEST PROCEDURES .....	47
4.6.5.	DEVIATION FROM TEST STANDARD .....	47
4.6.6.	TEST RESULTS.....	48
4.7.	MAXIMUM OUTPUT POWER.....	50
4.7.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT.....	50
4.7.2	TEST SETUP .....	50
4.7.3	TEST INSTRUMENTS .....	50
4.7.4	TEST PROCEDURES.....	50
4.7.5	DEVIATION FROM TEST STANDARD.....	50
4.7.6	EUT OPERATING CONDITION.....	50
4.7.7	TEST RESULTS.....	51
4.8.	OUT OF BAND EMISSION MEASUREMENT .....	52
4.8.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT .....	52
4.8.2	TEST INSTRUMENTS.....	52
4.8.3	TEST PROCEDURE .....	52
4.8.4	DEVIATION FROM TEST STANDARD.....	52
4.8.5	EUT OPERATING CONDITION.....	52
4.8.6	TEST RESULTS.....	52
<b>5.</b>	<b>PHOTOGRAPHS OF THE TEST CONFIGURATION .....</b>	<b>56</b>



Test Report No.: RF151008N004-1R1

6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE  
EUT BY THE LAB..... 57



Test Report No.: RF151008N004-1R1

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF151008N004-1R1	Original release	May 17, 2016

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)&15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

## 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.74dB
	30MHz ~ 1GMHz	3.55dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	4.84dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Tablet PC
<b>MODEL NO.</b>	MT10UWA116
<b>ADDITIONAL MODELS</b>	N/A
<b>FCC ID</b>	VUI-MT10UW
<b>POWER SUPPLY</b>	DC 3.8V by Li-ion Battery, DC 5.0V by Adaptor or USB Host Unit
<b>MODULATION TECHNOLOGY</b>	FHSS
<b>MODULATION TYPE</b>	GFSK, 8DPSK, π/4 DQPSK
<b>OPERATING FREQUENCY</b>	2402MHz~2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>MAX. OUTPUT POWER</b>	8.25dBm (Maximum Peak Power)
<b>ANTENNA TYPE</b>	Monopole Antenna, 3.76dBi Gain
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	USB Cable : Shielded, detachable, 1.0m

**NOTE:**

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- Please refer to the EUT photo document (Reference No.: 151008N004) for detailed product photo.
- The EUT was powered by the following adapters:

<b>ADAPTER 1</b>	
BRAND:	N/A
MODEL:	SA69-050200V
INPUT:	AC 100-240V, 50/60HZ, 300MA
OUTPUT:	DC 5V, 2000MA
<b>ADAPTER 2</b>	
BRAND:	N/A
MODEL:	ASSA55E-050200
INPUT:	AC 100-240V, 50/60HZ, 0.45A
OUTPUT:	DC 5V, 2A



### 3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



### 3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

### 3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	-	Powered by adapter with Bluetooth link
B	-	-	-	√	Powered by battery with Bluetooth link
C	-	-	-	-	Powered by USB with Bluetooth link

Where **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission

**RE≥1G**: Radiated Emission above 1GHz  
**APCM**: Antenna Port Conducted Measurement

#### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

**POWER LINE CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	39	FHSS	GFSK	DH5

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	26deg. C, 67%RH	DC 5.0V from Adapter	Sen He
RE≥1G	26deg. C, 67%RH	DC 5.0V from Adapter	Sen He
PLC	20deg. C, 56%RH	DC 5.0V from Adapter	Sen He
APCM	20deg. C, 55%RH	DC 3.8V From Battery	Yuqiang Yin



### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

- FCC Part 15, Subpart C. Section 15.247**
- ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Mobile Phone	SAMSUNG	GT-S7572	R21D85CCB7N	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

## 4 TEST TYPES AND RESULTS

### 4.1. CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	0.15 ~ 0.5	Quasi-peak
0.5 ~ 5	66 to 56	56 to 46
5 ~ 30	56	46
	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCS30	100340	May 11,15	May 10,16
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	May 11,15	May 10,16
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	May 11,15	May 10,16
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
  2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



Test Report No.: RF151008N004-1R1

#### 4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.1.5 TEST SETUP



- Note: 1.Support units were connected to second LISN.**  
**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

### 4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: GFSK CH39 (Adapter: ADP-10HW)

Charger SA69-050200V


PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector
1	0.19	54.3	13.00	65.0	-10.70	Peak
1**	0.19	36.0	13.00	55.0	-19.00	AV
2	0.26	45.3	13.00	62.9	-17.60	Peak
2**	0.26	31.5	13.00	52.9	-21.40	AV
3	0.32	44.1	13.00	61.1	-17.00	Peak
3**	0.32	23.0	13.00	51.1	-28.10	AV
4	4.07	45.0	13.00	56.0	-11.00	Peak
4**	4.07	29.0	13.00	46.0	-17.00	AV
5	12.79	46.2	13.00	60.0	-13.80	Peak
5**	12.79	35.0	13.00	50.0	-15.00	AV
6	17.36	41.9	13.00	60.0	-18.10	Peak
6**	17.36	29.5	13.00	50.0	-20.50	AV

#### REMARKS:

1. The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors.

2. Margin value = Results - Limit




<b>PHASE</b>	Neutral	<b>6dB BANDWIDTH</b>	9kHz
--------------	---------	----------------------	------

No	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector
1	0.18	53.3	13.00	65.1	-11.80	Peak
1**	0.18	38.0	13.00	55.1	-17.10	AV
2	0.25	47.6	13.00	63.2	-15.60	Peak
2**	0.25	33.9	13.00	53.2	-19.30	AV
3	2.31	45.9	13.00	56.0	-10.10	Peak
3**	2.31	32.9	13.00	46.0	-13.10	AV
4	4.06	49.7	13.00	56.0	-6.30	Peak
4**	4.06	32.7	13.00	46.0	-13.30	AV
5	13.29	43.2	13.00	60.0	-16.80	Peak
5**	13.29	33.9	13.00	50.0	-16.10	AV
6	15.81	42.6	13.00	60.0	-17.40	Peak
6**	15.81	31.2	13.00	50.0	-18.80	AV

**REMARKS:**

1. The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors.

2. Margin value = Results - Limit







CONDUCTED WORST-CASE DATA: GFSK CH39 (Adapter: ADP-10HW)

Charger ASSA55e-050200


PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector
1	0.17	59.2	13.00	65.5	6.30	Peak
1**	0.17	51.2	13.00	55.5	4.30	AV
2	0.27	49.2	13.00	62.7	13.50	Peak
2**	0.27	37.0	13.00	52.7	15.70	AV
3	0.43	42.6	13.00	57.9	15.30	Peak
3**	0.43	29.0	13.00	47.9	18.90	AV
4	0.99	36.0	13.00	56.0	20.00	Peak
4**	0.99	25.7	13.00	46.0	20.30	AV
5	2.51	33.5	13.00	56.0	22.50	Peak
5**	2.51	21.5	13.00	46.0	24.50	AV
6	5.74	36.4	13.00	60.0	23.60	Peak
6**	5.74	22.3	13.00	50.0	27.70	AV

REMARKS:

1. The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors.

2. Margin value = Results - Limit




<b>PHASE</b>	Neutral	<b>6dB BANDWIDTH</b>	9kHz
--------------	---------	----------------------	------

No	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector
1	0.16	57.7	13.00	65.7	8.00	Peak
1**	0.16	50.4	13.00	55.7	5.30	AV
2	0.20	51.4	13.00	64.5	13.10	Peak
2**	0.20	33.9	13.00	54.5	20.60	AV
3	0.31	45.7	13.00	61.3	15.60	Peak
3**	0.31	31.9	13.00	51.3	19.40	AV
4	0.89	36.0	13.00	56.0	20.00	Peak
4**	0.89	24.6	13.00	46.0	21.40	AV
5	2.18	34.6	13.00	56.0	21.40	Peak
5**	2.18	21.8	13.00	46.0	24.20	AV
6	7.72	36.9	13.00	60.0	23.10	Peak
6**	7.72	25.1	13.00	50.0	24.90	AV

**REMARKS:**

1. The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors.

2. Margin value = Results – Limit



## 4.2. RADIATED EMISSION AND BANDEGE MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION AND BANDEGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Agilent	E4446A	MY46180622	Apr. 29,15	Apr. 28,16
EMI Test Receiver	Rohde&Schwarz	ESVS10	841431/004	May 17,15	May 16,16
Loop antenna (9kHz~30MHz)	Daze	ZN30900A	0708	Dec. 22,15	Dec. 21,16
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 25, 15	Jul. 24, 16
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 30,14	May 29,16
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Jan. 21,15	Jan. 20,16
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,15	Mar. 03, 16
Signal Amplifier	Agilent	8447D	2944A10488	Jun. 25,15	Jun. 24,16
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 13,15	May 12,16
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,15	Nov. 19,16
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Apr. 19,14	Apr. 18,16
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 27,15	Oct. 26,16
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 494399.

#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with "Duty cycle correction factor".

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) =  $20 * \log(\text{Duty cycle})$ .

Duty cycle = on time / 100 milliseconds

On time = dwell time \* hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) =  $20 * \log((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dBuV/m.



**BUREAU  
VERITAS**

**Test Report No.: RF151008N004-1R1**

Example:

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + duty cycle correction factor (dB)

= 45.61 + (-21.21) = 24.4 (dBuV/m)


4. All modes of operation were investigated and the worst-case emissions are reported.



#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

### 4.2.7 TEST RESULTS

**BELOW 1GHz WORST-CASE DATA:**

Charge 1 SA69-050200V

8DPSK DH5


<b>CHANNEL</b>	Channel 0	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	155.34	35.33	-23.28	43.5	-8.17	Peak	222.70	100
2	200.68	38.13	-20.19	43.5	-5.37	Peak	312.10	100
3	232.19	38.19	-19.52	46.0	-7.81	Peak	183.70	100
4	288.20	39.26	-18.10	46.0	-6.74	Peak	194.90	100
5	342.02	37.50	-16.28	46.0	-8.50	Peak	150.40	100
6	427.36	42.74	-14.62	46.0	-3.26	Peak	256.50	100

**REMARKS:**

1. The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.3. The other emission levels were very low against the limit.

2. Margin value = Results– Limit.






<b>CHANNEL</b>	Channel 0	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	39.46	35.11	-19.91	40.0	-4.89	Peak	5.00	100
2	44.55	34.61	-18.75	40.0	-5.39	Peak	220.00	100
3	155.83	38.75	-23.23	43.5	-4.75	Peak	78.00	100
4	232.19	32.34	-19.52	46.0	-13.66	Peak	171.00	100
5	427.36	33.27	-14.62	46.0	-12.73	Peak	91.00	100
6	666.40	32.77	-9.92	46.0	-13.23	Peak	198.00	100

**REMARKS:**

1. The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.3. The other emission levels were very low against the limit.
2. Margin value = Results– Limit.



Charge 2 ASSA55e-050200

8DPSK DH5


<b>CHANNEL</b>	Channel 0	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	72.43	27.89	-23.63	40.0	12.11	Peak	1.00	100
2	112.67	29.35	-20.66	43.5	14.15	Peak	100.00	100
3	155.58	34.49	-23.23	43.5	9.01	Peak	310.90	100
4	180.31	31.89	-22.14	43.5	11.61	Peak	334.40	100
5	293.77	27.92	-17.88	46.0	18.08	Peak	253.60	100
6	709.07	37.81	-8.89	46.0	8.19	Peak	59.60	100

REMARKS:

1. The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.3. The other emission levels were very low against the limit.

2. Margin value = Results– Limit.




<b>CHANNEL</b>	Channel 0	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	30.00	36.29	-21.72	40.0	3.71	Peak	21.30	100
2	51.09	31.02	-18.62	40.0	8.98	Peak	292.90	100
3	113.40	37.20	-20.74	43.5	6.30	Peak	41.50	100
4	156.07	35.08	-23.23	43.5	8.42	Peak	260.00	100
5	180.07	33.58	-22.14	43.5	9.92	Peak	4.90	100
6	454.51	29.99	-14.43	46.0	16.01	Peak	0.40	100

**REMARKS:**

1. The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.3. The other emission levels were very low against the limit.
2. Margin value = Results– Limit.



**ABOVE 1GHz WORST-CASE DATA:  
GFSK DH5**

<b>CHANNEL</b>	TX Channel 0	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	#2401.65	103.95	-0.27			Peak	187.00	100
2	2869.03	49.54	2.10	74.0	24.46	Peak	97.00	100
3	4653.34	51.85	13.09	74.0	22.15	Peak	204.00	100
4	10155.57	49.33	18.91	74.0	24.67	Peak	62.00	100
5	16327.37	48.24	11.70	74.0	25.76	Peak	245.00	100
6	19309.48	50.48	13.46	74.0	23.52	Peak	244.00	100
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	#2441.14	84.58	-0.38			Peak	304.50	100
2	3414.65	48.78	9.25	74.0	25.22	Peak	100.80	100
3	5179.70	51.67	14.82	74.0	22.33	Peak	304.40	100
4	10975.46	50.87	20.00	74.0	23.13	Peak	274.90	100
5	18022.46	49.87	13.26	74.0	24.13	Peak	168.00	100
6	19309.48	50.86	13.46	74.0	23.14	Peak	57.40	100

**REMARKS:**

1. "#": The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.
2. For the test data above 1 GHz, according the ANSI C63.4, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1750.31	47.04	-3.87	74.0	26.96	Peak	107.00	100
2	#2441.14	105.40	-0.38			Peak	33.00	100
3	3255.69	50.98	9.02	74.0	23.02	Peak	228.00	100
4	10975.46	50.66	20.00	74.0	23.34	Peak	195.00	100
5	16264.98	48.24	11.53	74.0	25.76	Peak	34.00	100
6	19309.48	51.06	13.46	74.0	22.94	Peak	60.00	100
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1294.43	43.70	-4.81	74.0	30.30	Peak	297.00	100
2	#2441.14	84.58	-0.38			Peak	167.00	100
3	3414.65	48.78	9.25	74.0	25.22	Peak	10.00	100
4	10155.57	48.99	18.91	74.0	25.01	Peak	343.00	100
5	16275.37	48.72	11.56	74.0	25.28	Peak	335.00	100
6	19309.48	50.86	13.46	74.0	23.14	Peak	334.00	100

**REMARKS:**

1. "#": The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.
2. For the test data above 1 GHz, according the ANSI C63.4, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

<b>CHANNEL</b>	TX Channel 78	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1750.31	47.57	-3.87	74.0	26.43	Peak	356.00	100
2	#2480.13	104.72	-0.60			Peak	254.00	100
3	3307.42	52.02	8.86	74.0	21.98	Peak	117.00	100
4	10874.38	50.16	19.66	74.0	23.84	Peak	208.00	100
5	16327.37	48.85	11.70	74.0	25.15	Peak	122.00	100
6	19309.48	50.77	13.46	74.0	23.23	Peak	340.00	100
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1290.93	44.36	-4.81	74.0	29.64	Peak	244.00	100
2	#2480.13	84.57	-0.60			Peak	112.00	100
3	3333.67	48.12	8.92	74.0	25.88	Peak	247.00	100
4	8830.28	47.51	16.55	74.0	26.49	Peak	69.00	100
5	11975.04	51.86	20.76	74.0	22.14	Peak	178.00	100
6	19309.48	50.80	13.46	74.0	23.20	Peak	269.00	100

**REMARKS:**

1. "#": The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.
2. For the test data above 1 GHz, according the ANSI C63.4, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.



BT\_8DPSK DH5

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1843.29	44.75	-3.18	74.0	29.25	Peak	330.00	100
2	#2401.65	102.30	-0.27			Peak	318.00	100
3	3202.45	52.80	9.22	74.0	21.20	Peak	103.00	100
4	4672.83	52.34	13.16	74.0	21.66	Peak	278.00	100
5	12008.74	51.62	20.87	74.0	22.38	Peak	173.00	100
6	19309.48	51.08	13.46	74.0	22.92	Peak	163.00	100

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1993.75	44.65	-2.50	74.0	29.35	Peak	287.00	100
2	#2401.65	82.84	-0.27			Peak	132.00	100
3	5179.70	53.20	14.82	74.0	20.80	Peak	120.00	100
4	10975.46	49.85	20.00	74.0	24.15	Peak	172.00	100
5	16181.78	48.46	11.19	74.0	25.54	Peak	262.00	100
6	19309.48	51.13	13.46	74.0	22.87	Peak	327.00	100

REMARKS:

- " # ": The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.
- For the test data above 1 GHz, according the ANSI C63.4, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

<b>CHANNEL</b>	TX Channel 39	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1896.28	48.75	-2.98	74.0	25.25	Peak	272.00	100
2	#2441.14	103.52	-0.38			Peak	356.00	100
3	3254.94	51.18	9.05	74.0	22.82	Peak	119.00	100
4	5424.14	51.15	14.70	74.0	22.85	Peak	32.00	100
5	12053.66	51.50	20.82	74.0	22.50	Peak	161.00	100
6	19189.68	50.04	14.08	74.0	23.96	Peak	326.00	100
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	1869.28	44.75	-3.02	74.0	29.25	Peak	112.00	100
2	#2441.14	81.66	-0.38			Peak	315.00	100
3	4342.91	50.76	12.16	74.0	23.24	Peak	116.00	100
4	5648.34	52.16	15.66	74.0	21.84	Peak	265.00	100
5	12053.66	51.59	20.82	74.0	22.41	Peak	250.00	100
6	19189.68	49.89	14.08	74.0	24.11	Peak	233.00	100

**REMARKS:**

- "#": The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.
- For the test data above 1 GHz, according to the ANSI C63.4, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.



<b>CHANNEL</b>	TX Channel 78	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	2093.73	50.33	-1.59	74.0	23.67	Peak	233.00	100
2	#2480.13	102.41	-0.60			Peak	190.00	100
3	3306.67	52.09	8.86	74.0	21.91	Peak	70.00	100
4	5179.70	52.10	14.82	74.0	21.90	Peak	89.00	100
5	11975.04	51.77	20.76	74.0	22.23	Peak	140.00	100
6	19309.48	50.70	13.46	74.0	23.30	Peak	217.00	100
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)
1	2205.70	46.38	-0.37	74.0	27.62	Peak	29.00	100
2	#2479.63	83.61	-0.63			Peak	175.00	100
3	3332.92	49.90	8.89	74.0	24.10	Peak	281.00	100
4	5179.70	52.13	14.82	74.0	21.87	Peak	45.00	100
5	12053.66	51.73	20.82	74.0	22.27	Peak	302.00	100
6	19149.75	49.97	13.93	74.0	24.03	Peak	2.00	100

**REMARKS:**

1. "#": The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.
2. For the test data above 1 GHz, according the ANSI C63.4, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.




### 4.3. NUMBER OF HOPPING FREQUENCY USED

#### 4.3.1. LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

#### 4.3.2. TEST SETUP



#### 4.3.3. TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer (10Hz–40GHz)	Rohde&Schwarz	FSV40	101003	Apr. 07,15	Apr. 06,16
Power Meter	Anritsu	ML2495A	1139001	Feb. 20,15	Feb. 19,16
Power Sensor	Anritsu	MA2411B	1126068	Feb. 20,15	Feb. 19,16
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 27,15	Oct. 26,16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.04,15	Sep. 03,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Oct. 17, 15	Oct. 16, 16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 05,15	Nov. 04,16

**NOTE:**

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



Test Report No.: RF151008N004-1R1

#### 4.3.4. TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.



#### 4.3.5. DEVIATION FROM TEST STANDARD

No deviation.



#### 4.3.6. TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK



8DPSK




#### 4.4. DWELL TIME ON EACH CHANNEL

##### 4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

##### 4.4.2 TEST SETUP



##### 4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

##### 4.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.



#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 TEST RESULTS

##### GFSK

Mode	Pulse Width (ms)	Total of Dwell (ms)	Limit (msec)	PASS / FAIL
DH1	0.383	122.660	400	PASS
DH3	1.640	262.408	400	PASS
DH5	2.887	307.956	400	PASS

##### 8DPSK

Mode	Pulse Width (ms)	Total of Dwell (ms)	Limit (msec)	PASS / FAIL
DH1	0.390	124.804	400	PASS
DH3	1.633	261.288	400	PASS
DH5	2.893	308.596	400	PASS


**NOTE:** Test plots of the transmitting time slot are shown on next page.



BUREAU VERITAS

Test Report No.: RF151008N004-1R1

GFSK



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)






BUREAU VERITAS

Test Report No.: RF151008N004-1R1

### 8DPSK






## 4.5. CHANNEL BANDWIDTH

### 4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



BUREAU VERITAS


Test Report No.: RF151008N004-1R1

### 4.5.7 TEST RESULTS

#### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.123
39	2441	1.129
78	2480	1.124

#### CH 0







BUREAU VERITAS

Test Report No.: RF151008N004-1R1

CH 39



CH 78






8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.410
39	2441	1.407
78	2480	1.409

CH 0







BUREAU VERITAS

Test Report No.: RF151008N004-1R1

CH 39



CH 78






#### 4.6. HOPPING CHANNEL SEPARATION

##### 4.6.1. LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

##### 4.6.2. TEST SETUP



##### 4.6.3. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

##### 4.6.4. TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

##### 4.6.5. DEVIATION FROM TEST STANDARD

No deviation.




### 4.6.6. TEST RESULTS

CHANNEL	FREQUENCY SEPARATION (MHZ)	MAX 20 DB BANDWIDTH (MHZ)	TWO-THIRDS OF THE 20 DB BANDWIDTH (MHZ)	PASS / FAIL
GFSK	1.00	1.129	0.75	PASS
8-DPSK	1.00	1.410	0.94	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

#### GFSK








BUREAU VERITAS

Test Report No.: RF151008N004-1R1

8DPSK






#### 4.7. MAXIMUM OUTPUT POWER

##### 4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

##### 4.7.2 TEST SETUP



##### 4.7.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

##### 4.7.4 TEST PROCEDURES

A power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

##### 4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

##### 4.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



#### 4.7.7 TEST RESULTS

##### PEAK OUTPUT POWER

###### GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	7.50	5.62	125	PASS
39	2441	7.79	6.01	125	PASS
78	2480	6.91	4.91	125	PASS

###### 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	8.14	6.52	125	PASS
39	2441	<b>8.25</b>	<b>6.68</b>	125	PASS
78	2480	7.45	5.56	125	PASS



## 4.8. OUT OF BAND EMISSION MEASUREMENT

### 4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100KHz RBW).

### 4.8.2 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

### 4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

### 4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

### 4.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

### 4.8.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.



BUREAU VERITAS

Test Report No.: RF151008N004-1R1

GFSK



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch


No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)




BUREAU VERITAS

Test Report No.: RF151008N004-1R1



### 8DPSK



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch


No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



BUREAU VERITAS

# Test Report No.: RF151008N004-1R1



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



**BUREAU  
VERITAS**

Test Report No.: RF151008N004-1R1

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).





**BUREAU  
VERITAS**

Test Report No.: RF151008N004-1R1

## **6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**