

### #01\_LTE Band 2\_20M\_QPSK\_1\_0\_Right Side\_5mm\_Ant 3


Communication System: LTE ; Frequency: 1900 MHz;Duty Cycle: 1:1  
Medium: HSL\_1900\_230416 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.431$  S/m;  $\epsilon_r = 40.733$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.5 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(5.23, 5.23, 5.23) @ 1900 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (51x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.54 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 27.27 V/m; Power Drift = 0.01 dB  
Peak SAR (extrapolated) = 1.85 W/kg  
**SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.630 W/kg**  
Maximum value of SAR (measured) = 1.37 W/kg



0 dB = 1.37 W/kg = 1.37 dBW/kg

## #02\_LTE Band 5\_10M\_QPSK\_1\_0\_Back\_5mm\_Ch20525


Communication System: LTE; Frequency: 836.5 MHz; Duty Cycle: 1:1  
 Medium: HSL\_850\_230320 Medium parameters used :  $f = 836.5$  MHz;  $\sigma = 0.926$  S/m;  $\epsilon_r = 42.763$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.58, 6.58, 6.58) @ 836.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
 Maximum value of SAR (interpolated) = 0.844 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 30.16 V/m; Power Drift = 0.00 dB  
 Peak SAR (extrapolated) = 1.03 W/kg  
**SAR(1 g) = 0.715 W/kg; SAR(10 g) = 0.469 W/kg**  
 Maximum value of SAR (measured) = 0.820 W/kg



0 dB = 0.820 W/kg = -0.86 dBW/kg

### #03\_LTE Band 12\_10M\_QPSK\_1\_0\_Front\_5mm\_Ch23095;Ant 3


Communication System: LTE ; Frequency: 707.5 MHz;Duty Cycle: 1:1  
Medium: HSL\_750\_230321 Medium parameters used (interpolated):  $f = 707.5$  MHz;  $\sigma = 0.872$  S/m;  
 $\epsilon_r = 42.417$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.77, 6.77, 6.77) @ 707.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.932 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 31.76 V/m; Power Drift = -0.04 dB  
Peak SAR (extrapolated) = 1.24 W/kg  
**SAR(1 g) = 0.778 W/kg; SAR(10 g) = 0.500 W/kg**  
Maximum value of SAR (measured) = 0.907 W/kg



0 dB = 0.907 W/kg = -0.42 dBW/kg

### #04\_LTE Band 13\_10M\_QPSK\_1\_0\_Front\_5mm\_Ch23230;Ant 3


Communication System: LTE; Frequency: 782 MHz; Duty Cycle: 1:1  
Medium: HSL\_750\_230321 Medium parameters used:  $f = 782 \text{ MHz}$ ;  $\sigma = 0.896 \text{ S/m}$ ;  $\epsilon_r = 41.942$ ;  $\rho = 1000 \text{ kg/m}^3$   
Ambient Temperature :  $23.6 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.6 \text{ }^\circ\text{C}$

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.77, 6.77, 6.77) @ 782 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $1.14 \text{ W/kg}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $36.51 \text{ V/m}$ ; Power Drift =  $-0.08 \text{ dB}$   
Peak SAR (extrapolated) =  $1.46 \text{ W/kg}$   
**SAR(1 g) =  $0.995 \text{ W/kg}$ ; SAR(10 g) =  $0.657 \text{ W/kg}$**   
Maximum value of SAR (measured) =  $1.13 \text{ W/kg}$



0 dB =  $1.13 \text{ W/kg}$  =  $0.53 \text{ dBW/kg}$

### #05\_LTE Band 30\_10M\_QPSK\_1\_0\_Front\_5mm\_Ch27710;Ant 0

Communication System: LTE ; Frequency: 2310 MHz;Duty Cycle: 1:1

Medium: HSL\_2300\_230416 Medium parameters used:  $f = 2310$  MHz;  $\sigma = 1.653$  S/m;  $\epsilon_r = 39.197$ ;

$\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.5 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(4.95, 4.95, 4.95) @ 2310 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x111x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.20 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.21 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 1.86 W/kg

**SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.506 W/kg**

Maximum value of SAR (measured) = 1.36 W/kg



0 dB = 1.36 W/kg = 1.34 dBW/kg

### #06\_LTE Band 66\_20M\_QPSK\_1\_0\_Back\_5mm\_Ant 3


Communication System: LTE; Frequency: 1770 MHz; Duty Cycle: 1:1  
Medium: HSL\_1750\_230322 Medium parameters used:  $f = 1770$  MHz;  $\sigma = 1.374$  S/m;  $\epsilon_r = 40.533$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.7 °C ; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(5.6, 5.6, 5.6) @ 1770 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.10 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 29.24 V/m; Power Drift = 0.02 dB  
Peak SAR (extrapolated) = 1.53 W/kg  
**SAR(1 g) = 0.961 W/kg; SAR(10 g) = 0.617 W/kg**  
Maximum value of SAR (measured) = 1.16 W/kg



0 dB = 1.16 W/kg = 0.64 dBW/kg

### #07\_LTE Band 71\_20M\_QPSK\_1\_0\_Front\_5mm\_Ch133297;Ant 3


Communication System: LTE ; Frequency: 680.5 MHz;Duty Cycle: 1:1  
Medium: HSL\_750\_230321 Medium parameters used :  $f = 680.5 \text{ MHz}$ ;  $\sigma = 0.862 \text{ S/m}$ ;  $\epsilon_r = 42.529$ ;  
 $\rho = 1000 \text{ kg/m}^3$   
Ambient Temperature :  $23.6 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.6 \text{ }^\circ\text{C}$

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.77, 6.77, 6.77) @ 680.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $0.906 \text{ W/kg}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $31.80 \text{ V/m}$ ; Power Drift =  $-0.02 \text{ dB}$   
Peak SAR (extrapolated) =  $1.17 \text{ W/kg}$   
**SAR(1 g) =  $0.756 \text{ W/kg}$ ; SAR(10 g) =  $0.495 \text{ W/kg}$**   
Maximum value of SAR (measured) =  $0.866 \text{ W/kg}$



0 dB =  $0.866 \text{ W/kg} = -0.62 \text{ dBW/kg}$

### #08\_LTE Band 41\_20M\_QPSK\_1\_0\_Front\_5mm\_Ch40620;Ant 0


Communication System: LTE ; Frequency: 2593 MHz;Duty Cycle: 1:1.59038  
Medium: HSL\_2600\_230417 Medium parameters used :  $f = 2593$  MHz;  $\sigma = 1.95$  S/m;  $\epsilon_r = 39.143$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.4 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(4.52, 4.52, 4.52) @ 2593 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x111x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 0.879 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 20.92 V/m; Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 1.40 W/kg  
**SAR(1 g) = 0.695 W/kg; SAR(10 g) = 0.304 W/kg**  
Maximum value of SAR (measured) = 0.928 W/kg



0 dB = 0.928 W/kg = -0.32 dBW/kg



### #09\_LTE Band 48\_20M\_QPSK\_1\_0\_Front\_5mm\_Ch55340;Ant 0


Communication System: LTE; Frequency: 3560 MHz; Duty Cycle: 1:1.59  
Medium: HSL\_3700\_230327 Medium parameters used:  $f = 3560$  MHz;  $\sigma = 2.992$  S/m;  $\epsilon_r = 37.926$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.3 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7439; ConvF(6.82, 6.82, 6.82) @ 3560 MHz; Calibrated: 2023/2/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn853; Calibrated: 2022/7/20
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (71x111x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 2.41 W/kg

**Zoom Scan (7x7x21)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=1.4mm  
Reference Value = 29.47 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 3.45 W/kg  
**SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.421 W/kg**  
Maximum value of SAR (measured) = 2.29 W/kg



### #10\_FR1 n5\_20M\_BPSK\_1\_1\_Front\_5mm\_Ch167300;Ant 3


Communication System: FR1; Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_850\_230320 Medium parameters used :  $f = 836.5$  MHz;  $\sigma = 0.926$  S/m;  $\epsilon_r = 42.763$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.58, 6.58, 6.58) @ 836.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.30 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 35.56 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 1.55 W/kg  
**SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.618 W/kg**  
Maximum value of SAR (measured) = 1.15 W/kg



0 dB = 1.15 W/kg = 0.61 dBW/kg

### #11\_FR1 n12\_15M\_BPSK\_1\_1\_Front\_5mm\_Ch141500;Ant 3


Communication System: FR1; Frequency: 707.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_750\_230321 Medium parameters used :  $f = 707.5$  MHz;  $\sigma = 0.872$  S/m;  $\epsilon_r = 42.417$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.77, 6.77, 6.77) @ 707.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.12 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 34.96 V/m; Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 1.46 W/kg  
**SAR(1 g) = 0.942 W/kg; SAR(10 g) = 0.610 W/kg**  
Maximum value of SAR (measured) = 1.10 W/kg



0 dB = 1.10 W/kg = 0.41 dBW/kg

### #12\_FR1 n14\_10M\_BPSK\_1\_1\_Front\_5mm\_Ch158600;Ant 3


Communication System: FR1; Frequency: 793 MHz; Duty Cycle: 1:1  
Medium: HSL\_750\_230321 Medium parameters used:  $f = 793 \text{ MHz}$ ;  $\sigma = 0.9 \text{ S/m}$ ;  $\epsilon_r = 41.904$ ;  $\rho = 1000 \text{ kg/m}^3$   
Ambient Temperature :  $23.6 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.6 \text{ }^\circ\text{C}$

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.77, 6.77, 6.77) @ 793 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $0.975 \text{ W/kg}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $33.29 \text{ V/m}$ ; Power Drift =  $0.00 \text{ dB}$   
Peak SAR (extrapolated) =  $1.27 \text{ W/kg}$   
**SAR(1 g) =  $0.856 \text{ W/kg}$ ; SAR(10 g) =  $0.565 \text{ W/kg}$**   
Maximum value of SAR (measured) =  $0.988 \text{ W/kg}$



0 dB =  $0.988 \text{ W/kg} = -0.05 \text{ dBW/kg}$

### #13\_FR1 n25\_40M\_BPSK\_1\_1\_Front\_5mm\_ch376500;Ant 0


Communication System: FR1; Frequency: 1882.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_1900\_230323 Medium parameters used :  $f = 1882.5$  MHz;  $\sigma = 1.416$  S/m;  $\epsilon_r = 40.887$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(5.23, 5.23, 5.23) @ 1882.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.30 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 28.50 V/m; Power Drift = 0.08 dB  
Peak SAR (extrapolated) = 1.79 W/kg  
**SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.564 W/kg**  
Maximum value of SAR (measured) = 1.35 W/kg



0 dB = 1.35 W/kg = 1.30 dBW/kg

### #14\_FR1 n30\_10M\_BPSK\_1\_1\_Front\_5mm\_Ch462000;Ant 0


Communication System: FR1; Frequency: 2310 MHz; Duty Cycle: 1:1  
Medium: HSL\_2300\_230324 Medium parameters used:  $f = 2310$  MHz;  $\sigma = 1.621$  S/m;  $\epsilon_r = 39.027$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.3 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(4.95, 4.95, 4.95) @ 2310 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (71x101x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 1.39 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 29.42 V/m; Power Drift = 0.09 dB  
Peak SAR (extrapolated) = 1.87 W/kg  
**SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.475 W/kg**  
Maximum value of SAR (measured) = 1.29 W/kg



0 dB = 1.29 W/kg = 1.11 dBW/kg

**#15\_FR1 n66\_40M\_BPSK\_108\_54\_Back\_5mm\_Ch349000;Ant 3**

Communication System: FR1; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium: HSL\_1750\_230322 Medium parameters used:  $f = 1745 \text{ MHz}$ ;  $\sigma = 1.352 \text{ S/m}$ ;  $\epsilon_r = 40.625$ ;  
 $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature :  $23.7 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.7 \text{ }^\circ\text{C}$

**DASY5 Configuration:**

- Probe: ES3DV3 - SN3184; ConvF(5.6, 5.6, 5.6) @ 1745 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x91x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) =  $1.17 \text{ W/kg}$


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $29.81 \text{ V/m}$ ; Power Drift =  $0.05 \text{ dB}$

Peak SAR (extrapolated) =  $1.48 \text{ W/kg}$

**SAR(1 g) =  $0.992 \text{ W/kg}$ ; SAR(10 g) =  $0.624 \text{ W/kg}$**

Maximum value of SAR (measured) =  $1.16 \text{ W/kg}$



0 dB =  $1.16 \text{ W/kg}$  =  $0.64 \text{ dBW/kg}$

### #16\_FR1\_n70\_15M\_BPSK\_36\_22\_Front\_5mm\_Ch340500;Ant 0


Communication System: FR1; Frequency: 1702.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_1750\_230325 Medium parameters used :  $f = 1702.5$  MHz;  $\sigma = 1.344$  S/m;  $\epsilon_r = 40.154$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(5.6, 5.6, 5.6) @ 1702.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.11 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 26.16 V/m; Power Drift = -0.11 dB  
Peak SAR (extrapolated) = 1.53 W/kg  
**SAR(1 g) = 0.965 W/kg; SAR(10 g) = 0.544 W/kg**  
Maximum value of SAR (measured) = 1.20 W/kg



0 dB = 1.20 W/kg = 0.79 dBW/kg



### #17\_FR1 n71\_20M\_BPSK\_50\_28\_Front\_5mm\_ch136100;Ant 3


Communication System: FR1; Frequency: 680.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_750\_230321 Medium parameters used :  $f = 680.5$  MHz;  $\sigma = 0.862$  S/m;  $\epsilon_r = 42.529$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.6 °C ; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(6.77, 6.77, 6.77) @ 680.5 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (51x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 1.06 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 35.75 V/m; Power Drift = -0.07 dB  
Peak SAR (extrapolated) = 1.43 W/kg  
**SAR(1 g) = 0.897 W/kg; SAR(10 g) = 0.587 W/kg**  
Maximum value of SAR (measured) = 1.04 W/kg



0 dB = 1.04 W/kg = 0.17 dBW/kg

### #18\_FR1 n41\_100M\_BPSK\_1\_1\_Front\_5mm\_Ch518598;Ant 0


Communication System: FR1; Frequency: 2592.99 MHz;Duty Cycle: 1:1  
Medium: HSL\_2600\_230417 Medium parameters used :  $f = 2592.99$  MHz;  $\sigma = 1.95$  S/m;  $\epsilon_r = 39.143$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.4 °C

#### DASY5 Configuration:

- Probe: ES3DV3 - SN3184; ConvF(4.52, 4.52, 4.52) @ 2592.99 MHz; Calibrated: 2022/9/26
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn376; Calibrated: 2022/10/19
- Phantom: Twin-SAM V5.0 (30deg probe tilt)\_Right; Type: QD 000 P40 CD; Serial: TP-1479
- Measurement SW: DASY52, Version 52.10 (4);SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x111x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 1.53 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 29.14 V/m; Power Drift = 0.01 dB  
Peak SAR (extrapolated) = 2.33 W/kg  
**SAR(1 g) = 1.19 W/kg; SAR(10 g) = 0.521 W/kg**  
Maximum value of SAR (measured) = 1.57 W/kg



0 dB = 1.57 W/kg = 1.96 dBW/kg

### #19\_FR1 n48\_40M\_BPSK\_1\_1\_Front\_5mm\_Ch641666;Ant 0


Communication System: UID 0, FR1; Frequency: 3624.99 MHz; Duty Cycle: 1:1  
Medium: HSL\_3700\_230416 Medium parameters used:  $f = 3625$  MHz;  $\sigma = 3.031$  S/m;  $\epsilon_r = 37.797$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.5 °C; Liquid Temperature : 22.5 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN3728; ConvF(6.49, 6.49, 6.49) @ 3624.99 MHz; Calibrated: 2023/3/22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1512; Calibrated: 2023/3/20
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Ch/Area Scan (61x111x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 2.10 W/kg

**Ch/Zoom Scan (7x7x8)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=1.4mm  
Reference Value = 26.62 V/m; Power Drift = 0.06 dB  
Peak SAR (extrapolated) = 2.95 W/kg  
**SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.379 W/kg**  
Maximum value of SAR (measured) = 2.08 W/kg



0 dB = 2.08 W/kg = 3.18 dBW/kg

### #20\_FR1 n77\_100M\_BPSK\_135\_69\_Top Side\_5mm\_Ch633332;Ant 3


Communication System: FR1; Frequency: 3499.98 MHz; Duty Cycle: 1:1  
Medium: HSL\_3500\_230415 Medium parameters used:  $f = 3500$  MHz;  $\sigma = 2.89$  S/m;  $\epsilon_r = 37.833$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.3 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7306; ConvF(6.89, 6.89, 6.89) @ 3499.98 MHz; Calibrated: 2022/7/28
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1694; Calibrated: 2022/11/18
- Phantom: SAM\_Left; Type: QD 000 P40 CD; Serial: TP:1801
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

**Area Scan (61x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 2.11 W/kg

**Zoom Scan (7x7x8)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=1.4mm  
Reference Value = 26.97 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 3.15 W/kg  
**SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.453 W/kg**  
Maximum value of SAR (measured) = 2.21 W/kg



0 dB = 2.21 W/kg = 3.44 dBW/kg