

FCC RF Test Report

APPLICANT : PEGATRON CORPORATION
EQUIPMENT : Tablet
BRAND NAME : TOSHIBA
MODEL NAME : TOSHIBA AT10-A 、 TOSHIBA AT15-A
FCC ID : VUIPDAPDAAT10-A
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Feb. 28, 2013 and completely tested on Apr. 07, 2013. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION.....5

 1.1 Applicant.....5

 1.2 Manufacturer.....5

 1.3 Feature of Equipment Under Test.....5

 1.4 Product Specification of Equipment Under Test.....5

 1.5 Testing Site.....6

 1.6 Applied Standards6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....7

 2.1 Descriptions of Test Mode.....7

 2.2 Test Mode.....8

 2.3 Connection Diagram of Test System.....9

 2.4 Support Unit used in test configuration and system10

 2.5 Description of RF Function Operation Test Setup.....10

 2.6 Measurement Results Explanation Example.....11

3 TEST RESULT13

 3.1 Number of Channel Measurement13

 3.2 Hopping Channel Separation Measurement15

 3.3 Dwell Time Measurement.....22

 3.4 20dB and 99% Bandwidth Measurement25

 3.5 Peak Output Power Measurement38

 3.6 Conducted Band Edges Measurement.....40

 3.7 Conducted Spurious Emission Measurement47

 3.8 Radiated Band Edges and Spurious Emission Measurement57

 3.9 AC Conducted Emission Measurement.....68

 3.10 Antenna Requirements.....72

4 LIST OF MEASURING EQUIPMENT.....73

5 UNCERTAINTY OF EVALUATION.....74

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	RSS-210 A8.4(2)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	RSS-210 A8.1(b)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	RSS-210 A8.1(d)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	RSS-210 A8.1(a)	20dB Bandwidth	NA	Pass	-
3.4	-	RSS-Gen 4.6.1	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	RSS-210 A8.1(b)	Peak Output Power	≤ 1 W for 1Mbps ≤ 125 mW for 2, 3Mbps	Pass	-
3.6	15.247(d)	RSS-210 A8.5	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	RSS-210 A8.5	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	RSS-210 A8.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 11.45 dB at 51.060 MHz
3.9	15.207	RSS-Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 4.36 dB at 7.810 MHz
3.10	15.203 & 15.247(b)	RSS-210 A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

PEGATRON CORPORATION

No. 76, Ligong St., Beitou District, Taipei City 112

1.2 Manufacturer

Toshiba Corporation

1-1, Shibaura 1-chome, Minato-ku, Tokyo 105-8001, Japan

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Tablet
Brand Name	TOSHIBA
Model Name	TOSHIBA AT10-A、TOSHIBA AT15-A
FCC ID	VUIPDAPDAAT10-A
EUT supports Radios application	WLAN 11abgn / Bluetooth 2.1/3.0/4.0 / NFC
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 2.21 dBm (0.0017 W) Bluetooth EDR (2Mbps) : 0.67 dBm (0.0012 W) Bluetooth EDR (3Mbps) : 0.95 dBm (0.0012 W)
99% Occupied Bandwidth	Bluetooth (1Mbps) : 0.904MHz Bluetooth EDR (2Mbps) : 1.199MHz Bluetooth EDR (3Mbps) : 1.202MHz
Antenna Type	Chip Antenna type with gain 1.6999 dBi
Type of Modulation	Bluetooth 2.1 BR (1Mbps) : GFSK Bluetooth 2.1 EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth 2.1 EDR (3Mbps) : 8-DPSK Bluetooth 3.0 BR (1Mbps) : GFSK Bluetooth 3.0 EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth 3.0 EDR (3Mbps) : 8-DPSK

1.5 Testing Site

Test Site	SPORTON INTERNATIONAL INC.			
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978			
Test Site No.	Sporton Site No.			FCC/IC Registration No.
	TH02-HY	CO01-HY	03CH07-HY	722060/4086B-1

The test site complies with ANSI C63.4 2003 requirement.

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.10-2009
- ♦ IC RSS-210 Issue 8
- ♦ IC RSS-Gen Issue 3
- ♦ NOTICE 2012-DRS0126

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. Per the section 2.2.3 of Notice of 2012-DRS0126, " Receivers Excluded from Industry Canada Requirements", only radiocommunication receivers operating in stand-alone mode within the band 30-960 MHz and scanner receivers are subject to Industry Canada requirements.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	1.14 dBm	-0.25 dBm	-0.09 dBm
Ch39	2441MHz	2.16 dBm	0.64 dBm	0.87 dBm
Ch78	2480MHz	2.21 dBm	0.67 dBm	0.95 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals pursuant to ANSI C63.10-2009 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 KHz to 30 MHz), radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (X plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
 - b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth 1Mbps GFSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN Link + MP3 + SD Card + H Pattern + HDMI Cable + Earphone + USB Cable (Data Link with PC) + NFC On		
<p>Remark: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission .</p>			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DNS-G120	N/A	N/A	Unshielded, 1.5 m
3.	Bluetooth Earphone	SONY	Z354	N/A	N/A	N/A
4.	PC	HP	DC7700	FCC DoC	N/A	Unshielded, 1.8 m
5.	LCD Monitor	DELL	U2410f	FCC DoC	Shielded, 1.5 m	Unshielded, 1.8 m
6.	(USB) Mouse	Microsoft	1113	FCC DoC	Shielded, 1.8 m	N/A
7.	(USB) Keyboard	Microsoft	1366	FCC DoC	Shielded, 2.0 m	N/A
8.	Printer	EPSON	LQ300+	FCC DoC	Shielded, 1.8 m	Unshielded, 1.8 m
9.	Mic + Earphone	Apple	MB770FE/A	N/A	Unshielded, 1.5m	N/A
10.	MicroSD Card	Transcend	8G	FCC DoC	N/A	N/A
11.	NFC Card	Metro Taipei	Easy Card	N/A	N/A	N/A
12.	Modem	ACCEX	DM1414	IFAXDM1414	Shielded, 1 m	Unshielded, 1.8 m

2.5 Description of RF Function Operation Test Setup

For Bluetooth function, programmed RF utility, “ADB shell” installed in the notebook make the EUT provides functions like channel selection and power level for continuous transmitting and receiving signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$



For radiated band edges and spurious emission test :

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with "Duty cycle correction factor".

$$\text{Average Emission Level(dB}\mu\text{V/m)} = \text{Peak Emission Level(dB}\mu\text{V/m)} + \text{Duty cycle correction factor(dB)}$$

$$\text{Duty cycle correction factor(dB)} = 20 * \log(\text{Duty cycle}).$$

Duty cycle = On time / 100 milliseconds

On time = worst case dwell time * hopping number in 100 ms

For example : bluetooth with worst case dwell time 2.9ms and 2 hops in 100 ms, then

$$\text{Duty cycle correction factor(dB)} = 20 * \log((2.9 * 2) / 100) = -24.73 \text{ dB}$$

Following shows an average computation example with duty cycle correction factor = -24.73dB, and the peak emission level is 45.61 dB μ V/m.

Example :

$$\begin{aligned} \text{Average Emission Level(dB}\mu\text{V/m)} &= \text{Peak Emission Level(dB}\mu\text{V/m)} + \text{duty cycle correction factor(dB)} \\ &= 45.61 + (-24.73) = 20.88 \text{ (dB}\mu\text{V/m)} \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW \geq 1% of the span; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%


Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 28.MAR.2013 13:52:41



Date: 28.MAR.2013 13:56:18

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup






3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.000	0.6773	Pass
39	2441	1.000	0.6773	Pass
78	2480	1.000	0.6773	Pass


Channel Separation Plot on Channel 00 - 01



Date: 28.MAR.2013 22:07:58




Channel Separation Plot on Channel 39 - 40



Date: 28.MAR.2013 22:02:49

Channel Separation Plot on Channel 77 - 78




Date: 28.MAR.2013 21:54:20



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.000	0.9039	Pass
39	2441	1.000	0.9007	Pass
78	2480	1.000	0.9007	Pass


Channel Separation Plot on Channel 00 - 01



Date: 28.MAR.2013 22:20:17




Channel Separation Plot on Channel 39 - 40



Date: 28.MAR.2013 20:58:14

Channel Separation Plot on Channel 77 - 78




Date: 28.MAR.2013 21:01:37



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.000	0.8942	Pass
39	2441	1.000	0.8910	Pass
78	2480	1.000	0.8942	Pass


Channel Separation Plot on Channel 00 - 01



Date: 28.MAR.2013 21:18:17




Channel Separation Plot on Channel 39 - 40



Date: 28.MAR.2013 21:13:28

Channel Separation Plot on Channel 77 - 78



Date: 28.MAR.2013 21:03:42

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup





3.3.5 Test Result of Dwell Time

Test Mode :	DH5	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	3.00	0.32	0.4	Pass
AFH	20	53.33	3.00	0.16	0.4	Pass

Remark:

1. In normal mode, hopping rate is 1600hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 9.MAR.2013 13:23:39

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
For 99% Bandwidth measurement, the RBW=30kHz, and VBW = 100kHz. Sweep = auto ;
Detector function = sample. Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.016
39	2441	1.016
78	2480	1.016


20 dB Bandwidth Plot on Channel 00



Date: 28.MAR.2013 22:03:39




20 dB Bandwidth Plot on Channel 39



Date: 28.MAR.2013 21:54:54

20 dB Bandwidth Plot on Channel 78




Date: 28.MAR.2013 21:40:54



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.356
39	2441	1.351
78	2480	1.351


20 dB Bandwidth Plot on Channel 00



Date: 28.MAR.2013 20:51:22




20 dB Bandwidth Plot on Channel 39



Date: 28.MAR.2013 20:55:42

20 dB Bandwidth Plot on Channel 78




Date: 28.MAR.2013 20:58:54



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.341
39	2441	1.337
78	2480	1.341


20 dB Bandwidth Plot on Channel 00



Date: 28.MAR.2013 21:14:03




20 dB Bandwidth Plot on Channel 39



Date: 28.MAR.2013 21:09:33

20 dB Bandwidth Plot on Channel 78



Date: 28.MAR.2013 21:05:45




3.4.6 Test Result of 99% Occupied Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.904
39	2441	0.904
78	2480	0.904


99% Bandwidth Plot on Channel 00



Date: 28.MAR.2013 22:06:38




99% Occupied Bandwidth Plot on Channel 39



Date: 28.MAR.2013 21:57:19

99% Occupied Bandwidth Plot on Channel 78




Date: 28.MAR.2013 21:52:52



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.199
39	2441	1.199
78	2480	1.199


99% Bandwidth Plot on Channel 00



Date: 28.MAR.2013 21:33:59




99% Occupied Bandwidth Plot on Channel 39



Date: 28.MAR.2013 21:36:03

99% Occupied Bandwidth Plot on Channel 78




Date: 28.MAR.2013 21:39:49



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.202
39	2441	1.202
78	2480	1.202


99% Bandwidth Plot on Channel 00



Date: 28.MAR.2013 21:16:50




99% Occupied Bandwidth Plot on Channel 39



Date: 28.MAR.2013 21:12:18

99% Occupied Bandwidth Plot on Channel 78



Date: 28.MAR.2013 21:08:23

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, 3Mbps and AFH are 0.125 watts.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	1.14	20.97	Pass
39	2441	2.16	20.97	Pass
78	2480	2.21	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	-0.25	20.97	Pass
39	2441	0.64	20.97	Pass
78	2480	0.67	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	-0.09	20.97	Pass
39	2441	0.87	20.97	Pass
78	2480	0.95	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 KHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 300KHz ($\geq 1\%$ span=30MHz), VBW = 300KHz (\geq RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300KHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup






3.6.6 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

Low Band Edge Plot on Channel 00



Date: 28.MAR.2013 22:03:57

High Band Edge Plot on Channel 78




Date: 28.MAR.2013 21:41:13




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

Low Band Edge Plot on Channel 00



Date: 28.MAR.2013 20:51:41

High Band Edge Plot on Channel 78




Date: 28.MAR.2013 20:59:14




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

Low Band Edge Plot on Channel 00



Date: 28.MAR.2013 21:14:23

High Band Edge Plot on Channel 78




Date: 28.MAR.2013 21:06:04




3.6.7 Test Result of Conducted Hopping Mode Band Edges

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

1Mbps Hopping Mode Low Band Edge Plot




1Mbps Hopping Mode High Band Edge Plot






Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

2Mbps Hopping Mode Low Band Edge Plot



Date: 28.MAR.2013 21:31:17

2Mbps Hopping Mode High Band Edge Plot




Date: 28.MAR.2013 21:28:26




Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Reece Lee	Relative Humidity :	48~51%

3Mbps Hopping Mode Low Band Edge Plot



Date: 28.MAR.2013 21:19:54

3Mbps Hopping Mode High Band Edge Plot



Date: 28.MAR.2013 21:21:51

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 KHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 KHz, VBW = 300KHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 KHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup






3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 22:04:39

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 22:05:01




Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 21:55:19

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 21:55:40




Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 21:41:40

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 21:42:01




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 20:52:56

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 20:53:17




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 20:56:42

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 20:57:04




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 21:00:14

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 21:00:35




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 21:15:03

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 21:15:24




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 21:09:57

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 28.MAR.2013 21:10:19




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Reece Lee

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 28.MAR.2013 21:06:29

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 28.MAR.2013 21:06:51

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 KHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.




3.8.3 Test Procedures

1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines and the guidelines in ANSI C63.10-2009.
2. The EUT was placed on a turntable with 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 KHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


3.8.6 Duty cycle correction factor for average measurement

DH5 on time (One Pulse) Plot on Channel 39



Date: 7.APR.2013 20:39:54

DH5 on time/100ms (Count Pulses) Plot on Channel 39



Date: 7.APR.2013 20:38:31

Note:

1. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.88 / 100 = 5.76 %
2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.79 dB
3. DH5 has the highest duty cycle worst case and is reported.



Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2$ hops

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$



3.8.7 Test Result of Radiated Band Edges

Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	00	Relative Humidity :	51~53%
		Test Engineer :	Kyle Jhuang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2368.14	47.43	-26.57	74	42.56	32.26	6.88	34.27	197	35	Peak
2368.14	22.64	-31.36	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2363.28	44.75	-29.25	74	39.86	32.26	6.88	34.25	199	263	Peak
2363.28	19.96	-34.04	54	-	-	-	-	-	-	Average

Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	51~53%
		Test Engineer :	Kyle Jhuang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	60.83	-13.17	74	55.82	32.38	7.06	34.43	129	358	Peak
2483.5	36.04	-17.96	54	-	-	-	-	-	-	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	56.3	-17.70	74	51.29	32.38	7.06	34.43	196	248	Peak
2483.5	31.51	-22.49	54	-	-	-	-	-	-	Average



3.8.8 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	00	Relative Humidity :	51~53%
Test Engineer :	Kyle Jhuang	Polarization :	Horizontal
Remark :	1. 2402 MHz is fundamental signal which can be ignored. 2. 7206 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level. For example, 101.5 dBµV/m - 20dB = 81.05 dBµV/m.		

Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2402	101.5	-	-	96.59	32.3	6.91	34.3	197	35	Peak
2402	76.71	-	-	-	-	-	-	-	-	Average
4803	40.16	-33.84	74	54.9	33.98	8.75	57.47	100	0	Peak
4803	15.37	-38.63	54	-	-	-	-	-	-	Average
7206	40.18	-41.32	81.5	51.77	35.56	10.81	57.96	100	0	Peak

Note: Other harmonics are lower than background noise.

Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	00	Relative Humidity :	51~53%
Test Engineer :	Kyle Jhuang	Polarization :	Vertical
Remark :	1. 2402 MHz is fundamental signal which can be ignored. 2. 7206 MHz is not within a restricted band, and its limit line is 20dB below the highest emission level.		

Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2402	97.44	-	-	92.52	32.31	6.91	34.3	199	263	Peak
2402	72.65	-	-	-	-	-	-	-	-	Average
4803	41.24	-32.76	74	55.98	33.98	8.75	57.47	100	0	Peak
4803	16.45	-37.55	54	-	-	-	-	-	-	Average
7206	39.78	-37.66	77.44	51.37	35.56	10.81	57.96	100	0	Peak

Note: Other harmonics are lower than background noise.



Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	39	Relative Humidity :	51~53%
Test Engineer :	Kyle Jhuang	Polarization :	Horizontal
Remark :	2442 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2442	101.69	-	-	96.74	32.35	6.99	34.39	161	358	Peak
2442	76.9	-	-	-	-	-	-	-	-	Average
4881	39.97	-34.03	74	54.65	33.95	8.85	57.48	100	0	Peak
4881	15.18	-38.82	54	-	-	-	-	-	-	Average
7323	40.35	-33.65	74	51.95	35.53	10.91	58.04	100	0	Peak
7323	15.56	-38.44	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	39	Relative Humidity :	51~53%
Test Engineer :	Kyle Jhuang	Polarization :	Vertical
Remark :	2442 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2442	98.28	-	-	93.33	32.35	6.99	34.39	192	265	Peak
2442	73.49	-	-	-	-	-	-	-	-	Average
4881	40.27	-33.73	74	54.95	33.95	8.85	57.48	100	0	Peak
4881	15.48	-38.52	54	-	-	-	-	-	-	Average
7323	39.94	-34.06	74	51.54	35.53	10.91	58.04	100	0	Peak
7323	15.15	-38.85	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.



Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	51~53%
Test Engineer :	Kyle Jhuang	Polarization :	Horizontal
Remark :	2480 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.05	26.38	-13.62	40	40.57	17.12	0.57	31.88	-	-	Peak
53.76	27.68	-12.32	40	51.15	7.5	0.72	31.69	105	297	Peak
257.88	28.73	-17.27	46	45.68	12.71	1.58	31.24	-	-	Peak
365.8	29.81	-16.19	46	44.04	15.08	2.07	31.38	-	-	Peak
447	31.87	-14.13	46	43.73	16.99	2.29	31.14	-	-	Peak
474.3	28.25	-17.75	46	39.36	17.55	2.36	31.02	-	-	Peak
2480	101.23	-	-	96.22	32.38	7.06	34.43	129	358	Peak
2480	76.44	-	-	-	-	-	-	-	-	Average
4959	39.79	-34.21	74	54.45	33.91	8.92	57.49	100	0	Peak
4959	15	-39	54	-	-	-	-	-	-	Average
7440	40.51	-33.49	74	52.08	35.51	11.04	58.12	100	0	Peak
7440	15.72	-38.28	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.



Test Mode :	1Mbps	Temperature :	21~23°C
Test Channel :	78	Relative Humidity :	51~53%
Test Engineer :	Kyle Jhuang	Polarization :	Vertical
Remark :	2480 MHz is fundamental signal which can be ignored.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
47.01	26.68	-13.32	40	48.39	9.3	0.67	31.68	-	-	Peak
51.06	28.55	-11.45	40	51.57	7.9	0.71	31.63	100	128	Peak
64.29	28.31	-11.69	40	53.11	6.18	0.79	31.77	-	-	Peak
365.8	24.92	-21.08	46	39.15	15.08	2.07	31.38	-	-	Peak
407.8	25.33	-20.67	46	38.41	16.16	2.17	31.41	-	-	Peak
612.2	24.7	-21.3	46	32.57	19.89	2.73	30.49	-	-	Peak
2480	96.57	-	-	91.56	32.38	7.06	34.43	196	248	Peak
2480	71.78	-	-	-	-	-	-	-	-	Average
4959	40.21	-33.79	74	54.87	33.91	8.92	57.49	100	0	Peak
4959	15.42	-38.58	54	-	-	-	-	-	-	Average
7440	39.24	-34.76	74	50.81	35.51	11.04	58.12	100	0	Peak
7440	14.45	-39.55	54	-	-	-	-	-	-	Average

Note: Other harmonics are lower than background noise.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

See list of measuring instruments of this test report.

3.9.3 Test Procedures

1. The test follows the guidelines in ANSI C63.10-2009 test site requirement.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 KHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.9.4 Test Setup




AMN = Artificial mains network (LISN)
 AE = Associated equipment
 EUT = Equipment under test
 ISN = Impedance stabilization network



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	24~25°C
Test Engineer :	David Du	Relative Humidity :	47~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN Link + MP3 + SD Card + H Pattern + HDMI Cable + Earphone + USB Cable (Data Link with PC) + NFC On		




Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B LISN 2001/004-121228 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.178	48.09	-6.49	54.58	47.71	0.14	0.24	Average
2	0.178	50.74	-13.84	64.58	50.36	0.14	0.24	QP
3	0.239	38.46	-13.67	52.13	38.15	0.14	0.17	Average
4	0.239	41.24	-20.89	62.13	40.93	0.14	0.17	QP
5	0.299	34.84	-25.43	60.27	34.55	0.15	0.14	QP
6	0.299	30.77	-19.50	50.27	30.48	0.15	0.14	Average
7	1.050	38.83	-17.17	56.00	38.56	0.17	0.10	QP
8	1.050	33.19	-12.81	46.00	32.92	0.17	0.10	Average
9	7.810	51.96	-8.04	60.00	51.50	0.29	0.17	QP
10	7.810	44.98	-5.02	50.00	44.52	0.29	0.17	Average
11	14.727	39.48	-20.52	60.00	39.00	0.37	0.11	QP
12	14.727	36.84	-13.16	50.00	36.36	0.37	0.11	Average



Test Mode :	Mode 1	Temperature :	24~25°C
Test Engineer :	David Du	Relative Humidity :	47~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN Link + MP3 + SD Card + H Pattern + HDMI Cable + Earphone + USB Cable (Data Link with PC) + NFC On		



Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B LISN 2001/004-121228 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.181	47.17	-7.27	54.44	46.84	0.10	0.23	Average
2	0.181	49.78	-14.66	64.44	49.45	0.10	0.23	QP
3	0.239	37.19	-14.94	52.13	36.91	0.11	0.17	Average
4	0.239	39.78	-22.35	62.13	39.50	0.11	0.17	QP
5	0.476	32.02	-24.39	56.41	31.80	0.12	0.10	QP
6	0.476	31.83	-14.58	46.41	31.61	0.12	0.10	Average
7	1.040	43.87	-12.13	56.00	43.63	0.14	0.10	QP
8	1.040	39.30	-6.70	46.00	39.06	0.14	0.10	Average
9	7.810	52.96	-7.04	60.00	52.51	0.28	0.17	QP
10	7.810	45.64	-4.36	50.00	45.19	0.28	0.17	Average
11	14.728	41.06	-18.94	60.00	40.56	0.39	0.11	QP
12	14.728	38.99	-11.01	50.00	38.49	0.39	0.11	Average



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

Non-standard connector used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 06, 2012	Mar. 09, 2013 ~ Mar. 28, 2013	Jun. 05, 2013	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Feb. 05, 2013	Mar. 09, 2013 ~ Mar. 28, 2013	Feb. 04, 2014	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Feb. 05, 2013	Mar. 09, 2013 ~ Mar. 28, 2013	Feb. 04, 2014	Conducted (TH02-HY)
Bluetooth Base Station	R&S	CBT32	100519	N/A	Jun. 05, 2012	Mar. 09, 2013 ~ Mar. 28, 2013	Jun. 04, 2013	Conducted (TH02-HY)
EMC Receiver	R&S	ESCS 30	100132	9kHz ~ 2.75GHz	Nov. 14, 2012	Mar. 07, 2013	Nov. 13, 2013	Conduction (CO01-HY)
LISN	MessTec	NNB-2/16Z	2001/004	9kHz ~ 30MHz	Dec. 28, 2012	Mar. 07, 2013	Dec. 27, 2013	Conduction (CO01-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	2001/009	9kHz ~ 30MHz	Jan. 08, 2013	Mar. 07, 2013	Jan. 07, 2014	Conduction (CO01-HY)
EMI Filter	LINDGREN	LRE-2060	1004	< 450Hz	N/A	Mar. 07, 2013	N/A	Conduction (CO01-HY)
EMI Filter	LINDGREN	N6006	201052	0~60Hz	N/A	Mar. 07, 2013	N/A	Conduction (CO01-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832010001	9kHz ~ 30MHz	Mar. 01, 2013	Mar. 07, 2013	Feb. 28, 2014	Conduction (CO01-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Oct. 06, 2012	Apr. 07, 2013	Oct. 05, 2013	Radiation (03CH07-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9KHz ~ 30GHz	Nov. 30, 2012	Apr. 07, 2013	Nov. 29, 2013	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 22, 2012	Apr. 07, 2013	Aug. 21, 2013	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec. 01, 2012	Apr. 07, 2013	Nov. 30, 2013	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	159088	1GHz ~ 18GHz	Feb. 27, 2013	Apr. 07, 2013	Feb. 26, 2014	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10-1000MHz. 32dB.GAIN	Feb. 26, 2013	Apr. 07, 2013	Feb. 25, 2014	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Sep. 03, 2012	Apr. 07, 2013	Sep. 02, 2013	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9KHz ~ 30MHz	Jul. 03, 2012	Apr. 07, 2013	Jul. 02, 2013	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz ~ 40GHz	Sep. 28, 2012	Apr. 07, 2013	Sep. 27, 2013	Radiation (03CH07-HY)
Bluetooth Base Station	R&S	CBT32	100522	N/A	Feb. 09, 2012	Apr. 07, 2013	Feb. 08, 2014	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------



Appendix A. Photographs of EUT

Please refer to Sporton report number EP322823 as below.