



ATID Co., Ltd.

#1210 , Byuksan/Gyungin digital valley II #481-10, Gasan-Dong,
Gumchon-Gu, Seoul, Korea

Tel. +82-2-544-1436

Fax +82-2-2113-0040

TUNE-UP PROCEDURE

Programming of this product's transmit frequencies can be performed **ONLY** by the manufacturer or by service or maintenance personnel. The operator can not program transmit frequencies using the equipment's external operation.

WCDMA/GSM's Max. Target PWR and Tolerance inform as following the table in next page.

GSM 850	Voice	GPRS Data			
	GSM	GPRS	GPRS	EGPRS Data	EGPRS Data
		1 TX Slot	2 TX Slot	1 TX Slot	2 TX Slot
	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)
Max. Target PWR (dBm)	32.50	32.50	29.50	26.50	26.00
Tolerance (± dB)	2.00	2.00	2.00	2.00	2.00
PCS 1900	Voice	GPRS Data			
	GSM	GPRS	GPRS	EGPRS Data	EGPRS Data
		1 TX Slot	2 TX Slot	1 TX Slot	2 TX Slot
	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)
Max. Target PWR (dBm)	28.50	28.50	25.50	24.00	23.00
Tolerance (± dB)	2.00	2.00	2.00	2.00	2.00

BAND II	PCS WCDMA	HSDPA			
		Subtest1	Subtest2	Subtest3	Subtest4
Max. Target PWR (dBm)	23.50	23.50	23.50	22.50	22.50
Tolerance (± dB)	2.00	2.00	2.00	2.00	2.00
BAND V	Cellular WCDMA	HSDPA			
		Subtest1	Subtest2	Subtest3	Subtest4
Max. Target PWR (dBm)	23.50	22.50	22.00	21.00	21.00
Tolerance (± dB)	2.00	2.00	2.00	2.00	2.00