



Dates of Tests: JAN. 20 ~ FEB. 4, 2009
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

VUJAT870

APPLICANT

ATID CO.,Ltd

Equipment Class	:	Part 15 Spread Spectrum Transmitter (DSS)
Manufacturing Description	:	Industrial PDA
Manufacturer	:	ATID CO.,Ltd
Model name	:	AT870
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C; ANSI C-63.4-2003
Frequency Range	:	2402 ~ 2480MHz
RF power	:	Peak 2.14dBm - Conducted
Data of issue	:	February 6, 2009

This test report is issued under the authority of:



Dong -Min JUNG, Technical Manager

The test was supervised by:



Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION'S	3
2. INFORMATION'S ABOUT TEST ITEM	4
3. TEST REPORT	5
3.1 SUMMARY OF TESTS	5
3.2 TECHNICAL CHARACTERISTICS TEST	6
3.2.1 CARRIER FREQUENCY SEPARATION	6
3.2.2 NUMBER OF HOPPING FREQUENCIES	8
3.2.3 20 dB BANDWIDTH	11
3.2.4 TIME OF OCCUPANCY (Dwell Time)	15
3.2.5 TRANSMITTER OUTPUT POWER	17
3.2.6 BAND – EDGE & SPURIOUS	19
3.2.7 FIELD STRENGTH OF HARMONICS	25
3.2.8 AC CONDUCTED EMISSIONS	30
APPENDIX	
APPENDIX TEST EQUIPMENT USED FOR TESTS	37

1. General information's

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2009-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2009-06-20	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration
IC	CANADA	IC5799	2010-05-03	IC filing

2. Information's about test item

2-1 Applicant & Manufacturer

Company name : ATID CO.,Ltd
 Address : #1210 Byuksan/Gyungin digital valley II #481 – 10 Gasan-Dong
 Gumchon-Gu Seoul KOREA
 Tel / Fax : +82-2-544-1436 / +82-2-544-1438

2-2 Equipment Under Test (EUT)

Trade name : Industrial PDA
 Model name : AT870
 Serial number : Identical prototype
 Date of receipt : January 13, 2009
 EUT condition : Pre-production, not damaged
 Antenna type : Chip Antenna Max Gain 1.84dBi
 Frequency Range : 2402 ~ 2480MHz
 RF output power : Peak 2.14dBm - Conducted
 Number of channels : 79
 Duty cycle : 82.27 %
 Channel spacing : 1MHz
 Channel Access Protocol : Frequency Hopping
 Type of Modulation : GFSK
 Power Source (Battery) : 3.7Vdc Li-Ion Battery, 2960mAh

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
PC	HP COMPAG dx2200	CNG6500RX9	HP
Monitor	HSTND-2311-A	CNC816QHF2	HP
Keyboard	SK-8115	641-OEWW	DELL
Mouse	MO56UO	510022473	DELL
Print	STYLUS C65	N/A	EPSON
earphone	N/A	N/A	N/A
Adaptor	JPW118	KA050N08	AULT KOREA

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 15 hops		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	> 1.5 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 250 mWatt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	-		C
15.207 / 15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:

FCC Parts 15.247; ANSI C-63.4-2003

3.2 Transmitter requirements

3.2.1 Carrier Frequency Separation

Procedure:

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more) Sweep = auto

VBW = 10 kHz Detector function = peak

Trace = max hold

Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
1.043	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater.

Measurement Setup









Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency Separation



Number of Hopping Frequencies





3.2.3 20 dB Bandwidth

Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW \geq RBW)

Detector function = peak

Trace = max hold

dB/Div = 5dB

Measurement Data: Basic Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.945	0.915
2441	39	0.940	0.893
2480	78	0.935	0.900

- See next pages for actual measured spectrum plots.

Minimum Standard:


The EUT shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of 20dB bandwidth of the hopping channel, whichever is greater. Therefore, limit of 20dB bandwidth is 1.5MHz.

Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

Channel 0

20 dB Bandwidth



99% Bandwidth



3.2.4 Time of Occupancy (Dwell Time)

Procedure:

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW \geq RBW)

Trace = max hold

Detector function = peak

Measurement Data:

Channel Number	Channel Frequency (MHz)	Packet Type	Test Results		
			Duration Time (ms)	Dwell Time (ms)	Result
39	2441	Basic DH 1	0.5875	188.06	Complies
		Basic DH 3	1.8000	290.09	Complies
		Basic DH 5	3.0750	327.46	Complies

- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot) x duration time per channel} x 0.4 ms


Minimum Standard:

0.4 seconds within a 30 second period per any frequency


Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


DH1



DH3



DH5



3.2.5 Transmitter Output Power

Procedure:

The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 20 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW \geq RBW)

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data: Basic Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	W	Result
2402	0	2.14	0.0016	Complies
2441	39	1.88	0.0015	Complies
2480	78	1.48	0.0014	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:	< 250 mW
--------------------------	----------

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

3.2.6 Band Edge

Procedure:

The bandwidth at 20dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

VBW = 100 kHz

Span = 10 MHz

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


Minimum Standard:	> 20 dBc
--------------------------	----------

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


Band – edge

Lower edge



RL

Upper edge



RL

Band-edges in the restricted band 2483.5 ~ 2500 MHz measurement**- Document DA 00-705 Marker Delta Method**

Frequency (MHz)	Detect mode	Pol.	Reading (dBuV/m)	T.F (dB)	Step 1 Data	delta	Step 3 Data	Limit
2483.5	PK	V	101.5	1.1	102.6	60.25	42.35	74
	AV	V	89.33	1.1	90.43	60.25	30.18	54

Note) Step 1 = Reading + T.F

(T.F = Ant.F + Cable loss – PreAmp Gain)

Step 3 = Step 1 – Delta Value

3.2.7 Field Strength of Harmonics

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10th harmonic.

RBW = 100 kHz (30MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz

Trace = max hold

Peak:VBW \geq RBW

Average:VBW=10Hz

Detector function = Peak and Average

Sweep = auto

Measurement Data: Complies

- Refer to the next page.
- No other emissions were detected at a level greater than 10dB below limit.
- The three antennas were used with this EUT during the Testing.
- The used antenna is "R-AN2400-1901RS" and it gave the worse case emissions.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data:**1. PEAK data**

Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)
-	-	-	-	-	-
No emissions were detected at a level greater than 20dB below limit.					
-	-	-	-	-	-
-	-	-	-	-	-
Measurement uncertainty		± 6 dB			


2. AVERAGE data

Low channel		Mid channel		High channel	
Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)	Frequency (MHz)	Level (dBuV/m)
-	-	-	-	-	-
No emissions were detected at a level greater than 20dB below limit.					
-	-	-	-	-	-
-	-	-	-	-	-
Measurement uncertainty		± 6 dB			



243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: AT870 TEST MODE: Active Sync mode
Temp Humi : 11 / 30 Tested by: KIM.B.S




Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	117.41	-13.86	32.44	43.50	11.06	100	37	VERTICAL
2	121.35	-13.46	34.24	43.50	9.26	120	360	VERTICAL
3	133.52	-12.31	30.69	43.50	12.81	104	351	HORIZONTAL
4	208.21	-13.60	37.90	43.50	5.60	100	261	HORIZONTAL
5	230.62	-12.38	33.32	46.00	12.68	100	77	HORIZONTAL
6	439.31	-6.41	34.79	46.00	11.21	114	101	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: AT870 TEST MODE: GSM850 + WLAN + BT mode
Temp Humi : 5 / 24 Tested by: KIM.B.S



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	38.05	47.90	-14.55	33.35	40.00	6.65	153	165 VERTICAL
2	133.12	47.30	-12.35	34.95	43.50	8.55	100	292 VERTICAL
3	144.83	44.20	-11.63	32.57	43.50	10.93	100	343 HORIZONTAL
4	175.76	47.60	-12.62	34.98	43.50	8.52	110	360 VERTICAL
5	187.01	45.70	-13.35	32.35	43.50	11.15	106	66 VERTICAL
6	207.95	50.60	-13.61	36.99	43.50	6.51	117	94 HORIZONTAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: AT870 TEST MODE: GSM1900 + WLAN + BT mode

Temp Humi : 13 / 33 Tested by: KIM.B.S



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	133.32	47.60	-12.33	35.27	43.50	8.23	124	69 VERTICAL
2	140.02	47.90	-11.73	36.17	43.50	7.33	115	356 VERTICAL
3	145.83	46.80	-11.62	35.18	43.50	8.32	100	360 VERTICAL
4	166.80	47.20	-11.92	35.28	43.50	8.22	112	360 VERTICAL
5	177.67	47.50	-12.77	34.73	43.50	8.77	105	11 HORIZONTAL
6	208.52	51.10	-13.58	37.52	43.50	5.98	100	341 HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

3.2.8 AC Conducted Emissions

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: Complies

- See next pages for actual measured spectrum plots.
- No emissions were detected at a level greater than 10dB below limit.
- The used antenna is "R-AN2400-1901RS" and it gave the worse case emissions.

Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50


* Decreases with the logarithm of the frequency

AC Conducted Emissions – Line



243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-323-6008
Fax:+82-31-323-6010

EUT / Model No. : AT870	Phase : LINE
Test Mode : GSM850 + WLAN + BT mode	Test Power : 120 / 60
Temp./Humi. : 22 / 21	Test Engineer : B.S.KIM




Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – Neutral



243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-323-6008
Fax:+82-31-323-6010

EUT / Model No. : AT870 Phase : NEUTRAL
 Test Mode : GSM850 + WLAN + BT mode Test Power : 120 / 60
 Temp./Humi. : 22 / 21 Test Engineer : B.S.KIM



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.193	43.90	34.00	9.44	53.34	43.44	63.91	53.91	10.57	10.47
0.257	38.40	29.70	9.44	47.84	39.14	61.53	51.53	13.68	12.38
0.450	29.00	28.30	9.52	38.52	37.82	56.88	46.88	18.36	9.06
0.515	29.80	29.00	9.54	39.34	38.54	56.00	46.00	16.66	7.46
0.580	24.90	24.00	9.56	34.46	33.56	56.00	46.00	21.54	12.44
0.902	24.60	23.50	9.58	34.18	33.08	56.00	46.00	21.82	12.92


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – Line



243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-323-6008
Fax:+82-31-323-6010

EUT / Model No. : AT870 Phase : LINE
 Test Mode : GSM1900 + WLAN + BT mode Test Power : 120 / 60
 Temp./Humi. : 22 / 21 Test Engineer : B.S.KIM



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.192	44.20	34.10	9.43	53.63	43.53	63.95	53.95	10.32	10.42
0.256	38.50	29.60	9.45	47.95	39.05	61.56	51.56	13.62	12.52
0.451	29.10	28.30	9.53	38.63	37.83	56.86	46.86	18.23	9.03
0.515	29.70	29.00	9.54	39.24	38.54	56.00	46.00	16.76	7.46
0.580	25.30	24.40	9.56	34.86	33.96	56.00	46.00	21.14	12.04
3.943	28.70	27.80	9.68	38.38	37.48	56.00	46.00	17.62	8.52


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – Neutral



243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-323-6008
Fax:+82-31-323-6010

EUT / Model No. : AT870	Phase : NEUTRAL
Test Mode : GSM1900 + WLAN + BT mode	Test Power : 120 / 60
Temp./Humi. : 22 / 21	Test Engineer : B.S.KIM



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.193	44.50	34.40	9.44	53.94	43.84	63.91	53.91	9.97	10.07
0.258	38.70	30.30	9.44	48.14	39.74	61.50	51.50	13.35	11.75
0.451	30.00	29.40	9.52	39.52	38.92	56.86	46.86	17.34	7.94
0.515	28.90	28.20	9.54	38.44	37.74	56.00	46.00	17.56	8.26
2.966	24.70	23.00	9.69	34.39	32.69	56.00	46.00	21.61	13.31
3.934	27.00	26.30	9.68	36.68	35.98	56.00	46.00	19.32	10.02


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – Line



243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-323-6008
Fax:+82-31-323-6010

EUT / Model No. : AT870 Phase : LINE
 Test Mode : Active sync mode Test Power : 120 / 60
 Temp./Humi. : 22 / 21 Test Engineer : B.S.KIM



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.454	34.10	33.60	9.53	43.63	43.13	56.80	46.80	13.18	3.68
0.520	32.30	31.50	9.54	41.84	41.04	56.00	46.00	14.16	4.96
0.843	29.50	28.80	9.58	39.08	38.38	56.00	46.00	16.92	7.62
1.297	29.90	28.70	9.62	39.52	38.32	56.00	46.00	16.48	7.68
1.556	29.40	28.60	9.65	39.05	38.25	56.00	46.00	16.95	7.75
4.091	29.90	28.50	9.67	39.57	38.17	56.00	46.00	16.43	7.83


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

AC Conducted Emissions – Neutral



243 Jubug-ri, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-323-6008
Fax:+82-31-323-6010

EUT / Model No. :	AT870	Phase :	NEUTRAL
Test Mode :	Active sync mode	Test Power :	120 / 60
Temp./Humi. :	22 / 21	Test Engineer :	B.S.KIM



Freq MHz	RD		C.F	Result		Limit		Margin	
	QP dBuV	AV dBuV		QP dBuV	AV dBuV	QP dBuV	AV dBuV	QP dB	AV dB
0.451	33.40	32.90	9.52	42.92	42.42	56.86	46.86	13.94	4.44
0.518	32.80	32.00	9.54	42.34	41.54	56.00	46.00	13.66	4.46
2.265	29.60	28.50	9.70	39.30	38.20	56.00	46.00	16.70	7.80
2.652	30.40	28.50	9.69	40.09	38.19	56.00	46.00	15.91	7.81
3.362	29.70	28.40	9.68	39.38	38.08	56.00	46.00	16.62	7.92
3.949	33.00	30.00	9.68	42.68	39.68	56.00	46.00	13.32	6.32

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	8594E	3649A03649	HP	Apr-09
2	Signal Generator	8648C	3623A02597	HP	Apr-09
3	Attenuator (3dB)	8491A	37822	HP	Oct-09
4	Attenuator (10dB)	8491A	63196	HP	Oct-09
5	EMI Test Receiver	ESVD	843748/001	R&S	Aug-09
6	LISN	ENV216	100408	R&S	Oct-09
7	Two-Line V-Network	ESH3-Z5	893045/017	R&S	Oct-09
8	RF Amplifier	8447D	2944A07684	HP	Oct-09
9	RF Amplifier	8447D	2439A09058	HP	Oct-09
10	RF Amplifier	8449B	3008A02126	HP	Apr-09
11	Test Receiver	ESHS10	828404009	R&S	Aug-09
12	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Jul-09
13	Log.-Per. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-09
14	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-09
15	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-09
16	Dipole Antenna	VHA9103	2116	Schwarzbeck	Nov-09
17	Dipole Antenna	VHA9103	2117	Schwarzbeck	Nov-09
18	Dipole Antenna	UHA9105	2261	Schwarzbeck	Nov-09
19	Dipole Antenna	UHA9105	2262	Schwarzbeck	Nov-09
20	Spectrum Analyzer	8591E	3649A05888	HP	Oct-09
21	Spectrum Analyzer	8563E	3425A02505	HP	Apr-09
22	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Apr-09
23	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	Jun-09
24	RF Switch	MP59B	6200414971	ANRITSU	Jun-09
25	RF Switch	MP59B	6200438565	ANRITSU	Jun-09
26	Power Divider	11636A	6243	HP	Oct-09
27	DC Power Supply	6622A	3448A03079	HP	Oct-09
28	Attenuator (30dB)	11636A	6243	HP	Oct-09
29	Frequency Counter	5342A	2826A12411	HP	Apr-09
30	Power Meter	EPM-441A	GB32481702	HP	Apr-09
31	Power Sensor	8481A	2702A64048	HP	Apr-09
32	Audio Analyzer	8903B	3729A18901	HP	Oct-09
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-09
34	TEMP & HUMIDITY Chamber	YJ-500	L05022	JinYoung Tech	Oct-09
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-09
36	Stop Watch	HS-3	601Q09R	CASIO	Apr-09