

AT4 wireless, S.A.
Parque Tecnológico de Andalucía,
c/Severo Ochoa nº 2
29590 Campanillas/ Málaga/ España
Tel. 952 61 91 00 - Fax 952 61 91 13
MÁLAGA, C.I.F. A29 507 456
Registro Mercantil de Málaga, Tomo 1169
Libro 82 Folio 133 Hoja MA3729

ASSESSMENT REPORT

Report No.:
30751IDT.103

Rev. B



REPORT ON: RF EXPOSURE ASSESSMENT OF THE F3307 ERICSSON MOBILE BROADBAND MODULE INSTALLED IN GENERIC HOST PLATFORMS COVERING 7 DIFFERENT COLLOCATION SCENARIOS.

Product : Ericsson Mobile Broadband Module
Trade Mark : Ericsson
Model : F3307
FCC ID / IC: : VV7-MBMF33071 / 287AG-MBMF33071
Manufacturer : Ericsson AB
Requested by : Ericsson AB
Host Platform : Generic host platforms covering 7 different collocation scenarios

Standard(s) : OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR § 1.1307
FCC 47 CFR § 1.1310
RSS-102 Issue 4 - Marc 2010
EN 62311:2008 / 1999/519/EC
Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2003
ARPANSA RPS No. 3
AS 2772.2-1998:Radiofrequency radiation – Part 2
Vodafone requirements [1999/519/EC]

This test report includes 2 annexes and therefore, the total number of pages is 36.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless, S.A.

| | | | |
|------------------|--|--|---------------|
| Date: 2010-09-20 | Issued by: Date: 2010-09-20  Ricardo Orejas Worldwide Compliance Engineer | Approved by: Date: 2010-09-20  Juan Carlos Mora Technical Manager Laboratories Division | Page: 1 of 36 |
|------------------|--|--|---------------|

INDEX

| | |
|---|----|
| 1. COMPETENCE AND GUARANTEES | 3 |
| 2. GENERAL CONDITIONS | 3 |
| 3. CHARACTERISTICS OF THE EVALUATION | 3 |
| 3.1. SERVICES REQUESTED | 3 |
| 3.2. REQUIREMENTS AND METHOD..... | 4 |
| 4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT | 5 |
| 4.1. APPLICANT | 5 |
| 4.2. REPRESENTATIVE..... | 5 |
| 4.3. IDENTIFICATION OF ITEM/ITEMS EVALUATED..... | 5 |
| 5. EVALUATION RESULTS | 5 |
| 5.1. RESULTS FOR ITEM EVALUATED TRANSMITTING ALONE | 6 |
| 5.2. RESULTS FOR ITEM EVALUATED TRANSMITTING SIMULTANEOUSLY WITH OTHER COLLOCATED TRANSMITTERS | 6 |
| 6. REMARKS AND COMMENTS | 7 |
| 7. SUMMARY | 7 |
| | |
| ANNEXES | |
| A. HOST PLATFORM ANALYSIS..... | 8 |
| B. RF EXPOSURE ASSESSMENT..... | 23 |

1. COMPETENCE AND GUARANTEES

AT4 wireless is a testing laboratory competent to carry out the evaluation described in this report.

AT4 wireless guarantees the reliability of the data presented in this report, which is based on the information available at AT4 wireless at the time of performance of the evaluation.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under review and the results of such evaluation

2. GENERAL CONDITIONS

1. This report refers only to the item that has undergone the evaluation as described in Annex A of this report according to the information provided by the applicant.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

3. CHARACTERISTICS OF THE EVALUATION

3.1. SERVICES REQUESTED

RF exposure assessment of the F3307 Ericsson Mobile Broadband Module installed in generic host platforms covering 7 different collocation scenarios according to:

| Requirements | Frequency bands |
|--|----------------------------------|
| <p>OET Bulletin 65 Edition 97-01 August 1997 - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields</p> <p>FCC 47 CFR § 1.1307 - Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.</p> <p>FCC 47 CFR § 1.1310 - Radiofrequency radiation exposure limits.</p> <p>RSS-102 Issue 4 - March 2010</p> | GSM 850, FDD V, PCS 1900, FDD II |
| <p>EN 62311:2008 - Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)</p> <p>1999/519/EC Council Recommendation on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)</p> | E-GSM 900, DCS 1800 |

| | | |
|--|--|----------------------|
| <p>Report No.: 30751IDT.103 Rev. B</p> <p>Date: 2010-09-20</p> | | <p>Page: 3 of 36</p> |
|--|--|----------------------|

| | |
|---|---|
| <p>Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2003</p> <p>ARPANSA RPS No. 3 – Maximum Exposure Levels to Radiofrequency Fields (3 kHz to 300 GHz)</p> <p>AS 2772.2-1998: Radiofrequency radiation - Part 2: Principles and methods of measurement - 300 kHz to 100 GHz</p> | FDD V, E-GSM 900, DCS 1800 |
| Vodafone requirements [1999/519/EC] | GSM 850, FDD V, E-GSM 900, DCS 1800, PCS 1900, FDD II |

3.2. REQUIREMENTS AND METHOD

The evaluation has been carried out according to the following documents and standards:

| Requirements | Frequency bands |
|--|---|
| <p>OET Bulletin 65 Edition 97-01 August 1997 - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields</p> <p>FCC 47 CFR § 1.1307 - Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.</p> <p>FCC 47 CFR § 1.1310 - Radiofrequency radiation exposure limits.</p> <p>RSS-102 Issue 4 - March 2010</p> | GSM 850, FDD V, PCS 1900, FDD II |
| <p>EN 62311:2008 - Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)</p> <p>1999/519/EC Council Recommendation on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)</p> | E-GSM 900, DCS 1800 |
| <p>Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2003</p> <p>ARPANSA RPS No. 3 – Maximum Exposure Levels to Radiofrequency Fields (3 kHz to 300 GHz)</p> <p>AS 2772.2-1998: Radiofrequency radiation - Part 2: Principles and methods of measurement - 300 kHz to 100 GHz</p> | FDD V, E-GSM 900, DCS 1800 |
| Vodafone requirements [1999/519/EC] | GSM 850, FDD V, E-GSM 900, DCS 1800, PCS 1900, FDD II |

| | | |
|--|--|---------------|
| <p>Report No.: 30751IDT.103 Rev. B</p> <p>Date: 2010-09-20</p> | | Page: 4 of 36 |
|--|--|---------------|

4. IDENTIFICATION DATA SUPPLIED BY THE APPLICANT

Identification data included in this section has been supplied by the client.

4.1. APPLICANT

Name / Company: Ericsson AB

V.A.T. Registration number: SE 556056625801

Address: Lindholmspiren 11, SE-417 56 Goteborg

Country: Sweden

Telephone: +46 10 712 0000

Fax: +46 10 712 6033

4.2. REPRESENTATIVE

Name: Jonas Rinman

Address: Lindholmspiren 11, SE-417 56 Goteborg

Country: Sweden

Telephone: +46 10 712 0000

Fax: +46 10 712 6033

4.3. IDENTIFICATION OF ITEM/ITEMS EVALUATED

Product: Ericsson Mobile Broadband Module

Trade mark: Ericsson **Model:** F3307

FCC ID: VV7-MBMF33071

IC: 287AG-MBMF33071

Manufacturer: Ericsson AB

Country of manufacture: China

Host platform: Generic host platforms covering 7 different collocation scenarios

Description: 2G (GSM/GPRS/EDGE Class 10: 850/900/1800/1900 MHz) and 3G (HSDPA/HSUPA/WCDMA Release 6: FDD II, FDD V) module installed in generic host platforms covering 7 different collocation scenarios.

5. EVALUATION RESULTS

Abbreviations used in the VERDICT column of the following tables are:

- C** Compliant with requirements
- NC** Not Compliant with requirements
- NA** Not Applicable
- NE** Not Evaluated

| | | |
|------------------------------------|--|---------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 5 of 36 |
| Date: 2010-09-20 | | |

5.1. RESULTS FOR ITEM EVALUATED TRANSMITTING ALONE

| DOCUMENT/STANDARD | VERDICT | | | |
|--|---------|---|----|----|
| | NA | C | NC | NE |
| <p>OET Bulletin 65 Edition 97-01 August 1997 - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields</p> <p>FCC 47 CFR § 1.1307 - Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.</p> <p>FCC 47 CFR § 1.1310 - Radiofrequency radiation exposure limits.</p> <p>RSS-102 Issue 4 - March 2010</p> | | C | | |
| <p>EN 62311:2008 - Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)</p> <p>1999/519/EC Council Recommendation on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)</p> | | C | | |
| <p>Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2003</p> <p>ARPANSA RPS No. 3 – Maximum Exposure Levels to Radiofrequency Fields (3 kHz to 300 GHz)</p> <p>AS 2772.2-1998: Radiofrequency radiation - Part 2: Principles and methods of measurement - 300 kHz to 100 GHz</p> | | C | | |
| Vodafone requirements [1999/519/EC] | | C | | |

5.2. RESULTS FOR ITEM EVALUATED TRANSMITTING SIMULTANEOUSLY WITH OTHER COLLOCATED TRANSMITTERS

| DOCUMENT/STANDARD | VERDICT | | | |
|--|---------|---|----|----|
| | NA | C | NC | NE |
| <p>OET Bulletin 65 Edition 97-01 August 1997 - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields</p> <p>FCC 47 CFR § 1.1307 - Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.</p> <p>FCC 47 CFR § 1.1310 - Radiofrequency radiation exposure limits.</p> <p>RSS-102 Issue 4 - March 2010</p> | | C | | |
| <p>EN 62311:2008 - Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)</p> <p>1999/519/EC Council Recommendation on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)</p> | | C | | |

| | |
|--|---|
| Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2003 ARPANSA RPS No. 3 – Maximum Exposure Levels to Radiofrequency Fields (3 kHz to 300 GHz) AS 2772.2-1998: Radiofrequency radiation - Part 2: Principles and methods of measurement - 300 kHz to 100 GHz | C |
| Vodafone requirements [1999/519/EC] | C |

6. REMARKS AND COMMENTS

GSM and GPRS modes have been evaluated together because both modes share the same power class and modulation scheme in the uplink.

WCDMA and HSDPA modes have been evaluated together because HSDPA is an improved mode of operation only for Downlink (equipment reception), but using the normal WCDMA mode for the Uplink (equipment transmission).

The equipment is also commercialised under other FCC ID with the following structure:

FCC ID: VV7-MBMF33071-**X**

Where **X** is a letter identifying variants of the product.

Providing the changes in these variants do not affect to certified parameters, this report will be also applicable to them.

7. SUMMARY

Considering the results of the performed analysis and evaluation, stated in annexes A and B, the item under evaluation is **IN COMPLIANCE** with the specifications listed in section 3.1 “SERVICES REQUESTED”.

NOTE: The results presented in this report apply only to the particular item under evaluation established in section “4.3. IDENTIFICATION OF ITEM/ITEMS EVALUATED” of this document, as presented for evaluation by the applicant.

| | | |
|------------------------------------|--|---------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 7 of 36 |
| Date: 2010-09-20 | | |

ANNEX A

HOST PLATFORMS ANALYSIS

Report No: 30751IDT.103

Rev. B

| | |
|-----------------------|----|
| A.1. SCENARIO 1 | 9 |
| A.2. SCENARIO 2 | 11 |
| A.3. SCENARIO 3 | 13 |
| A.4. SCENARIO 4 | 15 |
| A.5. SCENARIO 5 | 17 |
| A.6. SCENARIO 6 | 19 |
| A.7. SCENARIO 7 | 21 |

A.1. SCENARIO 1

Scenario 1 covers a host device where the F3307 Ericsson Mobile Broadband Module is in mobile exposure conditions (antenna-to-user distance > 20 cm) and it is collocated with a Bluetooth transmitter (F3307 antenna-to-Bluetooth antenna distance < 20 cm) which is also in mobile exposure conditions. Other transmitters may be installed in the same host platform but they are not collocated with F3307 Ericsson Mobile Broadband Module.

MAIN/PRIMARY TRANSMITTER:

WWAN transmitter:

Type of equipment : Ericsson Mobile Broadband Module
 Trade mark : Ericsson
 Model : F3307
 FCC ID / IC : VV7-MBMF33071 / 287AG-MBMF33071
 Maximum antenna gain : Low bands: 2.70 dBi // High bands: 2.90 dBi
 Output power : See table below

| Frequency Band | Mode | Frequency range (MHz) | Maximum conducted output power (dBm) | Maximum conducted output power (mW) | Duty Cycle | Equivalent conducted output power (mW) | Maximum antenna gain (dBi) | Maximum antenna gain (numerical) | EIRP (mW) |
|----------------|-------------|-----------------------|--------------------------------------|-------------------------------------|------------|--|----------------------------|----------------------------------|-----------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| | EDGE | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 28,16 | 654,64 | 100% | 654,64 | 2,70 | 1,86 | 1218,99 |
| | HSUPA | 826,4 - 846,6 | 27,98 | 628,06 | 100% | 628,06 | 2,70 | 1,86 | 1169,50 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 32,60 | 1819,70 | 25% | 454,93 | 2,70 | 1,86 | 847,11 |
| | EDGE | 880,2 - 914,8 | 27,90 | 616,60 | 25% | 154,15 | 2,70 | 1,86 | 287,04 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 29,80 | 954,99 | 25% | 238,75 | 2,90 | 1,95 | 465,52 |
| | EDGE | 1710,2 - 1784,8 | 27,10 | 512,86 | 25% | 128,22 | 2,90 | 1,95 | 250,00 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 30,11 | 1025,65 | 25% | 256,41 | 2,90 | 1,95 | 499,97 |
| | EDGE | 1850,2 - 1909,8 | 30,09 | 1020,94 | 25% | 255,23 | 2,90 | 1,95 | 497,67 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 28,10 | 645,65 | 100% | 645,65 | 2,90 | 1,95 | 1258,93 |
| | HSUPA | 1852,4 - 1907,6 | 28,30 | 676,08 | 100% | 676,08 | 2,90 | 1,95 | 1318,26 |

ADDITIONAL/SECONDARY TRANSMITTERS:

Bluetooth transmitter:

Type of equipment : Bluetooth¹
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below

| Scenario 1 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| Bluetooth | 100 | 76% | 76,43 |


¹ It could be also Bluetooth + UWB transmitter)
 UWB contribution does not need to be considered.

| | | |
|------------------------------------|--|---------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 9 of 36 |
| Date: 2010-09-20 | | Annex A |

WORST CASE CONSIDERATIONS:

- Antenna-to-user distance: 20 cm.
 - o Any antenna-to-user distance > 20 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- F3307 antenna gains: Low bands: 2.70 dBi // High bands: 2.90 dBi
 - o Any antenna gains below the specified would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Bluetooth EIRP: 100 mW
 - o Any Bluetooth (or Bluetooth + UWB) transmitter with EIRP below 100 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Antenna-to-antenna distances: 0 cm
 - o Any antenna-to-antenna distance > 0 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.

SAMPLE CONFIGURATION:



| | | |
|--|--|-------------------------------|
| Report No.: 30751IDT.103 Rev. B Date: 2010-09-20 | | Page: 10 of 36 Annex A |
|--|--|-------------------------------|

A.2. SCENARIO 2

Scenario 2 covers a host device where the F3307 Ericsson Mobile Broadband Module is in mobile exposure conditions (antenna-to-user distance > 20 cm) and it is collocated with a WLAN transmitter (F3307 antenna-to-WLAN antenna distance < 20 cm) which is also in mobile exposure conditions.

WLAN transmitter may have other antennas in portable exposure conditions but they are not collocated with F3307 Ericsson Mobile Broadband Module antenna.

Other transmitters may be installed in the same host platform but they are not collocated with F3307 Ericsson Mobile Broadband Module.

MAIN/PRIMARY TRANSMITTER:

WWAN transmitter:

Type of equipment : Ericsson Mobile Broadband Module
 Trade mark : Ericsson
 Model : F3307
 FCC ID / IC : VV7-MBMF33071 / 287AG-MBMF33071
 Maximum antenna gain : Low bands: 2.70 dBi // High bands: 2.90 dBi
 Output power : See table below

| Frequency Band | Mode | Frequency range (MHz) | Maximum conducted output power (dBm) | Maximum conducted output power (mW) | Duty Cycle | Equivalent conducted output power (mW) | Maximum antenna gain (dBi) | Maximum antenna gain (numerical) | EIRP (mW) |
|----------------|-------------|-----------------------|--------------------------------------|-------------------------------------|------------|--|----------------------------|----------------------------------|-----------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| | EDGE | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 28,16 | 654,64 | 100% | 654,64 | 2,70 | 1,86 | 1218,99 |
| | HSUPA | 826,4 - 846,6 | 27,98 | 628,06 | 100% | 628,06 | 2,70 | 1,86 | 1169,50 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 32,60 | 1819,70 | 25% | 454,93 | 2,70 | 1,86 | 847,11 |
| | EDGE | 880,2 - 914,8 | 27,90 | 616,60 | 25% | 154,15 | 2,70 | 1,86 | 287,04 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 29,80 | 954,99 | 25% | 238,75 | 2,90 | 1,95 | 465,52 |
| | EDGE | 1710,2 - 1784,8 | 27,10 | 512,86 | 25% | 128,22 | 2,90 | 1,95 | 250,00 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 30,11 | 1025,65 | 25% | 256,41 | 2,90 | 1,95 | 499,97 |
| | EDGE | 1850,2 - 1909,8 | 30,09 | 1020,94 | 25% | 255,23 | 2,90 | 1,95 | 497,67 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 28,10 | 645,65 | 100% | 645,65 | 2,90 | 1,95 | 1258,93 |
| | HSUPA | 1852,4 - 1907,6 | 28,30 | 676,08 | 100% | 676,08 | 2,90 | 1,95 | 1318,26 |

ADDITIONAL/SECONDARY TRANSMITTERS:

WLAN transmitter:

Type of equipment : WLAN²
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below


| Scenario 3 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| WLAN | 2000 | 100% | 2000,00 |

² It could be also WLAN/WiMAX combo transmitter where WLAN and WiMAX transmitters do not transmit simultaneously.

WORST CASE CONSIDERATIONS:

- Antenna-to-user distance: 20 cm.
 - o Any antenna-to-user distance > 20 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- F3307 antenna gains: Low bands: 2.70 dBi // High bands: 2.90 dBi
 - o Any antenna gains below the specified would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- WLAN EIRP: 2000 mW
 - o Any WLAN transmitter with EIRP below 2000 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Antenna-to-antenna distances: 0 cm
 - o Any antenna-to-antenna distance > 0 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.

SAMPLE CONFIGURATION:



| | | |
|--|--|-------------------------------|
| Report No.: 30751IDT.103 Rev. B Date: 2010-09-20 | | Page: 12 of 36 Annex A |
|--|--|-------------------------------|

A.3. SCENARIO 3

Scenario 3 covers a host device where the F3307 Ericsson Mobile Broadband Module is in mobile exposure conditions (antenna-to-user distance > 20 cm) and it is collocated with a WLAN transmitter and a Bluetooth transmitter (F3307 antenna-to-WLAN/Bluetooth antenna distance < 20 cm) which are also in mobile exposure conditions.

WLAN transmitter may have other antennas in portable exposure conditions but they are not collocated with F3307 Ericsson Mobile Broadband Module antenna.

Other transmitters may be installed in the same host platform but they are not collocated with F3307 Ericsson Mobile Broadband Module.

MAIN/PRIMARY TRANSMITTER:

WWAN transmitter:

Type of equipment : Ericsson Mobile Broadband Module
 Trade mark : Ericsson
 Model : F3307
 FCC ID / IC : VV7-MBMF33071 / 287AG-MBMF33071
 Maximum antenna gain : Low bands: 2.70 dBi // High bands: 2.90 dBi
 Output power : See table below

| Frequency Band | Mode | Frequency range (MHz) | Maximum conducted output power (dBm) | Maximum conducted output power (mW) | Duty Cycle | Equivalent conducted output power (mW) | Maximum antenna gain (dBi) | Maximum antenna gain (numerical) | EIRP (mW) |
|----------------|-------------|-----------------------|--------------------------------------|-------------------------------------|------------|--|----------------------------|----------------------------------|-----------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| | EDGE | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 28,16 | 654,64 | 100% | 654,64 | 2,70 | 1,86 | 1218,99 |
| | HSUPA | 826,4 - 846,6 | 27,98 | 628,06 | 100% | 628,06 | 2,70 | 1,86 | 1169,50 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 32,60 | 1819,70 | 25% | 454,93 | 2,70 | 1,86 | 847,11 |
| | EDGE | 880,2 - 914,8 | 27,90 | 616,60 | 25% | 154,15 | 2,70 | 1,86 | 287,04 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 29,80 | 954,99 | 25% | 238,75 | 2,90 | 1,95 | 465,52 |
| | EDGE | 1710,2 - 1784,8 | 27,10 | 512,86 | 25% | 128,22 | 2,90 | 1,95 | 250,00 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 30,11 | 1025,65 | 25% | 256,41 | 2,90 | 1,95 | 499,97 |
| | EDGE | 1850,2 - 1909,8 | 30,09 | 1020,94 | 25% | 255,23 | 2,90 | 1,95 | 497,67 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 28,10 | 645,65 | 100% | 645,65 | 2,90 | 1,95 | 1258,93 |
| | HSUPA | 1852,4 - 1907,6 | 28,30 | 676,08 | 100% | 676,08 | 2,90 | 1,95 | 1318,26 |

ADDITIONAL/SECONDARY TRANSMITTERS:

WLAN transmitter:

Type of equipment : WLAN³
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below

| Scenario 3 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| WLAN | 2000 | 100% | 2000,00 |

³ It could be also WLAN/WiMAX combo transmitter where WLAN and WiMAX transmitters do not transmit simultaneously.

Bluetooth transmitter:

Type of equipment : Bluetooth⁴
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below


| Scenario 3 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| Bluetooth | 100 | 76% | 76,43 |

⁴ It could be also Bluetooth + UWB transmitter)
 UWB contribution does not need to be considered.

WORST CASE CONSIDERATIONS:

- Antenna-to-user distance: 20 cm.
 - o Any antenna-to-user distance > 20 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- F3307 antenna gains: Low bands: 2.70 dBi // High bands: 2.90 dBi
 - o Any antenna gains below the specified would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- WLAN EIRP: 2000 mW
 - o Any WLAN transmitter with EIRP below 2000 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Bluetooth EIRP: 100 mW
 - o Any Bluetooth (or Bluetooth + UWB) transmitter with EIRP below 100 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Antenna-to-antenna distances: 0 cm
 - o Any antenna-to-antenna distance > 0 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.

SAMPLE CONFIGURATION:



| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 14 of 36 |
| Date: 2010-09-20 | | Annex A |

A.4. SCENARIO 4

Scenario 4 covers a host device where the F3307 Ericsson Mobile Broadband Module is in mobile exposure conditions (antenna-to-user distance > 20 cm) and it is collocated with a WiMAX transmitter (F3307 antenna-to-WiMAX antenna distance < 20 cm) which is also in mobile exposure conditions.

WiMAX transmitter may have other antennas in portable exposure conditions but they are not collocated with F3307 Ericsson Mobile Broadband Module antenna.

Other transmitters may be installed in the same host platform but they are not collocated with F3307 Ericsson Mobile Broadband Module.

MAIN/PRIMARY TRANSMITTER:

WWAN transmitter:

Type of equipment : Ericsson Mobile Broadband Module
 Trade mark : Ericsson
 Model : F3307
 FCC ID / IC : VV7-MBMF33071 / 287AG-MBMF33071
 Maximum antenna gain : Low bands: 2.70 dBi // High bands: 2.90 dBi
 Output power : See table below

| Frequency Band | Mode | Frequency range (MHz) | Maximum conducted output power (dBm) | Maximum conducted output power (mW) | Duty Cycle | Equivalent conducted output power (mW) | Maximum antenna gain (dBi) | Maximum antenna gain (numerical) | EIRP (mW) |
|----------------|-------------|-----------------------|--------------------------------------|-------------------------------------|------------|--|----------------------------|----------------------------------|-----------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| | EDGE | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 28,16 | 654,64 | 100% | 654,64 | 2,70 | 1,86 | 1218,99 |
| | HSUPA | 826,4 - 846,6 | 27,98 | 628,06 | 100% | 628,06 | 2,70 | 1,86 | 1169,50 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 32,60 | 1819,70 | 25% | 454,93 | 2,70 | 1,86 | 847,11 |
| | EDGE | 880,2 - 914,8 | 27,90 | 616,60 | 25% | 154,15 | 2,70 | 1,86 | 287,04 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 29,80 | 954,99 | 25% | 238,75 | 2,90 | 1,95 | 465,52 |
| | EDGE | 1710,2 - 1784,8 | 27,10 | 512,86 | 25% | 128,22 | 2,90 | 1,95 | 250,00 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 30,11 | 1025,65 | 25% | 256,41 | 2,90 | 1,95 | 499,97 |
| | EDGE | 1850,2 - 1909,8 | 30,09 | 1020,94 | 25% | 255,23 | 2,90 | 1,95 | 497,67 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 28,10 | 645,65 | 100% | 645,65 | 2,90 | 1,95 | 1258,93 |
| | HSUPA | 1852,4 - 1907,6 | 28,30 | 676,08 | 100% | 676,08 | 2,90 | 1,95 | 1318,26 |

ADDITIONAL/SECONDARY TRANSMITTERS:

WiMAX transmitter:

Type of equipment : WiMAX⁵
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below


| Scenario 4 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| WiMAX | 2000 | 100% | 2000,00 |

⁵ It could be also WLAN/WiMAX combo transmitter where WLAN and WiMAX transmitters do not transmit simultaneously.

WORST CASE CONSIDERATIONS:

- Antenna-to-user distance: 20 cm.
 - o Any antenna-to-user distance > 20 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- F3307 antenna gains: Low bands: 2.70 dBi // High bands: 2.90 dBi
 - o Any antenna gains below the specified would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- WiMAX EIRP: 2000 mW
 - o Any WiMAX transmitter with EIRP below 2000 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Antenna-to-antenna distances: 0 cm
 - o Any antenna-to-antenna distance > 0 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.

SAMPLE CONFIGURATION:



| | | |
|--|--|-------------------------------|
| Report No.: 30751IDT.103 Rev. B Date: 2010-09-20 | | Page: 16 of 36 Annex A |
|--|--|-------------------------------|

A.5. SCENARIO 5

Scenario 5 covers a host device where the F3307 Ericsson Mobile Broadband Module is in mobile exposure conditions (antenna-to-user distance > 20 cm) and it is collocated with a WiMAX transmitter and a Bluetooth transmitter (F3307 antenna-to-WiMAX/Bluetooth antenna distance < 20 cm) which are also in mobile exposure conditions.

WiMAX transmitter may have other antennas in portable exposure conditions but they are not collocated with F3307 Ericsson Mobile Broadband Module antenna.

Other transmitters may be installed in the same host platform but they are not collocated with F3307 Ericsson Mobile Broadband Module.

MAIN/PRIMARY TRANSMITTER:

WWAN transmitter:

Type of equipment : Ericsson Mobile Broadband Module
 Trade mark : Ericsson
 Model : F3307
 FCC ID / IC : VV7-MBMF33071 / 287AG-MBMF33071
 Maximum antenna gain : Low bands: 2.70 dBi // High bands: 2.90 dBi
 Output power : See table below

| Frequency Band | Mode | Frequency range (MHz) | Maximum conducted output power (dBm) | Maximum conducted output power (mW) | Duty Cycle | Equivalent conducted output power (mW) | Maximum antenna gain (dBi) | Maximum antenna gain (numerical) | EIRP (mW) |
|----------------|-------------|-----------------------|--------------------------------------|-------------------------------------|------------|--|----------------------------|----------------------------------|-----------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| | EDGE | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 28,16 | 654,64 | 100% | 654,64 | 2,70 | 1,86 | 1218,99 |
| | HSUPA | 826,4 - 846,6 | 27,98 | 628,06 | 100% | 628,06 | 2,70 | 1,86 | 1169,50 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 32,60 | 1819,70 | 25% | 454,93 | 2,70 | 1,86 | 847,11 |
| | EDGE | 880,2 - 914,8 | 27,90 | 616,60 | 25% | 154,15 | 2,70 | 1,86 | 287,04 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 29,80 | 954,99 | 25% | 238,75 | 2,90 | 1,95 | 465,52 |
| | EDGE | 1710,2 - 1784,8 | 27,10 | 512,86 | 25% | 128,22 | 2,90 | 1,95 | 250,00 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 30,11 | 1025,65 | 25% | 256,41 | 2,90 | 1,95 | 499,97 |
| | EDGE | 1850,2 - 1909,8 | 30,09 | 1020,94 | 25% | 255,23 | 2,90 | 1,95 | 497,67 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 28,10 | 645,65 | 100% | 645,65 | 2,90 | 1,95 | 1258,93 |
| | HSUPA | 1852,4 - 1907,6 | 28,30 | 676,08 | 100% | 676,08 | 2,90 | 1,95 | 1318,26 |

ADDITIONAL/SECONDARY TRANSMITTERS:

WiMAX transmitter:

Type of equipment : WiMAX⁶
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below

| Scenario 5 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| WiMAX | 2000 | 100% | 2000,00 |

⁶ It could be also WLAN/WiMAX combo transmitter where WLAN and WiMAX transmitters do not transmit simultaneously.

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 17 of 36 |
| Date: 2010-09-20 | | Annex A |

Bluetooth transmitter:

Type of equipment : Bluetooth⁷
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below


| Scenario 5 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| Bluetooth | 100 | 76% | 76,43 |

⁷ It could be also Bluetooth + UWB transmitter)
 UWB contribution does not need to be considered.

WORST CASE CONSIDERATIONS:

- Antenna-to-user distance: 20 cm.
 - o Any antenna-to-user distance > 20 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- F3307 antenna gains: Low bands: 2.70 dBi // High bands: 2.90 dBi
 - o Any antenna gains below the specified would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- WiMAX EIRP: 2000 mW
 - o Any WiMAX transmitter with EIRP below 2000 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Bluetooth EIRP: 100 mW
 - o Any Bluetooth (or Bluetooth + UWB) transmitter with EIRP below 100 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Antenna-to-antenna distances: 0 cm
 - o Any antenna-to-antenna distance > 0 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.

SAMPLE CONFIGURATION:



| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 18 of 36 |
| Date: 2010-09-20 | | Annex A |

A.6. SCENARIO 6

Scenario 6 covers a host device where the F3307 Ericsson Mobile Broadband Module is in mobile exposure conditions (antenna-to-user distance > 20 cm) and it is collocated with a WLAN transmitter and a WiMAX transmitter (F3307 antenna-to-WLAN/WiMAX antenna distance < 20 cm) which are also in mobile exposure conditions.

WLAN/WiMAX transmitters may have other antennas in portable exposure conditions but they are not collocated with F3307 Ericsson Mobile Broadband Module antenna.

Other transmitters may be installed in the same host platform but they are not collocated with F3307 Ericsson Mobile Broadband Module.

MAIN/PRIMARY TRANSMITTER:

WWAN transmitter:

Type of equipment : Ericsson Mobile Broadband Module
 Trade mark : Ericsson
 Model : F3307
 FCC ID / IC : VV7-MBMF33071 / 287AG-MBMF33071
 Maximum antenna gain : Low bands: 2.70 dBi // High bands: 2.90 dBi
 Output power : See table below

| Frequency Band | Mode | Frequency range (MHz) | Maximum conducted output power (dBm) | Maximum conducted output power (mW) | Duty Cycle | Equivalent conducted output power (mW) | Maximum antenna gain (dBi) | Maximum antenna gain (numerical) | EIRP (mW) |
|----------------|-------------|-----------------------|--------------------------------------|-------------------------------------|------------|--|----------------------------|----------------------------------|-----------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| | EDGE | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 28,16 | 654,64 | 100% | 654,64 | 2,70 | 1,86 | 1218,99 |
| | HSUPA | 826,4 - 846,6 | 27,98 | 628,06 | 100% | 628,06 | 2,70 | 1,86 | 1169,50 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 32,60 | 1819,70 | 25% | 454,93 | 2,70 | 1,86 | 847,11 |
| | EDGE | 880,2 - 914,8 | 27,90 | 616,60 | 25% | 154,15 | 2,70 | 1,86 | 287,04 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 29,80 | 954,99 | 25% | 238,75 | 2,90 | 1,95 | 465,52 |
| | EDGE | 1710,2 - 1784,8 | 27,10 | 512,86 | 25% | 128,22 | 2,90 | 1,95 | 250,00 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 30,11 | 1025,65 | 25% | 256,41 | 2,90 | 1,95 | 499,97 |
| | EDGE | 1850,2 - 1909,8 | 30,09 | 1020,94 | 25% | 255,23 | 2,90 | 1,95 | 497,67 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 28,10 | 645,65 | 100% | 645,65 | 2,90 | 1,95 | 1258,93 |
| | HSUPA | 1852,4 - 1907,6 | 28,30 | 676,08 | 100% | 676,08 | 2,90 | 1,95 | 1318,26 |

ADDITIONAL/SECONDARY TRANSMITTERS:

WLAN/WiMAX transmitter:

Type of equipment : WLAN / WiMAX
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below

| Scenario 6 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| WLAN / WiMAX | 2000 ⁸ | 100% | 2000,00 |


⁸ Aggregated EIRP of WLAN and WiMAX transmitters

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 19 of 36 |
| Date: 2010-09-20 | | Annex A |

WORST CASE CONSIDERATIONS:

- Antenna-to-user distance: 20 cm.
 - o Any antenna-to-user distance > 20 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- F3307 antenna gains: Low bands: 2.70 dBi // High bands: 2.90 dBi
 - o Any antenna gains below the specified would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- WLAN EIRP + WiMAX EIRP: 2000 mW
 - o Any WLAN transmitter and WiMAX transmitters with aggregated EIRP below 2000 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Antenna-to-antenna distances: 0 cm
 - o Any antenna-to-antenna distance > 0 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.

SAMPLE CONFIGURATION:



| | | |
|--|--|-------------------------------|
| Report No.: 30751IDT.103 Rev. B Date: 2010-09-20 | | Page: 20 of 36 Annex A |
|--|--|-------------------------------|

A.7. SCENARIO 7

Scenario 6 covers a host device where the F3307 Ericsson Mobile Broadband Module is in mobile exposure conditions (antenna-to-user distance > 20 cm) and it is collocated with a WLAN transmitter a WiMAX transmitter and a Bluetooth transmitter (F3307 antenna-to-WLAN/WiMAX/Bluetooth antenna distance < 20 cm) which are also in mobile exposure conditions.

WLAN/WiMAX transmitters may have other antennas in portable exposure conditions but they are not collocated with F3307 Ericsson Mobile Broadband Module antenna.

Other transmitters may be installed in the same host platform but they are not collocated with F3307 Ericsson Mobile Broadband Module.

MAIN/PRIMARY TRANSMITTER:

WWAN transmitter:

Type of equipment : Ericsson Mobile Broadband Module
 Trade mark : Ericsson
 Model : F3307
 FCC ID / IC : VV7-MBMF33071 / 287AG-MBMF33071
 Maximum antenna gain : Low bands: 2.70 dBi // High bands: 2.90 dBi
 Output power : See table below

| Frequency Band | Mode | Frequency range (MHz) | Maximum conducted output power (dBm) | Maximum conducted output power (mW) | Duty Cycle | Equivalent conducted output power (mW) | Maximum antenna gain (dBi) | Maximum antenna gain (numerical) | EIRP (mW) |
|----------------|-------------|-----------------------|--------------------------------------|-------------------------------------|------------|--|----------------------------|----------------------------------|-----------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| | EDGE | 824,2 - 848,8 | 33,51 | 2243,88 | 25% | 560,97 | 2,70 | 1,86 | 1044,58 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 28,16 | 654,64 | 100% | 654,64 | 2,70 | 1,86 | 1218,99 |
| | HSUPA | 826,4 - 846,6 | 27,98 | 628,06 | 100% | 628,06 | 2,70 | 1,86 | 1169,50 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 32,60 | 1819,70 | 25% | 454,93 | 2,70 | 1,86 | 847,11 |
| | EDGE | 880,2 - 914,8 | 27,90 | 616,60 | 25% | 154,15 | 2,70 | 1,86 | 287,04 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 29,80 | 954,99 | 25% | 238,75 | 2,90 | 1,95 | 465,52 |
| | EDGE | 1710,2 - 1784,8 | 27,10 | 512,86 | 25% | 128,22 | 2,90 | 1,95 | 250,00 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 30,11 | 1025,65 | 25% | 256,41 | 2,90 | 1,95 | 499,97 |
| | EDGE | 1850,2 - 1909,8 | 30,09 | 1020,94 | 25% | 255,23 | 2,90 | 1,95 | 497,67 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 28,10 | 645,65 | 100% | 645,65 | 2,90 | 1,95 | 1258,93 |
| | HSUPA | 1852,4 - 1907,6 | 28,30 | 676,08 | 100% | 676,08 | 2,90 | 1,95 | 1318,26 |

ADDITIONAL/SECONDARY TRANSMITTERS:

WLAN/WiMAX transmitter:

Type of equipment : WLAN / WiMAX
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below

| Scenario 6 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| WLAN / WiMAX | 2000 ⁹ | 100% | 2000,00 |

⁹ Aggregated EIRP of WLAN and WiMAX transmitters

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 21 of 36 |
| Date: 2010-09-20 | | Annex A |

Bluetooth transmitter:

Type of equipment : Bluetooth¹⁰
 Trade mark : Any
 Model : Any
 FCC ID / IC : Any
 Output power : See table below


| Scenario 5 | | | |
|---------------------|-------------------|------------|-----------|
| Type of transmitter | Maximum EIRP (mW) | Duty Cycle | EIRP (mW) |
| Bluetooth | 100 | 76% | 76,43 |

¹⁰ It could be also Bluetooth + UWB transmitter)
 UWB contribution does not need to be considered.

WORST CASE CONSIDERATIONS:

- Antenna-to-user distance: 20 cm.
 - o Any antenna-to-user distance > 20 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- F3307 antenna gains: Low bands: 2.70 dBi // High bands: 2.90 dBi
 - o Any antenna gains below the specified would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- WLAN EIRP + WiMAX EIRP: 2000 mW
 - o Any WLAN transmitter and WiMAX transmitters with aggregated EIRP below 2000 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Bluetooth EIRP: 100 mW
 - o Any Bluetooth (or Bluetooth + UWB) transmitter with EIRP below 100 mW would be covered by the analysis included in this report as far as it would provide better exposure conditions.
- Antenna-to-antenna distances: 0 cm
 - o Any antenna-to-antenna distance > 0 cm would be covered by the analysis included in this report as far as it would provide better exposure conditions.

SAMPLE CONFIGURATION:



| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 22 of 36 |
| Date: 2010-09-20 | | Annex A |

ANNEX B

RF EXPOSURE ASSESSMENT

Report No: 30751IDT.103

Rev. B

| | |
|--|----|
| B.1. MAXIMUM PERMISSIBLE EXPOSURE (MPE) LIMITS..... | 24 |
| B.1.1. FCC / IC LIMITS | 24 |
| B.1.2. EUROPEAN UNION MPE LIMITS | 25 |
| B.1.3. AUSTRALIA MPE LIMITS..... | 25 |
| B.1.4. VODAFONE MPE LIMITS | 26 |
| B.2. RF EXPOSURE ASSESSMENT – INDIVIDUAL TRANSMITTERS..... | 27 |
| B.2.1. INTRODUCTION..... | 27 |
| B.2.2. RF EXPOSURE ASSESSMENT FOR F3307 ERICSSON MOBILE BROADBAND MODULE INSTALLED IN GENERIC HOST PLATFORMS | 28 |
| B.2.3. RF EXPOSURE ASSESSMENT FOR SECONDARY TRANSMITTERS INSTALLED IN GENERIC HOST PLATFORMS ... | 29 |
| B.3. RF EXPOSURE ASSESSMENT – COLLOCATION CONSIDERATIONS.. | 30 |
| B.3.1. INTRODUCTION..... | 30 |
| B.3.2. FCC / IC REQUIREMENTS | 30 |
| B.3.3. EUROPEAN UNION REQUIREMENTS..... | 32 |
| B.3.4. AUSTRALIA REQUIREMENTS | 33 |
| B.3.5. VODAFONE REQUIREMENTS | 35 |

| | | |
|------------------------------------|--|---------------|
| Report No.: 30751IDT.103 Rev. B | | Page 23 of 36 |
| Date: 2010-09-20 | | Annex B |

B.1. MAXIMUM PERMISSIBLE EXPOSURE (MPE) LIMITS

B.1.1. FCC / IC LIMITS

Normative documents:

- OET Bulletin 65 Edition 97-01 August 1997 - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields
- FCC 47 CFR § 1.1307 - Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
- FCC 47 CFR § 1.1310 - Radiofrequency radiation exposure limits.1999/519/EC Council Recommendation on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)
- RSS-102 Issue 4 – March 2010

Reference levels:

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure:

| Frequency Range (MHz) | Power density ($\frac{mW}{cm^2}$) | Averaging time (minutes) |
|-----------------------|-------------------------------------|--------------------------|
| 300 – 1500 | $\frac{f(MHz)}{1500}$ | 30 |
| 1500 – 100.000 | 1.0 | 30 |

The table below is excerpted from item 4.2 of RSS-102 Issue 4, titled RF Field Strength Limits for Devices Used by the General Public:

| Frequency Range (MHz) | Power density ($\frac{W}{m^2}$) | Averaging time (minutes) |
|-----------------------|-----------------------------------|--------------------------|
| 300 – 1500 | $f(MHz) / 150$ | 6 |
| 1500 – 100.000 | 10 | 6 |

MPE limits:

- Main/Primary transmitter (F3307 Ericsson Mobile Broadband Module):

| Frequency Band | Mode | Frequency Range (MHz) | Reference frequency (MHz) | MPE limit (S_{eq}) ($\frac{mW}{cm^2}$) |
|----------------|-------------|-----------------------|---------------------------|--|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 824,20 | 0,5495 |
| | EDGE | 824,2 - 848,8 | 824,20 | 0,5495 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 826,40 | 0,5509 |
| | HSUPA | 826,4 - 846,6 | 826,40 | 0,5509 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 1850,20 | 1,0000 |
| | EDGE | 1850,2 - 1909,8 | 1850,20 | 1,0000 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 1852,40 | 1,0000 |
| | HSUPA | 1852,4 - 1907,6 | 1852,40 | 1,0000 |

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 24 of 36 |
| Date: 2010-09-20 | | Annex B |

- Additional/Secondary transmitters: All the transmission frequencies for collocated transmitter modules are above 1.5 GHz, so that the MPE limit is 1 mW/cm².

B.1.2. EUROPEAN UNION MPE LIMITS

Normative document:

- EN 62311:2008 - Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)
- 1999/519/EC Council Recommendation on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)

Reference levels:

The table below is excerpted from Table 2 of 1999/519/EC, titled “Reference levels for electric, magnetic and electromagnetic fields (0 Hz to 300 GHz, unperturbed rms values)”:

| Frequency range | E-field strength ($\frac{V}{m}$) | H-field strength ($\frac{A}{m}$) | B-field (μT) | Equivalent plane wave power density S_{eq} ($\frac{W}{m^2}$) |
|-----------------|---------------------------------------|---------------------------------------|-----------------------------|---|
| 400 - 2000 MHz | $1,375 \cdot f(MHz)^{1/2}$ | $0,0037 \cdot f(MHz)^{1/2}$ | $0,0046 \cdot f(MHz)^{1/2}$ | $\frac{f(MHz)}{200}$ |
| 2 - 300 GHz | 61 | 0,16 | 0,2 | 10 |

MPE limits:

- Main/Primary transmitter (F3307 Ericsson Mobile Broadband Module):

| Frequency Band | Mode | Frequency Range (MHz) | Reference frequency (MHz) | MPE limit (S_{eq}) ($\frac{mW}{cm^2}$) |
|----------------|----------|-----------------------|---------------------------|---|
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 880,20 | 0,4401 |
| | EDGE | 880,2 - 914,8 | 880,20 | 0,4401 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 1710,20 | 0,8551 |
| | EDGE | 1710,2 - 1784,8 | 1710,20 | 0,8551 |

- Additional/Secondary transmitters: All the transmission frequencies for collocated transmitter modules are above 2 GHz, so that the MPE limit is 1 mW/cm².

B.1.3. AUSTRALIA MPE LIMITS

Normative documents:

- Radiocommunications (Electromagnetic Radiation – Human Exposure) Standard 2003
- ARPANSA RPS No. 3 – Maximum Exposure Levels to Radiofrequency Fields (3 kHz to 300 GHz)

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 25 of 36 |
| Date: 2010-09-20 | | Annex B |

- AS 2772.2-1998: Radiofrequency radiation - Part 2: Principles and methods of measurement - 300 kHz to 100 GHz

Reference levels:

The table below is excerpted from Table 7 of ARPANSA RPS No. 3, titled “Reference levels for time averaged exposure to RMS electric and magnetic fields (unperturbed rms values)”:

| Exposure category | Frequency range | E-field strength $\left(\frac{V}{m} \text{ rms}\right)$ | H-field strength $\left(\frac{A}{m} \text{ rms}\right)$ | Equivalent plane wave power density S_{eq} $\left(\frac{W}{m^2}\right)$ | Equivalent plane wave power density S_{eq} $\left(\frac{mW}{cm^2}\right)$ |
|-------------------|-----------------|--|--|---|--|
| General public | 400 MHz - 2 GHz | $1,37 \cdot f(MHz)^{1/2}$ | $0,00364 \cdot f(MHz)^{1/2}$ | $\frac{f(MHz)}{200}$ | $\frac{f(MHz)}{2000}$ |
| General public | 2 - 300 GHz | 61 | 0,16 | 10 | 1 |

MPE limits:

- Main/Primary transmitter (F3307 Ericsson Mobile Broadband Module):

| Frequency Band | Mode | Frequency Range (MHz) | Reference frequency (MHz) | MPE limit (S_{eq}) $\left(\frac{mW}{cm^2}\right)$ |
|----------------|-------------|-----------------------|---------------------------|--|
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 826,40 | 0,4132 |
| | HSUPA | 826,4 - 846,6 | 826,40 | 0,4132 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 880,20 | 0,4401 |
| | EDGE | 880,2 - 914,8 | 880,20 | 0,4401 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 1710,20 | 0,8551 |
| | EDGE | 1710,2 - 1784,8 | 1710,20 | 0,8551 |

- Additional/Secondary transmitters: All the transmission frequencies for collocated transmitter modules are above 2 GHz, so that the MPE limit is 1 mW/cm^2 .

B.1.4. VODAFONE MPE LIMITS

Normative document:

- 1999/519/EC Council Recommendation on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)

Reference levels:

The table below is excerpted from Table 2 of 1999/519/EC, titled “Reference levels for electric, magnetic and electromagnetic fields (0 Hz to 300 GHz, unperturbed rms values)”:

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 26 of 36 |
| Date: 2010-09-20 | | Annex B |

| Exposure category | Frequency range | E-field strength $\left(\frac{V}{m} \text{ rms}\right)$ | H-field strength $\left(\frac{A}{m} \text{ rms}\right)$ | Equivalent plane wave power density S_{eq} $\left(\frac{W}{m^2}\right)$ | Equivalent plane wave power density S_{eq} $\left(\frac{mW}{cm^2}\right)$ |
|-------------------|-----------------|--|--|---|---|
| General public | 400 MHz - 2 GHz | $1,37 \cdot f(MHz)^{1/2}$ | $0,00364 \cdot f(MHz)^{1/2}$ | $\frac{f(MHz)}{200}$ | $\frac{f(MHz)}{2000}$ |
| General public | 2 - 300 GHz | 61 | 0,16 | 10 | 1 |

MPE limits:

- Main/Primary transmitter (F3307 Ericsson Mobile Broadband Module):

| Frequency Band | Mode | Frequency Range (MHz) | Reference frequency (MHz) | MPE limit (S_{Lim}) $\left(\frac{mW}{cm^2}\right)$ |
|----------------|-------------|-----------------------|---------------------------|--|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 824,20 | 0,4121 |
| | EDGE | 824,2 - 848,8 | 824,20 | 0,4121 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 826,40 | 0,4132 |
| | HSUPA | 826,4 - 846,6 | 826,40 | 0,4132 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 880,20 | 0,4401 |
| | EDGE | 880,2 - 914,8 | 880,20 | 0,4401 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 1710,20 | 0,8551 |
| | EDGE | 1710,2 - 1784,8 | 1710,20 | 0,8551 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 1850,20 | 0,9251 |
| | EDGE | 1850,2 - 1909,8 | 1850,20 | 0,9251 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 1852,40 | 0,9262 |
| | HSUPA | 1852,4 - 1907,6 | 1852,40 | 0,9262 |

- Additional/Secondary transmitters: All the transmission frequencies for WLAN and Bluetooth modules are above 2 GHz, so that the MPE limit is 1 mW/cm^2 .

B.2. RF EXPOSURE ASSESSMENT – INDIVIDUAL TRANSMITTERS

B.2.1. INTRODUCTION

Calculations to predict power density levels in the far-field of the antenna are made by use of the following equation:

$$S = \frac{P \cdot G}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm^2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 27 of 36 |
| Date: 2010-09-20 | | Annex B |

B.2.2. RF EXPOSURE ASSESSMENT FOR F3307 ERICSSON MOBILE BROADBAND MODULE INSTALLED IN GENERIC HOST PLATFORMS

FCC / IC REQUIREMENTS

| Frequency Band | Mode | Frequency Range (MHz) | EIRP (mW) | Evaluation distance (R) (cm) | Power Density (S_{eq}) $S = \frac{P \cdot G}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$ ($\frac{mW}{cm^2}$) | MPE limit (S_{Lim}) ($\frac{mW}{cm^2}$) | COMPLIANCE ($S_{eq} < S_{Lim}$) ($\frac{mW}{cm^2}$) |
|----------------|-------------|-----------------------|-----------|------------------------------|---|---|---|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 1044,58 | 20,00 | 0,2078 | 0,5495 | COMPLIANT |
| | EDGE | 824,2 - 848,8 | 1044,58 | 20,00 | 0,2078 | 0,5495 | COMPLIANT |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 1218,99 | 20,00 | 0,2425 | 0,5509 | COMPLIANT |
| | HSUPA | 826,4 - 846,6 | 1169,50 | 20,00 | 0,2327 | 0,5509 | COMPLIANT |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 499,97 | 20,00 | 0,0995 | 1,0000 | COMPLIANT |
| | EDGE | 1850,2 - 1909,8 | 497,67 | 20,00 | 0,0990 | 1,0000 | COMPLIANT |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 1258,93 | 20,00 | 0,2505 | 1,0000 | COMPLIANT |
| | HSUPA | 1852,4 - 1907,6 | 1318,26 | 20,00 | 0,2623 | 1,0000 | COMPLIANT |

EUROPEAN UNION REQUIREMENTS

| Frequency Band | Mode | Frequency Range (MHz) | EIRP (mW) | Evaluation distance (R) (cm) | Power Density (S_{eq}) $S = \frac{P \cdot G}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$ ($\frac{mW}{cm^2}$) | MPE limit (S_{Lim}) ($\frac{mW}{cm^2}$) | COMPLIANCE ($S_{eq} < S_{Lim}$) ($\frac{mW}{cm^2}$) |
|----------------|----------|-----------------------|-----------|------------------------------|---|---|---|
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 847,11 | 20,00 | 0,1685 | 0,4401 | COMPLIANT |
| | EDGE | 880,2 - 914,8 | 287,04 | 20,00 | 0,0571 | 0,4401 | COMPLIANT |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 465,52 | 20,00 | 0,0926 | 0,8551 | COMPLIANT |
| | EDGE | 1710,2 - 1784,8 | 250,00 | 20,00 | 0,0497 | 0,8551 | COMPLIANT |

AUSTRALIA REQUIREMENTS

| Frequency Band | Mode | Frequency Range (MHz) | EIRP (mW) | Evaluation distance (R) (cm) | Power Density (S_{eq}) $S = \frac{P \cdot G}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$ ($\frac{mW}{cm^2}$) | MPE limit (S_{Lim}) ($\frac{mW}{cm^2}$) | COMPLIANCE ($S_{eq} < S_{Lim}$) ($\frac{mW}{cm^2}$) |
|----------------|-------------|-----------------------|-----------|------------------------------|---|---|---|
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 1218,99 | 20,00 | 0,2425 | 0,4132 | COMPLIANT |
| | HSUPA | 826,4 - 846,6 | 1169,50 | 20,00 | 0,2327 | 0,4132 | COMPLIANT |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 847,11 | 20,00 | 0,1685 | 0,4401 | COMPLIANT |
| | EDGE | 880,2 - 914,8 | 287,04 | 20,00 | 0,0571 | 0,4401 | COMPLIANT |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 465,52 | 20,00 | 0,0926 | 0,8551 | COMPLIANT |
| | EDGE | 1710,2 - 1784,8 | 250,00 | 20,00 | 0,0497 | 0,8551 | COMPLIANT |

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 28 of 36 |
| Date: 2010-09-20 | | Annex B |

VODAFONE REQUIREMENTS

| Frequency Band | Mode | Frequency Range (MHz) | EIRP (mW) | Evaluation distance (R) (cm) | Power Density (S_{eq}) $S = \frac{P \cdot G}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$ $\left(\frac{mW}{cm^2}\right)$ | MPE limit (S_{Lim}) $\left(\frac{mW}{cm^2}\right)$ | COMPLIANCE ($S_{eq} < S_{Lim}$) $\left(\frac{mW}{cm^2}\right)$ |
|----------------|-------------|-----------------------|-----------|------------------------------|--|---|--|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 1044,58 | 20 | 0,2078 | 0,4121 | COMPLIANT |
| | EDGE | 824,2 - 848,8 | 1044,58 | 20 | 0,2078 | 0,4121 | COMPLIANT |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 1218,99 | 20 | 0,2425 | 0,4132 | COMPLIANT |
| | HSUPA | 826,4 - 846,6 | 1169,50 | 20 | 0,2327 | 0,4132 | COMPLIANT |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 847,11 | 20 | 0,1685 | 0,4401 | COMPLIANT |
| | EDGE | 880,2 - 914,8 | 287,04 | 20 | 0,0571 | 0,4401 | COMPLIANT |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 465,52 | 20 | 0,0926 | 0,8551 | COMPLIANT |
| | EDGE | 1710,2 - 1784,8 | 250,00 | 20 | 0,0497 | 0,8551 | COMPLIANT |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 499,97 | 20 | 0,0995 | 0,9251 | COMPLIANT |
| | EDGE | 1850,2 - 1909,8 | 497,67 | 20 | 0,0990 | 0,9251 | COMPLIANT |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 1258,93 | 20 | 0,2505 | 0,9262 | COMPLIANT |
| | HSUPA | 1852,4 - 1907,6 | 1318,26 | 20 | 0,2623 | 0,9262 | COMPLIANT |

B.2.3. RF EXPOSURE ASSESSMENT FOR SECONDARY TRANSMITTERS INSTALLED IN GENERIC HOST PLATFORMS

| Model name | FCC ID | EIRP (mW) | Evaluation distance (cm) | Power Density (S_{eq}) $S = \frac{P \cdot G}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$ $\left(\frac{mW}{cm^2}\right)$ | MPE limit (S_{Lim}) $\left(\frac{mW}{cm^2}\right)$ | COMPLIANCE ($S_{eq} < S_{Lim}$) |
|------------|-----------|-----------|--------------------------|--|---|--------------------------------------|
| Scenario 1 | Bluetooth | 76,43 | 20,00 | 0,0152 | 1,0000 | COMPLIANT |
| Scenario 2 | WLAN | 2000,00 | 20,00 | 0,3979 | 1,0000 | COMPLIANT |
| Scenario 3 | WLAN | 2000,00 | 20,00 | 0,3979 | 1,0000 | COMPLIANT |
| | Bluetooth | 76,43 | 20,00 | 0,0152 | 1,0000 | COMPLIANT |
| Scenario 4 | WiMAX | 2000,00 | 20,00 | 0,3979 | 1,0000 | COMPLIANT |
| Scenario 5 | WiMAX | 2000,00 | 20,00 | 0,3979 | 1,0000 | COMPLIANT |
| | Bluetooth | 76,43 | 20,00 | 0,0152 | 1,0000 | COMPLIANT |
| Scenario 6 | WLAN | 2000,00 | 20,00 | 0,3979 | 1,0000 | COMPLIANT |
| | WiMAX | | | | 1,0000 | COMPLIANT |
| Scenario 7 | WLAN | 2000,00 | 20,00 | 0,3979 | 1,0000 | COMPLIANT |
| | WiMAX | | | | 1,0000 | COMPLIANT |
| | Bluetooth | 76,43 | 20,00 | 0,0152 | 1,0000 | COMPLIANT |

B.3. RF EXPOSURE ASSESSMENT – COLLOCATION CONSIDERATIONS

B.3.1. INTRODUCTION

In situations where simultaneous exposure to fields of different equipment and frequencies occurs, the possibility that these exposures will be additive in their effects must be considered. Calculations based on this additivity are performed by the sum of relative exposure for each equipment according to the following compliance criteria:

$$\sum_1^N \frac{S_{eqn}}{S_{Limn}} = \frac{S_{eq1}}{S_{Lim1}} + \frac{S_{eq2}}{S_{Lim2}} + \dots + \frac{S_{eqN}}{S_{LimN}} \leq 1$$

where:

S_{eq} is the power density of the electromagnetic field caused, at a given distance (evaluation distance), by a specific equipment transmitting at a defined frequency.

S_{Lim} is the MPE limit for the evaluated transmission frequency.

B.3.2. FCC / IC REQUIREMENTS

RELATIVE EXPOSURE FOR F3307 ERICSSON BROADBAND MODULE

| Frequency Band | Mode | Frequency Range (MHz) | S_{eq} | S_{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|----------------|-------------|-----------------------|----------|-----------|--------------------------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 0,2078 | 0,5495 | 0,3782 |
| | EDGE | 824,2 - 848,8 | 0,2078 | 0,5495 | 0,3782 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 0,2425 | 0,5509 | 0,4402 |
| | HSUPA | 826,4 - 846,6 | 0,2327 | 0,5509 | 0,4223 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 0,0995 | 1,0000 | 0,0995 |
| | EDGE | 1850,2 - 1909,8 | 0,0990 | 1,0000 | 0,0990 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 0,2505 | 1,0000 | 0,2505 |
| | HSUPA | 1852,4 - 1907,6 | 0,2623 | 1,0000 | 0,2623 |

RELATIVE EXPOSURE FOR SECONDARY TRANSMITTERS

| SCENARIO | Type of transmitter | S_{eq} | S_{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|------------|---------------------|----------|-----------|--------------------------|
| Scenario 1 | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 2 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| Scenario 3 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 4 | WiMAX | 0,3979 | 1,0000 | 0,3979 |
| Scenario 5 | WiMAX | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 30 of 36 |
| Date: 2010-09-20 | | Annex B |

| | | | | |
|------------|-----------|--------|--------|--------|
| Scenario 6 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| Scenario 7 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |

SIMULTANEOUS EXPOSURE

| SCENARIO | Equipment | | Maximum $\frac{S_{eq}}{S_{Lim}}$ | Maximum $\frac{S_{Pri}}{S_{Lim_Pri}} +$ $\sum \frac{S_{Sec}}{S_{Lim_Sec}}$ | COMPLIANCE $\frac{S_{Pri}}{S_{Lim_Pri}} +$ $\sum \frac{S_{Sec}}{S_{Lim_Sec}} < 1$ |
|------------|-----------------------|----------------|-------------------------------------|--|---|
| | | | | | |
| Scenario 1 | Primary transmitter | Ericsson F3307 | 0,4402 | 0,4554 | COMPLIANT |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 2 | Primary transmitter | Ericsson F3307 | 0,4402 | 0,8381 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| Scenario 3 | Primary transmitter | Ericsson F3307 | 0,4402 | 0,8533 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 4 | Primary transmitter | Ericsson F3307 | 0,4402 | 0,8381 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| Scenario 5 | Primary transmitter | Ericsson F3307 | 0,4402 | 0,8533 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 6 | Primary transmitter | Ericsson F3307 | 0,4402 | 0,8381 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| Scenario 7 | Primary transmitter | Ericsson F3307 | 0,4402 | 0,8533 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |

B.3.3. EUROPEAN UNION REQUIREMENTS

RELATIVE EXPOSURE FOR F3307 ERICSSON BROADBAND MODULE

| Frequency Band | Mode | Frequency Range (MHz) | S _{eq} | S _{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|----------------|----------|-----------------------|-----------------|------------------|--------------------------|
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 0,1685 | 0,4401 | 0,3829 |
| | EDGE | 880,2 - 914,8 | 0,0571 | 0,4401 | 0,1298 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 0,0926 | 0,8551 | 0,1083 |
| | EDGE | 1710,2 - 1784,8 | 0,0497 | 0,8551 | 0,0582 |

RELATIVE EXPOSURE FOR SECONDARY TRANSMITTERS

| SCENARIO | Type of transmitter | S _{eq} | S _{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|------------|---------------------|-----------------|------------------|--------------------------|
| Scenario 1 | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 2 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| Scenario 3 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 4 | WiMAX | 0,3979 | 1,0000 | 0,3979 |
| Scenario 5 | WiMAX | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 6 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| Scenario 7 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| | Bluetooth | | | |

SIMULTANEOUS EXPOSURE

| SCENARIO | Equipment | | Maximum $\frac{S_{eq}}{S_{Lim}}$ | Maximum $\frac{S_{Pri}}{S_{Lim_Pri}} + \sum \frac{S_{Sec}}{S_{Lim_Sec}}$ | COMPLIANCE $\frac{S_{Pri}}{S_{Lim_Pri}} + \sum \frac{S_{Sec}}{S_{Lim_Sec}} < 1$ |
|------------|-----------------------|----------------|----------------------------------|--|---|
| Scenario 1 | Primary transmitter | Ericsson F3307 | 0,3829 | 0,3981 | COMPLIANT |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 2 | Primary transmitter | Ericsson F3307 | 0,3829 | 0,7808 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 32 of 36 |
| Date: 2010-09-20 | | Annex B |

| | | | | | |
|-------------------|-----------------------|----------------|--------|---------------|------------------|
| Scenario 3 | Primary transmitter | Ericsson F3307 | 0,3829 | 0,7960 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 4 | Primary transmitter | Ericsson F3307 | 0,3829 | 0,7808 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| Scenario 5 | Primary transmitter | Ericsson F3307 | 0,3829 | 0,7960 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 6 | Primary transmitter | Ericsson F3307 | 0,3829 | 0,7808 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| Scenario 7 | Primary transmitter | Ericsson F3307 | 0,3829 | 0,7960 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |

B.3.4. AUSTRALIA REQUIREMENTS

RELATIVE EXPOSURE FOR F3307 ERICSSON BROADBAND MODULE

| Manufacturer | Model name | Frequency range (MHz) | S_{eq} | S_{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|--------------|-------------|-----------------------|----------|-----------|--------------------------|
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 0,2425 | 0,4132 | 0,5869 |
| | HSUPA | 826,4 - 846,6 | 0,2327 | 0,4132 | 0,5631 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 0,1685 | 0,4401 | 0,3829 |
| | EDGE | 880,2 - 914,8 | 0,0571 | 0,4401 | 0,1298 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 0,0926 | 0,8551 | 0,1083 |
| | EDGE | 1710,2 - 1784,8 | 0,0497 | 0,8551 | 0,0582 |

RELATIVE EXPOSURE FOR SECONDARY TRANSMITTERS

| SCENARIO | Type of transmitter | S_{eq} | S_{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|------------|---------------------|----------|-----------|--------------------------|
| Scenario 1 | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 2 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| Scenario 3 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 4 | WiMAX | 0,3979 | 1,0000 | 0,3979 |

| | | |
|------------------------------------|--|----------------|
| Report No.: 30751IDT.103 Rev. B | | Page: 33 of 36 |
| Date: 2010-09-20 | | Annex B |

| | | | | |
|------------|-----------|--------|--------|--------|
| Scenario 5 | WiMAX | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 6 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| Scenario 7 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |

SIMULTANEOUS EXPOSURE

| SCENARIO | Equipment | | Maximum $\frac{S_{eq}}{S_{Lim}}$ | Maximum | COMPLIANCE |
|------------|-----------------------|----------------|-------------------------------------|--|--|
| | | | | $\frac{S_{Pri}}{S_{Lim_Pri}} + \sum \frac{S_{Sec}}{S_{Lim_Sec}}$ | $\frac{S_{Pri}}{S_{Lim_Pri}} + \sum \frac{S_{Sec}}{S_{Lim_Sec}} < 1$ |
| Scenario 1 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,6021123 | COMPLIANT |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 2 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9847951 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| Scenario 3 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9999997 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 4 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9847951 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| Scenario 5 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9999997 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 6 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9847951 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| Scenario 7 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9999997 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |

B.3.5. VODAFONE REQUIREMENTS

RELATIVE EXPOSURE FOR F3307 ERICSSON BROADBAND MODULE

| Manufacturer | Model name | Frequency range (MHz) | S _{eq} | S _{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|--------------|-------------|-----------------------|-----------------|------------------|--------------------------|
| GSM 850 | GSM/GPRS | 824,2 - 848,8 | 0,2078 | 0,4121 | 0,5043 |
| | EDGE | 824,2 - 848,8 | 0,2078 | 0,4121 | 0,5043 |
| FDD V | WCDMA/HSDPA | 826,4 - 846,6 | 0,2425 | 0,4132 | 0,5869 |
| | HSUPA | 826,4 - 846,6 | 0,2327 | 0,4132 | 0,5631 |
| E-GSM 900 | GSM/GPRS | 880,2 - 914,8 | 0,1685 | 0,4401 | 0,3829 |
| | EDGE | 880,2 - 914,8 | 0,0571 | 0,4401 | 0,1298 |
| DCS 1800 | GSM/GPRS | 1710,2 - 1784,8 | 0,0926 | 0,8551 | 0,1083 |
| | EDGE | 1710,2 - 1784,8 | 0,0497 | 0,8551 | 0,0582 |
| PCS 1900 | GSM/GPRS | 1850,2 - 1909,8 | 0,0995 | 0,9251 | 0,1075 |
| | EDGE | 1850,2 - 1909,8 | 0,0990 | 0,9251 | 0,1070 |
| FDD II | WCDMA/HSDPA | 1852,4 - 1907,6 | 0,2505 | 0,9262 | 0,2704 |
| | HSUPA | 1852,4 - 1907,6 | 0,2623 | 0,9262 | 0,2832 |

RELATIVE EXPOSURE FOR SECONDARY TRANSMITTERS

| SCENARIO | Type of transmitter | S _{eq} | S _{Lim} | $\frac{S_{eq}}{S_{Lim}}$ |
|------------|---------------------|-----------------|------------------|--------------------------|
| Scenario 1 | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 2 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| Scenario 3 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 4 | WiMAX | 0,3979 | 1,0000 | 0,3979 |
| Scenario 5 | WiMAX | 0,3979 | 1,0000 | 0,3979 |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |
| Scenario 6 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| Scenario 7 | WLAN | 0,3979 | 1,0000 | 0,3979 |
| | WiMAX | | | |
| | Bluetooth | 0,0152 | 1,0000 | 0,0152 |

SIMULTANEOUS EXPOSURE

| SCENARIO | Equipment | | Maximum $\frac{S_{eq}}{S_{Lim}}$ | Maximum | COMPLIANCE |
|------------|-----------------------|----------------|-------------------------------------|--|--|
| | | | | $\frac{S_{Pri}}{S_{Lim_Pri}} + \sum \frac{S_{Sec}}{S_{Lim_Sec}}$ | $\frac{S_{Pri}}{S_{Lim_Pri}} + \sum \frac{S_{Sec}}{S_{Lim_Sec}} < 1$ |
| Scenario 1 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,6021123 | COMPLIANT |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 2 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9847951 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| Scenario 3 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9999997 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 4 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9847951 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| Scenario 5 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9999997 | COMPLIANT |
| | Secondary transmitter | WiMAX | 0,3979 | | |
| | Secondary transmitter | Bluetooth | 0,0152 | | |
| Scenario 6 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9847951 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| Scenario 7 | Primary transmitter | Ericsson F3307 | 0,5869 | 0,9999997 | COMPLIANT |
| | Secondary transmitter | WLAN | 0,3979 | | |
| | Secondary transmitter | WiMAX | | | |
| | Secondary transmitter | Bluetooth | | | |