1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v6, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times $ E ^2$, $ H ^2$ or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E)	Magnetic Field Strength (H)	Power Density (S) (mW/cm ²)	Averaging Times $ E ^2$, $ H ^2$ or $ E ^2$
0.3-1.34	(V/m) 614	(A/m) 1.63	(100)*	S (minutes)
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.2 MPE Calculation Method

 $S = (30*P*G) / (377*R^2)$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.3 MPE Calculation Result

Product Description: <u>Bluetooth Smart Module 4.1 – LM930</u>

Model No.: <u>LM930-XXXX</u> FCC ID: <u>VVX-LM930-XXXX</u>

Maximum peak output power: 8.719 (dBm)

Maximum peak output power at antenna input terminal: 7.45(mW)

Prediction distance: >20(cm)
Prediction frequency: 2480 (MHz)
Antenna gain (typical): 2 (dBi)

Antenna gain (typical): 1.58 (numeric)

The worst case is power density at prediction frequency at 20cm: <u>0.0023(mw/cm²)</u> MPE limit for general population exposure at prediction frequency: <u>1 (mw/cm²)</u>

 $0.0023 \text{ (mw/cm}^2) < 1 \text{ (mw/cm}^2)$

Result: Pass