1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times $ E ^2$, $ H ^2$ or S (minutes) |
|--------------------------|-----------------------------------------|-----------------------------------------|--------------------------------------------|------------------------------------------------------------|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | / | / | F/300 | 6 |
| 1500-100000 | / | / | 5 | 6 |

(a) Limits for Occupational / Controlled Exposure

(b) Limits for General Population / Uncontrolled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times $ E ^2$, $ H ^2$ or S (minutes) |
|--------------------------|-----------------------------------------|-----------------------------------------|--------------------------------------------|------------------------------------------------------------|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | F/1500 | 30 |
| 1500-100000 | / | / | 1 | 30 |

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.2 MPE Calculation Method

- $S = (30*P*G) / (377*R^2)$
- S = power density (in appropriate units, e.g., mw/cm²)
- P = power input to the antenna (in appropriate units, e.g., mw)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.
- R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.3 MPE Calculation Result

Product Description: <u>Bluetooth Smart Module 4.1 – LM931</u> Model No.: <u>LM931-XXXX</u> FCC ID: <u>VVX-LM931-XXXX</u> Maximum peak output power: <u>8.752 (dBm)</u> Maximum peak output power at antenna input terminal: <u>7.502(mW)</u> Prediction distance: <u>>20(cm)</u> Prediction frequency: <u>2402 (MHz)</u> Antenna gain (typical): <u>2 (dBi)</u> Antenna gain (typical): <u>1.58(numeric)</u> The worst case is power density at prediction frequency at 20cm: <u>0.0024(mw/cm²)</u> MPE limit for general population exposure at prediction frequency: <u>1 (mw/cm²)</u>

 $0.0024 \text{ (mw/cm}^2) < 1 \text{ (mw/cm}^2)$

Result: Pass