

# FCC Part 15C Measurement and Test Report

For

**LM Technologies Ltd.**

**Unit 19, Spectrum House, 32-34 Gordon House Road, London, NW5 1LP,**

**United Kingdom**

**FCC ID: VVXLM074**

<b>FCC Rule(s):</b>	<u>FCC Part 15.247</u>
<b>Product Description:</b>	<u>LM074 Bluetooth 5.0 Dual Mode Module</u>
<b>Tested Model:</b>	<u>LM074-0190</u>
<b>Report No.:</b>	<u>WTX19X10071446W-2</u>
<b>Sample Receipt Date:</b>	<u>2019-10-17</u>
<b>Tested Date:</b>	<u>2019-10-17 to 2019-12-18</u>
<b>Issued Date:</b>	<u>2019-12-19</u>
<b>Tested By:</b>	<u>Jack Huang / Engineer</u> <i>Jack Huang</i>
<b>Reviewed By:</b>	<u>Silin Chen / EMC Manager</u> <i>Silin Chen</i>
<b>Approved &amp; Authorized By:</b>	<u>Jandy So / PSQ Manager</u> <i>Jandy So</i>
<b>Prepared By:</b>	

**Shenzhen SEM Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....4**

    1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

    1.2 TEST STANDARDS.....5

    1.3 TEST METHODOLOGY .....5

    1.4 TEST FACILITY .....5

    1.5 EUT SETUP AND TEST MODE.....6

    1.6 MEASUREMENT UNCERTAINTY .....6

    1.7 TEST EQUIPMENT LIST AND DETAILS .....7

**2. SUMMARY OF TEST RESULTS .....9**

**3. RF EXPOSURE .....10**

    3.1 STANDARD APPLICABLE.....10

    3.2 TEST RESULT.....10

**4. ANTENNA REQUIREMENT .....11**

    4.1 STANDARD APPLICABLE.....11

    4.2 EVALUATION INFORMATION .....11

**5. POWER SPECTRAL DENSITY .....12**

    5.1 STANDARD APPLICABLE.....12

    5.2 TEST PROCEDURE.....12

    5.3 SUMMARY OF TEST RESULTS/PLOTS .....12

**6. DTS BANDWIDTH.....14**

    6.1 STANDARD APPLICABLE.....14

    6.2 TEST PROCEDURE.....14

    6.3 SUMMARY OF TEST RESULTS/PLOTS .....14

**7. RF OUTPUT POWER .....16**

    7.1 STANDARD APPLICABLE.....16

    7.2 TEST PROCEDURE.....16

    7.3 SUMMARY OF TEST RESULTS/PLOTS .....16

**8. FIELD STRENGTH OF SPURIOUS EMISSIONS .....18**

    8.1 STANDARD APPLICABLE.....18

    8.2 TEST PROCEDURE.....18

    8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....19

    8.4 SUMMARY OF TEST RESULTS/PLOTS .....19

**9. OUT OF BAND EMISSIONS.....27**

    9.1 STANDARD APPLICABLE.....27

    9.2 TEST PROCEDURE.....27

    9.3 SUMMARY OF TEST RESULTS/PLOTS .....28

**10. CONDUCTED EMISSIONS .....34**

    10.1 TEST PROCEDURE.....34

    10.2 BASIC TEST SETUP BLOCK DIAGRAM.....34

    10.3 TEST RECEIVER SETUP .....34

    10.4 SUMMARY OF TEST RESULTS/PLOTS .....34

## Report version

Version No.	Date of issue	Description
Rev.00	2019-12-19	Original
/	/	/

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: LM Technologies Ltd.  
Address of applicant: Unit 19, Spectrum House, 32-34 Gordon House Road,  
London, NW5 1LP, United Kingdom

Manufacturer: LM Technologies Ltd.  
Address of manufacturer: Unit 19, Spectrum House, 32-34 Gordon House Road,  
London, NW5 1LP, United Kingdom

General Description of EUT	
Product Name:	LM074 Bluetooth 5.0 Dual Mode Module
Brand Name:	LM Technologies
Model No.:	LM074-0190
Adding Model(s):	LM074-0191, LM074-0192
Rated Voltage:	DC5V
Power Adapter:	/
Software Version:	/
Hardware Version:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. LM074-0190:MOD SMT PROG BT5.0 D/Mode SPPwithGAPCentral_0106 9dBm NO-ANT PCS LM074-0191:MOD SMT PROG BT5.0 D/Mode SPPwithGAPCentral_0106 9dBm NO-ANT Tray LM074-0192:MOD SMT PROG BT5.0 D/Mode SPPwithGAPCentral_0106 9dBm NO-ANT T&amp;R ,but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V5.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	7.378dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	2.0dBi

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**558074 D01 15.247 Meas Guidance v05r02:** Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### Address of the test laboratory

Laboratory: Shenzhen SEM Test Technology Co., Ltd.

Address: 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

### FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E445	EB12648265
USB Cable	/	/	/
Fixed frequency board	LM Technologies Ltd.	LM068 REV02	/

## 1.6 Measurement Uncertainty

Measurement uncertainty			
Parameter	Conditions	Uncertainty	
RF Output Power	Conducted	±0.42dB	
Occupied Bandwidth	Conducted	±1.5%	
Power Spectral Density	Conducted	±1.8dB	
Conducted Spurious Emission	Conducted	±2.17dB	
Conducted Emissions	Conducted	9-150kHz ±3.74dB	
		0.15-30MHz ±3.34dB	
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB	
		0.2-1GHz ±5.56dB	
		1-6GHz ±3.84dB	

		6-18GHz $\pm$ 3.92dB
--	--	----------------------

### 1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2019-04-30	2020-04-29
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2019-04-30	2020-04-29
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2019-04-30	2020-04-29
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2019-04-30	2020-04-29
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2019-04-30	2020-04-29
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2019-04-30	2020-04-29
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2019-04-30	2020-04-29
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2019-04-30	2020-04-29
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2019-04-30	2020-04-29
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2019-04-30	2020-04-29
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2019-04-30	2020-04-29
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2019-04-30	2020-04-29
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2019-04-30	2020-04-29
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2019-04-30	2020-04-29
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17

<b>Software List</b>			
<b>Description</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Version</b>
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing



## 2. SUMMARY OF TEST RESULTS

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§2.1091	RF Exposure	Compliant
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to §1.1307 and §2.1091 the mobile transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has an Integral antenna, fulfill the requirement of this section.

## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 5.3 Summary of Test Results/Plots

Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE)	Low	-7.536	8
	Middle	-7.762	8
	High	-9.293	8

Please refer to the following test plots:

<p>Low</p>	 <p>Agilent 11:36:49 Dec 12, 19 R T</p> <p>Ref 10 dBm Atten 20 dB Mkr1 2.4019520 GHz -7.536 dBm</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Marker 2.401952000 GHz -7.536 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.402 GHz Span 1.5 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 171.5 ms (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>
<p>Middle</p>	 <p>Agilent 11:40:58 Dec 12, 19 R T</p> <p>Ref 10 dBm Atten 20 dB Mkr1 2.4399490 GHz -7.762 dBm</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Marker 2.439949000 GHz -7.762 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.44 GHz Span 1.5 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 171.5 ms (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>
<p>High</p>	 <p>Agilent 11:43:36 Dec 12, 19 R T</p> <p>Ref 10 dBm Atten 20 dB Mkr1 2.4799475 GHz -9.293 dBm</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Marker 2.479947500 GHz -9.293 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.48 GHz Span 1.5 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 171.5 ms (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>

## 6. DTS Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Summary of Test Results/Plots

Test Mode	Test Channel	6 dB Bandwidth MHz	Limit kHz
GFSK(BLE)	Low	0.730	$\geq 500$
	Middle	0.736	$\geq 500$
	High	0.742	$\geq 500$

Please refer to the following test plots:

<p>Low</p>	 <p>Agilent 11:35:44 Dec 12, 19 R T</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref Level 20.00 dBm</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.402 GHz Span 3 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 1.0734 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -55.148 kHz x dB Bandwidth 730.129 kHz</p>
<p>Middle</p>	 <p>Agilent 11:41:26 Dec 12, 19 R T</p> <p>Ch Freq 2.44 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref Level 20.00 dBm</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.44 GHz Span 3 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 1.0716 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -61.001 kHz x dB Bandwidth 736.086 kHz</p>
<p>High</p>	 <p>Agilent 11:43:06 Dec 12, 19 R T</p> <p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref Level 20.00 dBm</p> <p>Ref 20 dBm Atten 30 dB</p> <p>#Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.48 GHz Span 3 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p><b>Occupied Bandwidth</b> 1.0745 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -63.069 kHz x dB Bandwidth 741.509 kHz</p>

## 7. RF Output Power

### 7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure




According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Set span  $\geq 3 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

### 7.3 Summary of Test Results/Plots

Test Mode	Test Channel	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	Low	7.378	5.47	1000
	Middle	7.239	5.30	1000
	High	5.798	3.80	1000



<p>Low</p>	 <p>Agilent 11:34:35 Dec 12, 19 R T</p> <p>Ref 15 dBm Atten 25 dB Mkr1 2.402175 GHz 7.378 dBm</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Marker 2.402175000 GHz 7.378 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.402 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 10 ms (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>
<p>Middle</p>	 <p>Agilent 11:40:17 Dec 12, 19 R T</p> <p>Ref 15 dBm Atten 25 dB Mkr1 2.439675 GHz 7.239 dBm</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Marker 2.439675000 GHz 7.239 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.44 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 10 ms (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>
<p>High</p>	 <p>Agilent 11:44:02 Dec 12, 19 R T</p> <p>Ref 15 dBm Atten 25 dB Mkr1 2.479695 GHz 5.798 dBm</p> <p>#Peak Log 10 dB/Offst 1 dB</p> <p>Marker 2.479695000 GHz 5.798 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.48 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 10 ms (1001 pts)</p> <p>Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2</p>

## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=300KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of  $-6\text{dB}\mu\text{V}$  means the emission is  $6\text{dB}\mu\text{V}$  below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

### 8.4 Summary of Test Results/Plots

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*


## ➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	40.7015	36.13	-14.13	22.00	40.00	-18.00	111	100	peak
2	107.5100	33.05	-14.82	18.23	43.50	-25.27	157	100	peak
3	317.7010	30.33	-8.29	22.04	46.00	-23.96	80	100	peak
4*	916.0687	29.80	-0.93	28.87	46.00	-17.13	94	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1*	50.9420	37.44	-13.90	23.54	40.00	-16.46	99	100	peak
2	98.1419	37.87	-15.29	22.58	43.50	-20.92	164	100	peak
3	122.8340	39.57	-16.34	23.23	43.50	-20.27	111	100	peak
4	279.0436	31.67	-9.64	22.03	46.00	-23.97	112	100	peak
5	798.9796	29.39	-4.47	24.92	46.00	-21.08	193	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	49.0144	33.85	-13.69	20.16	40.00	-19.84	310	100	peak
2	98.8325	33.88	-15.16	18.72	43.50	-24.78	182	100	peak
3	323.3204	31.46	-8.44	23.02	46.00	-22.98	90	100	peak
4*	912.8619	29.80	-0.99	28.81	46.00	-17.19	156	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	50.9420	37.01	-13.90	23.11	40.00	-16.89	324	100	peak
2	122.8340	39.92	-16.34	23.58	43.50	-19.92	100	100	peak
3	295.1469	31.84	-8.24	23.60	46.00	-22.40	208	100	peak
4*	929.0081	31.53	-0.85	30.68	46.00	-15.32	117	100	peak


Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	49.0144	33.59	-13.69	19.90	40.00	-20.10	336	100	peak
2	98.1419	34.19	-15.29	18.90	43.50	-24.60	217	100	peak
3	299.3158	30.62	-7.87	22.75	46.00	-23.25	60	100	peak
4*	929.0081	30.59	-0.85	29.74	46.00	-16.26	298	100	peak



Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	50.9420	36.34	-13.90	22.44	40.00	-17.56	249	100	peak
2	122.8340	38.50	-16.34	22.16	43.50	-21.34	90	100	peak
3*	925.7563	30.66	-0.79	29.87	46.00	-16.13	214	100	peak

## ➤ Spurious Emissions Above 1GHz

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2402MHz							
4804	59.17	-3.41	55.76	74	-18.24	H	PK
4804	38.06	-3.41	34.65	54	-19.35	H	AV
7206	59.21	-0.42	58.79	74	-15.21	H	PK
7206	38.67	-0.42	38.25	54	-15.75	H	AV
4804	59.09	-3.41	55.68	74	-18.32	V	PK
4804	38.64	-3.41	35.23	54	-18.77	V	AV
7206	61.56	-0.42	61.14	74	-12.86	V	PK
7206	38.06	-0.42	37.64	54	-16.36	V	AV
Middle Channel-2440MHz							
4880	59.94	-3.49	56.45	74	-17.55	H	PK
4880	39.16	-3.49	35.67	54	-18.33	H	AV
7320	58.15	-0.47	57.68	74	-16.32	H	PK
7320	38.66	-0.47	38.19	54	-15.81	H	AV
4880	58.21	-3.49	54.72	74	-19.28	V	PK
4880	39.5	-3.49	36.01	54	-17.99	V	AV
7320	58.1	-0.47	57.63	74	-16.37	V	PK
7320	38.51	-0.47	38.04	54	-15.96	V	AV
High Channel-2480MHz							
4960	61.34	-3.41	57.93	74	-16.07	H	PK
4960	40.4	-3.41	36.99	54	-17.01	H	AV
7440	60.6	-0.42	60.18	74	-13.82	H	PK
7440	39.04	-0.42	38.62	54	-15.38	H	AV
4960	58.56	-3.41	55.15	74	-18.85	V	PK
4960	41.9	-3.41	38.49	54	-15.51	V	AV
7440	58.64	-0.42	58.22	74	-15.78	V	PK
7440	38.76	-0.42	38.34	54	-15.66	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

---

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

**B. Antenna-port conducted measurements**

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW  $\geq [3 \times \text{RBW}]$ .
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

**Table 9—RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

**9.3 Summary of Test Results/Plots**


➤ Radiated test

Test Channel	Low	Polarity:	Horizontal worst case)
--------------	-----	-----------	------------------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.38	-9.66	33.72	54.00	-20.28	Average Detector
	2310.000	54.87	-9.66	45.21	74.00	-28.79	Peak Detector
2	2390.000	55.39	-9.50	45.89	54.00	-8.11	Average Detector
	2390.000	62.41	-9.50	52.91	74.00	-21.09	Peak Detector
3	2402.000	103.60	-9.47	94.13	/	/	Average Detector
	2402.300	108.79	-9.47	99.32	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal worst case)
--------------	------	-----------	------------------------





No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.950	99.39	-9.32	90.07	/	/	Average Detector
	2479.650	104.18	-9.32	94.86	/	/	Peak Detector
2	2483.500	58.90	-9.31	49.59	54.00	-4.41	Average Detector
	2483.500	67.49	-9.31	58.18	74.00	-15.82	Peak Detector
3	2500.000	52.11	-9.28	42.83	54.00	-11.17	Average Detector
	2500.000	59.47	-9.28	50.19	74.00	-23.81	Peak Detector

➤ Conducted test





Middle





High




## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram




### 10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz  
 Stop Frequency ..... 30 MHz  
 Sweep Speed ..... Auto  
 IF Bandwidth..... 10 kHz  
 Quasi-Peak Adapter Bandwidth ..... 9 kHz  
 Quasi-Peak Adapter Mode ..... Normal


### 10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2340	30.03	10.00	40.03	52.30	-12.27	AVG
2	0.2580	40.69	10.02	50.71	61.49	-10.78	QP
3	0.6419	25.65	10.05	35.70	46.00	-10.30	AVG
4*	0.6860	38.28	10.05	48.33	56.00	-7.67	QP
5	1.3580	27.41	10.37	37.78	46.00	-8.22	AVG
6	1.3619	34.33	10.37	44.70	56.00	-11.30	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1700	37.62	9.95	47.57	64.96	-17.39	QP
2	0.1980	31.36	9.97	41.33	53.69	-12.36	AVG
3	0.5260	20.72	10.03	30.75	46.00	-15.25	AVG
4*	0.6540	36.48	10.05	46.53	56.00	-9.47	QP
5	2.1020	23.21	10.37	33.58	46.00	-12.42	AVG
6	2.2500	33.09	10.37	43.46	56.00	-12.54	QP

\*\*\*\*\* END OF REPORT \*\*\*\*\*