



**中认信通**  
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



# RF EXPOSURE EVALUATION REPORT

**Applicant: LM Technologies Ltd.**

Address: Sierra Quebec Bravo, 2nd Floor, 77 Marsh Wall, E14 9SH, London, United Kingdom

**FCC ID: VVXLM3001**

**Product Name: LM3001 Bluetooth 5.0 Dual Mode Access Point**

**Standard(s): 47 CFR §1.1307**

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

**Report Number: CR231059192-00E**

**Date Of Issue: 2023/12/5**

**Reviewed By: Calvin Chen**

Title: RF Engineer

**Approved By: Sun Zhong**

Title: Manager

**Test Laboratory: China Certification ICT Co., Ltd (Dongguan)**

No. 113, Pingkang Road, Dalang Town, Dongguan,  
Guangdong, China

Tel: +86-769-82016888

*Calvin Chen*

*Sun Zhong*

## Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

## Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

# CONTENTS

<b>DOCUMENT REVISION HISTORY .....</b>	<b>4</b>
<b>1. RF EXPOSURE EVALUATION .....</b>	<b>5</b>
<b>1.1 SIMULTANEOUS TRANSMISSION WITH MPE-BASED .....</b>	<b>5</b>
1.1.1 Applicable Standard.....	5
1.1.2 Measurement Result.....	7

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR231059192-00E	Original Report	2023/12/5

## 1. RF EXPOSURE EVALUATION

### 1.1 Simultaneous Transmission with MPE-based

#### 1.1.1 Applicable Standard

According to §1.1307(b)(3)(ii)(B)

Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions

This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of Formula (1) is satisfied.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2f$ .
1,500-100,000	$19.2R^2$ .

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1 \quad (1)$$

Where:

$a$  = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

$b$  = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

$c$  = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,j}$  = the exemption threshold power ( $P_{th}$ ) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Evaluated_k$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source  $k$  either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure Limit_k$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source  $k$ , as applicable from [§ 1.1310 of this chapter](#).

### 1.1.2 Measurement Result

Radio	Frequency (MHz)	$\lambda / 2\pi$ (mm)	Distance (mm)	Exemption ERP (mW)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP	
							dBm	mW
Module 1 BDR/EDR	2402-2480	19.88	200	768	7	5.18	10.03	10.07
Module 1 BLE	2402-2480	19.88	200	768	5	5.18	8.03	6.35
Module 2 BDR/EDR	2402-2480	19.88	200	768	8	5.18	11.03	12.68
Module 2 BLE	2402-2480	19.88	200	768	6	5.18	9.03	8.00
Module 3 BDR/EDR	2402-2480	19.88	200	768	8	5.18	11.03	12.68
Module 3 BLE	2402-2480	19.88	200	768	6	5.18	9.03	8.00
Module 4 BDR/EDR	2402-2480	19.88	200	768	7	5.18	10.03	10.07
Module 4 BLE	2402-2480	19.88	200	768	5	5.18	8.03	6.35
Wi-Fi	2412-2462	19.80	200	768	24	1.50	23.35	216.27

Note:

The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

The Wi-Fi and four Bluetooth modules can transmit simultaneously.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$$

$$= ERP_{Wi-Fi} / ERP_{th} + ERP_{Module 1} / ERP_{th} + ERP_{Module 2} / ERP_{th} + ERP_{Module 3} / ERP_{th} + ERP_{Module 4} / ERP_{th}$$

$$= 216.27/768 + 10.07/768 + 12.68/768 + 12.68/768 + 10.07/768$$

$$= 0.341$$

$$< 1.0$$

**Result:** The device meet FCC MPE at 20 cm distance.

===== END OF REPORT =====