

Conducted test results

No.1-7077/23-01-04_TR1-A203-R1

January 16, 2024

Test Standard(s)	FCC 15.247 ISED RSS247
------------------	---------------------------

This document is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.

Authorized

David Lang
Lab Manager
Radio Labs

Table of Content

NA # Message with SA scan ~	4
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	5
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	7
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	10
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	14
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	17
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	20
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	22
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	25
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	29
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	32
FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	35
FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	37
NA # Message with SA scan ~	39
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	40
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	42
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	45
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	49
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	52
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	55
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	57
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	60
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	64
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	67
FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	70
FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	72
NA # Message with SA scan ~	74
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	75
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	77
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	80
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	84
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	87
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	90
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	92
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	95
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	99
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	102
FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	105
FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	107
NA # Create group ~	109
NA # Message with SA scan ~	110

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	111
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	113
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	116
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	120
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	123
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	126
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	128
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	131
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	135
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	138
FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	141
FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	143
NA # Message with SA scan ~	145
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	146
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	148
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	151
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	155
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	158
FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode	161
FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode	163
FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode	166
FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode	170
FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode	173
FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	176
FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz	178

NA # Message with SA scan ~

References

TC start	13.01.2024 13:53:43
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	NA NI
Method	
Description	Message with SA Scan n-HT20 mode
Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	13.01.2024 13:53:44
Message	set WLAN2G4 to n-HT20 mode, Frequency [MHz] 2412 ,

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Verdict

INFO

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 13:53:53
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2412 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.20	dBm	INFO
Ref. Frequency	--	--	2410.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.20 13.85 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17256	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 13:54:27
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2412 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.28	dBm	INFO
Ref. Frequency	--	--	2413.300	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.28 13.85 20
Start [MHz] Stop [MHz]	2397.000 2427.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-18.74	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-18.74	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 13:55:30
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2412 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.24	dBm	INFO
Ref. Frequency	--	--	2415.100	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.24 13.85 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18438.000	kHz	INFO
T1 99%	2400.000000	--	2402.8009	MHz	PASS
T2 99%	--	2483.500000	2421.2391	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	20936	kHz	INFO
T1 20DB	2400.000000	--	2401.5360	MHz	PASS
T2 20dB	--	2483.500000	2422.4720	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 13:56:09
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2412 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	11.86	dBm	INFO
Ref. Frequency	--	--	2410.600	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.86 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2417.00 MHz	--	--	2.76	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 30 MHz	0	--	-149.82	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:02:52
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2412 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.05	dBm	INFO
Ref. Frequency	--	--	2410.800	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.05 13.85 25
Start [MHz] Stop [MHz]	2392.000 2432.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	15.01	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	15.01	dBm	PASS

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:04:07
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2412 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.77	dBm	INFO
Ref. Frequency	--	--	2413.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.77 13.85 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17556	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:04:41
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2412 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.52	dBm	INFO
Ref. Frequency	--	--	2413.300	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.52 13.85 20
Start [MHz] Stop [MHz]	2397.000 2427.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-18.44	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-18.44	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:05:46
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2412 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.61	dBm	INFO
Ref. Frequency	--	--	2413.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.61 13.85 20
Start [MHz] Stop [MHz]	2392.000 2432.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18014.000	kHz	INFO
T1 99%	2400.000000	--	2403.0049	MHz	PASS
T2 99%	--	2483.500000	2421.0191	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	20476	kHz	INFO
T1 20DB	2400.000000	--	2401.7440	MHz	PASS
T2 20dB	--	2483.500000	2422.2200	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:06:22
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2412 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.01	dBm	INFO
Ref. Frequency	--	--	2411.300	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.01 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2412.75 MHz	--	--	3.18	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 2486.25 MHz	0	--	4.29	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:13:06
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2412 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.88	dBm	INFO
Ref. Frequency	--	--	2413.700	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.88 13.85 25
Start [MHz] Stop [MHz]	2392.000 2432.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	15.19	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	15.19	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	13.01.2024 14:14:20
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg output power SA DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2412 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg power DC corr.	--	--	15.01	dBm	INFO
Ant:2 Avg power DC corr.	--	--	15.19	dBm	INFO
Σ Avg output power DC corr.	--	30	18.11	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	13.01.2024 14:25:23
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg psd DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2412 MHz

RESULT psd

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg psd DC corr	--	--	-18.74	dBm/3kHz	INFO
Ant:2 Avg psd DC corr	--	--	-18.44	dBm/3kHz	INFO
Σ Avg psd DC corr	--	8	-15.58	dBm/3kHz	PASS

Verdict

PASS

NA # Message with SA scan ~

References

TC start	13.01.2024 14:26:08
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	NA NI
Method	
Description	Message with SA Scan n-HT20 mode
Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	13.01.2024 14:26:08
Message	set WLAN2G4 to n-HT20 mode, Frequency [MHz] 2437 ,

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Verdict

INFO

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:28:52
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2437 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	16.21	dBm	INFO
Ref. Frequency	--	--	2433.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.21 14.01 25
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17572	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:29:24
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	16.55	dBm	INFO
Ref. Frequency	--	--	2432.600	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.55 14.01 25
Start [MHz] Stop [MHz]	2422.000 2452.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-15.17	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-15.17	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:30:27
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	16.31	dBm	INFO
Ref. Frequency	--	--	2433.900	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.31 14.01 25
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	19626.000	kHz	INFO
T1 99%	2400.000000	--	2427.4530	MHz	PASS
T2 99%	--	2483.500000	2447.0790	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	25168	kHz	INFO
T1 20dB	2400.000000	--	2426.3360	MHz	PASS
T2 20dB	--	2483.500000	2451.5040	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:31:06
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	16.26	dBm	INFO
Ref. Frequency	--	--	2434.200	MHz	INFO



READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.26 0 35
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2432.00 MHz	--	--	8.30	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 22342.25 MHz	0	--	7.4	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:37:49
Ambit temp [°C] humidity [rel%]	22.4 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	16.08	dBm	INFO
Ref. Frequency	--	--	2439.600	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	26.08 14.01 30
Start [MHz] Stop [MHz]	2417.000 2457.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	20.01	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	20.01	dBm	PASS

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:39:03
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2437 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	16.96	dBm	INFO
Ref. Frequency	--	--	2430.810	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.96 14.01 25
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17584	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:39:36
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	16.84	dBm	INFO
Ref. Frequency	--	--	2443.190	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.84 14.01 25
Start [MHz] Stop [MHz]	2422.000 2452.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-14.5	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-14.5	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:40:41
Ambit temp [°C] humidity [rel%]	22.4 26
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	17.09	dBm	INFO
Ref. Frequency	--	--	2442.490	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.09 14.01 25
Start [MHz] Stop [MHz]	2417.000 2457.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	19010.000	kHz	INFO
T1 99%	2400.000000	--	2427.6329	MHz	PASS
T2 99%	--	2483.500000	2446.6430	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	21148	kHz	INFO
T1 20dB	2400.000000	--	2426.5560	MHz	PASS
T2 20dB	--	2483.500000	2447.7040	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:41:17
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	17.25	dBm	INFO
Ref. Frequency	--	--	2439.000	MHz	INFO



READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.25 0 35
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2432.00 MHz	--	--	8.36	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 24952.75 MHz	0	--	7.11	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:48:00
Ambit temp [°C] humidity [rel%]	22.4 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2437 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	17.21	dBm	INFO
Ref. Frequency	--	--	2435.300	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	27.21 14.01 30
Start [MHz] Stop [MHz]	2417.000 2457.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	20.21	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	20.21	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	13.01.2024 14:49:15
Ambit temp [°C] humidity [rel%]	22.4 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg output power SA DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2437 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg power DC corr.	--	--	20.01	dBm	INFO
Ant:2 Avg power DC corr.	--	--	20.21	dBm	INFO
Σ Avg output power DC corr.	--	30	23.12	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	13.01.2024 14:50:39
Ambit temp [°C] humidity [rel%]	22.4 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg psd DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	True Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2437 MHz

RESULT psd

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg psd DC corr	--	--	-15.17	dBm/3kHz	INFO
Ant:2 Avg psd DC corr	--	--	-14.5	dBm/3kHz	INFO
Σ Avg psd DC corr	--	8	-11.81	dBm/3kHz	PASS

Verdict

PASS

NA # Message with SA scan ~

References

TC start	13.01.2024 14:50:50
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	NA NI
Method	
Description	Message with SA Scan n-HT20 mode
Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	13.01.2024 14:50:50
Message	set WLAN2G4 to n-HT20 mode, Frequency [MHz] 2462

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Verdict

INFO

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:52:28
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2462 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.36	dBm	INFO
Ref. Frequency	--	--	2463.300	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.36 14.14 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17524	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:53:03
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2462 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.81	dBm	INFO
Ref. Frequency	--	--	2460.900	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.81 14.14 20
Start [MHz] Stop [MHz]	2447.000 2477.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-18.58	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-18.58	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:54:06
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2462 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.28	dBm	INFO
Ref. Frequency	--	--	2465.800	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.28 14.14 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18422.000	kHz	INFO
T1 99%	2400.000000	--	2452.7889	MHz	PASS
T2 99%	--	2483.500000	2471.2111	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	20968	kHz	INFO
T1 20DB	2400.000000	--	2451.5120	MHz	PASS
T2 20dB	--	2483.500000	2472.4800	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 14:54:44
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2462 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	11.96	dBm	INFO
Ref. Frequency	--	--	2459.800	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.96 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2464.50 MHz	--	--	3.21	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 24238 MHz	0	--	4.6	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 15:01:27
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2462 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.45	dBm	INFO
Ref. Frequency	--	--	2460.700	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.45 14.14 25
Start [MHz] Stop [MHz]	2442.000 2482.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	15.17	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	15.17	dBm	PASS

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 15:02:42
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2462 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.15	dBm	INFO
Ref. Frequency	--	--	2460.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.15 14.14 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17552	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 15:03:15
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2462 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.06	dBm	INFO
Ref. Frequency	--	--	2460.700	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.06 14.14 20
Start [MHz] Stop [MHz]	2447.000 2477.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-18.6	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-18.6	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 15:04:19
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2462 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.70	dBm	INFO
Ref. Frequency	--	--	2461.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.70 14.14 20
Start [MHz] Stop [MHz]	2442.000 2482.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18026.000	kHz	INFO
T1 99%	2400.000000	--	2452.9809	MHz	PASS
T2 99%	--	2483.500000	2471.0071	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	20476	kHz	INFO
T1 20dB	2400.000000	--	2451.7560	MHz	PASS
T2 20dB	--	2483.500000	2472.2320	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 15:04:56
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2462 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.19	dBm	INFO
Ref. Frequency	--	--	2462.900	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.19 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2460.75 MHz	--	--	2.63	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 24683 MHz	0	--	4.04	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	13.01.2024 15:11:39
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2462 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	12.41	dBm	INFO
Ref. Frequency	--	--	2459.700	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.41 14.14 25
Start [MHz] Stop [MHz]	2442.000 2482.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	14.96	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	14.96	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	13.01.2024 15:12:53
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg output power SA DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2462 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg power DC corr.	--	--	15.17	dBm	INFO
Ant:2 Avg power DC corr.	--	--	14.96	dBm	INFO
Σ Avg output power DC corr.	--	30	18.08	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	13.01.2024 15:13:47
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg psd DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2412
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2462
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2462 MHz

RESULT psd

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg psd DC corr	--	--	-18.58	dBm/3kHz	INFO
Ant:2 Avg psd DC corr	--	--	-18.6	dBm/3kHz	INFO
Σ Avg psd DC corr	--	8	-15.58	dBm/3kHz	PASS

Verdict

PASS

NA # Create group ~

References

TC start	13.01.2024 15:13:57
Ambit temp [°C] humidity [rel%]	22.5 26
System version	4.7.1.5
Standard Version	NA NI
Method	
Description	Create group
Information	

Test Parameter

Group name	n20-mode PS 60_80_58
Clear logging/group	Yes

Verdict

INFO

NA # Message with SA scan ~

References

TC start	16.01.2024 10:24:10
Ambit temp [°C] humidity [rel%]	22.2 27
System version	4.7.1.5
Standard Version	NA NI
Method	
Description	Message with SA Scan n-HT20 mode
Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	16.01.2024 10:24:11
Message	set WLAN2G4 to n-HT20 mode, Frequency [MHz] 2417 ,

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Verdict

INFO

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:26:51
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2417 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.26	dBm	INFO
Ref. Frequency	--	--	2414.900	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.26 13.88 25
Start [MHz] Stop [MHz]	2397.000 2437.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17564	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:27:25
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2417 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.58	dBm	INFO
Ref. Frequency	--	--	2412.300	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.58 13.88 25
Start [MHz] Stop [MHz]	2402.000 2432.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-16.92	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-16.92	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:28:29
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2417 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.33	dBm	INFO
Ref. Frequency	--	--	2419.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.33 13.88 25
Start [MHz] Stop [MHz]	2397.000 2437.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18918.000	kHz	INFO
T1 99%	2400.000000	--	2407.6329	MHz	PASS
T2 99%	--	2483.500000	2426.5510	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	21320	kHz	INFO
T1 20DB	2400.000000	--	2406.3920	MHz	PASS
T2 20dB	--	2483.500000	2427.7120	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:29:08
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2417 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.41	dBm	INFO
Ref. Frequency	--	--	2419.800	MHz	INFO



READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.41 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2410.75 MHz	--	--	6.26	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 2399.75 MHz	0	--	2.89	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:35:52
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2417 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.32	dBm	INFO
Ref. Frequency	--	--	2419.900	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	24.32 13.88 25
Start [MHz] Stop [MHz]	2397.000 2437.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	18.21	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	18.21	dBm	PASS

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:37:08
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2417 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.58	dBm	INFO
Ref. Frequency	--	--	2421.300	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.58 13.88 25
Start [MHz] Stop [MHz]	2397.000 2437.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17580	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:37:42
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2417 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	15.04	dBm	INFO
Ref. Frequency	--	--	2421.700	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.04 13.88 25
Start [MHz] Stop [MHz]	2402.000 2432.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-17.53	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-17.53	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:38:48
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2417 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.55	dBm	INFO
Ref. Frequency	--	--	2419.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.55 13.88 25
Start [MHz] Stop [MHz]	2397.000 2437.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18378.000	kHz	INFO
T1 99%	2400.000000	--	2407.8769	MHz	PASS
T2 99%	--	2483.500000	2426.2551	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	20848	kHz	INFO
T1 20DB	2400.000000	--	2406.6080	MHz	PASS
T2 20dB	--	2483.500000	2427.4560	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:39:26
Ambit temp [°C] humidity [rel%]	22.3 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2417 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.79	dBm	INFO
Ref. Frequency	--	--	2420.100	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.79 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2415.75 MHz	--	--	5.57	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 2399.75 MHz	0	--	5.37	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:46:10
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2417 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.24	dBm	INFO
Ref. Frequency	--	--	2413.800	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	24.24 13.88 25
Start [MHz] Stop [MHz]	2397.000 2437.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	17.72	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	17.72	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	16.01.2024 10:47:26
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg output power SA DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2417 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg power DC corr.	--	--	18.21	dBm	INFO
Ant:2 Avg power DC corr.	--	--	17.72	dBm	INFO
Σ Avg output power DC corr.	--	30	20.98	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	16.01.2024 10:48:09
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg psd DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	False Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2417 MHz

RESULT psd

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg psd DC corr	--	--	-16.92	dBm/3kHz	INFO
Ant:2 Avg psd DC corr	--	--	-17.53	dBm/3kHz	INFO
Σ Avg psd DC corr	--	8	-14.2	dBm/3kHz	PASS

Verdict

PASS

NA # Message with SA scan ~

References

TC start	16.01.2024 10:48:19
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	NA NI
Method	
Description	Message with SA Scan n-HT20 mode
Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	16.01.2024 10:48:19
Message	set WLAN2G4 to n-HT20 mode, Frequency [MHz] 2457

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Verdict

INFO

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:50:19
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2457 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.58	dBm	INFO
Ref. Frequency	--	--	2455.500	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.58 14.13 20
Start [MHz] Stop [MHz]	2437.000 2477.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17580	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:50:52
Ambit temp [°C] humidity [rel%]	22.4 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2457 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.42	dBm	INFO
Ref. Frequency	--	--	2454.600	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.42 14.13 20
Start [MHz] Stop [MHz]	2442.000 2472.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-17.64	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-17.64	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:51:56
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2457 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.33	dBm	INFO
Ref. Frequency	--	--	2455.700	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.33 14.13 20
Start [MHz] Stop [MHz]	2437.000 2477.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18738.000	kHz	INFO
T1 99%	2400.000000	--	2447.6649	MHz	PASS
T2 99%	--	2483.500000	2466.4031	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	21272	kHz	INFO
T1 20dB	2400.000000	--	2446.3680	MHz	PASS
T2 20dB	--	2483.500000	2467.6400	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:52:35
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2457 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.40	dBm	INFO
Ref. Frequency	--	--	2458.300	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.40 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2459.50 MHz	--	--	5.37	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 24879.25 MHz	0	--	6.52	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 10:59:20
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2457 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.38	dBm	INFO
Ref. Frequency	--	--	2458.700	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	23.38 14.13 25
Start [MHz] Stop [MHz]	2437.000 2477.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	17.24	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	17.24	dBm	PASS

Verdict

PASS

FCC 15.247 # Bandwidth 6dB DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 11:00:35
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	FCC 15.247 Bandwidth 6dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2457 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.03	dBm	INFO
Ref. Frequency	--	--	2458.900	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.03 14.13 20
Start [MHz] Stop [MHz]	2437.000 2477.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
DTS Bandwidth (6dB)	500	--	17584	kHz	PASS

Verdict

PASS

FCC 15.247 # Avg psd DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 11:01:09
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.10.5 or.3
Description	FCC 15.247 Avg psd DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2457 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.54	dBm	INFO
Ref. Frequency	--	--	2459.100	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg. psd

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.54 14.13 20
Start [MHz] Stop [MHz]	2442.000 2472.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.003000 0.010000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	334 100 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg psd uncorrected	--	--	-18.34	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg psd DC corrected	--	8	-18.34	dBm/3kHz	PASS

Verdict

PASS

FCC 15.247, ISED RSS247 # Bandwidth 99PCT and 20dB ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 11:02:15
Ambit temp [°C] humidity [rel%]	22.5 27
System version	4.7.1.5
Standard Version	FCC 15.247, ISED RSS247 NI
Method	
Description	FCC 15.247 Bandwidth 99PCT-20dB DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 2457 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.77	dBm	INFO
Ref. Frequency	--	--	2462.990	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.77 14.13 20
Start [MHz] Stop [MHz]	2437.000 2477.000
RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	50 200 10001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	--	--	18246.000	kHz	INFO
T1 99%	2400.000000	--	2447.8849	MHz	PASS
T2 99%	--	2483.500000	2466.1311	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	--	--	20756	kHz	INFO
T1 20dB	2400.000000	--	2446.5880	MHz	PASS
T2 20dB	--	2483.500000	2467.3440	MHz	PASS

Verdict

PASS

FCC 15.247 # TX spurious conducted 30dBc ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 11:02:52
Ambit temp [°C] humidity [rel%]	22.6 27
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	IF DTS then 8.5 DTS emissions in non-restricted frequency bands: Subclause 11.11 of ANSI C63.10 is applicable
Description	FCC 15.247 TX Emissions Conducted 30dBc DTS DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer


Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2457 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	14.03	dBm	INFO
Ref. Frequency	--	--	2455.800	MHz	INFO



TX emissions

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.03 0 30
Start [MHz] Stop [MHz]	24530.000 25030.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	200 25 2001 SWE



TX emissions band zoomed

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Reference @ 2462.00 MHz	--	--	5.24	dBm	INFO
No peaks detected	--	--			PASS
Lowest margin to limit 30 MHz	0	--	-147.75	dB	INFO

Verdict

PASS

FCC 15.247 # Avg output power SA DTS ~ WLAN2G4 n-HT20 mode

References

TC start	16.01.2024 11:09:37
Ambit temp [°C] humidity [rel%]	22.6 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	ANSI C63.10-2013 Chapter 11.9.2.2.2 or .4
Description	FCC 15.247 Avg output power SA DTS - WLAN2G4 n-HT20 mode
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 2457 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	--	--	13.44	dBm	INFO
Ref. Frequency	--	--	2454.200	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




Avg output power SA DTS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	23.44 14.13 25
Start [MHz] Stop [MHz]	2437.000 2477.000

READ SA SETTINGS:

RBW [MHz] VBW [MHz]	0.500000 2.000000
Detector TraceMode	RMS AVER
Sweep: time [ms] count points per Section type	500 100 160 SWE



Avg output power SA DTS

RESULT (Channel power method)

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Avg output power uncorrected	--	--	16.79	dBm	INFO
Duty cycle correction	--	--	0	dB	INFO
Avg power DC corrected	--	30	16.79	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg output power SA DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	16.01.2024 11:10:52
Ambit temp [°C] humidity [rel%]	22.7 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg output power SA DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2457 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg power DC corr.	--	--	17.24	dBm	INFO
Ant:2 Avg power DC corr.	--	--	16.79	dBm	INFO
Σ Avg output power DC corr.	--	30	20.03	dBm	PASS

Verdict

PASS

FCC 15.247 # MIMO Σ Avg psd DTS ~ WLAN2G4 n-HT20 mode 2400-2483.5 MHz

References

TC start	16.01.2024 11:11:45
Ambit temp [°C] humidity [rel%]	22.7 26
System version	4.7.1.5
Standard Version	FCC 15.247 NI
Method	
Description	MIMO Σ FCC Avg psd DTS - WLAN2G4 n-HT20 mode 2400-2483.5 MHz
Information	

EUT Common Settings WLAN2G4

Number of Antenna Ports	2
User Interaction	No

Test Parameter

Technology to test	WLAN2G4 n-HT20 mode
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 2417
Frequency mid to test	False Freq [MHz] 2437
Frequency high to test	True Freq [MHz] 2457
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0.7
Full path name type	None

Equipment

Test at TX 2457 MHz

RESULT psd

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Avg psd DC corr	--	--	-17.64	dBm/3kHz	INFO
Ant:2 Avg psd DC corr	--	--	-18.34	dBm/3kHz	INFO
Σ Avg psd DC corr	--	8	-14.97	dBm/3kHz	PASS

Verdict

PASS

- END OF DOCUMENT -