



L C I E

Bluetooth Classic Template: Release August 08th, 2017

TEST REPORT

N°: 152845-715034-B

Version : 01

Subject

Radio spectrum matters
tests according to standards:
47 CFR Part 15.247 [FB](#)

Issued to

SAGEMCOM BROADBAND SAS
250 Route de l' Empereur
92500 – RUEIL MALMAISON
FRANCE

Apparatus under test

↻ Product	DCIW387 ATN
↻ Trade mark	SAGEMCOM
↻ Manufacturer	SAGEMCOM
↻ Model under test	DCIW387 ATN
↻ Serial number	617510000063
↻ FCC ID	VW3DCIW387

Test date

: January 22, 2018 to January 29, 2018

Test location

Fontenay Aux Roses


Composition of document

76 pages

Document issued on

April 23, 2018

Written by :
Armand MAHOUNGOU
Tests operator



This document shall not be reproduced, except in full, without the written approval of the LCIE. This document contains results related only to the items tested. It does not imply the conformity of the whole production to the items tested. Unless otherwise specified, the decision of conformity takes into account the uncertainty of measurement. This document doesn't anticipate any certification decision.

LCIE

Laboratoire Central des Industries Electriques
Une société de Bureau Veritas

33, Av du Général Leclerc
92266 Fontenay Aux Roses
FRANCE

Tél : +33 1 40 95 60 60
contact@lcie.fr
www.lcie.fr



PUBLICATION HISTORY

Version	Date	Author	Modification
01	February 19, 2018	Armand MAHOUNGOU	Creation of the document



SUMMARY

1.	TEST PROGRAM	4
2.	EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER)	5
3.	OCCUPIED BANDWIDTH	10
4.	20DB EMISSION BANDWIDTH	15
5.	NUMBER OF HOPPING FREQUENCY	20
6.	CARRIER FREQUENCY SEPARATION	25
7.	TIME OF OCCUPANCY	30
8.	DUTY CYCLE	35
9.	MAXIMUM CONDUCTED OUTPUT POWER	40
10.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS AT THE BAND EDGE	45
11.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS	53
12.	AC POWER LINE CONDUCTED EMISSIONS	58
13.	UNWANTED EMISSIONS IN RESTRICTED FREQUENCY BANDS	63
14.	UNCERTAINTIES CHART	76



1. TEST PROGRAM

References

- 47 CFR Part 15.247
- ANSI C63.10-2013
- FCC DA 00-705

Radio requirement:

Clause (47CFR Part 15.247) Test Description	Test result - Comments			
Occupied Bandwidth P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
20dB Bandwidth P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Number of Hopping Frequency P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Carrier Frequency Separation P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Time of Occupancy P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Duty Cycle P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Maximum Conducted Output Power P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Conducted Spurious Emission at the Band Edge P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Unwanted Emissions into Non-Restricted Frequency Bands P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA()	<input type="checkbox"/> NP(1)
AC Power Line Conducted Emission P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA(2)	<input type="checkbox"/> NP(1)
Unwanted Emissions into Restricted Frequency Bands P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Receiver Radiated emissions P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)

This table is a summary of test report, see conclusion of each clause of this test report for detail.

(1): Limited program

(2): EUT not directly or indirectly connected to the AC Power Public Network

PASS: EUT complies with standard's requirement

FAIL: EUT does not comply with standard's requirement

NA: Not Applicable


NP: Test Not Performed

2. EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER)

2.1. HARDWARE IDENTIFICATION (EUT AND AUXILIARIES):

Equipment under test (EUT):
SAGEMCOM DCIW387 ATN

Serial Number: 617510000063



Front face



Back face

Equipment Under Test



Power supply cable



USB – RS232 cable

Equipment Under Test

Inputs/outputs - Cable:

Access	Type	Length used (m)	Declared <3m	Shielded	Under test	Comments
Power supply cable	-	-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-
USB – RS232 cable	-	-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-
Data cable	-	-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-

Auxiliary equipment used during test:

Type	Reference	Sn	Comments
Laptop computer	-	-	Use to set the EUT



Equipment information:

Bluetooth Classic Type:	<input type="checkbox"/> v1.2	<input type="checkbox"/> v2.0	<input type="checkbox"/> v2.1+EDR	<input type="checkbox"/> v3.0+HS
	<input type="checkbox"/> v4.0	<input type="checkbox"/> v4.1	<input checked="" type="checkbox"/> v4.2	
Frequency band:	[2400 – 2483.5] MHz			
Sub-band REC7003:	Annex 3 (a)			
Spectrum Modulation:	<input checked="" type="checkbox"/> FHSS			
Number of Channel:	Maximum:	79	Minimum:	20
Spacing channel:	1MHz			
Channel bandwidth:	1MHz			
Antenna Type:	<input checked="" type="checkbox"/> Integral	<input type="checkbox"/> External	<input type="checkbox"/> Dedicated	
Antenna connector:	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> Temporary for test	
Transmit chains:	<input checked="" type="checkbox"/> 1			<input type="checkbox"/> 2
Beam forming gain:	No			
Receiver chains:	1			
Type of equipment:	<input checked="" type="checkbox"/> Stand-alone	<input type="checkbox"/> Plug-in	<input type="checkbox"/> Combined	
Ad-Hoc mode:	<input type="checkbox"/> Yes		<input checked="" type="checkbox"/> No	
Duty cycle:	<input checked="" type="checkbox"/> Continuous duty	<input type="checkbox"/> Intermittent duty	<input type="checkbox"/> 100% duty	
Equipment type:	<input checked="" type="checkbox"/> Production model		<input type="checkbox"/> Pre-production model	
Operating temperature range:	Tmin:	<input type="checkbox"/> -20°C	<input checked="" type="checkbox"/> 0°C	<input type="checkbox"/> X°C
	Tnom:	20°C		
	Tmax:	<input type="checkbox"/> 35°C	<input type="checkbox"/> 55°C	<input checked="" type="checkbox"/> 40°C
Type of power source:	<input checked="" type="checkbox"/> AC power supply	<input type="checkbox"/> DC power supply	<input type="checkbox"/> Battery	
Operating voltage range:	Vnom:	<input checked="" type="checkbox"/> 120V/60Hz	<input type="checkbox"/> XVdc	

Antenna Characteristic

Antenna assembly	Gain (dBi)	Frequency Band (MHz)	Impedance(Ω)
1	3.6	2400 – 2483.5	50



L C I E

CHANNEL PLAN

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
Cmin: 0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	Cmax: 78	2480
25	2427	52	2454		
26	2428	53	2455		

DATA RATE

Available for EUT	Modulation type	Max. Data Rate (Mbps)	Packet type	Worst Case Modulation
<input type="checkbox"/>	GFSK	1	1-DM1	<input type="checkbox"/>
<input checked="" type="checkbox"/>	GFSK	1	1-DH1	<input checked="" type="checkbox"/>
<input type="checkbox"/>	GFSK	1	1-DM3	<input type="checkbox"/>
<input checked="" type="checkbox"/>	GFSK	1	1-DH3	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	GFSK	1	1-DM5	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	GFSK	1	1-DH5	<input checked="" type="checkbox"/>
<input type="checkbox"/>	GFSK	1	AUX1	<input type="checkbox"/>
<input checked="" type="checkbox"/>	$\pi/4$ DQPSK	2	2-DH1	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	$\pi/4$ DQPSK	2	2-DH3	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	$\pi/4$ DQPSK	2	2-DH5	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	8DPSK	3	3-DH1	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	8DPSK	3	3-DH3	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	8DPSK	3	3-DH5	<input checked="" type="checkbox"/>

2.2. RUNNING MODE


The EUT is set in the following modes during tests:

- Permanent emission with modulation on a fixed channel in the data rate that produced the highest power
- Permanent emission with modulation & hopping in the data rate that produced the highest power
- Permanent reception

Following commands with the specific test software “TERATERM” are used to set the product:

- See document :”SD-20171218 - U44_997950_01 - BT-BLE FCC Notice for certification.pdf” for the command used during test

2.3. EQUIPMENT LABELLING



2.4. EQUIPMENT MODIFICATION

- None Modification:

3. OCCUPIED BANDWIDTH

3.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : January 26, 2018 & January 29, 2018
Ambient temperature : 26 °C & 27 °C
Relative humidity : 48 % & 43 %

3.2. TEST SETUP

- The Equipment Under Test is installed:
 - On a table
 - In an anechoic chamber
- Measurement is performed with a spectrum analyzer in:
 - Conducted Method
 - Radiated Method
- Test Procedure:
 - RSS-Gen Issue 4 § 6.6
 - ANSI C63.10 § 6.9.3



Photograph for Occupied bandwidth



3.1. LIMIT



No Limit

3.2. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2017/09	2018/09
Multi-meter	KEITHLEY	2000	A1242090	2016/06	2018/06
Programmable AC/DC power supply	KIKUSUI	PCR500M	A7040079	2016/06	2018/06
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2017/09	2018/09

Note: In our quality system, the test equipment calibration due is more & less 2 months


3.3. RESULTS



Channel	Occupied Bandwidth (MHz)
Cmin	0,903
Cnom	0,902
Cmax	0,906




L C I E





L C I E



3.4. CONCLUSION

Occupied Bandwidth measurement performed on the sample of the product **SAGEMCOM DCIW387 ATN**, SN: **617510000063**, in configuration and description presented in this test report, show levels compliant to the **47 CFR PART 15.247** limits.

4. 20dB EMISSION BANDWIDTH

4.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : January 29, 2018
Ambient temperature : 26 °C
Relative humidity : 43 %

4.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- FCC DA 00-705 (20dB Bandwidth)
- ANSI C63.10 § 6.9.2



Photograph for 20dB emission bandwidth



4.3. LIMIT

No Limit

4.4. TEST EQUIPMENT LIST


DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2017/09	2018/09
Multi-meter	KEITHLEY	2000	A1242090	2016/06	2018/06
Programmable AC/DC power supply	KIKUSUI	PCR500M	A7040079	2016/06	2018/06
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2017/09	2018/09

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E


4.5. RESULTS






L C I E

$\pi/4$ DQPSK




Cmax



Channel	20dB Bandwidth (MHz)
Cmin	1,351
Cnom	1,349
Cmax	1,351



L C I E



4.6. CONCLUSION

20dB Emission Bandwidth measurement performed on the sample of the product **SAGEMCOM DCIW387 ATN**, SN: **617510000063**, in configuration and description presented in this test report, show levels compliant to the **47 CFR PART 15.247** limits.

5. NUMBER OF HOPPING FREQUENCY

5.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : January 29, 2018
Ambient temperature : 26 °C
Relative humidity : 43 %

5.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- FCC DA 00-705 (Number of Hopping Frequencies)
- ANSI C63.10 § 7.8.3



Photograph for Number of Frequency Hopping



5.3. LIMIT


Number of Hopping Frequencies shall be at least 15 channels

5.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2017/09	2018/09
Multi-meter	KEITHLEY	2000	A1242090	2016/06	2018/06
Programmable AC/DC power supply	KIKUSUI	PCR500M	A7040079	2016/06	2018/06
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2017/09	2018/09


Note: In our quality system, the test equipment calibration due is more & less 2 months

5.5. RESULTS






L C I E





L C I E



5.6. CONCLUSION

Number of Frequency Hopping measurement performed on the sample of the product **SAGEMCOM DCIW387 ATN**, SN: **61751000063**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.

6. CARRIER FREQUENCY SEPARATION

6.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : January 29, 2018
Ambient temperature : 26 °C
Relative humidity : 43 %

6.2. TEST SETUP

- The Equipment Under Test is installed:
 - On a table
 - In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:
 - Conducted Method
 - Radiated Method

- Test Procedure:
 - FCC DA 00-705 (Carrier Frequency Separation)
 - ANSI C63.10 § 7.8.2



Photograph for Carrier Frequency Separation



6.3. LIMIT

Carrier Frequency Separation shall be at least two-thirds of the 20dB Bandwidth

6.4. TEST EQUIPMENT LIST



DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2017/09	2018/09
Multi-meter	KEITHLEY	2000	A1242090	2016/06	2018/06
Programmable AC/DC power supply	KIKUSUI	PCR500M	A7040079	2016/06	2018/06
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2017/09	2018/09

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E



6.5. RESULTS





Channel	Carrier Frequency Separation (MHz)	Limit (MHz)
Cmin	0,999	Minimum 2/3 of 20dB Emission Bandwidth
Cnom	1,0	Minimum 2/3 of 20dB Emission Bandwidth
Cmax	1,0	Minimum 2/3 of 20dB Emission Bandwidth



L C I E



Channel	Carrier Frequency Separation (MHz)	Limit (MHz)
Cmin	1,0	Minimum 2/3 of 20dB Emission Bandwidth
Cnom	1,0	Minimum 2/3 of 20dB Emission Bandwidth
Cmax	1,0	Minimum 2/3 of 20dB Emission Bandwidth



Channel	Carrier Frequency Separation (MHz)	Limit (MHz)
Cmin	1,0	Minimum 2/3 of 20dB Emission Bandwidth
Cnom	1,0	Minimum 2/3 of 20dB Emission Bandwidth
Cmax	1,0	Minimum 2/3 of 20dB Emission Bandwidth

6.6. CONCLUSION

Carrier Frequency Separation measurement performed on the sample of the product **SAGEMCOM DCIW387 ATN**, SN: **617510000063**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.

7. TIME OF OCCUPANCY

7.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : January 29, 2018
Ambient temperature : 26 °C
Relative humidity : 43 %

7.2. TEST SETUP

- The Equipment Under Test is installed:

- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:


- Conducted Method
- Radiated Method

- Test Procedure:

- FCC DA 00-705 (Time of Occupancy)
- ANSI C63.10 § 7.8.4



Photograph for Time of Occupancy



Photograph for Time of Occupancy

7.3. LIMIT



The Time of Occupancy shall not exceed 0.4s within any period of 0.4s multiplied by the number of hopping channels employed

7.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2017/09	2018/09
Multi-meter	KEITHLEY	2000	A1242090	2016/06	2018/06
Programmable AC/DC power supply	KIKUSUI	PCR500M	A7040079	2016/06	2018/06
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2017/09	2018/09

Note: In our quality system, the test equipment calibration due is more & less 2 months

7.5. RESULTS



Packet Type	Burst Length (ms)	Number of Hopping during Time of Occupancy	Time of Occupancy (ms)	Limit of Time of Occupancy (ms)
DH1	0,385	320	123,2	400
DH3	1,64	177	290,28	400
DH5	2,89	99	286,11	400





L C I E

Burst Length				
$\pi/4$ DQPSK				
2DH1	2DH3	2DH5		
Time of Occupancy				
2DH1	2DH3	2DH5		
Packet Type	Burst Length (ms)	Number of Hopping during Time of Occupancy	Time of Occupancy (ms)	Limit of Time of Occupancy (ms)
2DH1	0,392	310	121,52	400
2DH3	1,65	169	278,85	400
2DH5	2,89	87	251,43	400



L C I E



Packet Type	Burst Length (ms)	Number of Hopping during Time of Occupancy	Time of Occupancy (ms)	Limit of Time of Occupancy (ms)
DH1	0,394	320	126,08	400
DH3	1,644	170	279,48	400
DH5	2,89	90	260,1	400

7.6. CONCLUSION

Time of Occupancy measurement performed on the sample of the product **SAGEMCOM DCIW387 ATN**, SN: **617510000063**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.

8. DUTY CYCLE

8.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : January 26, 2018 & January 29, 2018
Ambient temperature : 26 °C & 27 °C
Relative humidity : 48 % & 43 %

8.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- ANSI C63.10 § 11.6



Photograph for Duty Cycle



8.3. LIMIT

None

8.4. TEST EQUIPMENT LIST


DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2017/09	2018/09
Multi-meter	KEITHLEY	2000	A1242090	2016/06	2018/06
Programmable AC/DC power supply	KIKUSUI	PCR500M	A7040079	2016/06	2018/06
RF cable & 20 dB attenuator	Télédyne	920-0202-048	A5329661	2017/09	2018/09

Note: In our quality system, the test equipment calibration due is more & less 2 months




L C I E

8.5. RESULTS






L C I E



Channel	Duty Cycle (%)	Duty Cycle Correction (dB)
Channel	77,20	2,247



L C I E



8.6. CONCLUSION

Duty Cycle measurement performed on the sample of the product **SAGEMCOM DCIW387 ATN**, SN: 61751000063, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.