

RF Exposure Evaluation according to KDB 447498 D01 v06

Report identification number: 1-3977/22-03-23_MPE_FCC

Certification numbers and labeling requirements	
FCC ID	VW3F5688W

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:

Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC

Marco Scigliano
Testing Manager
Radio Communications & EMC

1. MPE at given distance (KDB 447498 D01 General RF Exposure Guidance v06)

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
P = Power input to the antenna
G = Antenna gain
R = Distance to the center of radiation of the antenna
PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

2. EUT technologies

Declared minimum safety distance: **31cm**

SRD Technology	Frequency [MHz]		Reference #	Output Power [dBm]			Power Density [mW/cm ²]		Share of Limit
	f _{Min}	f _{Max}		P _{ERP}	P _{EIRP}	P _{RF Exp}	S _{Result}	S _{Limit}	%
Bluetooth LE	2402	2480	A	N/A	11.7	11.7	0.001	1.000	0.12%
WLAN 2.4 GHz	2412	2462	B	N/A	36.0	36.0	0.329	1.000	32.89%
WLAN U-NII-1	5180	5240	C	N/A	35.2	35.2	0.272	1.000	27.23%
WLAN U-NII-2A	5260	5320	C	N/A	30.0	30.0	0.082	1.000	8.22%
WLAN U-NII-2C	5500	5700	C	N/A	30.1	30.1	0.084	1.000	8.42%
WLAN U-NII-3	5745	5825	C	N/A	36.0	36.0	0.327	1.000	32.74%

Note:

- EIRP Output Power [dBm] = Conducted Output Power [dBm] + Antenna Gain (dBi)
- Worst case of WLAN 5 GHz is marked green.

Referenced Documents:

#	Results from:
A	Test Report 1-3977/22-03-02; pp. 20, 24
B	Test Report 1-3977/22-03-03; pp. 22, 24-26
C	Test Report 1-3977/22-03-04; pp. 30, 33-35

Cellular Technology	Frequency [MHz]		Reference	Output Power [dBm]					Power Density [mW/cm ²]		Share of Limit %
	f _{Min}	f _{Max}		#	Conducted		Radiated		Corrected	S _{Result}	
			P _{Meas}		P _{Max}	P _{ERP}	P _{EIRP}	P _{RF Exp}			
LTE Band 2	1850	1910	D	22.4	24.0	N/A	25.8	27.4	0.05	1.00	4.55%
LTE Band 4	1710	1755	E	22.2	24.0	N/A	27.0	28.8	0.06	1.00	6.28%
LTE Band 5	824	849	F	22.4	24.0	24.3	N/A	28.1	0.05	0.55	9.62%
LTE Band 12	699	716	G	23.0	23.9	23.3	N/A	26.4	0.04	0.47	7.67%
LTE Band 25	1850	1915	H	22.4	24.0	N/A	25.9	27.5	0.05	1.00	4.66%
LTE Band 26	814	849	I, J	22.3	24.0	24.2	N/A	28.1	0.05	0.54	9.74%
LTE Band 41	2496	2690	K	25.5	27.0	N/A	29.8	31.3	0.11	1.00	11.17%
LTE Band 66	1710	1780	L	22.7	24.0	N/A	27.4	28.7	0.06	1.00	6.14%
LTE Band 71	663	698	M	21.5	23.5	22.6	N/A	26.8	0.04	0.44	8.86%
5G n25	1850	1915	N	24.5	25.0	N/A	28.0	28.5	0.06	1.00	5.81%
5G n41	2496	2690	O	28.2	28.5	N/A	32.1	32.4	0.14	1.00	14.39%
5G n66	1710	1780	P	24.5	25.0	N/A	29.2	29.7	0.08	1.00	7.66%
5G n71	663	698	Q	24.2	25.0	25.3	N/A	28.3	0.06	0.44	12.52%
5G n77	3450	3550	R	25.8	26.5	N/A	30.0	30.7	0.10	1.00	9.73%
5G n77	3550	3700	R		18.0	N/A		18.0	0.01	1.00	0.52%
5G n77	3700	3980	R	25.8	26.5	N/A	30.0	30.7	0.10	1.00	9.73%
LTE CA_41_C	2496	2690	S	25.2	27.0	N/A	29.5	31.3	0.11	1.00	11.17%
LTE CA_2A_4A	N/A	N/A	D, E	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10.83%
LTE CA_2A_12A	N/A	N/A	D, G	N/A	N/A	N/A	N/A	N/A	N/A	N/A	12.22%
LTE CA_2A_66A	N/A	N/A	D, L	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10.69%
LTE CA_12A_66A	N/A	N/A	G, L	N/A	N/A	N/A	N/A	N/A	N/A	N/A	13.81%

Note:

- Max rated conducted output power taken from customer's tune up info as attached in this filing.
- Worst case is marked green.

Referenced Documents:

#	Results from:
D	Test Report 1-3977/22-03-06; pp. 20-23
E	Test Report 1-3977/22-03-07; pp. 19-22
F	Test Report 1-3977/22-03-08; pp. 14-16
G	Test Report 1-3977/22-03-09; pp. 19-21
H	Test Report 1-3977/22-03-10; pp. 20-23
I	Test Report 1-3977/22-03-11; pp. 14-17
J	Test Report 1-3977/22-03-12; pp. 17-19
K	Test Report 1-3977/22-03-13; pp. 20-22
L	Test Report 1-3977/22-03-15; pp. 19-22
M	Test Report 1-3977/22-03-16; pp. 18-21
N	Test Report 1-3977/22-03-17; pp. 20-23
O	Test Report 1-3977/22-03-18; pp. 20-25 & 27
P	Test Report 1-3977/22-03-19; pp. 19-22
Q	Test Report 1-3977/22-03-20; pp. 19-21
R	Test Report 1-3977/22-03-21; pp. 22-30 (3450-3550 MHz) & 34-42 (3550-3700 MHz)
S	Test Report 1-3977/22-03-14; pp. 13-17

3. Collocation overview:

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modeled, or measured field strengths or power density.

Technology	Share of Limit [%]
5G n41	14.39%
Bluetooth LE	0.12%
WLAN 2.4 GHz	32.89%
WLAN U-NII-3	32.74%
Sum	80.14%

4. Conclusion

This prediction demonstrates the following:

The power density levels for FCC at a distance of 31 cm are below the maximum levels allowed by regulations.

Conclusion: RF exposure evaluation is not required.