

FCC §15.247 (i), §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Standard Applicable

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Test Data

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally *numeric* gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For 802.11b:

Maximum peak output power at antenna input terminal: 17.49 (dBm)

Maximum peak output power at antenna input terminal: 56.105 (mW)

Prediction distance: 20 (cm)

Predication frequency: 2437 (MHz)

Antenna Gain (typical): 1.8 (dBi)

Antenna Gain (typical): 1.51 (numeric)

The power density at predication frequency at 20 cm: 0.0168 (mW/cm²)

For 802.11g:

Maximum peak output power at antenna input terminal: 16.42 (dBm)

Maximum peak output power at antenna input terminal: 43.85 (mW)

Prediction distance: 20 (cm)

Predication frequency: 2437 (MHz)

Antenna Gain (typical): 1.8 (dBi)

Antenna Gain (typical): 1.51 (numeric)

The power density at predication frequency at 20 cm: 0.0132 (mW/cm²)

Result

MPE limit for General Population/Uncontrolled exposure at prediction frequency: 1.0 (mW/cm²);

For 802.11b, $0.0168 \text{ (mW/cm}^2\text{)} < 1.0 \text{ (mW/cm}^2\text{)}$

For 80211g, $0.0132 \text{ (mW/cm}^2\text{)} < 1.0 \text{ (mW/cm}^2\text{)}$

The predicted power density level at 20 cm is s below the uncontrolled exposure limit of 1.0 mw/cm^2 ,
The EUT is used at least 20 cm away from user's body. It is determined as mobile equipment and
complies with the MPE limit.