



Neutron Engineering Inc.

FCC RF EXPOSURE REPORT

FCC ID: VW3FAST4320US

Project No. : 1211C023
Equipment : Wireless xDSL Bonding Router
Model : F@ST 4320 US
Applicant : SAGEMCOM BROADBAND SAS
Address : 250 Route de l'Empereur - 92848 RUEIL
MALMAISON CEDEX- FRANCE
According: : FCC Guidelines for Human Exposure IEEE C95.1

Tested by:

Neutron Engineering Inc. EMC Laboratory

Date of Receipt: Nov. 05, 2012

Date of Test:

Nov. 05, 2012 ~ Nov. 30, 2012

Testing Engineer :

David Mao
(David Mao)

Technical Manager :

Leo Hung
(Leo Hung)

Authorized Signatory :

Steven Lu
(Steven Lu)

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	Airgain)))	N2430GNS	Embedded Antenna	N/A	5
2	Airgain)))	N2430GNS	Embedded Antenna	N/A	5

This EUT supports MIMO 2T2R, All transmit signals are completely uncorrelated, then Directional gain = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/N]$ dBi , that is Directional gain=5;

TEST RESULTS

EUT:	Wireless xDSL Bonding Router	Model Name :	F@ST 4320 US
Temperature:	24 °C	Relative Humidity:	60 %
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX B MODE CH01/CH06/CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	18.34	68.2339	0.04294873	1	Complies
5	3.1623	17.75	59.5662	0.03749302	1	Complies
5	3.1623	17.56	57.0164	0.03588809	1	Complies



Neutron Engineering Inc.

EUT:	Wireless xDSL Bonding Router	Model Name :	F@ST 4320 US
Temperature:	24 °C	Relative Humidity:	60 %
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX G MODE CH01/CH06/CH11		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	20.76	119.1242	0.07498085	1	Complies
5	3.1623	20.39	109.3956	0.06885736	1	Complies
5	3.1623	20.96	124.7384	0.07851459	1	Complies

EUT:	Wireless xDSL Bonding Router	Model Name :	F@ST 4320 US
Temperature:	24 °C	Relative Humidity:	60 %
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N20MHz MODE CH01/CH06/CH11-ANT1+ANT2		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	20.82	120.7814	0.07602394	1	Complies
5	3.1623	21.07	127.9381	0.08052864	1	Complies
5	3.1623	20.85	121.6186	0.07655091	1	Complies

EUT:	Wireless xDSL Bonding Router	Model Name :	F@ST 4320 US
Temperature:	24 °C	Relative Humidity:	60 %
Pressure:	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX N40MHz MODE CH03/CH06/CH09-ANT1+ANT2		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
5	3.1623	18.63	72.9458	0.04591455	1	Complies
5	3.1623	18.43	69.6627	0.04384806	1	Complies
5	3.1623	18.31	67.7642	0.04265308	1	Complies