



L C I E

Bluetooth Low Energy Template: Release August 08th, 2017

TEST REPORT

N°: 157205-726501-A

Version : 02

Subject

Radio spectrum matters
tests according to standards:
47 CFR Part 15.247 [fb](#)

Issued to

SAGEMCOM BROADBAND SAS
250 Route de l' Empereur
92500 – RUEIL MALMAISON
FRANCE

Apparatus under test

- ↻ Product
- ↻ Trade mark
- ↻ Manufacturer
- ↻ Model under test
- ↻ Serial number
- ↻ FCC ID

Sound Box
Sagemcom®
SAGEMCOM
Sound Box SBDV01
253770742
VW3SBDV01

Test date

September 13, 2018 to October 2, 2018

Test location

Fontenay Aux Roses

Test Site

6230B-1

Composition of document

61 pages

Document issued on

November 19, 2018

Written by :
Armand MAHOUNGOU
Tests operator



This document shall not be reproduced, except in full, without the written approval of the LCIE. This document contains results related only to the items tested. It does not imply the conformity of the whole production to the items tested. Unless otherwise specified, the decision of conformity takes into account the uncertainty of measurement. This document doesn't anticipate any certification decision.

LCIE

Laboratoire Central des Industries Electriques
Une société de Bureau Veritas

33, Av du Général Leclerc
92266 Fontenay Aux Roses
FRANCE

Tél : +33 1 40 95 60 60
contact@lcie.fr
www.lcie.fr



PUBLICATION HISTORY

Version	Date	Author	Modification
01	October 8, 2018	Armand MAHOUNGOU	Creation of the document
02	November 19, 2018	Armand MAHOUNGOU	Customer request withdraw all picture of the EUT from test report Add clarification on limit P29/62 & 33/62 Add conducted measurement at 240V / 50 Hz P41-42/62



SUMMARY

1.	TEST PROGRAM	4
2.	EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER)	5
3.	OCCUPIED BANDWIDTH	8
4.	6DB EMISSION BANDWIDTH	12
5.	DUTY CYCLE	16
6.	MAXIMUM CONDUCTED OUTPUT POWER	20
7.	POWER SPECTRAL DENSITY	24
8.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS AT THE BAND EDGE	28
9.	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS	32
10.	AC POWER LINE CONDUCTED EMISSIONS	36
11.	UNWANTED EMISSIONS IN RESTRICTED FREQUENCY BANDS	43
12.	UNCERTAINTIES CHART	61



1. TEST PROGRAM

References

- 47 CFR Part 15.247
- ANSI C63.10-2013

Radio requirement:

Clause (47CFR Part 15.247) Test Description	Test result - Comments			
Occupied Bandwidth P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
6dB Bandwidth P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA()	<input type="checkbox"/> NP(1)
Duty Cycle P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Maximum Conducted Output Power P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Power Spectral Density P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Conducted Spurious Emission at the Band Edge P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA()	<input type="checkbox"/> NP(1)
Unwanted Emissions into Non-Restricted Frequency Bands P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA()	<input type="checkbox"/> NP(1)
AC Power Line Conducted Emission P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA(2)	<input type="checkbox"/> NP(1)
Unwanted Emissions into Restricted Frequency Bands P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
Receiver Radiated emissions P	<input checked="" type="checkbox"/> PASS	<input type="checkbox"/> FAIL	<input type="checkbox"/> NA	<input type="checkbox"/> NP(1)
This table is a summary of test report, see conclusion of each clause of this test report for detail.				

(1): Limited program

(2): EUT not directly or indirectly connected to the AC Power Public Network

PASS: EUT complies with standard's requirement

FAIL: EUT does not comply with standard's requirement

NA: Not Applicable

NP: Test Not Performed



2. EQUIPMENT UNDER TEST: CONFIGURATION (DECLARED BY PROVIDER)

2.1. HARDWARE IDENTIFICATION (EUT AND AUXILIARIES):

Equipment under test (EUT):

Sagemcom® Sound Box SBDV01

Power supply : NBC80A200400M2

Serial Number: 253770742

Inputs/outputs - Cable:

Access	Type	Length used (m)	Declared <3m	Shielded	Under test	Comments
Cable	Power supply	-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-
Ethernet cable	-	-	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	-

Auxiliary equipment used during test:

Type	Reference	Sn	Comments
Laptop computer	-	-	-

Equipment information:

Bluetooth LE Type:	<input checked="" type="checkbox"/> BLE	<input type="checkbox"/> v4.0	<input type="checkbox"/> v4.1	<input checked="" type="checkbox"/> v4.2	<input checked="" type="checkbox"/> v5.0
Frequency band:	[2400 – 2483.5] MHz				
Number of Channel:	40				
Spacing channel:	2MHz				
Channel bandwidth:	1MHz for 4.2 / 2MHz for 5.0				
Antenna Type:	<input checked="" type="checkbox"/> Integral	<input type="checkbox"/> External		<input type="checkbox"/> Dedicated	
Antenna connector:	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No		<input type="checkbox"/> Temporary for test	
Transmit chains:	1				
Receiver chains	Single antenna				
Type of equipment:	<input checked="" type="checkbox"/> Stand-alone	<input type="checkbox"/> Plug-in		<input type="checkbox"/> Combined	
Ad-Hoc mode:	<input type="checkbox"/> Yes			<input checked="" type="checkbox"/> No	
Duty cycle:	<input checked="" type="checkbox"/> Continuous duty	<input type="checkbox"/> Intermittent duty		<input type="checkbox"/> 100% duty	
Equipment type:	<input checked="" type="checkbox"/> Production model			<input type="checkbox"/> Pre-production model	
Operating temperature range:	Tmin:	<input type="checkbox"/> -20°C	<input checked="" type="checkbox"/> 0°C		<input type="checkbox"/> X°C
	Tnom:	20°C			
	Tmax:	<input type="checkbox"/> 35°C	<input type="checkbox"/> 55°C		<input checked="" type="checkbox"/> 40°C
Type of power source:	<input checked="" type="checkbox"/> AC power supply	<input type="checkbox"/> DC power supply		<input type="checkbox"/> Battery	
Operating voltage range:	Vnom:	<input checked="" type="checkbox"/> 120V/60Hz		<input type="checkbox"/> X Vdc	
	Vnom:	<input checked="" type="checkbox"/> 240V/50Hz		<input type="checkbox"/> X Vdc	

Antenna Characteristic

Antenna assembly	Gain (dBi)	Frequency Band (MHz)	Impedance(Ω)
1	4.72	2400 – 2483.5	50



L C I E

CHANNEL PLAN

Channel	Frequency (MHz)	Channel	Frequency (MHz)
Cmin: 0	2402	Cmid: 20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	Cmax: 39	2480

DATA RATE

Data Rate (Mbps)	Modulation Type	Worst Case Modulation
1	GFSK	<input checked="" type="checkbox"/>

2.2. RUNNING MODE


The EUT is set in the following modes during tests:


- Permanent emission with modulation on a fixed channel in the data rate that produced the highest power
- Permanent reception

Following commands with the specific test software "Tera-Term" are used to set the product:

- See document: 998050_02_Bluetooth test commands of PONY 2,4GHz, for the commands used during test.

2.3. EQUIPMENT LABELLING



Factory S/N Code barre type 128	Code barre type 128	 LISTED I.T.E. E308616	SAGEMCOM Sound Box SBDV01 253770742-ind 20V 4A Date Code: WW/YY SSID : amplify-CCDDEE Made in CZECH Republic
	MSO Part Number: 12345		
	Code barre type 128		
	SGC S/N: 123456789012		
MAC Address : aa:bb:cc:dd:ee	FCC ID: VW3SBDV01	Manufactured under license from Dolby Laboratories. Dolby, Dolby Audio and the double-D symbol are trademarks of Dolby Laboratories.	
TYM S/N : XXXXXXXXXX			

2.4. EQUIPMENT MODIFICATION

- None Modification:


3. OCCUPIED BANDWIDTH

3.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : September 25, 2018
Ambient temperature : 28 °C
Relative humidity : 48 %

3.2. TEST SETUP

- The Equipment Under Test is installed:
 - On a table
 - In an anechoic chamber
- Measurement is performed with a spectrum analyzer in:
 - Conducted Method
 - Radiated Method
- Test Procedure:
 - ANSI C63.10 § 6.9.2



Photograph for Occupied bandwidth



3.1. LIMIT

None

3.2. TEST EQUIPMENT LIST


DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2016/11	2018/11
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Cable	TELEDYNE	920-0202-048	A5329674	2017/10	2018/10

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E


3.3. RESULTS






L C I E

Occupied Bandwidth for BLE 5.0



Cmax



Channel	Occupied Bandwidth (MHz)
Cmin	2.049
Cnom	2.049
Cmax	2.048

3.1. CONCLUSION

Occupied Channel Bandwidth measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.

4. 6DB EMISSION BANDWIDTH

4.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : September 25, 2018
Ambient temperature : 28 °C
Relative humidity : 48 %

4.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- ANSI C63.10 § 11.8.1
- ANSI C63.10 § 11.8.2



Photograph for 6dB emission bandwidth



4.3. LIMIT

The 6dB bandwidth shall be at least 500kHz

4.4. TEST EQUIPMENT LIST



DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2016/11	2018/11
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Cable	TELEDYNE	920-0202-048	A5329674	2017/10	2018/10

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

4.5. RESULTS




Channel	6dB Emission Bandwidth (MHz)	Limit (MHz)
Cmin	0.677	Minimum 0.5
Cnom	0.674	Minimum 0.5
Cmax	0.676	Minimum 0.5




L C I E

6dB Emission Bandwidth for BLE 5.0



Cmax



Channel	6dB Emission Bandwidth (MHz)	Limit (MHz)
Cmin	0.914	Minimum 0.5
Cnom	0.871	Minimum 0.5
Cmax	0.865	Minimum 0.5

4.6. CONCLUSION

6dB Emission Bandwidth measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.

5. DUTY CYCLE

5.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : September 25, 2018
Ambient temperature : 28 °C
Relative humidity : 48 %

5.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- ANSI C63.10 § 11.6 b)



Photograph for Duty Cycle



5.3. LIMIT

None

5.4. TEST EQUIPMENT LIST


DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2016/11	2018/11
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Cable	TELEDYNE	920-0202-048	A5329674	2017/10	2018/10

Note: In our quality system, the test equipment calibration due is more & less 2 months




L C I E

5.5. RESULTS





L C I E



5.6. CONCLUSION

Duty Cycle measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.

6. MAXIMUM CONDUCTED OUTPUT POWER

6.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : September 25, 2018
Ambient temperature : 28 °C
Relative humidity : 48 %

6.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- ANSI C63.10 § 11.9.1.1 (for BLE 5.0)
- ANSI C63.10 § 11.9.2.2.2 (for BLE 4.2)



Photograph for Maximum Conducted Output Power



6.3. LIMIT

Maximum Conducted Output power:
2400MHz-2483.5MHz: Shall not exceed 30dBm
Limits are reduced by G-6dBi if Overall Antenna Gain above 6dBi

6.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2016/11	2018/11
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Cable	TELEDYNE	920-0202-048	A5329674	2017/10	2018/10



Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

6.5. RESULTS

Maximum Conducted Output Power for BLE 4.2




Channel	Offset Cable + Att (dB)	Antenna Gain (dBi)	Maximum Conducted Power (dBm)	Limit (dBm)
Cmin	21.10	3	10.84	30
Cnom	21.10	3	10.78	30
Cmax	21.10	3	10.59	30




L C I E

Maximum Conducted Output Power for BLE 5.0


Cmin



Cnom



Cmax



Channel	Offset Cable + Att (dB)	Antenna Gain (dBi)	Maximum Conducted Power (dBm)	Limit (dBm)
Cmin	21.10	3	10.34	30
Cnom	21.10	3	10.34	30
Cmax	21.10	3	10.25	30

6.6. CONCLUSION

Maximum Conducted Output Power measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.

7. POWER SPECTRAL DENSITY

7.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : September 25, 2018
Ambient temperature : 28 °C
Relative humidity : 48 %

7.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- ANSI C63.10 § 11.10.2 (for BLE 5.0)
- ANSI C63.10 § 11.10.3 (for BLE 4.2)



Photograph for Power Spectral Density



7.3. LIMIT

Power Spectral Density:

2400MHz-2483.5MHz: Shall not exceed 8dBm/3kHz

Limits are reduced by G-6dBi if Overall Antenna Gain above 6dBi

7.4. TEST EQUIPMENT LIST



DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2016/11	2018/11
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Cable	TELEDYNE	920-0202-048	A5329674	2017/10	2018/10

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

7.5. RESULTS





Channel	Offset Cable + Att (dB)	Antenna Gain (dBi)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
Cmin	21.10	3	6.55	8
Cnom	21.10	3	6.47	8
Cmax	21.10	3	6.29	8



L C I E

Power Spectral Density for BLE 5.0



Channel	Offset Cable + Att (dB)	Antenna Gain (dBi)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
Cmin	21.10	3	5.52	8
Cnom	21.10	3	5.53	8
Cmax	21.10	3	5.44	8

7.6. CONCLUSION

Power Spectral Density measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant to the 47 CFR PART 15.247** limits.

8. UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS AT THE BAND EDGE

8.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : September 25, 2018
Ambient temperature : 28 °C
Relative humidity : 48 %

8.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- ANSI C63.10 § 11.11



Photograph for Unwanted Emission into non-restricted frequency bands at the band edge



8.3. LIMIT

All Spurious Emissions must be at least 20dB below the Fundamental Radiator Level at the Band Edge Edge “2400MHz & 2483,5MHz” for BLE 5.0

All Spurious Emissions must be at least 30dB below the Fundamental Radiator Level at the Band Edge Edge “2400MHz & 2483,5MHz” for BLE 4.2

8.4. TEST EQUIPMENT LIST


DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESR 7	A2642023	2016/11	2018/11
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Cable	TELEDYNE	920-0202-048	A5329674	2017/10	2018/10

Note: In our quality system, the test equipment calibration due is more & less 2 months




L C I E

8.5. RESULTS





L C I E



8.6. CONCLUSION

Unwanted Emission into non-restricted frequency bands at the band edge measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **Select Result** to the **47 CFR PART 15.247** limits.

9. UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS

9.1. TEST CONDITIONS

Test performed by : Armand MAHOUNGOU
Date of test : October 1, 2018
Ambient temperature : 28 °C
Relative humidity : 49 %

9.2. TEST SETUP

- The Equipment Under Test is installed:


- On a table
- In an anechoic chamber

- Measurement is performed with a spectrum analyzer in:

- Conducted Method
- Radiated Method

- Test Procedure:

- ANSI C63.10 § 11.11



Photograph for Unwanted Emission into non-restricted frequency bands



9.3. LIMIT

All Spurious Emissions must be at least 20 below the Fundamental Radiator Level for BLE 5.0

All Spurious Emissions must be at least 30 below the Fundamental Radiator Level for BLE 4.2

9.4. TEST EQUIPMENT LIST


DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESI40 1088 740K40	A2642010	2018/07	2020/07
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Cable	Télédyne	084-0555-2MTR	A5329758	2017/10	2018/10
Attenuator 3dB	WEINSCHEL	WA54-3-12	A7122223	2017/10	2018/10

Note: In our quality system, the test equipment calibration due is more & less 2 months



L C I E

9.5. RESULTS



Frequency (MHz)	Level (dBm)	Level (dBc)	Limit (dBc)
2402	2.46		
4804	-56.79	54.33	30
7206	-57.80	55.34	30
9607	-75.65	73.19	30
16814	-76.38	73.92	30
2440	2.27		
4882	-56.33	54.06	30
7323	-59.76	57.49	30
9763	-78.05	75.78	30
17086	-74.64	72.37	30
2480	2.20		
4960	-58.95	56.75	30
7440	-60.35	58.15	30
9920	-78.00	75.80	30
17360	-72.35	70.15	30



L C I E

BLE 5.0


Cmin/Cnom/Cmax

Description Sous-bande 1

Fréquences: 30 MHz - 25 GHz (Mode: Lin, Pas: 100 kHz)

Réglages: RBW: 100kHz, VBW: 300kHz, Durée balayage : 1 ms/Pts, Atténuation : Auto, Nombre de Balayages : 1, Preamp : Off, LN Preamp : Off, Preselecte

— Mes.Peak Cnom
— Mes.Peak Cmax
— Mes.Peak -Cnom



Frequency (MHz)	Level (dBm)	Level (dBc)	Limit (dBc)
2402	2.35		
4804	-56.05	53.70	20
7206	-56.47	54.12	20
9607	-74.50	72.15	20
16814	-75.39	73.04	20
2440	2.32		
4882	-55.58	53.26	20
7323	-58.70	56.38	20
9763	-76.95	74.63	20
17086	-73.02	70.70	20
2480	2.23		
4960	-58.39	56.16	20
7440	-59.30	53.07	20
9920	-77.30	75.07	20
17360	-70.31	68.08	20

9.6. CONCLUSION

Unwanted Emission into non-restricted frequency bands measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant** to the **47 CFR PART 15.247** limits.


10. AC POWER LINE CONDUCTED EMISSIONS

10.1. TEST CONDITIONS


Test performed by : Armand MAHOUNGOU
Date of test : September 24, 2018
Ambient temperature : 23 °C
Relative humidity : 45 %

10.2. TEST SETUP

The product has been tested according to ANSI C63.10 (2013) method. The EUT is placed on the ground reference plane, at 80cm from the LISN. The distance between the EUT and the vertical ground plane is 40cm. Auxiliaries are powered by another LISN. The cable has been shorted to 1meter length. The EUT is powered through the LISN. Measurement is made with a receiver in peak mode. This was followed by a Quasi-Peak, i.e. CISPR measurement for any strong signal. If the average limit is met when using a Quasi-Peak detector, the EUT shall be deemed to meet both limits and measurement with the average detector is unnecessary. The LISN (measure) is $50\Omega / 50\mu\text{H}$. Interconnecting cables and equipment's were moved to position that maximized emission.



Photograph for AC Power Line Conducted Emissions (Front view)



Photograph for AC Power Line Conducted Emissions (Rear view)

10.3. LIMIT

Quasi-Peak

0,15kHz to 0,5MHz: 66dB μ V to 56dB μ V*

0,5MHz to 5MHz: 56dB μ V

5MHz to 30MHz: 60dB μ V

Average

0,15kHz to 0,5MHz: 56dB μ V to 46dB μ V*

0,5MHz to 5MHz: 46dB μ V

5MHz to 30MHz: 50dB μ V

*Decreases with the logarithm of the frequency

10.4. TEST EQUIPMENT LIST

Description	Constructor	Model	N°	Cal. Date	Cal. Due
EMI Receiver	ROHDE & SCHWARZ	ESU26	A2642018	2016/10	2018/10
RSIL	ROHDE & SCHWARZ	ENV215	C2320162	2018/01	2019/01
Cable	-	-	A5329712	2018/03	2019/03

Note: In our quality system, the test equipment calibration due is more & less 2 months

10.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION

None Divergence:

10.6. RESULTS

BLE 4.2 120V / 60Hz

Phase


Description Sous-bande 1

Fréquences: 150 kHz - 30 MHz (Mode: Lin, Pas: 5 kHz)

Réglages: RBW: 9kHz, VBW: Auto, Durée balayage: 50 ms/Pts, Atténuation: 10 dB, Nombre de Balayages: 1, Preamp: Off, LN Preamp: Off, Preselecteur: On

Ligne: Phase 1

- FCC/FCC 15.107 - Classe: B - Moyenne/
- FCC/FCC 15.107 - Classe: B - QCrête/
- FCC/FCC 15.207 - Classe: B - Moyenne/
- FCC/FCC 15.207 - Classe: B - QCrête/
- Mes. Peak (Phase 1)
- Mes. Avg (Phase 1)



Line


Description Sous-bande 2

Fréquences: 150 kHz - 30 MHz (Mode: Lin, Pas: 5 kHz)

Réglages: RBW: 9kHz, VBW: Auto, Durée balayage: 50 ms/Pts, Atténuation: 10 dB, Nombre de Balayages: 1, Preamp: Off, LN Preamp: Off, Preselecteur: On

Ligne: Neutre

- FCC/FCC 15.107 - Classe: B - Moyenne/
- FCC/FCC 15.107 - Classe: B - QCrête/
- FCC/FCC 15.207 - Classe: B - Moyenne/
- FCC/FCC 15.207 - Classe: B - QCrête/
- Mes. Peak (Neutre)
- Mes. Avg (Neutre)





L C I E

Phase Line BLE 4.2 120V / 60Hz

Frequency (MHz)	Peak Level (dB μ V)	Quasi-Peak Level (dB μ V)	Quasi-Peak Limit (dB μ V)	Margin Quasi-Peak (dB μ V)	Average Level (dB μ V)	Average Limit (dB μ V)	Margin Average (dB μ V)
0.41	41.9	-	57.65	15,75	32.7	47.65	15,95
2.305	32.83	-	56	23.17	22.14	46	23.86
3.840	33.31	-	56	24.64	23.16	46	22.84
23.13	30.38	-	60	29.62	20.76	50	29.24
26.11	30.63	-	60	29.37	21.37	50	28.63
29.23	30.46	-	60	29.54	21.82	50	28.18

Neutral Line BLE 4.2 120V / 60Hz

Frequency (MHz)	Peak Level (dB μ V)	Quasi-Peak Level (dB μ V)	Quasi-Peak Limit (dB μ V)	Margin Quasi-Peak (dB μ V)	Average Level (dB μ V)	Average Limit (dB μ V)	Margin Average (dB μ V)
0.41	45.8	-	57.65	11.85	38.56	47.65	9.09
0.77	35.45	-	56	20.55	26.86	46	19.14
2.305	33.83	-	56	22.17	22.37	46	23.63
23.13	30.69	-	60	29.31	21.51	50	28.49
26.11	30.27	-	60	29.73	21.52	50	28.48
29.23	30.01	-	60	29.99	21.61	50	28.39



L C I E

BLE 4.2 240V / 50Hz

Phase


Description Sous-bande 1

Fréquences: 150 kHz - 30 MHz (Mode: Lin, Pas: 5 kHz)

Réglages: RBW: 9kHz, VBW: Auto, Durée balayage : 50 ms/Pts, Atténuation : 10 dB, Nombre de Balayages : 1, Preamp : Off, LN Preamp : Off, Preselecteur: On

Ligne:Phase 1

- FCC/FCC 15.107 - Classe:B - Moyenne/
- FCC/FCC 15.107 - Classe:B - QCrête/
- Mes.Peak (Phase 1)
- Mes.Avg (Phase 1)



Line


Description Sous-bande 2

Fréquences: 150 kHz - 30 MHz (Mode: Lin, Pas: 5 kHz)

Réglages: RBW: 9kHz, VBW: Auto, Durée balayage : 50 ms/Pts, Atténuation : 10 dB, Nombre de Balayages : 1, Preamp : Off, LN Preamp : Off, Preselecteur: On

Ligne:Neutre

- FCC/FCC 15.107 - Classe:B - Moyenne/
- FCC/FCC 15.107 - Classe:B - QCrête/
- Mes.Peak (Neutre)
- Mes.Avg (Neutre)



Phase Line BLE 4.2 240V / 50Hz							
Frequency (MHz)	Peak Level (dB μ V)	Quasi-Peak Level (dB μ V)	Quasi-Peak Limit (dB μ V)	Margin Quasi-Peak (dB μ V)	Average Level (dB μ V)	Average Limit (dB μ V)	Margin Average (dB μ V)
0.44	37.06	-	57.06	20.0	30.17	47.06	16.89
2.305	27.27	-	56	28.73	20.89	46	25.11
3.840	29.32	-	56	26.68	23.89	46	22.11
13.05	31.02	-	60	28.98	22.62	50	27.38
16.13	27.80	-	60	20.80	23.12	50	26.88
28.22	35.02	-	60	24.98	22.11	50	27.89

Neutral Line BLE 4.2 240V / 50Hz							
Frequency (MHz)	Peak Level (dB μ V)	Quasi-Peak Level (dB μ V)	Quasi-Peak Limit (dB μ V)	Margin Quasi-Peak (dB μ V)	Average Level (dB μ V)	Average Limit (dB μ V)	Margin Average (dB μ V)
0.44	34.74	-	57.06	22.32	27.59	47.06	19.47
2.305	27.75	-	56	28.25	23.37	46	22.63
3.840	29.88	-	56	26.12	24.91	46	21.09
13.05	32.30	-	60	27.70	25.23	50	24.77
16.13	33.12	-	60	26.88	24.86	50	25.14
28.22	34.82	-	60	25.18	22.33	50	27.67

10.7. CONCLUSION

Ac Power Line Conducted Emission measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant** to the 47 CFR PART 15.247 limits.

11. UNWANTED EMISSIONS IN RESTRICTED FREQUENCY BANDS

11.1. TEST CONDITIONS


Test performed by : Armand MAHOUNGOU
Date of test : October 1, 2018
Ambient temperature : 28 °C
Relative humidity : 49 %

11.2. TEST SETUP


The product has been tested according to ANSI C63.10 (2013).

Test is performed in parallel, perpendicular and ground parallel axis with a loop antenna below 30MHz. Measurement bandwidth was 200Hz below 150kHz and 9kHz between 150kHz & 30MHz. The level has been maximised by the turntable rotation of 360 degrees range on the 3 axis of EUT. Antenna height was 1m. The EUT is placed **in a semi-anechoic chamber**. Distance between measuring antenna and the EUT is **3m**.


Test is performed in horizontal (H) and vertical (V) polarization with **bilog** between 30MHz & 1GHz and with a horn antenna above 1GHz. Measurement bandwidth was 120kHz below 1GHz and 1MHz above 1GHz. The level has been maximised by the turntable rotation of 360 degrees range on the 3 axis of EUT. Antenna height search was performed from 1 to 4m. The EUT is place at 1.5m high above 1GHz and at 0.8m high under 1GHz. The EUT is placed **in a full anechoic chamber** above 1GHz and **in a semi-anechoic chamber** from 30MHz to 1GHz. Distance between measuring antenna and the EUT is **3m**.




Photograph for Unwanted Emission in restricted frequency bands



Photograph for Unwanted Emission in restricted frequency bands



Photograph for Unwanted Emission in restricted frequency bands



Photograph for Unwanted Emission in restricted frequency bands

11.3. LIMIT

Limit at 3m:

9kHz to 0,490MHz: $2400/F(\text{kHz})\mu\text{V}/\text{m}$ (300m) or $20\log(2400/F(\text{kHz}))\text{dB}\mu\text{V}/\text{m}$ (3m) QPeak
0,490MHz to 1.705MHz: $240000/F(\text{kHz})\mu\text{V}/\text{m}$ (30m) or $20\log(240000/F(\text{kHz}))\text{dB}\mu\text{V}/\text{m}$ (3m) QPeak
1.705MHz to 30MHz: $30\mu\text{V}/\text{m}$ (30m) or $\text{dB}\mu\text{V}/\text{m}$ (3m) QPeak
30MHz to 88MHz: $40\text{dB}\mu\text{V}/\text{m}$ QPeak
88MHz to 216MHz: $43,5\text{dB}\mu\text{V}/\text{m}$ QPeak
216MHz to 960MHz: $46\text{dB}\mu\text{V}/\text{m}$ QPeak
960MHz to 1000MHz: $54\text{dB}\mu\text{V}/\text{m}$ QPeak
Above 1000MHz: $74\text{dB}\mu\text{V}/\text{m}$ Peak
 $54\text{dB}\mu\text{V}/\text{m}$ Average

Limit at 10m:

30MHz to 88MHz: $29,5\text{dB}\mu\text{V}/\text{m}$ QPeak
88MHz to 216MHz: $33\text{dB}\mu\text{V}/\text{m}$ QPeak
216MHz to 960MHz: $35,5\text{dB}\mu\text{V}/\text{m}$ QPeak
960MHz to 1000MHz: $43,5\text{dB}\mu\text{V}/\text{m}$ QPeak
Above 1000MHz: $63,5\text{dB}\mu\text{V}/\text{m}$ Peak
 $43,5\text{dB}\mu\text{V}/\text{m}$ Average



LCIE

11.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
EMI receiver	ROHDE & SCHWARZ	ESI40 1088 740K40	A2642010	2018/07	2019/07
Full anechoic chamber	SIEPEL	-	D3044019	2014/10	2018/10
Preamplifier	LCIE	LCIE-ALB-001	A7080073	2016/10	2018/10
Horn antenna	AH SYSTEMS	SAS 571	C2042041	2017/09	2019/09
Horn antenna (18-26,5GHz)	PASTERNAK	PE9852/2F-20	C2042048	2017/12	2019/12
Cable	Télédyne	084-0505-1MTR	A5329757	2018/03	2019/03
Cable	Télédyne	084-0555-3MTR	A5329760	2018/03	2019/03
Cable	Télédyne	084-555-1.5MTR	A5329759	2018/03	2019/03
Multimeter	KEITHLEY	2000	A1242090	2017/05	2019/05
Power supply	KIKUSUI	PCR500M	A7040079	Cal with Multimeter	Cal with Multimeter
Bilog antenna	SCHWARZBECK	VULB9160	C2040150	2018/04	2019/04
Cable	-	-	A5329711	2018/06	2019/06
Horn antenna	A-infoMW	Broadband 1-18	C2042056	2016/07	2018/07
SEMI ANECHOIC CHAMBER	SIEPEL	ANE	D3044008	2014/10	2018/10
EMI Receiver	ROHDE & SCHWARZ	ESU26	A2642018	2016/10	2018/10
Preamplifier	LCIE	-	A7086012	2018/03	2019/03
Loop antenna	SCHWARZBECK	FMZB1513	C2040209	2018/03	2020/03
Rejector filter 2,4GHz	-	2.45GHz	A7484048	2017/11	2018/11

Note: In our quality system, the test equipment calibration due is more & less 2 months

11.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION


None Divergence:

11.6. RESULTS


BLE 4.2 9kHz – 30 MHz

Cmin


Parallel Polarization



Perpendicular polarization



Ground Parallel polarization






L C I E


BLE 4.2 30MHz – 1GHz

Channel

Vertical Polarization



Horizontal polarization






L C I E

BLE 4.2 Above 1GHz

Cmin


Vertical Polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Verticale)
- Mes.Avg (Verticale)



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Horizontale)
- Mes.Avg (Horizontale)






L C I E

BLE 4.2 Above 1GHz

Cnom


Vertical Polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Verticale)
- Mes.Avg (Verticale)



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Horizontale)
- Mes.Avg (Horizontale)



BLE 4.2 Above 1GHz




L C I E

Cmax


Vertical Polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Verticale)
- Mes.Avg (Verticale)



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Horizontale)
- Mes.Avg (Horizontale)





L C I E

BLE 4.2 Above 1GHz Zoom 2310MHz-2500MHz

Cmin/Cnom/Cmax

Vertical Polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Avg Cmax - Verticale (Verticale)
- Mes.Peak Cnom - Verticale (Verticale)
- Mes.Avg Cnom - Verticale (Verticale)
- Mes.Peak Cmin - Verticale (Verticale)
- Mes.Peak Cmax - Verticale (Verticale)
- Mes.Avg Cmin - Verticale (Verticale)


Description Sous-bande 2

Fréquences: 2.31 GHz - 2.5 GHz (Mode: Lin, Pas: 1 MHz)

Réglages: RBW: 1MHz, VBW: Auto, Durée balayage : 50 ms/Pts, Atténuation : Auto, Nombre de Balayages : 1, Preamp : On: 20 dB, LN Preamp : Off, Preselecteur

Polarisation:Verticale

Distance: 3 m



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak Cmin - Horizontale (Horizontale)
- Mes.Peak Cmax - Horizontale (Horizontale)
- Mes.Avg Cmin - Horizontale (Horizontale)
- Mes.Avg Cmax - Horizontale (Horizontale)
- Mes.Peak Cnom - Horizontale (Horizontale)
- Mes.Avg Cnom - Horizontale (Horizontale)


Description Sous-bande 1

Fréquences: 2.31 GHz - 2.5 GHz (Mode: Lin, Pas: 1 MHz)

Réglages: RBW: 1MHz, VBW: Auto, Durée balayage : 50 ms/Pts, Atténuation : Auto, Nombre de Balayages : 1, Preamp : On: 20 dB, LN Preamp : Off, Preselecteur

Polarisation:Horizontale

Distance: 3 m





L C I E

BLE 4.2 9kHz to 30MHz				
Polarization	Frequency (MHz)	Peak Level (dBµV/m)	QPeak Level (dBµV/m)	Limit (dBµV/m)
all emissions were greater than 20 dB below the limit				

BLE 4.2 30MHz – 1GHz					
Polarization	Frequency (MHz)	Peak Level (dBµV/m)	QPeak Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Verticale	65.4	34.15	-	40.0	5.85
Verticale	49.15	30.37	-	40.0	9.62
Verticale	108.3	30.79	-	43.5	12.71
Verticale	204.26	35.14	-	43.5	8.36
Horizontale	204.32	30.23	-	43.5	13.27
Verticale	796.58	40.19	-	46.0	5.81

BLE 4.2 Above 1GHz								
Cmin/Cnom/Cmax								
Polarization	Frequency (MHz)	Average Level (dBµV/m)	Average Level + Duty Cycle Factor (dBµV/m)	Average Limit (dBµV/m)	Average Margin Level (dB)	Peak Level (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin Level (dB)
Horizontale	2390	33.80	37.79	54	20.20	51.52	74	22.48
Verticale	2390	31.46	35.45	54	22.54	45.76	74	28.24
Horizontale	2483.5	36.11	40.10	54	17.89	55.67	74	18.33
Verticale	2483.5	32.27	36.26	54	21.73	50.40	74	23.60
Verticale	5000	43.60	47.59	54	10.40	49.58	74	24.42
Horizontale	4804	39.68	43.67	54	14.32	47.58	74	26.42
Horizontale	5791	37.13	41.12	54	16.87	47.01	74	26.99
Horizontale	7206	43.46	47.45	54	10.54	51.85	74	22.15
Horizontale	7319	46.22	50.21	54	07.78	54.09	74	19.91




L C I E


BLE 5.0 9kHz – 30 MHz

Cmin


Parallel Polarization



Perpendicular polarization



Ground Parallel polarization






L C I E


BLE 5.0 Below 1GHz

Channel

Vertical Polarization



Horizontal polarization






L C I E

BLE 5.0 Above 1GHz

Cmin


Vertical Polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Verticale)
- Mes.Avg (Verticale)



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Horizontale)
- Mes.Avg (Horizontale)



BLE 5.0 Above 1GHz




L C I E

Cnom


Vertical Polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Verticale)
- Mes.Avg (Verticale)



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Horizontale)
- Mes.Avg (Horizontale)



BLE 5.0 Above 1GHz


Cmax



L C I E


Vertical Polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Verticale)
- Mes.Avg (Verticale)



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak (Horizontale)
- Mes.Avg (Horizontale)



BLE 5.0 Above 1GHz Zoom 2310MHz-2500MHz

Cmin/Cnom/Cmax

Vertical Polarization



L C I E

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Avg Cmax - Verticale (Verticale)
- Mes.Peak Cnom - Verticale (Verticale)
- Mes.Avg Cnom - Verticale (Verticale)
- Mes.Peak Cmin - Verticale (Verticale)
- Mes.Peak Cmax - Verticale (Verticale)
- Mes.Avg Cmin - Verticale (Verticale)


Description Sous-bande 2

Fréquences: 2.31 GHz - 2.5 GHz (Mode: Lin, Pas: 1 MHz)

Réglages: RBW: 1MHz, VBW: Auto, Durée balayage : 50 ms/Pts, Atténuation : Auto, Nombre de Balayages : 1, Preamp : On: 20 dB, LN Preamp : Off, Preselect

Polarisation:Verticale

Distance: 3 m



Horizontal polarization

- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Moyenne/3.0m/
- FCC/FCC 15.209 2400MHz-2483MHz Band - Classe:1 - Crête/3.0m/
- Mes.Peak Cmin - Horizontale (Horizontale)
- Mes.Peak Cmax - Horizontale (Horizontale)
- Mes.Avg Cmin - Horizontale (Horizontale)
- Mes.Avg Cmax - Horizontale (Horizontale)
- Mes.Peak Cnom - Horizontale (Horizontale)
- Mes.Avg Cnom - Horizontale (Horizontale)


Description Sous-bande 1

Fréquences: 2.31 GHz - 2.5 GHz (Mode: Lin, Pas: 1 MHz)

Réglages: RBW: 1MHz, VBW: Auto, Durée balayage : 50 ms/Pts, Atténuation : Auto, Nombre de Balayages : 1, Preamp : On: 20 dB, LN Preamp : Off, Preselect

Polarisation:Horizontale

Distance: 3 m



BLE 5.0 9kHz to 30MHz



Polarization	Frequency (MHz)	Peak Level (dB μ V/m)	QPeak Level (dB μ V/m)	Limit (dB μ V/m)
all emissions were greater than 20 dB below the limit				

BLE 5.0 30MHz – 1GHz					
Polarization	Frequency (MHz)	Peak Level (dB μ V/m)	QPeak Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Verticale	66.05	34.68	-	40.0	5.32
Verticale	108.3	30.47	-	43.5	13.03
Verticale	138.0	31.94	-	43.5	11.56
Verticale	204.3	33.79	-	43.5	9.71
Verticale	271.9	32.44	-	46.0	13.55
Horizontale	271.9	33.38	-	46.0	12.62
Horizontale	432.8	35.69	-	46.0	10.31

BLE 5.0 Above 1GHz								
Cmin/Cnom/Cmax								
Polarization	Frequency (MHz)	Average Level (dB μ V/m)	Average Level + Duty Cycle Factor (dB μ V/m)	Average Limit (dB μ V/m)	Average Margin Level (dB)	Peak Level (dB μ V/m)	Peak Limit (dB μ V/m)	Peak Margin Level (dB)
Horizontale	1558	21.67	31.05	54	32.33	48.06	74	25.94
Horizontale	1715	21.94	31.32	54	32.06	46.43	74	27.57
Horizontale	1865	23.10	32.48	54	30.90	46.45	74	27.55
Verticale	1897	22.11	31.49	54	31.89	46.92	74	27.08
Horizontale	2390	32.77	42.15	54	21.23	47.01	74	26.99
Verticale	2390	31.13	40.51	54	22.87	44.35	74	29.65
Horizontale	2483.5	34.77	44.15	54	19.23	55.98	74	18.02
Verticale	2483.5	32.06	41.44	54	21.94	49.66	74	24.34
Horizontale	4000	39.58	48.96	54	14.42	45.62	74	28.38
Horizontale	5000	41.95	51.33	54	12.05	49.07	74	24.93
Horizontale	5789	47.79	57.17	54	06.21	58.10	74	15.90
Horizontale	7206	38.76	48.14	54	15.24	51.31	74	22.69

11.7. CONCLUSION

Unwanted Emission in restricted frequency bands measurement performed on the sample of the product **Sagemcom® Sound Box SBDV01**, SN: **253770742**, in configuration and description presented in this test report, show levels **compliant** to the 47 CFR PART 15.247 limits.

12. UNCERTAINTIES CHART

47 CFR Part 15.209 & 15.207 Kind of test	Wide uncertainty laboratory (k=2) ±x(dB) / (Hz)/ ms	Uncertainty limit
Measurement of conducted disturbances in voltage on the AC power port (9 kHz – 150 kHz)	2,67	3.8
Measurement of conducted disturbances in voltage on the AC power port (150 kHz – 30 MHz)	2,67	3.4
Measurement of conducted disturbances in voltage on the telecommunication port. (AAN)	3,67	5.0
Measurement of conducted disturbances in current (current clamp)	2,73	2.9
Measurement of disturbance power	2,67	4.5
Measurement of radiated magnetic field from 10kHz to 30MHz in SAC V01	4,48	/
Measurement of radiated magnetic field from 10kHz to 30MHz in SAC C01	4,48	/
Measurement of radiated electric field from 30 to 1000MHz in horizontal position on the OATS (Ecuellas)	4,88	6.3
Measurement of radiated electric field from 1 to 18GHz on the Ecuellas site	5.16	/
Measurement of radiated electric field from 30 to 1000MHz in vertical position on the OATS (Ecuellas)	4,99	6.3
Measurement of radiated electric field from 30 to 1000MHz in horizontal position in SAC C01	5,08	6.3
Measurement of radiated electric field from 30 to 1000MHz in vertical position in SAC C01	5,16	6.3
Measurement of radiated electric field from 30 to 1000MHz in horizontal position in SAC V01	5,08	6.3
Measurement of radiated electric field from 30 to 1000MHz in vertical position in SAC V01	5,15	6.3
Measurement of radiated electric field from 1 to 6 GHz C01	5,1	5.2
Measurement of radiated electric field from 1 to 6 GHz V01	4,85	5.2
Measurement of radiated magnetic field from 10kHz to 30MHz on the OATS (Ecuellas)	4,48	/

The uncertainty values calculated by the laboratory are lower than limit uncertainty values defined by the CISPR. The conformity of the sample is directly established by the applicable limits values. This table includes all uncertainties maximum feasible for testing in the laboratory, whether or not made in this report