



FCC 47 CFR PART 15 SUBPART E

for

802.11ac FTTH/VDSL2 Gateway

Model: SR570ac

Brand: SmartRG

Test Report Number:

C170322Z06-RP1-2

Issued Date: August 29, 2017

Issued for

SmartRG Inc.

**501 SE Columbia Shores Boulevard, Suite 500 Vancouver, Washington
98661**

Issued by:

Compliance Certification Services (Shenzhen) Inc.

No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,

Guan Lan Town, Baoan District, Shenzhen, China

TEL: 86-755-28055000

FAX: 86-755-28055221

E-Mail: service@ccssz.com



Certificate Number: 2861.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The TEST RESULTS in the report only apply to the tested sample.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 29, 2017	Initial Issue	ALL	Amzula Chen



TABLE OF CONTENTS

1. TEST CERTIFICATION 4

2. EUT DESCRIPTION..... 5

3. TEST METHODOLOGY..... 9

 3.1 EUT CONFIGURATION..... 9

 3.2 EUT EXERCISE..... 9

 3.3 GENERAL TEST PROCEDURES 9

 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS 10

 3.5 DESCRIPTION OF TEST MODES 11

4. SETUP OF EQUIPMENT UNDER TEST 13

 4.1 DESCRIPTION OF SUPPORT UNITS..... 13

 4.2 CONFIGURATION OF SYSTEM UNDER TEST 13

5. FACILITIES AND ACCREDITATIONS 14

 5.1 FACILITIES..... 14

 5.2 EQUIPMENT..... 14

 5.3 ACCREDITATIONS 14

 5.4 MEASUREMENT UNCERTAINTY..... 15

6. FCC PART 15 REQUIREMENTS 16

 6.1 26dB EMISSION BANDWIDTH 16

 6.2 6dB BANDWIDTH MEASUREMENT 85

 6.3 ANTENNA GAIN 105

 6.4 OUTPUT POWER..... 110

 6.5 BAND EDGES MEASUREMENT..... 119

 6.6 PEAK POWER SPECTAL DENSITY 157

 6.7 RADIATED UNDESIRABLE EMISSION..... 240

 6.8 CONDUCTED UNDESIRABLE EMISSION 324

 6.9 POWERLINE CONDUCTED EMISSIONS..... 351

 6.10 FREQUENCY STABILITY..... 357



1. TEST CERTIFICATION

Product	802.11ac FTTH/VDSL2 Gateway
Model	SR570ac
Brand	SmartRG
Tested	March 22~ August 28, 2017
Applicant	SmartRG Inc. 501 SE Columbia Shores Boulevard, Suite 500 Vancouver, Washington 98661
Manufacturer	SmartRG Inc. 501 SE Columbia Shores Boulevard, Suite 500 Vancouver, Washington 98661

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart E	No non-compliance noted

We hereby certify that:

Compliance Certification Services (Shenzhen) Inc. tested the above equipment. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.407 、 FCC 14-30.

The TEST RESULTS of this report relate only to the tested sample identified in this report.

Approved by:

Sunday Hu
Supervisor of EMC Dept.
Compliance Certification Services (Shenzhen) Inc.

Reviewed by:

Ruby Zhang
Supervisor of Report Dept.
Compliance Certification Services (Shenzhen) Inc.



2. EUT DESCRIPTION

Product	802.11ac FTTH/VDSL2 Gateway	
Model Number	SR570ac	
Brand	SmartRG	
Model Discrepancy	N/A	
Serial Number	C170322Z06-RP1-2	
Received Date	March 22, 2017	
Power Supply	DC 12V supply by the adapter	
Adapter Specification	Shenzhen Gongjin Electronics Co., Ltd./ S36B52-120A300-04 INPUT:100-240V,50/60Hz Max 1.0A OUTPUT: 12V,3A DC Cable: Unshielded, 1.55m	
Frequency Range	UNII Band I: IEEE 802.11a, 802.11n HT20 : 5180MHz ~ 5240MHz; IEEE 802.11n HT40: 5190MHz ~ 5230MHz IEEE 802.11ac 80: 5210MHz UNII Band II IEEE 802.11a, 802.11n HT20 : 5260MHz ~ 5320MHz IEEE 802.11n HT40: 5270MHz ~ 5310MHz IEEE 802.11ac 80: 5290MHz UNII Band III IEEE 802.11a, 802.11n HT20 : 5500MHz ~ 5700MHz IEEE 802.11n HT40: 5510MHz ~ 5670MHz IEEE 802.11ac 80: 5530MHz UNII Band IV IEEE 802.11a, 802.11n HT20 : 5745MHz ~ 5825MHz IEEE 802.11n HT40: 5755MHz ~ 5795MHz IEEE 802.11ac 80: 5775MHz	
Transmit Power	UNII Band I: 19.27dBm (Antenna 0) IEEE 802.11a: 19.31dBm (Antenna 1) 19.21dBm (Antenna 2) 19.42dBm (Antenna 3) IEEE 802.11n HT 20 MHz mode: 20.07dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3) IEEE 802.11n HT 40 MHz mode: 17.32dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3) IEEE 802.11ac 80: 17.35dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3) UNII Band II 17.52dBm (Antenna 0) IEEE 802.11a: 17.61dBm (Antenna 1) 17.57dBm (Antenna 2) 17.41dBm (Antenna 3) IEEE 802.11n HT 20 MHz mode: 19.70dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3) IEEE 802.11n HT 40 MHz mode: 20.22dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)	



	<p>IEEE 802.11ac 80: 19.71dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)</p> <p>UNII Band III</p> <p>IEEE 802.11a: 19.53dBm (Antenna 0) 19.28dBm (Antenna 1) 19.37dBm (Antenna 2) 19.12dBm (Antenna 3)</p> <p>IEEE 802.11n HT 20 MHz mode: 19.85dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)</p> <p>IEEE 802.11n HT 40 MHz mode: 20.38dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)</p> <p>IEEE 802.11ac 80: 19.85dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)</p> <p>UNII Band IV</p> <p>IEEE 802.11a: 19.82dBm (Antenna 0) 18.94dBm (Antenna 1) 19.41dBm (Antenna 2) 19.38dBm (Antenna 3)</p> <p>IEEE 802.11n HT 20 MHz mode: 23.44dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)</p> <p>IEEE 802.11n HT 40 MHz mode: 24.35dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)</p> <p>IEEE 802.11ac 80: 24.22dBm (Antenna 0 + Antenna 1 + Antenna 2+ Antenna 3)</p>
Modulation Technique	OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
Transmit Data Rate	<p>IEEE 802.11a mode: 54, 48, 36, 24, 18, 12, 9, 6Mbps</p> <p>IEEE802.11n HT20MHz mode(800ns GI): 384,346,288,260,231,173,115,86,57,28.8Mbps</p> <p>IEEE802.11n HT40MHz mode(800ns GI): 800,720,600,540,480,360,240,180,120,60Mbps</p> <p>IEEE802.11ac VHT80MHz mode(800ns GI): 2166,1950,1625,1462,1300,975,650,487,312,162Mbps</p>
Number of Channels	<p>UNII Band I:</p> <p>IEEE 802.11a, 802.11n HT20 : 4 Channels</p> <p>IEEE 802.11n HT40 : 2 Channels</p> <p>IEEE 802.11ac 80: 1 Channel</p> <p>UNII Band II</p> <p>IEEE 802.11a, 802.11n HT20 : 4 Channels</p> <p>IEEE 802.11n HT40: 2 Channels</p> <p>IEEE 802.11ac 80: 1 Channel</p> <p>UNII Band III</p> <p>IEEE 802.11a, 802.11n HT20 : 9 Channels</p> <p>IEEE 802.11n HT 40 MHz mode: 4 Channels</p> <p>IEEE 802.11ac 80: 1 Channels</p> <p>UNII Band IV</p> <p>IEEE 802.11a, 802.11n HT20 : 5 Channels</p> <p>IEEE 802.11n HT 40 MHz mode: 2 Channels</p> <p>IEEE 802.11ac 80: 1 Channel</p>
Antenna Specification	Omni-directional antenna with 3.5dBi gain (Max)
Channels Spacing	<p>IEEE 802.11a, 802.11n HT20 : 20MHz</p> <p>IEEE 802.11n HT40: 40MHz</p> <p>IEEE 802.11ac 80: 80MHz</p>
Temperature Range	0°C ~ +40°C



Hardware Version	A0
Software Version	1.0.0.68

Note: 1. *The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.*



Operation Frequency:

UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII)	
CHANNEL	MHz
36	5180
38	5190
40	5200
42	5210
44	5220
46	5230
48	5240
52	5260
54	5270
56	5280
58	5290
60	5300
62	5310
64	5320
100	5500
102	5510
104	5520
106	5530
108	5540
110	5550
112	5560
116	5580
132	5660
134	5670
136	5680
140	5700
149	5745
151	5755
153	5765
155	5775
157	5785
159	5795
161	5805
165	5825

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: VW7SR570A filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules and FCC 14-30.



3. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 Radiated testing was performed at an antenna to EUT distance 3 meters.

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC CFR 47 Part 15.207, 15.209, 15.407 and FCC 14-30.

Radio testing was performed according to KDB DA 02-2138、KDB 789033 D02、KDB 905462 D06;

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed for RF field strength measurement to meet the Commissions requirement, and is operated in a manner intended to generate the maximum emission in a continuous normal application.

3.2 EUT EXERCISE

The EUT is operated in the engineering mode to fix the TX frequency for the purposes of measurement.

According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is positioned at 0.8 m above the ground plane. According to the requirements in Section 6.2 of ANSI C63.10, the conducted emission from the EUT is measured in the frequency range between 0.15 MHz and 30MHz, using the CISPR Quasi-Peak detector mode.

Radiated Emissions

The EUT is placed on the turntable, which is 0.8 m (below 1GHz) /1.5m (Above 1GHz) above the ground plane. The turntable is then rotated for 360 degrees to determine the proper orientation for the maximum emission level. The EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission level. And, each emission is to be maximized by changing the horizontal and vertical polarization of the receiving antenna. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.4 to Section 6.6 of ANSI C63.10.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT is a 3x3 configuration spatial MIMO (3TX & 3RX) without beam forming function. Use MTool to control the EUT for staying in continuous transmitting mode was programmed.

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: 100Mbps 10%	<input checked="" type="checkbox"/>
Radiated Emission	Mode 4: Continuously Transmitting	<input checked="" type="checkbox"/>

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

UNII Band I:

IEEE 802.11a for 5180 ~ 5240MHz:

Channel Low (5180MHz), Channel Mid (5200MHz) and Channel High (5240MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 MHz for 5180 ~ 5240MHz:

Channel Low (5180MHz), Channel Mid (5200MHz) and Channel High (5240MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT 40 MHz Channel for 5190 ~ 5230MHz:

Channel Low (5190MHz) and Channel High (5230MHz) with 27Mbps data rate were chosen for full testing.

IEEE 802.11ac 80 Channel for 5210MHz:

Channel Low (5210MHz) with 27Mbps data rate were chosen for full testing.



UNII Band II:

IEEE 802.11a for 5260 ~ 5320MHz:

Channel Low (5260MHz), Channel Mid (5300MHz) and Channel High (5320MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 MHz for 5260 ~ 5320MHz:

Channel Low (5260MHz), Channel Mid (5300MHz) and Channel High (5320MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT 40 MHz Channel for 5270~ 5310MHz:

Channel Low (5270MHz) and Channel High (5310MHz) with 27Mbps data rate were chosen for full testing.

IEEE 802.11ac 80 Channel for 5290MHz:

Channel Low (5290MHz) with 27Mbps data rate were chosen for full testing.

UNII Band III:

IEEE 802.11a for 5500 ~ 5700MHz:

Channel Low (5500MHz), Channel Mid (5580MHz) and Channel High (5700MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 MHz for 5500 ~ 5700MHz:

Channel Low (5500MHz), Channel Mid (5580MHz) and Channel High (5700MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT 40 MHz Channel for 5510~ 5670MHz:

Channel Low (5510MHz) and Channel High (5670MHz) with 27Mbps data rate were chosen for full testing.

IEEE 802.11ac 80 Channel for 5530MHz:

Channel Low (5530MHz) with 27Mbps data rate were chosen for full testing.

UNII Band IV:

IEEE 802.11a for 5745 ~ 5825MHz:

Channel Low (5745MHz), Channel Mid (5785MHz) and Channel High (5825MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 MHz for 5745 ~ 5825MHz:

Channel Low (5745MHz), Channel Mid (5785MHz) and Channel High (5825MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT 40 MHz Channel for 5755~ 5795MHz:

Channel Low (5755MHz) and Channel High (5795MHz) with 27Mbps data rate were chosen for full testing.

IEEE 802.11ac 80 Channel for 5775MHz:

Channel Low (5775MHz) with 27Mbps data rate were chosen for full testing.



4. SETUP OF EQUIPMENT UNDER TEST

4.1 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook1#	Probook 5310m	N/A	DoC	HP	Unshielded 2.00m (RJ45 Cable)	Unshielded 1.80m (AC cable) Unshielded 1.50m (DC cable)
2	Notebook 2#	Aspire V13	N/A	DoC	Acer	Unshielded 2.00m (RJ45 Cable)	Unshielded 1.80m (AC cable) Unshielded 1.50m (DC cable)
3	DLSAM	ZXDSL 9806H	N/A	DoC	ZTE	N/A	Unshielded 1.50m
4	HDD3.01#	WDBACY5000ASL- OP	WX31A9109 168	DoC	WD	Shielded 0.50m	N/A
5	HDD3.0 2#	WDBACY3202ABK- PESN	WXF1A9027 339	DoC	WD	Shielded 0.50m	N/A

Note:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at **No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.10, ANSI C63.7 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
China	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	FCC
Japan	VCCI(C-3478, R-3135, T-652, G-10624)
Canada	INDUSTRY CANADA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccssz.com>



5.4 MEASUREMENT UNCERTAINTY

Parameter	Uncertainty
RF frequency	+/-1 * 10 ⁻⁵
RF power conducted	+/- 1,5 dB
RF power radiated	+/- 6 dB
Spurious emissions, conducted	+/- 3 dB
Spurious emissions, radiated	+/- 6 dB
Humidity	+/- 5 %
Temperature	+/- 1°C
Time	+/-10 %

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



6. FCC PART 15 REQUIREMENTS

6.1 26dB EMISSION BANDWIDTH

6.1.1 LIMIT


According to §15.403(c), for purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Compliance with the emissions limits is based on the use of measurement instrumentation employing a peak detector function with an instrument resolutions bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

6.1.2 MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	02/21/2017	02/20/2018

Remark: Each piece of equipment is scheduled for calibration once a year.

6.1.3 TEST CONFIGURATION



6.1.4 TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low-loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW > 1%EBW, VBW > RBW, Span >26dB bandwidth, Detector = Peak, and Sweep = auto.
4. Mark the peak frequency and -26dB (upper and lower) frequency.
5. Repeat until all the rest channels were investigated.



6.1.5 TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11a mode / 5180 ~ 5240MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5180	21.32	21.48	21.55	21.61
Mid	5200	21.33	21.40	21.51	21.60
High	5240	21.39	21.43	21.56	21.52

Test mode: IEEE 802.11a mode / 5260 ~ 5320MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5260	21.48	21.50	21.49	21.46
Mid	5300	21.63	21.56	21.54	21.38
High	5320	21.56	21.61	21.47	21.59

Test mode: IEEE 802.11a mode / 5500 ~ 5700MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5500	21.45	21.55	21.39	21.23
Mid	5580	21.37	21.44	21.64	21.61
High	5700	21.34	21.44	21.42	21.40



Test mode: IEEE 802.11n HT 20 MHz mode / 5180 ~ 5240MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5180	21.65	21.60	21.57	21.59
Mid	5200	21.81	21.74	21.16	21.42
High	5240	21.48	21.50	21.41	21.49

Test mode: IEEE 802.11n HT 20 MHz mode / 5260 ~ 5320MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5260	21.70	21.44	21.50	21.62
Mid	5300	21.76	21.44	21.70	21.36
High	5320	21.82	21.60	21.45	21.55

Test mode: IEEE 802.11n HT 20 MHz mode / 5500 ~ 5700MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5500	21.32	21.41	21.13	21.41
Mid	5580	20.93	21.36	21.43	21.52
High	5700	21.35	21.39	21.38	21.46



Test mode: IEEE 802.11n HT 40 MHz mode / 5190 ~ 5230MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5190	40.25	39.94	40.05	40.14
High	5230	40.09	39.82	40.04	39.98

Test mode: IEEE 802.11n HT 40 MHz mode / 5270 ~ 5310MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5270	40.12	40.05	40.22	39.96
High	5310	39.92	40.41	40.08	40.27

Test mode: IEEE 802.11n HT 40 MHz mode / 5510~5670MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
Low	5510	39.79	40.19	40.30	40.06
Mid	5550	40.25	39.98	40.29	40.36
High	5670	40.07	40.01	40.11	40.07



Test mode: IEEE 802.11ac 80 mode / 5210MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
	5210	81.06	80.78	81.13	81.53

Test mode: IEEE 802.11ac 80 mode / 5290MHz

Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
	5290	80.40	80.43	79.89	80.68

Test mode: IEEE 802.11ac 80 mode / 5530MHz


Channel	Frequency (MHz)	26dB Bandwidth(B) (MHz)			
		Antenna 0	Antenna 1	Antenna 2	Antenna 3
	5530	80.85	80.67	80.29	80.50




Test Plot

IEEE 802.11a mode / 5180 ~ 5240MHz

26dB Bandwidth (CH Low)




26dB Bandwidth (CH Mid)





26dB Bandwidth (CH High)


Antenna 0







IEEE 802.11a mode / 5260~ 5320MHz


26dB Bandwidth (CH Low)



Antenna 0
















IEEE 802.11a mode / 5260~ 5320MHz









26dB Bandwidth (CH Mid)





26dB Bandwidth (CH High)












26dB Bandwidth (CH High)


Antenna 2



IEEE 802.11a mode / 5260~ 5320MHz


26dB Bandwidth (CH Low)

Antenna 2









26dB Bandwidth (CH Mid)



26dB Bandwidth (CH High)











IEEE 802.11a mode / 5180 ~ 5240MHz

26dB Bandwidth (CH Low)




26dB Bandwidth (CH Mid)





26dB Bandwidth (CH High)


Antenna 3



IEEE 802.11a mode / 5260~ 5320MHz


26dB Bandwidth (CH Low)

Antenna 3









26dB Bandwidth (CH Mid)






26dB Bandwidth (CH High)



















IEEE 802.11n HT 20 MHz mode / 5260~ 5320MHz
















IEEE 802.11n HT 20 MHz mode / 5260~ 5320MHz









26dB Bandwidth (CH Mid)



26dB Bandwidth (CH High)












IEEE 802.11n HT 20 MHz mode / 5180 ~ 5240MHz

26dB Bandwidth (CH Low)






26dB Bandwidth (CH Mid)










IEEE 802.11n HT 20 MHz mode / 5260~ 5320MHz















26dB Bandwidth (CH High)




IEEE 802.11n HT 20 MHz mode / 5260~ 5320MHz

26dB Bandwidth (CH Low)









26dB Bandwidth (CH Mid)



26dB Bandwidth (CH High)










IEEE 802.11n HT 40 MHz mode / 5190 ~ 5230MHz

26dB Bandwidth (CH Low)



26dB Bandwidth (CH High)

