	1	2	3	4	5		6			
					Remark	Desc	ription Editor	Date		
		-0.2mm			V02	更新电	2.源信息 洪平	170918		
		60mm 0.2mm		编码规则: HFC MAC Address / Adresse						
А				₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩					Α	
	80211ac DO	CSIS 3.0 Gateway	V02 Serial N	o. / N° de série						
	+0 Model/Mode	Address / Adresse WiFi Key / Clé WiFi								
	-0.2mm E HFC MAC Addr		Dentena 2550	SR808A:固定						
	O HFC MAC Addr		Pantone 426C	XX: 硬件版本 -16 进制(硬件版本由产品经理提供,见产品信息发布流程) (Hex number indicating HW Ver. e.g. A0,A1,~A9,B0,B1,etc)						
	4		Pantone 420C	40						
	This device complies wi (1) This device may not including interference t	th part 15 of the FCC Rules. Operation is subject to the following two conditions: cause harmful interference, and (2) this device must accept any interference received, hat may cause undesired operation.	Cutlines, do not print							
	including interference that may cause underfere operation. Engineered in the USA / Conçu aux Etats-Unis Crafted in China / Fabrique en Chine YY: 出厂时间 月年 -16 进制									
	Hex number indicating ex-factory date (Month and Year) e.g. August 2013 (08/13) = 83 December 2015 (12/15) = C5									
В				nnnnnn:0000001-99999999(按生产流水号) B					В	
	2. 以下内容	由工厂在供应商印刷基础	上打印	(serial number e.g.0000001,0000002,etc)						
			2.4GHz: SmartRG-nnnn							
	CNAA			z: SmartRG-nnnn-5G						
		CSIS 3.0 Gateway		: MAC地址后四位,字母需小写 [·] Base MAC = 00236A5BE45D 卜	FC MAC=BASI	= MAC				
	Model/Modé Serial No. / N°	ele: SR808ac COUS A 12V 3A LFBA O-C-O de série WiFi SSIDs	then	then 2.4GHz: SmartRG-e45d タロナビに書田 400 Jan: ナエビロナロナビロ						
	Image: SR08AXXYY-nnnnnnn 2.4G: SmartRG-nnnn SG: SmartRG-nnnn-SG HFC MAC Address / Adresse WiFi Key / Clé WiFi Image: SG: SmartRG-nnnn-SG Image: SR08AXXYY-Nnnnnnnn SG: SmartRG-nnnn-SG WiFi Key / Clé WiFi Image: SR08AXXYY-Nnnnnnnn SG: SmartRG-nnnn-SG WiFi Key / Clé WiFi Image: SR08AXXYY-Nnnnnnnn SG: SmartRG-nnnn-SG WiFi Key / Clé WiFi Image: SR08AXXYY-Nnnnnnnn SG: SmartRG-nnnn-SG WiFi Key / Clé WiFi Image: SR08AXXYY-Nnnnnnnn SG: SmartRG-nnnn-SG WiFi Key / Clé WiFi Image: SR08AXXYY-Nnnnnnnn SG: SmartRG-nnnn-SG SG: SmartRG-nnnn-SG Image: SR08AXXYY-Nnnnnnnn SG: SmartRG-nnnn-SG SG: SmartRG-nnnn-SG Image: SR08AXXYY-Nnnnnnn SG: SmartRG-nnnn-SG SG: SmartRG-nnnn-SG Image: SR08AXXY-Nnnnn Subject SR04AXXXXXX SK:			WiFi Key: 位数及内容由質号器生成						
				Serial No. / N° de série WiFi SSIDs						
С				2.4G: SmartRG-nnnn ← Bliss 2 Bold, 6pt C \$R808AXXYY-nnnnnnnn 5G						
				Bliss 2 Regular, 6pt HFC MAC Address / Adresse WiFi Key / Clé WiFi						
	了一个空格。 「新来」「新来」「新来」「新来」「新来」「新来」「新来」「新来」「新来」「新来」									
			MAC Add	dress: ALL CAPS — XXXXXXXXXX		XXXXXX				
D	NOTES(技术要求):		RCODE: CODE 128	NOTE: 打印内容需框内整体居中打印!					_	
	1. 三专色印刷,无边框,R0.5*3,C1.85*1 (3 pantone color printing,no frame,R0.5*3,C1.85*1)			RANGE C1 C2 C3 C4						
		T,耐8 5度以上高温测试不起泡	,覆可打印哑膜,背胶	0~6 0.1 0.1 0.15 0.2 6~30 0.2 0.3 0.4 0.5 TITL	E: MODEL:	MODEL: PART NO:				
	(Material:50# Bright white embossing PET, Heat resistant of at least 85°C,			30~80 0.25 0.5 0.9 1.2 印刷	盒底标贴				D	
	no bubble,with matte printing film,adhesive) 3.原材料及后处理工艺均能满足我司《环保技术标准》要求.			80~180 0.3 0.8 1.2 1.5 180~315 0.5 1.3 1.8 3 UNIT	'S mm VER: V	02 DRAW	洪平 DATE:	170825		
		esponding post processing shoul	ld meet requirements defined	315~500 0.7 1.5 2.5 4 500~800 0.9 1.8 3 5	L / SCALE 1	1 CHECK	李蕃			
	in the T&W Environmental P	rotection Technical Standards)		ANG.TOL± 0°~30'/0.1° 30°~60'/0.3° 60°~90'/0.5° FINIS	H / SHEET 1	1 PDE	N/A			
	1	2	3	4	5		6			



