

MG700 WiFi Gateway/Router

User's Manual



Features	Supports WiFi 802.11 b/g/n Optional internal battery Micro SD Card/SIM Card Slot
Description	The MG700 is a high performance global router for M2M applications. It is WiFi gateway which supports three serial ports and functions to expand a user's M2M application. A user can easily configure settings from the GUI interface and record data on a micro SD card or USB storage device. An optional internal battery provides backup power which allows for an alert to be sent in the event of a power failure.

Table of Contents

1	Introduction	4
2	Installation Guide	6
3	Login Page.....	8
4	Status Page	9
	5.1 Router	9
	5.2 User / DHCP	10
5	Setup Page	11
	6.1 WAN.....	11
	6.2 LAN	16
	6.3 DHCP Server	16
	6.4 DDNS	17
	6.5 Time	18
	6.6 Relay	19
	6.7 Alert	21
6	Wireless Page.....	23
	7.1 Basic.....	23
	7.2 Advanced.....	27
	7.3 WDS.....	28
7	Security Page	32
	8.1 Firewall.....	32
	8.2 IP Access Control	32
	8.3 Outbound MAC ACL	33
	8.4 Web Filtering	35
	8.5 VPN/PPTP Page	35
8	Applications Page	37
	9.1 Port Range Forward	37
	9.2 Streaming/VPN.....	39
	9.3 UPnP	39
9	Bandwidth Page	40
	10.1 Throughput Optimize	40
	10.2 TurboNAT	40
	10.3 Session Manager.....	41

10	Serial Setting Page.....	42
11.1	Status Page.....	42
11.2	Port1/2/3 Page.....	42
11.3	File Mode Page	44
11	GPS/GNSS Application	47
11.1	GPS/GNSS NMEA data.....	48
11.2	GPS/GNSS RAW Data	49
12	Admin Application	50
13.1	Management	50
13.2	System Utilities	51
13.3	Log	52
13	MG700 M2M Application.....	54
14	Hardware Specifications	55
15	Application Note – ATM remote control Application	56
	Application Note – AMBULANCE Application.....	57
	Application Note – Tracker/Car Management Application	58

1 Introduction

The MG700 is a mobile router. MG700 has a built-in 802.11 b/g/n WiFi radio that functions as both an access point and a WAN bridge. This allows WiFi devices to securely communicate with the MG700 and access a wired network or the internet. It also enables the MG700 to use available WiFi networks for even higher speed internet access.

Panel Indicators

- Top Panel



LED indicators on top

Item	Description
1	WiFi indicator. LED on when WiFi AP is ready. LED flashes when data is transmitting.
2	Cellular indicator. LED on when the cellular function is ready. If Cellular led is flashing, it means searching Service Provider.
3	Power indicator. LED on when the power is on.
4	Optional battery charging indicator. LED on when the battery is charging.

- Back Panel



Back side


Item	Description
9	Optional GPS antenna connector.
10	On/Off Switch
11	12VDC power input
12	LAN Port
13	WAN Port
14	External USB device, only for USB storage.
15	Cellular antenna connector
16	SIM card slot

2 Installation Guide


Open the MG700's Box, there are include MG700 body、AC adapter box and accessory box on MG700's Box. User can login the MG700's web GUI by three steps.



Step 1: Install the WiFi Antenna、SD card、Micro Fit Cable and RJ45 to DB9 Cable.



Step 2: Install Cellular Antenna、SIM Card、Adapter、GPS Antenna and LAN cable to Computer. Then Turn the Switch on.



Step 3: Input <http://192.168.60.1:8080> to login page on browser.




The image shows a screenshot of a web browser displaying the login interface for an ALLISCOM device. The page has a light gray background with a white login form. At the top left, the word 'Login' is written in a small, dark font. Below it are three input fields: 'User Name' with an empty text box, 'Password' with an empty text box, and 'Language' with a dropdown menu set to 'English'. At the bottom of the form is a single 'Login' button. The entire form is enclosed in a thin gray border.

Note:

1. SD card、SIM card、Micro Fit Cable、Cellular Antenna、GPS Antenna、RJ45 to DB9 Cable depend on different MG700's model.
2. WiFi Antenna and Adaptor are necessary.
3. If user uses the ADSL or Static IP, please connect the WAN port.

3 Login Page


For the initial setup of a MG700, a user will use an Ethernet cable to connect to a computer. Using a web browser, enter the default IP address and port (192.168.60.1:8080) into the address bar. The Login page will appear. Enter “admin” into the User Name and Password fields. The User Name and Password can be changed during initial setup. If you logged in successfully, then you will see the Login Success page. Press the “Confirm” button to enter into the configuration page.



The diagram illustrates the MG700 Login process. It shows two windows. The top window is a 'Login' form with fields for User Name, Password, and Language (set to English), and a 'Login' button. The bottom window is a 'Login Success' page with a 'Confirm' button.

4 Status Page

Under the Status tab, information for the Router, User/DHCP and User/Current can be selected through the drop-down menu.



4.1 Router

On the Router Page, the router information will be shown in four sections: Router Information, WAN 1, LAN 1, and Wireless Network 1.

Router Information includes model name, firmware version, license, and current and running times.

Router Information	
Model Name	MG700
Firmware Version	1.5.2
License	Unauthorized(-29935)
Current Time	Thu, 02 Jul 2015 10:00:41
Running Time	5 days, 9 hours, 3 mins

The WAN 1 information shows MAC address, connection type, IP address, subnet mask, and gateway.

WAN 1	
MAC Address	No MAC Address
Connection Type	wwan
IP Address	100.106.29.207
Subnet Mask	32
Gateway	10.64.64.64

The LAN 1 page shows MAC address, IP address, subnet mask, DHCP service, DHCP start IP address, DHCP end IP address, and max DHCP clients.

LAN 1

MAC Address	5C:B8:CB:00:04:0C
IP Address	192.168.60.1
Subnet Mask	24
DHCP Service	Enabled
DHCP Start IP Address	192.168.60.20
DHCP End IP Address	192.168.60.69
Max DHCP Clients	50

The Wireless Network 1 includes the wireless channel, wireless SSIDs, and MAC addresses.

Wireless Network 1

Wireless Channel	6
Wireless SSID 1	PXS8-A1
MAC Address	5C:B8:CB:00:04:08
Wireless SSID 2	PXS8-A2
MAC Address	5C:B8:CB:00:04:09

4.2 User / DHCP


Status - User/DHCP

Name	IP Address	MAC Address	Expiration Time
android-c1e6603a97c1564f	192.168.60.37	a8:26:d9:30:d1:6c	49709 day(s), 15:34:47
android-979375f9f3a1dda	192.168.60.38	50:2e:5c:e7:fd:ac	49709 day(s), 15:34:37

[Refresh](#)

5 Setup Page

On the Setup – WAN page, a user can set up the WAN, LAN, DHCP, DDNS, Time, and Relay.




5.1 WAN

In the WAN 1 section of the WAN page, select Enable and Connection Type. The connection types to choose from are DHCP, PPPoE, Static IP, 3G/4G Mobile Internet, and WISP. For most Ethernet connections, the default DHCP client mode is sufficient. If your WAN interface has been assigned a static IP address, then select “Static IP” and enter the appropriate TCP/IP setting value. If your Ethernet connection uses the PPPoE protocol, then select “PPPoE” and enter your login information. The MG700’s WiFi radio can also be used in place of the wired Ethernet WAN connect.

- Failover

In MG700 support failover function. The failover is switching to a redundant Service Provider between Verizon and T-Mobile network. If Service Provider is selected Verizon, the MG700 will select Verizon network to be the main Service Provider. MG700 will connect internet by Verizon network first. If Verizon network cannot connect internet, MG700 will change to T-mobile network automatically.




Location	USA
Service Provider	T-Mobile(new)
FailOver	<input checked="" type="checkbox"/>
Access Point Name (APN)	epc.tmobile.com
Personal Identification Number (PIN)	
Authentication	CHAP (Auto)
User Name	
Password	*****
Dial Number	*99#

Important: The Failover function is only support Verizon and T-mobile network system switch automatically.

- **DHCP mode**

If DHCP is selected, then the MG700 will be assigned an IP address from the server. The IP address is automatically assigned to you by your ISP (most common Ethernet WAN option).

Setup - WAN



WAN	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type	DHCP
Host Name	
MTU	1500 Bytes
Bigpond Login	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Bigpond Login Server	New South Wales (61.9.192.13)
Bigpond Login User Name	
Bigpond Login Password	*****
VPN Client	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

- **PPPoE mode**

In PPPoE mode, a user needs to key in the User Name and Password. If your ISP provides the username and password, then please enter the information accordingly.

WAN 1

WAN	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type	PPPoE
Authentication	CHAP (Auto)
User Name	<input type="text"/>
Password	<input type="password"/> *****
PPP Echo Interval	20 Seconds (20 ~ 180)
PPP Retry Threshold	20 Time(s) (3 ~ 50)
PPP MTU	1492 Bytes (592-1492)
MTU	1500 Bytes (600~1500)
VPN Client	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

- **Static IP mode**

For Static IP connections, enter the IP address, netmask, gateway and DNS information. The IP address, subnet mask, gateway and DNS server are provided by your ISP. The IP address cannot be the same as the LAN's IP address.

WAN 1

WAN	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type	Static IP
External IP Address	10.1.1.25
Netmask	255.255.255.0
Gateway	10.1.1.254
Static DNS 1	10.1.1.254
Static DNS 2	<input type="text"/>
MTU	1500 Bytes
VPN Client	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

- **WISP mode**

The built-in WiFi radio can be used as a WAN interface to establish a connection to an external WiFi network. The MG700 supports both AP mode and WiFi Client mode. Whenever the MG700 detects the target WiFi network, it will automatically try to make a connection to this network. This option can be disabled at the Ethernet WAN interface, but the MG700 can still function as a local WiFi access point while connected to the remote WiFi network. A user can also set the MG700 to connect to other WiFi AP. In the WISP mode, press the Survey button and the MG700 will search for WiFi AP. For example, the Client1 and Client2 can connect internet by WISP setting through Host WiFi AP.



A site survey list will appear. After selecting the proper WiFi AP, the target SSID and MAC address will fill in automatically.

WISP

Site Survey

Channel	SSID	BSSID	Security Mod	Signal	ExtCH	Wireless Mode
1	DSL-6740C	78:54:2e:e9:06:af	WPA2PSK/AES	15	BELOW	11b/g/n
3	TennVac-WIFI	c0:a0:bb:d2:04:f4	WPA1PSKWPAP2P	91	BELOW	11b/g/n
4	TennVac-Office	c0:a0:bb:d2:07:78	WPA1PSKWPAP2P	39	BELOW	11b/g/n
6	ACC-GPS-Client1	5c:b8:cb:10:00:20	WPA2PSK/TKIP	96	BELOW	11b/g/n
6	ACC-GPS-Client2	5c:b8:cb:10:00:21	WPA2PSK/TKIP	86	BELOW	11b/g/n
6	ALLISCOM1	5c:8b:cb:10:00:10	NONE	100	BELOW	11b/g/n
7	GlyconexAP	84:c9:b2:6f:0e:ff	WPA1PSKWPAP2P	20	BELOW	11b/g/n
9	GNIntAP	50:67:f0:45:7f:68	WPA2PSK/AES	76	BELOW	11b/g/n
11	ACC_AP_2.4	e8:94:f6:eb:be:ab	WPA2PSK/AES	44	BELOW	11b/g/n

WAN 1

WAN	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Connection Type	WISP <input style="border: 1px solid #ccc; padding: 2px 5px;" type="button" value="..."/>
Target SSID	ALLISCOM1 <input style="border: 1px solid #ccc; padding: 2px 5px;" type="button" value="..."/>
Target BSSID (MAC)	5c:8b:cb:10:00:10 <input style="border: 1px solid #ccc; padding: 2px 5px;" type="button" value="..."/>
Wireless Channel	Channel 6 [2.437GHz] <input style="border: 1px solid #ccc; padding: 2px 5px;" type="button" value="..."/>
Extention Channel	Below <input style="border: 1px solid #ccc; padding: 2px 5px;" type="button" value="..."/>
Site Survey	<input style="border: 1px solid #ccc; padding: 2px 10px;" type="button" value="Survey"/>
Security Mode	Disable <input style="border: 1px solid #ccc; padding: 2px 5px;" type="button" value="..."/>
VPN Client	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

- **VPN Client**

The MG700 support act as PPTP “client”, it will enable to allow the WAN to make a client connection to a remote PPTP server. If enabled, enter the PPTP username, password, VPN host IP address an MPPE128 parameters required for the PPTP VPN connect.

VPN Client	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
VPN Client Type	PPTP
User Name	<input type="text"/>
Password	<input type="text"/>
VPN Host	<input type="text"/>
MPPE128	<input checked="" type="radio"/> Enable <input type="radio"/> Disable

6 LAN

If a user needs to change the MG700 default LAN subnet, then go to the Setup - LAN page and enter the IP address assigned to the MG700 and select the desired subnet mask from the drop-down list. The MG700 DHCP server will automatically adjust to serve addresses from the new subnet.

Setup - LAN

LAN 1	
Internal IP Address	192.168.60.1
Netmask	255.255.255.0
Spanning Tree Protocol (STP)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
MTU	1500 Bytes


Setup - LAN

LAN 1	
Internal IP Address	192.168.60.1
Netmask	255.255.255.0 <ul style="list-style-type: none"> 255.255.0.0 255.255.128.0 255.255.192.0 255.255.224.0 255.255.240.0 255.255.248.0 255.255.252.0 255.255.254.0 255.255.255.0 255.255.255.128 255.255.255.192
Spanning Tree Protocol (STP)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
MTU	1500 Bytes

7 DHCP Server

The DHCP service is enabled by default, a user can set the Start IP address and Max DHCP Clients number.

Setup - DHCP Server



DHCP Server - LAN 1

DHCP Service	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
DHCP Start IP Address	192.168.60.20
Max DHCP Clients	50
Lease	1 hour
Domain	lan
DHCP DNS Server Type	DNS Relay
DHCP DNS Server IP Address	[Empty field]
	[Empty field]

8 DDNS

DDNS (Dynamic Domain Name Service) allows an “internet domain name” to be assigned to a computer /router which has a dynamic IP address. This makes it possible for other internet devices to connect to the computer/router without needing to trace the changing IP addresses themselves. To enable DDNS, you will first need to sign up for DDNS services from one of the supported DDNS service providers such as DynDNS.org, TZO.com or ZoneEdit.com...etc. The MG700 supports the unique DDNS server for free. DDNS is useful when combined with the virtual host and/or port-forwarding features. It allows internet users to connect to your virtual host by using a domain name rather than an IP address. The DDNS service helps users to locate the correct IP address through the domain name.

For example, assume that you wish to remotely access a web server embedded in one of your LAN devices, but you obtain a different IP address from your ISP each time you connect to the internet. In this case, you will need to enable DDNS, so users can connect to your web server through a fixed domain name without regard for the changing IP address of your WAN connection. The DDNS service is disabled by default. A user can configure the host name and password.

As a service to its customers, MGDDNS operates a Dynamic DNS service which is automatically updated each time a MG700 IP changes. The DDNS host name is the MAC address of the MG700 in the “mgddns.com” domain. For example: 5CB8CB000500.mgddns.com. This “permanent” DDNS names is always available but cannot be changed. To create your own hostname, register with one of the supported DDNS service providers before configuring the MG700’s DDNS settings.

Dynamic Domain Name Service - WAN 1

DDNS Service	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
DDNS Type	Mgddns.com
User Name	6f39e97e73ded4f7e8cd286cbc59bd
Password	*****
Host Name	alvin.mgddns.com
Update Time	10 (Min)

DDNS Service	Select Enable to enable DDNS service. Select Disable to disable DDNS service.
DDNS Type	Mgddns.com
Host Name	Enter the name (such as “alvin”) assigned by DDNS service for MG700, e.g: alvin.mgddns.com, the DDNS service will be updated the hostname on MG700. The hostname must match exactly on both the DDNS account.
Update Time	Update DDNS IP period.

Remote Management needs to be enabled if a user wants get the MG700 by a DDNS server.

Administration Interface

Language	English
Administrator Password	*****
Re-type Password	*****
Remote Management	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Management Port	HTTP 8080

Important:

- 8.1.1.1 The DDNS should be public IP address.
- 8.1.1.2 Remote Management need to Enable

9 Time

The MG700 supports NTP client to update the time. A user can set up the Time Server Area, Time Zone and synchronization interval. A user can also set up the automatic reboot time on this page.

Setup - Time

Time Synchronization	
Time Synchronization	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Time Server Type	<input checked="" type="radio"/> Time Server Pool <input type="radio"/> Manual
Time Server Area	Asia <input type="button" value="▼"/>
Time Server IP Address	<input type="text"/>
Time Zone	UTC+08:00 Taiwan, China, Hong Kong, Western Australia, Singapore <input type="button" value="▼"/>
Periodic Synchronization	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Daylight Saving Support	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Synchronization Interval	Every Day <input type="button" value="▼"/>
Action	<input type="button" value="Update"/>
Automatic Reboot	
Reboot Interval	<input type="text"/> (5 ~ 43200 min(s))
Daily Reboot	NONE <input type="button" value="▼"/>

10 Relay

MG700 support the 2 channel GPIO Relay Function. User can see and control the Relay status on this page.

Setup - Relay

Status																																																																																																																																																																																																	
Relay 1	ON																																																																																																																																																																																																
Relay 2	ON																																																																																																																																																																																																
Control																																																																																																																																																																																																	
<input type="radio"/> Schedule <input checked="" type="radio"/> Manually																																																																																																																																																																																																	
Direct																																																																																																																																																																																																	
Relay 1 :	<input checked="" type="radio"/> ON <input type="radio"/> OFF																																																																																																																																																																																																
Relay 2 :	<input checked="" type="radio"/> ON <input type="radio"/> OFF																																																																																																																																																																																																
Relay 1 Schedule																																																																																																																																																																																																	
<table border="1"> <tr> <td>00</td><td>01</td><td>02</td><td>03</td><td>04</td><td>05</td><td>06</td><td>07</td><td>08</td><td>09</td><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td> </tr> <tr> <td>Sunday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Monday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Tuesday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Wednesday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Thursday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Friday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Saturday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> </table>		00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23	Sunday																								Monday																								Tuesday																								Wednesday																								Thursday																								Friday																								Saturday																							
00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23																																																																																																																																																																										
Sunday																																																																																																																																																																																																	
Monday																																																																																																																																																																																																	
Tuesday																																																																																																																																																																																																	
Wednesday																																																																																																																																																																																																	
Thursday																																																																																																																																																																																																	
Friday																																																																																																																																																																																																	
Saturday																																																																																																																																																																																																	
<input type="button" value="Select ALL"/> <input type="button" value="Clean ALL"/>																																																																																																																																																																																																	
Relay 2 Schedule																																																																																																																																																																																																	
<table border="1"> <tr> <td>00</td><td>01</td><td>02</td><td>03</td><td>04</td><td>05</td><td>06</td><td>07</td><td>08</td><td>09</td><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td> </tr> <tr> <td>Sunday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Monday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Tuesday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Wednesday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Thursday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Friday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>Saturday</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> </table>		00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23	Sunday																								Monday																								Tuesday																								Wednesday																								Thursday																								Friday																								Saturday																							
00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23																																																																																																																																																																										
Sunday																																																																																																																																																																																																	
Monday																																																																																																																																																																																																	
Tuesday																																																																																																																																																																																																	
Wednesday																																																																																																																																																																																																	
Thursday																																																																																																																																																																																																	
Friday																																																																																																																																																																																																	
Saturday																																																																																																																																																																																																	
<input type="button" value="Select ALL"/> <input type="button" value="Clean ALL"/>																																																																																																																																																																																																	

In control block, MG700 support Schedule and Manually mode. If User select Manually mode, user can setting the Relay is On or Off immediately. If User select Schedule mode, MG700 will set Relay On/Off by schedule.

Control	
<input type="radio"/> Schedule <input checked="" type="radio"/> Manually	
Direct	
Relay 1 :	<input checked="" type="radio"/> ON <input type="radio"/> OFF
Relay 2 :	<input checked="" type="radio"/> ON <input type="radio"/> OFF

As the control mode change to Schedule, user can setting the Relay1/Relay2 Schedule time is on or off status.

Control	
<input checked="" type="radio"/> Schedule <input type="radio"/> Manually	

As Schedule selected on Control block, the Relay schedule table will be enabled. User can select the Relay on or off time, the MG700 will turn relay on or off by schedule table automatically. There are 2 tabs in an hour row. After setup done, press “Save settings” button to update the newest configuration.

Relay 1 Schedule

	00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Sunday																								
Monday																								
Tuesday																								
Wednesday																								
Thursday																								
Friday																								
Saturday																								

Relay 2 Schedule

	00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Sunday																								
Monday																								
Tuesday																								
Wednesday																								
Thursday																								
Friday																								
Saturday																								

Day of week

One tab is half-hour

Note:

10.1.1.1 Relay Schedule tab could be selected as in schedule mode.

10.1.1.2 The time of day depends on MG700's time.

11 Alert

In this Page, MG700 support 2 E-mail Alert notice. When the Event trigger, it will send the mail to notice user. The Event include SD card full、USB storage Full、Relay On and Relay Off.

Setup - Alert

Alert Notice

<p>Event</p>	<input type="checkbox"/> Battery low <input type="checkbox"/> SD Card Event <input type="checkbox"/> USB Storage Event <input type="checkbox"/> Relay On/Off <input type="checkbox"/> E-mail
Event Send	
Email setting	E-mail: <input type="text"/> E-mail: <input type="text"/>

ALLIS COMMUNICATIONS

Page 21 of 58

MG700 Specifications Rev:1.5.2

Email setting

E-Mail	<input type="text"/>
SMTP Server	<input type="text"/>
Send Mail	<input type="text"/>
SMTP Account	<input type="text"/>
SMTP Password	<input type="text"/>

[Save Settings](#) [Cancel Changes](#)


E-Mail	User e-mail address
SMTP Server	SMTP mail server : Port, such as smtp.gmail.com:465
Send Mail	User e-mail address name
SMTP Account	SMTP user's account name
SMTP Password	SMTP user's password

Note: The Battery notice low event is for option.

12 Wireless Page

The MG700's multiple simultaneous SSIDs provide the ability to create separate security mode and key settings for both convenience and increased protection. For example, users can configure their network devices to access the first SSID with the WPA2 PSK (Pre-Shared Key), while guests can be assigned to the second SSID with a WEP key that changes periodically. In addition, the SSIDs can be isolated to prevent malicious attacks and local area network access for guests using the second SSID. This provides an extremely convenient approach to providing internet access for guests while maintaining strong security protection at all times.

The Wireless Page has the WiFi Basic and WDS settings. The MG700's internal 802.11 b/g/n WiFi radio is disabled by default as a security precaution. To provide laptops, tablets and other WiFi devices with internet connectivity through the MG700, go to the Wireless - Basic page and enable the wireless connection.



12.1 Basic

On the Basic Page, a user can select to enable or disable wireless connection. A user can also change the wireless mode, WiFi power and channel. Only SSID1 will be enabled by default. You may change the SSID name to suit your preference. We strongly recommend that you change the security mode to prevent unauthorized access to your internet connection. The MG700 also supports a second SSID. This is most often used when you wish to provide “guest” access to your internet service and maintain guest devices on a LAN subnet different than your other devices.

Wireless - Basic

WLAN 1

Wireless Connection	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless Mode	B/G/N Mixed
Transmission Power	100%
Wireless Channel	Channel 6 [2.437GHz]
Wireless Isolation Between SSIDs	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

WLAN 1 - SSID 1

Wireless SSID	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless SSID Name	PXS8-A1
Wireless SSID Broadcasting	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wi-Fi Multimedia (WMM)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless Isolation	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Security Mode	Disable

Users connecting to SSID2 can be segregated into their own local area network to provide Internet service while preventing access to other device on the primary LAN. Enter the Guest LAN starting IP Address which will be assigned to the MG700, and the corresponding subnet mark. Guest WiFi devices will be assigned a DHCP address in this subnet. For more flexibility in controlling guest WiFi access.

WLAN 1 - SSID 2

Wireless SSID	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless SSID Name	PXS8-A2
Wireless SSID Broadcasting	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wi-Fi Multimedia (WMM)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless Isolation	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Security Mode	Disable
Guest LAN	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Guest LAN IP Address	192.168.2.1
Guest LAN Netmask	255.255.255.0

- WiFi Security Mode

The choice for WiFi security mode include: Disable, WEP, WPA PSK(Pre-Shared Key), WPA (Radius), WPA2 PSK(Pre-Shared Key), and WPA2 (Radius) mode.

WLAN 1 - SSID 1

Wireless SSID	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless SSID Name	<input type="text" value="MG700_1"/>
Wireless SSID Broadcasting	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wi-Fi Multimedia (WMM)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless Isolation	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Security Mode	<input type="button" value="WPA2 PSK (Pre-Shared Key) ▾"/> <div style="border: 1px solid #ccc; padding: 5px; width: 150px; margin-top: 5px;"> <input type="button" value="Disable"/> <input type="button" value="WEP"/> <input type="button" value="WPA PSK (Pre-Shared Key)"/> <input type="button" value="WPA (Radius)"/> <input type="button" value="WPA2 PSK (Pre-Shared Key)"/> <input type="button" value="WPA2 (Radius)"/> </div>
Key	
Encryption Method	

(The Key is an ASCII string of 8-63 digits, or a HEX string of 64 digits.)

- WEP Mode

Users can setup the WEP key index indicates which WEP key is used for data encryption. The WEP Key(1~4), for 64-bit WEP mode, type 10 hexadecimal digits or 5 ASCII characters. For 128-bit WEP, type 26 hexadecimal digits or 13 ASCII characters.


WLAN 1 - SSID 1

Wireless SSID	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless SSID Name	<input type="text" value="PXS8-A1"/>
Wireless SSID Broadcasting	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wi-Fi Multimedia (WMM)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Wireless Isolation	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Security Mode	<input type="button" value="WEP ▾"/> <div style="border: 1px solid #ccc; padding: 5px; width: 150px; margin-top: 5px;"> <input type="button" value="1 ▾"/> </div>
Key Index	
Key 1	<input type="text"/>
Key 2	<input type="text"/>
Key 3	<input type="text"/>
Key 4	<input type="text"/>

(The WEP Keys are ASCII strings of 5/13 digits, or HEX strings of 10/26 digits.)

- **WPA PSK mode**

Setup the Pre-shared Key index as the credential for the packet encryption. This same value must be entered in all WiFi deices connecting to this SSID. In Encryption Mode, TKIP & AES are supported.



WLAN 1 - SSID 1

Wireless SSID Enable Disable
PXS8-A1

Wireless SSID Broadcasting Enable Disable
Wi-Fi Multimedia (WMM) Enable Disable
Wireless Isolation Enable Disable


Security Mode: WPA PSK (Pre-Shared Key)

Key:

Encryption Method: TKIP
TKIP
AES
Mixed (TKIP+AES)

(The Key is an ASCII string of 8-63 digits, or a HEX string of 16-128 digits.)

- **WPA (Radius)**



WLAN 1 - SSID 1

Wireless SSID Enable Disable
PXS8-A1

Wireless SSID Broadcasting Enable Disable
Wi-Fi Multimedia (WMM) Enable Disable
Wireless Isolation Enable Disable

Security Mode: WPA (Radius)

Radius Server IP Address: 192.168.1.1

Radius Server Port: 1812

Radius Key:

Encryption Method: TKIP

Rekey Method: Disable

Rekey Time Interval: 3600

Rekey Packet Interval: 5000

(The Key is an ASCII string of 8-63 digits, or a HEX string of 64 digits.)

In WPA mode, the list as below:

Radius Server IP Address	Input the RADIUS server's IP address
Radius Server Port	Input the RADIUS server's port number. The default port is 1812.
Radius Key	Input the RADIUS server's Key
Encryption Method	Select TKIP or AER for the packet encryption.
Rekey Method	Select method for determining when new key is required.
Rekey Time Interval	Input the frequency of key renewals in seconds.
Rekey Packet Interval	Input the frequency of key renewals in number of packets.

12.2 Advanced

On the Advanced Page, a user can set the Region and other WLAN settings.

Wireless - Advanced

Region Setting

Region	US, Canada and Taiwan (channel 1 - 11)	<input type="button" value="▼"/>
--------	--	----------------------------------

WLAN 1

Fragmentation	2346	Bytes (256 ~ 2346)
RTS	2347	Seconds (1 ~ 2347)
DTim	1	(1 ~ 255)
Beacon Interval	100	Milliseconds (20 ~ 1024)
Header Preamble	Long	<input type="button" value="▼"/>
TxMode	None	<input type="button" value="▼"/>
MPDU	4	<input type="button" value="▼"/> Microseconds
MSDU Aggregate	<input type="radio"/> Enable <input checked="" type="radio"/> Disable	
Tx Burst	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
Packet Aggregate	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
HT Control Field	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
Reverse Direction Grant	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
Link Adapt	<input type="radio"/> Enable <input checked="" type="radio"/> Disable	
Short Guard Interval(GI)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
Operation Mode	Mixed Mode	<input type="button" value="▼"/>
HT Band Width	20/40	<input type="button" value="▼"/> MHz
Block Ack Setup Automatically	<input checked="" type="radio"/> Enable <input type="radio"/> Disable	
Block Ack Window Size	64	x16 Bits (1 ~ 64)
Reject Block Ack	<input type="radio"/> Enable <input checked="" type="radio"/> Disable	

Region	Choose the region in which the MG700 is currently operating (sets channels).
Fragmentation	Enter the fragmentation bytes. The default value is 2346 bytes.
RTS	Enter the RTS seconds. The default value is 2347 seconds.
DTim	Enter the DTim seconds. The default value is 1.
Beacon Interval	Enter the interval to send a beacon. The default value is 100 milliseconds.
Header Preamble	Choose Long or Short header preamble.
TxMode	Choose different transmission mode.
MPDU	MPDU data length. The transmission rate is increased when you choose a larger number, but usually the max value will be 4 in the wireless card
MSDU Aggregate	A kind of packet aggregation method, it can improve the transmission efficiency. Please make sure you Wireless card has this function supported.
Tx Burst	Some 802.11g wireless cards support this mode. The transmission rate can be increased when this function is enabled.
Packet Aggregate	An aggregation method like A-MSDU(MAC Service Data Unit), it can improve the transmission efficiency. Please make sure you Wireless card has this function supported.
HT Control Field	Choose Enable/Disable. It is useful when you need to debug the wireless network.
Reverse Direction Grant	Choose Enable/Disable. The response time can be shorter enable this function is enabled.
Link Adapt	Choose Enable/Disable. The function is used to dynamically change the modulation and encoding mechanism between wireless devices.
Short Guard Interval (SGI)	Choose Enable/Disable. Short GI can improve the transmission rate, but with less immunity when interference exists.
Operation Mode	Choose Mixed mode or Greenfield. You may choose Greenfield mode to increase the transmission rate when you using 802.11n wireless network only.
HT Band Width	Using HT20MHz or HT20/40MHz
Block Ack Setup Automatically	Choose Enable/Disable. If your Wi-Fi Card supports the Block Ack mechanism, it can improve the data transmission efficiency when this function is enabled.
Block Ack Window Size	Specify a Block Ack window size.
Reject Block Ack	Choose Enable to reject the request of BA from another other Wireless device.
MCS	Select transmission (connection) speed.


12.3 WDS

A wireless distribution system (WDS) is a system which enables the wireless interconnection of access points in an 802.11 network. It allows a wireless network's coverage area to be expanded using multiple access points without a wired backbone to link the APs. A user can set the WDS settings in this page.


The MG700 supports two modes of WDS operation:

- Repeating: APs communicate with each other and with wireless clients.
- Bridging: APs only communicate with each other and don't allow wireless clients to access them.

All base stations in a wireless distribution system must be configured to use the same radio channel, method of encryption (none, WEP or WPA) and the same encryption keys. They may be configured to different service set identifiers (SSIDs). WDS also requires every base station to be configured to forward to others in the system.



WDS has three selections: Disabled, Repeater and Bridge modes. By default, WDS Mode is disabled. If a user selects Repeater mode, then the WiFi AP function still support and a user can still connect to the MG700's AP. If a user selects Bridge mode, then the MG700 will only be in bridge mode and the WiFi AP function will be disabled.



WDS supports four WDS points. Press the Survey button to search for WiFi AP.

Make sure of the following in order for WDS to work correctly:

- All WDS devices must use the same radio channel.
- All WDS devices must use the same encryption mode and encryption keys.

Wireless - WDS

WLAN 1

WDS Mode

WDS 1

WDS MAC Address

Security Mode

WDS 2

WDS MAC Address

Security Mode

WDS 3

WDS MAC Address

Security Mode

WDS 4

WDS MAC Address

Security Mode

Press Survey button, it shows the wireless AP. Then, click the SSID that user want to connect and press “Select” button.

Site Survey

Channel	SSID	BSSID	Security Mode	Signal	ExtCH	Wireless Mo..
1	DSL-6740C	78:54:2e:e9:06:af	WPA2PSK/AES	15	BELOW	11b/g/n
3	TennVac-WIFI	c0:a0:bb:d2:04:f4	WPA1PSKWPA2...	81	BELOW	11b/g/n
4	TennVac-Office	c0:a0:bb:d2:07:78	WPA1PSKWPA2...	34	BELOW	11b/g/n
4	USER-HP_ASUS	00:1a:2b:3c:ff:02	WPAPSK/TKIP	20	ABOVE	11b/g/n
6	ACC-GPS-Client1	5c:b8:cb:10:00:20	WPA2PSK/TKIP...	86	BELOW	11b/g/n
6	ACC-GPS-Client2	5c:b8:cb:10:00:21	WPA2PSK/TKIP...	86	BELOW	11b/g/n
6	ALLISCOM1	5c:8b:cb:10:00:10	NONE	100	BELOW	11b/g/n
7	GlyconexAP	84:c9:b2:6f:0e:ff	WPA1PSKWPA2...	15	BELOW	11b/g/n
9	GNIntAP	50:67:f0:45:7f:68	WPA2PSK/AES	70	BELOW	11b/g/n

Choose the WiFi AP and press the Select button. The WDS MAC Address will fill in automatically.

Wireless - WDS

WLAN 1

WDS Mode

WDS 1

WDS MAC Address

Security Mode

WDS 2

WDS MAC Address

Security Mode

WDS 3

WDS MAC Address

Security Mode

WDS 4

WDS MAC Address

Security Mode

Important:

- 12.3.1.1 If WDS mode is Bridge mode, user cannot see the SSID
- 12.3.1.2 Setup WDS system suggest use the same devices (MG700 series).

13 Security Page

Security mode include: Firewall, IP Access Control, Outbound MAC ACL, Web Filtering, VPN/PPTP and VPN/IPsec mode.

	Status	Setup	Wireless	Security	Applications	Bandwidth
Security - Firewall				Firewall		
Firewall Protection				IP Access Control		
SPI Firewall Protection	<input checked="" type="radio"/>	Enable	<input type="radio"/>	Disable	Outbound MAC ACL	
TCP SYN DoS Protection	<input checked="" type="radio"/>	Enable	<input type="radio"/>	Disable	Web Filtering	
ICMP Broadcasting Protection	<input checked="" type="radio"/>	Enable	<input type="radio"/>	Disable	VPN / PPTP	
ICMP Redirect Protection	<input checked="" type="radio"/>	Enable	<input type="radio"/>	Disable	VPN / IPsec	
Broadcast Storming	<input type="radio"/>	Enable	<input checked="" type="radio"/>	Disable		

13.1 Firewall

The Firewall page allows the enabling/disabling of SPI Firewall protection, TCP SYN DoS Protection, ICMP Broadcasting Protection, ICMP Redirect Protection and Broadcast Storming method.

Security - Firewall

Firewall Protection	
SPI Firewall Protection	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
TCP SYN DoS Protection	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
ICMP Broadcasting Protection	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
ICMP Redirect Protection	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Broadcast Storming	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

13.2 IP Access Control

The IP Access Control page lets a user control access to the MG700 from a specific IP address.

Security - Access Control

Access Control List (ACL)

Access Control	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Default Access Control Action	<input checked="" type="radio"/> ALLOW <input type="radio"/> DENY

Access Control List (ACL) Rule

Rule Name	Rule Enable	External Inte	Internal IP Range	External IP Range	Protocol	Service Port Rai	Action
+ Add Delete Modify Up Down							

A user can add rules by setting up a Rule Name, Internal and External IP ranges, and Action (Allow or Deny).

ACL Data

Rule Name:

Enable:

External Interface:

Internal IP Range: From: To:

External IP Range: From: To:

Protocol:

Service Port Range: From: To:

Action:

Rule Name	Webcam1
Rule Enable	Enable
External Interface	WAN1
Internal IP Range	If assign, it applies to specific IP. If blank, it applies to all LAN devices.
External IP Range	Assign external IP address range
Protocol	TCP/UDP
Service Port Range	33
Action	ALLOW

13.3 Outbound MAC ACL

The MG700 can allow a specific MAC address to log in. The MAC Access Control of MG700 is used to either allow or deny specific devices identified by their MAC address from making “outbound”

connections. The MAC rules also enable you to “statically” assign an IP address from MG700’s DHCP pool to a specific MAC address.

Security - MAC Access Control

MAC Access Control

MAC Access Control	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Default MAC Access Control Action	<input checked="" type="radio"/> ALLOW <input type="radio"/> DENY

MAC Access Control Rule

Rule Enable	Action	MAC	ACL Enable	Static ARP Enable	Static DHCP Enable	IP
<input type="button" value="Add"/> <input type="button" value="Delete"/> <input type="button" value="Modify"/> <input type="button" value="Up"/> <input type="button" value="Down"/>						

For example, user press “Add” and set the specific MAC address to assign IP address.

MAC Data


Rule Name:	<input type="text" value="Rule1"/>
MAC:	<input type="text" value="00:00:00:00:00:09"/>
Action:	<input type="button" value="ALLOW"/>
ACL Enable:	<input checked="" type="checkbox"/>
Static ARP Enable:	<input checked="" type="checkbox"/>
Static DHCP Enable:	<input checked="" type="checkbox"/>
IP:	<input type="text" value="192.168.60.30"/>

Rule Name	Name of the MAC access rule. Spaces are not allowed. For example :“Rule1”
MAC	Set up the MAC Address to which you would like to enable the MAC ACL action. For example, the MAC address as: 00:00:00:00:00:09
Action	Select whether the MG700 should ALLOW / DENY packets matching this rule.
ACL Enabled	Enable/Disable this MAC access rule.
Static ARP Enabled	Enable/Disable this Static ARP rule.
Static DHCP Enabled	Enable/Disable this Static DHCP rule.
IP	The IP address to assign via static ARP or static DHCP. The address must be within the DHCP pool configured for the MG700 and the DHCP Server feature must be enabled. For example : 192.168.60.30

13.4 Web Filtering

The MG700 can set web filtering, include ActiveX, Java Scripting and Proxy filtering.

Security - Web Filtering



Web Filtering

Web Filtering Enable Disable

Web Content Filtering

Activex Filtering Enable Disable

Java/JavaScript Filtering Enable Disable

Proxy Filtering Enable Disable

Web Filtering Rule

Rule Enable	Filter Keyword	Filter Type	Action
+ Add	Delete	Modify	Up Down

13.5 VPN/PPTP Page

The MG700 supports VPN server. Add rule enable, if VPN PPTP enable. User can set rule to connect MG700 by VPN and VPN start IP address. The Point-to-Point Tunneling Protocol (PPTP) is a method for implementing virtual private networks. PPTP uses a control channel over TCP and GRE tunnel operating to encapsulate PPP packets. The PPTP settings in this section define the parameters and user access rules when the MG700 is acting as a PPTP “server” allow connections from remote PPTP clients such as Windows PC's.

PPTP

PPTP	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
MTU	1482 Bytes
VPN Start IP Address	192.168.39.1
Max VPN Clients	10
Auto DNS	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
DNS	<input type="text"/>
CHAP Enable	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
MSCHAP Enable	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
MSCHAP v2 Enable	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
MPPE128 Enable	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Proxy ARP Enable	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
NAT Enable	<input checked="" type="radio"/> Enable <input type="radio"/> Disable

Press “Add”, setup the rule enable, User Name and password.

User Rule

Rule Enable	User Name	Password
Add Delete Modify		


PPTP Data x

Rule Enable:	<input type="checkbox"/>
User Name:	<input type="text"/>
Password:	<input type="text"/>

Confirm
Cancel

14 Applications Page

Application function includes Port Range Forward, Streaming VPN and UPnP. By enabling the DMZ Host Function, you can set up a Demilitarized Zone (DMZ) host, that is, a particular computer which is fully exposed to the Internet. This may be necessary for certain applications that use random ports or when you do not know the specific ports required for remote access.



14.1 Port Range Forward

The MG700 provides Network Address Translation (NAT) services to protect private LAN IP addresses from access by users on the external WAN. Port-Forwarding is a technique to selectively allow remote users to access selected devices and services on the private LAN.

The MG700 supports both Port Forwarding and Port Translation features. These features are integrated with the MG700's firewall feature. Creating new port forwarding/translation rules automatically opens the corresponding ports in the firewall – no other configuration is necessary.

The port forwarding function gives remote users access to devices on the local network via the public WAN IP address. Users can assign a specific external port range to a local server (or IP address).

Furthermore, users can specify a different internal port range to be associated with external ports in a port forwarding rule. When the MG700 receives an external request to access any one of the configured external ports, it will redirect the request to the corresponding internal server and change its destination port to one of the internal ports specified. This allows multiple LAN devices with the same port (e.g. port 80) to be accessed remotely without having to change their settings.

Applications - Port Range Forward

DMZ - WAN 1

DMZ Enable Disable
DMZ IP Address

Port Range Forwarding

Port Forwarding Enable Disable

Port Range Forwarding Rule

Rule Name	Rule Enable	External Interfa	Protocol	External Port R	Internal IP	Internal Port Ra
+ Add	Delete	Modify	Up	Down		
Add	Delete	Modify	Up	Down	Save Settings	Cancel Changes

Press Add, then shows the Forward Data page to setting the forward IP and Port.

Forward Data

Rule Name:

Enable:

External Interface:

Protocol:

External Port Range: From: To:

Internal IP:

Internal Port Range: From: To:

Rule Name	Enter the name of the port forwarding rule. Do not contain spaces.
Rule Enabled	Check/Uncheck to enable/disable this port forwarding rule.
External Interface	Choose USB or Ethernet WAN as the External port forwarding interface. Each WAN interface must have its own port forwarding rules, so duplicate rules if using the MG700 in a WAN fail-over configuration.
Protocol	Choose TCP, UDP or TCP/UDP for the rule to be applied.
External Port Range	Set up the External Port Range for the rule to capture.
Internal IP	Set up the Internal IP (single address) where incoming packets will be directed when the rule is matched.
Internal Port Range	Set up the Internal Port Range where the rule will send matched packets. The internal and external port ranges must contain the same number of ports, but can be different to enable port translation.

14.2 Streaming/VPN

MG700 can enhance media streaming quality by enabling RTSP, MSS and H.323 protocols. Also, the MG700's VPN Pass-through functionality can also be enabled on this page. All of these features are enabled by default. User could set the Streaming/Video and VPN enable or disable.

Applications - Streaming / VPN

Streaming	
RTSP	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
MMS	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Video Conference	
H.323	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
VPN	
IPSec	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
PPTP	<input checked="" type="radio"/> Enable <input type="radio"/> Disable

14.3 UPnP

Universal Plug and Play (UPnP) is a set of networking protocols that permits networked devices, such as personal computers, printers, Internet gateways, Wi-Fi access points and mobile devices to seamlessly discover each other's presence on the network and establish functional network services for communications.

Applications - UPnP

UPnP	
UPnP	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
UPnP Port	49152

15 Bandwidth Page

The MG700 bandwidth management feature provides powerful and unique mechanism to manage bandwidth – Static Bandwidth Management (SBM) and Dynamic Bandwidth Management (DBM). SBM provide user with the option to allocate a fixed amount of bandwidth for a specific computer or a particular application, while DBM intellectually manages to rest of the bandwidth while all the time satisfying the complicated bandwidth requirements/settings of SBM. The MG700 allow user manage the bandwidth. The bandwidth include: Throughput Optimizer, TurboNAT and Session Manager.

15.1 Throughput Optimize

User can set the throughput optimizer enable and choice the application priority to manage bandwidth automatically.

Bandwidth - Throughput Optimizer

Throughput Optimizer	
Throughput Optimizer	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Application Priority	
TCP ACK	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
ICMP	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
DNS	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
SSH	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Telnet (BBS)	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
TCP Max Segment Size	<input checked="" type="radio"/> Enable <input type="radio"/> Disable

15.2 TurboNAT

Network Address Translation (NAT) is often a performance bottleneck in routers and firewalls. Generic routers are generally insufficient when dealing with a high-speed broadband network. TurboNAT is designed to solve this problem by accelerating NAT performance allowing the MG700 to maximize the higher speed networks and to reserve system performance for other features such as ACL and VPN servers.

Bandwidth - TurboNAT

TurboNAT	
TurboNAT	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
<input type="button" value="Save Settings"/> <input type="button" value="Cancel Changes"/>	

15.3 Session Manager

Session manager will automatically recycle old/dead sessions to get better connection efficiency. Users can choose the re-cycle rate to optimize the connection efficiency especially for applications which rapidly open and close many ports.


Bandwidth - Session Manager

Session Manager

Recycle Mode	Fast ▾
--------------	--------

16 Serial Setting Page

In this page, MG700 shows the Port1/Port2/Port3 Operating Mode, data count and listening status. The MG700 supports serial port to user serial device. The serial port data will be change to internet packet data. User can get the data by IP address and Port.




LINE						
Port	OP Mode	Data	ISP1	ISP2	ISP3	ISP4
Port 1	TCP Server	0	Listen	Listen	Listen	Listen
Port 2	TCP Server	0	Listen	Listen	Listen	Listen
Port 3	TCP Server	0	Listen	Listen	Listen	Listen

16.1 Status Page

In Status Page, user can monitoring the serial port setting mode and login information.

Serial - Status




LINE						
Port	OP Mode	Data	ISP1	ISP2	ISP3	ISP4
Port 1	TCP Server	494341506	Listen	Listen	Listen	Listen
Port 2	TCP Server	467538394	220.133.29.222	Listen	Listen	Listen
Port 3	TCP Server	0	Listen	Listen	Listen	Listen

16.2 Port1/2/3 Page

In Port1/2/3 page, user can set the serial port alias name, baud rate, hardware flow control...etc. The Port alias name will create the same directory in SD/USB storage.

Serial setting - Port 1



Serial Setting	
Port alias	port1
Baud Rate	115200
Data bits	5
Stop bits	1
Parity	None
Flow Control	None
FIFO	<input type="radio"/> Enable <input checked="" type="radio"/> Disable

The operation mode could be set to TCP Server Mode, TCP Client mode and UDP mode. The TCP Server Mode allow user login the MG700's specific port to get the serial port 1 data. The specific port set into

local port.

In TCP Server mode, user MG700 will keep listening for TCP connection.

Operating Setting

Operation Mode	TCP Server Mode TCP Server Mode (selected) TCP Client Mode UDP Mode
Packing length	1024 (0 - 1024)
Force transmit	700 (0 - 65535 ms)
TCP alive check time	7 (0 - 99 min)
Inactivity time	0 (0 - 65535 ms)
Connection Limit	4
Ignore Disconnection IP	<input type="radio"/> No <input checked="" type="radio"/> Yes
TCP Server Mode	
Local TCP Port	101

Operation Mode	TCP Server Mode
Packing length (Byte)	MG700 will force out as data length meet the parameter.
Force transmit (ms)	MG700 will Force transmit serial data to the Ethernet port.
TCP alive check time(min)	MG700 will check the TCP connection is alive or not, if not, MG700 will close the connection.
Inactivity time(ms)	If TCP connection is no response with MG700, MG700 will close the connection.
Connection Limit	Allow TCP connection request data in the same time. The maximum is 4.
Ignore Disconnection IP	If select Yes, the TCP connection is not responding will be ignored.
Local TCP Port	Setting the proper Local TCP Port, MG700 will listen Local TCP Port to connection. Note: Do NOT set the same Local TCP Port on Port1/Port2/Port3.

The Client Mode, user can send serial port data out to Destination IP address and Port.

Operating Setting

Operation Mode	<input type="button" value="TCP Client Mode"/>
Data Packing	
Packing length	<input type="text" value="1024"/> (0 - 1024)
Force transmit	<input type="text" value="700"/> (0 - 65535 ms)
TCP alive check time	<input type="text" value="7"/> (0 - 99 min)
Inactivity time	<input type="text" value="0"/> (0 - 65535 ms)
Ignore Disconnection IP	<input checked="" type="radio"/> Yes <input type="radio"/> No
TCP Client Mode	
Destination IP Address	Port
Destination IP address 1	<input type="text" value="4001"/>
Destination IP address 2	<input type="text" value="4001"/>
Destination IP address 3	<input type="text" value="4001"/>
Destination IP address 4	<input type="text" value="4001"/>
Destination Local Port 1	<input type="text" value="5011"/> (0 - 65535) (0 represents assigned automatically.)
Destination Local Port 2	<input type="text" value="5012"/> (0 - 65535)
Destination Local Port 3	<input type="text" value="5013"/> (0 - 65535)
Destination Local Port 4	<input type="text" value="5014"/> (0 - 65535)

16.3 File Mode Page

In this page, user can set the serial data save to SD card or/and USB storage. The SD card is default.

Serial - File Mode

Global Setting

File Mode	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
Destination	<input checked="" type="checkbox"/> SD (Default) <input checked="" type="checkbox"/> USB Storage

Before user remove the SD card or USB storage, please select File Mode to Disable. It will protect the record data. It is because of the FAT/FAT32 format. If the SD/USB is EXT3/EXT4 format, the data will be performance and reliability. Please see the Appendix II: Ext3/Ext4 Format.


Important: Select File mode to disable before remove the SD card or USB storage.

The record method means if the storage space is full, the serial data will be re-cycle record or stop record.


Signal Setting

UART Source	Record Method
Port 1	<input type="radio"/> Re Cycle <input checked="" type="radio"/> Full Stop
Port 2	<input type="radio"/> Re Cycle <input checked="" type="radio"/> Full Stop
Port 3	<input type="radio"/> Re Cycle <input checked="" type="radio"/> Full Stop

User can login MG700 to download the record data. In the windows system, user input the “\\192.168.60.1” to login. In the Linux system, user input the “SMB://192.168.60.1/” to login.



The port1/port2/port3 directory depends on device alias name.



The DDNS with File Mode, user can enter the “<\\alvin.mgddns.com>” on file explore to login the MG700 and upload/download the file by remote.

Dynamic Domain Name Service - WAN 1

DDNS Service	<input checked="" type="radio"/> Enable <input type="radio"/> Disable
DDNS Type	Mgddns.com
User Name	6f39e97e73ded4f7e8cd286cbc59bd
Password	*****
Host Name	alvin.mgddns.com



Important:

1. Use "xxxx.mgddns.com" have to public IP address.
2. SAMBA port will be locked by Firewall. If user use SAMBA File mode, the SAMBA port need to unlocked. The SAMBA port is from 135 ~ 139 and port 445.

17 GPS/GNSS Application

The GNSS default port of MG700 is on Port103, user could get the GNSS data by IP address and port, such as “192.168.60.1:103”. On Web GUI, user will see the GNSS data is increase on Port3.

Serial - Status

LINE							
Port	OP Mode	Data	ISP1	ISP2	ISP3	ISP4	
Port 1	TCP Server	0	Listen	Listen	Listen	Listen	
Port 2	TCP Server	0	Listen	Listen	Listen	Listen	
Port 3	TCP Server	333835134	Listen	Listen	Listen	Listen	

Serial setting - Port 3

Serial Setting

Port alias	<input type="text" value="port3"/>
Baud Rate	<input type="text" value="115200"/>
Data bits	<input type="text" value="8"/>
Stop bits	<input type="text" value="1"/>
Parity	<input type="text" value="None"/>
Flow Control	<input type="text" value="None"/>
FIFO	<input type="radio"/> Enable <input type="radio"/> Disable

Operating Setting

Operation Mode	<input type="text" value="TCP Server Mode"/>
Data Packing	
Packing length	<input type="text" value="1024"/> (0 - 1024)
Force transmit	<input type="text" value="700"/> (0 - 65535 ms)
TCP alive check time	<input type="text" value="7"/> (0 - 99 min)
Inactivity time	<input type="text" value="0"/> (0 - 65535 ms)
Connection Limit	<input type="text" value="4"/>
Ignore Disconnection IP	<input type="radio"/> No <input checked="" type="radio"/> Yes
TCP Server Mode	
Local TCP Port	<input type="text" value="103"/>


17.1 GPS/GNSS NMEA data

MG700 support NMEA data, user can get the GPS data by IP address and Port, such as 192.168.60.1:103.

```


$GPGGA,084155.00,2504.18507,N,12137.31827,E,1,10,0.95,94.0,M,15.3,M,*67
$GPGSA,A,3,32,06,23,17,30,11,10,01,03,28,,,1.71,0.95,1.42*04
$GPGSV,3,1,12,32,11,041,44,06,35,265,46,23,10,115,43,17,44,335,48*72
$GPGSV,3,2,12,30,14,203,44,11,15,063,44,09,08,149,,10,21,199,43*74
$GPGSV,3,3,12,01,21,044,43,02,03,249,38,03,49,061,48,28,81,224,48*74
$GPGLL,2504.18507,N,12137.31827,E,084155.00,A,A*65
$GPGGA,084156.00,2504.18509,N,12137.31828,E,1,10,0.95,93.9,M,15.3,M,*6B
$GPGSA,A,3,32,06,23,17,30,11,10,01,03,28,,,1.71,0.95,1.42*04
$GPGSV,3,1,12,32,11,041,44,06,35,265,46,23,10,115,43,17,44,335,48*72
$GPGSV,3,2,12,30,14,203,44,11,15,063,44,09,08,149,,10,22,199,43*77
$GPGSV,3,3,12,01,21,044,43,02,03,249,38,03,49,061,49,28,81,224,48*75
$GPGLL,2504.18509,N,12137.31828,E,084156.00,A,A*67
$GPGGA,084157.00,2504.18510,N,12137.31830,E,1,10,0.95,93.9,M,15.3,M,*6B
$GPGSA,A,3,32,06,23,17,30,11,10,01,03,28,,,1.71,0.95,1.42*04
$GPGSV,3,1,12,32,11,041,44,06,35,265,46,23,10,115,44,17,44,335,48*75
$GPGSV,3,2,12,30,14,203,45,11,14,063,44,09,08,149,,10,22,199,43*77
$GPGSV,3,3,12,01,21,044,44,02,03,249,38,03,49,061,49,28,81,224,48*72
$GPGLL,2504.18510,N,12137.31830,E,084157.00,A,A*67
$GPGGA,084158.00,2504.18510,N,12137.31832,E,1,10,0.95,93.9,M,15.3,M,*66
$GPGSA,A,3,32,06,23,17,30,11,10,01,03,28,,,1.71,0.95,1.42*04
$GPGSV,3,1,12,32,11,041,43,06,35,265,46,23,10,115,44,17,44,335,48*72
$GPGSV,3,2,12,30,14,203,45,11,14,063,44,09,08,149,,10,22,199,43*77
$GPGSV,3,3,12,01,21,044,44,02,03,249,38,03,49,061,49,28,81,224,48*72
$GPGLL,2504.18510,N,12137.31832,E,084158.00,A,A*6A
$GPGGA,084159.00,2504.18511,N,12137.31834,E,1,10,0.95,93.9,M,15.3,M,*60
$GPGSA,A,3,32,06,23,17,30,11,10,01,03,28,,,1.71,0.95,1.42*04
$GPGSV,3,1,12,32,11,041,43,06,35,265,46,23,10,115,44,17,44,335,48*72
$GPGSV,3,2,12,30,14,203,44,11,14,063,44,09,08,149,,10,22,199,43*76
$GPGSV,3,3,12,01,21,044,43,02,03,249,38,03,49,061,48,28,81,224,48*74
$GPGLL,2504.18511,N,12137.31834,E,084159.00,A,A*6C

```



17.2 GPS/GNSS RAW Data

MG700 support GNSS data, user can get the GNSS data by IP address and Port, such as 192.168.60.1:103.



Important: GPS NMEA /GNSS RAW data depend on GPS Module type.

18 Admin Application

The management screen is used to perform various administrative task on the MG700 such as changing the login password, saving and restoring system settings, scheduling a reboot, and performing firmware upgrade.

Admin - Management

Administration Interface

Language	English <input type="button" value="▼"/>
Administrator Password	***** <input type="text"/>
Re-type Password	***** <input type="text"/>
Remote Management	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Management Port	HTTP 8080 <input type="button"/>

Reboot

Reboot <input type="button"/>	Reboot Router <input type="button"/>
-------------------------------	--------------------------------------

Configuration

Configuration Export <input type="button" value="Export"/>
Default Configuration Restore <input type="button" value="Default"/>
Configuration Import <input type="button" value="Browse..."/> No file selected. <input type="button" value="Import"/>

Firmware

Firmware Upgrade <input type="button" value="Browse..."/> No file selected. <input type="button" value="Upgrade"/>
--

18.1 Management

User can set the login password in this page.

Admin - Management

Administration Interface


Language	English <input type="button" value="▼"/>
Administrator Password	***** <input type="text"/>
Re-type Password	***** <input type="text"/>
Remote Management	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Management Port	HTTP 8080 <input type="button"/>

If user needs to reboot the MG700, press “Reboot Router” button. Then the MG700 will reboot


immediately.



User can export/import the configuration of MG700.



If user need upgrade firmware, press Browser button and choice firmware file.



After press "Upgrade" button, MG700v ask again. If press OK, it will start to upgrade firmware. Upgrade firmware should spent about 7 minutes.



18.2 System Utilities

The System Utilities screen provides several useful tools for network and device diagnostics. MG700 include Ping, ARP tracing and Trace Route function

The Ping utility sends a series of ICMP packets to a designated IP address to test communications with that IP.

Admin - System Utilities

Ping

Interface	<input type="button" value="* ▾"/>
Target Host	<input type="text"/>
Number of Packets	<input type="text" value="4"/> Packets (1 ~ 10)
Ping	<input type="button" value="Ping"/>

The ARPing similar to “ping”, used to discover hosts on a network. The utility tests whether a given IP address is in use on the local network, and can get additional information about the device using that address. ARPing operates at layer 2(or the link layer of the OSI model) – using the Address Resolution Protocol (ARP) for probing hosts.

ARPing (Within the same broadcasting domain)

Interface	<input type="button" value="WAN1 ▾"/>
Target Host	<input type="text"/>
Number of Packets	<input type="text" value="4"/> Packets (1 ~ 10)
ARPing	<input type="button" value="ARPing"/>

Trace Route is a network diagnostic tool for displaying the route and measuring transit delays of packets across and IP network. Trace Route sends a sequence of ICMP echo request packets addressed to a destination host. Trace Route uses the returned ICMP messages to produce a list of that the packets have traversed. The time stamp values returned for each router along the path are the delay (latency) values measured in milliseconds for each packet. The Trace Route results are displayed in the result window.

Trace Route

Interface	<input type="button" value="* ▾"/>
Target Host	<input type="text"/>
Hop Count	<input type="text" value="30"/> Counts (1 ~ 15)
Trace route	<input type="button" value="Trace Route"/>

18.3 Log

The system log records various events that have occurred during the MG700 operation. Events are divided into classes to make it easier to review specific event chains. The MG700 has a limited amount of space available for log events the oldest events are overwritten when the log is full.

Admin - Log

Sys Log

Type	Content
{success: true, ms: Jan 29 16:50:14 Using Default DNS 208.67.220.220 208.67.222.222\r\n< DNS >	

Page 1 of 1 | 20 | View 1 - 1 of 1

Log Server Setting

Syslog Server	<input type="radio"/> Enable <input checked="" type="radio"/> Disable
Remote IP Address	<input type="text"/>
Protocol	<input type="text" value="UDP"/>
Remote Port	<input type="text" value="514"/>

Save Settings **Cancel Changes**

19 MG700 M2M Application




20 Hardware Specifications

Hardware Specifications	
Main Chip	
Core	MIPS24KEc,580MHz
RAM	1G bit DDR2 RAM
Flash Memory	128M Bit Flash
Wireless	802.11 b/g/n
Antenna	2T2R
Linux OS	Linux 2.6.3
Connector	
RJ45	2 Ethernet port(LAN and WAN) + 3 Serial Port or 3 LAN(option)
TFlash/Micro SD	1
USB Port	1
SIM Card	1
WiFi Antenna	2
GSM Antenna	1
GPIO/Relay	2(Relay Normal Open)
Specific	
Battery	1100mAH(Option)
Reset Button	1
Switch	2(1 for Power on/off, 1 for GPS Select)
Temperature	-20°C ~ 65°C
Dimension	90 x 130 x 20mm
DC Power	
Power In	12V
Power consumption	Max. 2A
AC Adaptor	
Power In	Input : 110~260VAC Output : 12VDC
Power consumption	Max. 2A
Temperature	0°C ~ 40°C

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference, including interference that may cause undesired operation.


21 Application Note – ATM remote control Application

In the ATM remote control power application, If ATM occur the shutdown or stop, the Service Center could reset the ATM's power by MG700 through Manually control or Schedule mode.



Application Note – AMBULANCE Application

When someone with accident, the ambulance arrived at the scene. The MG700 could send the patient's physiological data, heart rate, blood pressure and other information sent to the hospital immediately. Then, the emergency center will provide the best solution for patient quickly . Also, if MG700 with GPS, Hospital will show the ambulance's position.



Application Note – Tracker/Car Management Application

User can the temperature sensor(RS232 interface) connect with the MG700, then, the Server center will receive the temperature data and monitoring the temperature with Tracker. If MG700 with GPS, the Server can also monitor the Tracker Position.

