

FCC

EMC

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
EFT POS

ISSUED TO
SPECTRA Technologies Holdings Co., Ltd.

Unit 1301-09, 19-20, Tower II, Grand Century Place, 193 Prince
Edward Road West, Kowloon, Hong Kong



Tested by: Xia Long
Xia Long
(Engineer)

Date Jul. 12, 2017

Approved by: Cao Shaodong
Cao Shaodong
(Laboratory Manager)

Date Jul. 12, 2017

Report No.: BL-SZ1750340-401

EUT Name: EFT POS

Model Name: T300-T

Brand Name: SPECTRA

Test Standard: 47 CFR Part 15 Subpart B

FCC ID: VWZT300

Test Conclusion: Pass

Test Date: May 19, 2017 ~ Jul. 12, 2017

Date of Issue: Jul. 12, 2017

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Jul. 11, 2017</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Jul. 12, 2017</u>	<u>Update the test configuration, data and photos</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Identification of the Testing Laboratory	4
1.2	Identification of the Responsible Testing Location	4
1.3	Laboratory Condition	4
1.4	Announce	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	Factory Information	5
2.4	General Description for Equipment under Test (EUT)	5
2.5	Ancillary Equipment	6
2.6	Technical Information	6
3	SUMMARY OF TEST RESULTS.....	7
3.1	Test Standards.....	7
3.2	Verdict.....	7
3.3	Test Uncertainty	7
4	GENERAL TEST CONFIGURATIONS.....	8
4.1	Test Environments	8
4.2	Test Equipment List	8
4.3	Test Enclosure list.....	9
4.4	Test Configurations	10
4.5	Test Setups	11
4.6	Test Conditions	13
5	TEST ITEMS.....	14
5.1	Emission Tests.....	14

ANNEX A TEST RESULTS..... 16

 A.1 Radiated Emission 16

 A.2 Conducted Emission 20

ANNEX B TEST SETUP PHOTOS 22

ANNEX C EUT EXTERNAL PHOTOS 22

ANNEX D EUT INTERNAL PHOTOS 22

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C~25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v6.4.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	SPECTRA Technologies Holdings Co., Ltd.
Address	Unit 1301-09, 19-20, Tower II, Grand Century Place, 193 Prince Edward Road West, Kowloon, Hong Kong

2.2 Manufacturer Information

Manufacturer	SPECTRA Technologies Holdings Co., Ltd.
Address	Unit 1301-09, 19-20, Tower II, Grand Century Place, 193 Prince Edward Road West, Kowloon, Hong Kong

2.3 Factory Information

Factory	Dongguan Jinda Electronic Limited
Address	StreetNo.2,Xinwei Cun, Langbei, Changping Town, Dongguan City, Guangdong Province, P.R.China.

2.4 General Description for Equipment under Test (EUT)

EUT Name	EFT POS
Model Name Under Test	T300-T
Series Model Name	T300-T, T300
Description of Model name differentiation	T300-T and T300 have the same circuit diagram, same wifi module, and hardware and software are also same. T300 removed the the printing function. T300-T and T300 wifi antenna & antenna position are different.
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	WIFI, NFC

Note: The two models were tested but only the worst mode is reported by this report.

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	McNair
	Model No.	ICR18650-2600mAh
	Serial No.	N/A
	Capacitance	2600 mAh
	Rated Voltage	3.6 V
	Limit Charge Voltage	4.2 V
Ancillary Equipment 2	Adapter	
	Brand Name	All-Key
	Model No.	AKN1G-0500100UU
	Serial No.	N/A
	Rated Input	100-240 V~, 200 mA, 50/60 Hz
	Rated Output	5 V=, 1000 mA
Ancillary Equipment 3	USB Cable	
	Length	90 cm

2.6 Technical Information

Note: Not applicable.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	FCC 47 CFR Part 15 Subpart B (10-1-16 Edition)	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low- Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Result
1	Radiated Emission	15.109	Pass	Annex A .1
2	Conducted Emission, AC Ports	15.107	Pass	Annex A .2

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.23 dB
Radiated emissions (30 MHz-1 GHz)	4.30 dB
Radiated emissions (1 GHz-18 GHz)	4.81 dB
Radiated emissions (18 GHz-40 GHz)	5.71 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

Environment Parameter	Selected Values During Tests			
	Temperature	Voltage	Relative Humidity	Ambient Pressure
Normal Temperature, Normal Voltage (NTNV)	23°C~26°C	AC 120 V/60 Hz	50%-55%	100 to 102 kPa

4.2 Test Equipment List

Radiated Emission Test For Frequency Below 1 GHz						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWA RZ	ESRP	101036	2016.07.05	2017.07.04	<input checked="" type="checkbox"/>
Test Antenna- Bi-Log	SCHWARZBECK	VULB 9163	9163-977	2016.07.19	2018.07.18	<input checked="" type="checkbox"/>
Test Antenna- Horn	SCHWARZBECK	BBHA 9120D	9120D-1600	2016.07.12	2018.07.11	<input type="checkbox"/>
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60 *7.35m	N/A	2016.08.09	2018.08.08	<input checked="" type="checkbox"/>

Radiated Emission Test For Frequency Above 1 GHz						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2016.09.09	2017.09.08	<input checked="" type="checkbox"/>
Test Antenna- Bi-Log	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21	<input type="checkbox"/>
Test Antenna- Horn	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21	<input checked="" type="checkbox"/>
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2019.02.20	<input checked="" type="checkbox"/>

Conducted Emission Test						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWA RZ	ESRP	101036	2016.07.05	2017.07.04	<input checked="" type="checkbox"/>
LISN	SCHWARZBECK	NSLK 8127	8127-687	2016.07.05	2017.07.04	<input checked="" type="checkbox"/>
LISN	SCHWARZBECK	NNLK 8129	8129-462	2016.09.14	2017.09.13	<input type="checkbox"/>
AMN	SCHWARZBECK	NNBM8124	8124-509	2016.07.05	2017.07.04	<input type="checkbox"/>
AMN	SCHWARZBECK	NNBM8124	8124-510	2016.07.05	2017.07.04	<input type="checkbox"/>
ISN	TESEQ	ISN T800	34449	2016.07.05	2017.07.04	<input type="checkbox"/>
Shielded Enclosure	ChangNing	CN-130701	130703	N/A	N/A	<input checked="" type="checkbox"/>

4.3 Test Enclosure list


Description	Manufacturer	Model	Serial No.	Length	Description	Use
PC	Dell	015K3N	N/A	N/A	Special Handled	<input checked="" type="checkbox"/>
Laptop	Apple	A1465	N/A	N/A	N/A	<input type="checkbox"/>
Printer	HP	DESKJET 1000	N/A	N/A	N/A	<input checked="" type="checkbox"/>
Keyboard	Logitech	Y-BP62a	N/A	N/A	N/A	<input checked="" type="checkbox"/>
Mouse	Logitech	M100	N/A	N/A	N/A	<input checked="" type="checkbox"/>
USB disk	Kingston	N/A	N/A	N/A	N/A	<input type="checkbox"/>
TF Card	Kingston	N/A	N/A	N/A	N/A	<input type="checkbox"/>
VGA Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>
HDMI Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input checked="" type="checkbox"/>
DVI Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>
Coaxial video cable	N/A	N/A	N/A	2.0 m	Shielded with core	<input type="checkbox"/>
iPhone	Apple	A1586	N/A	N/A	N/A	<input type="checkbox"/>
Phone	MI	M4	N/A	N/A	N/A	<input type="checkbox"/>
Bluetooth Earphone	SAMSUNG	Gear Circle	N/A	N/A	N/A	<input type="checkbox"/>
GPS/GLONASS Vector signal generator	R&S	N5172B EXG	N/A	N/A	N/A	<input type="checkbox"/>
WIFI Router	TP-LINK	TL-WDR7500	N/A	N/A	N/A	<input type="checkbox"/>
Earphone	N/A	OPPO	N/A	1.1 m	N/A	<input type="checkbox"/>
Car Battery	Camel	55530	N/A	N/A	12 V/55 Ah	<input type="checkbox"/>
Artificial load	N/A	N/A	N/A	N/A	2.5 Ω/100 W	<input type="checkbox"/>
Artificial load	N/A	N/A	N/A	N/A	5 Ω/100 W	<input type="checkbox"/>
Electronic Load	ITECH	IT8511	N/A	N/A	N/A	<input type="checkbox"/>
USB Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>
DC Power Supply	ITECH	IT6863A	60001401068 7210006	N/A	N/A	<input type="checkbox"/>
LCD Monitor	SAMSUNG	UA32C4000P	N/A	N/A	N/A	<input type="checkbox"/>
LCD Monitor	Dell	U241HB	N/A	N/A	N/A	<input checked="" type="checkbox"/>
RJ45 Cable	N/A	N/A	N/A	1.5 m	Shielded with core	<input type="checkbox"/>

4.4 Test Configurations

Test Configurations (TC) No.	Description
TC01	<u>The Print Test Mode</u> EUT + Battery + Adapter + USB Cable + PC + Mouse + Keyboard + Printer + LCD Monitor + HDMI Cable
TC02	<u>The USB Test Mode</u> EUT + Battery + Adapter + USB Cable + PC + Mouse + Keyboard + Printer + LCD Monitor + HDMI Cable + WIFI Idle


4.5 Test Setups

Test Setup 1




(For Radiated Emission Test (30 MHz-1 GHz))

Test Setup 2



(For Radiated Emission Test (above 1 GHz))

Test Setup 3



(For Conducted Emission, AC Ports Test)

4.6 Test Conditions

Test Case	Test Conditions	
Radiated Emission	Test Env.	NTNV
	Test Setup	Test Setup 1&2
	Test Configuration	TC01 - TC02 ^{Note}
Conducted Emission, AC Ports	Test Env.	NTNV
	Test Setup	Test Setup 3
	Test Configuration	TC01 - TC02 ^{Note}

Note: Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report. The print test mode is the worst mode in this report.

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 10 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	90	39
88 - 216	150	43.5	150	43.5
216 - 960	200	46	210	46.4
Above 960	500	54	300	49.5

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log$ [Field Strength ($\mu\text{V/m}$)].
- 2) In the emission tables above, the tighter limit applies at the band edges.

5.1.1.2 Test Setup

Refer to 4.5 section (test setup 1 to test setup 2) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

5.1.1.4 Test Result

Please refer to ANNEX A.1.

5.1.2 Conducted Emission

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.5 section test (test setup 3) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.1.2.4 Test Result

Please refer to ANNEX A.2.

ANNEX A TEST RESULTS

A.1 Radiated Emission


Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Data and Plots


The Print Test Mode

A.1.1 Test Antenna Vertical, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	155.099	20.80	-14.90	33.5	12.70	Peak	120.00	100	Vertical	Pass
2	211.587	26.96	-11.71	33.5	6.54	Peak	0.00	200	Vertical	Pass
3	291.835	29.85	-9.07	36.0	6.15	Peak	349.00	100	Vertical	Pass
4	429.298	27.18	-5.42	36.0	8.82	Peak	49.00	400	Vertical	Pass
5	520.697	27.57	-3.66	36.0	8.43	Peak	76.00	400	Vertical	Pass
6	698.163	30.00	-0.56	36.0	6.00	Peak	360.00	300	Vertical	Pass

A.1.2 Test Antenna Horizontal, 30 MHz – 1 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	223.224	24.64	-11.10	36.0	11.36	Peak	107.00	400	Horizontal	Pass
2	291.835	24.49	-9.07	36.0	11.51	Peak	249.00	300	Horizontal	Pass
3	417.661	27.45	-5.65	36.0	8.55	Peak	111.00	200	Horizontal	Pass
4	583.732	27.58	-2.30	36.0	8.42	Peak	66.00	200	Horizontal	Pass
5	663.979	29.65	-0.93	36.0	6.35	Peak	230.00	200	Horizontal	Pass
6	767.016	29.28	0.67	36.0	6.72	Peak	78.00	100	Horizontal	Pass

A.1.3 Test Antenna Vertical, 1 GHz – 13 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1332.000	42.38	-6.16	74.0	31.62	Peak	219.10	100	Vertical	Pass
2	2214.500	44.90	-2.58	74.0	29.10	Peak	13.30	100	Vertical	Pass
3	3709.000	41.97	7.98	74.0	32.03	Peak	155.70	100	Vertical	Pass
4	5077.000	44.54	10.96	74.0	29.46	Peak	204.00	100	Vertical	Pass
5	9436.562	49.36	16.31	74.0	24.64	Peak	64.80	100	Vertical	Pass
6	12501.313	52.14	18.69	74.0	21.86	Peak	287.80	100	Vertical	Pass

A.1.4 Test Antenna Horizontal, 1 GHz – 13 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1367.500	42.85	-6.01	74.0	31.15	Peak	0.60	100	Horizontal	Pass
2	2243.000	45.19	-2.49	74.0	28.81	Peak	130.10	100	Horizontal	Pass
3	3716.000	42.53	8.12	74.0	31.47	Peak	118.70	100	Horizontal	Pass
4	4975.000	45.15	10.55	74.0	28.85	Peak	147.90	100	Horizontal	Pass
5	7035.937	46.14	12.81	74.0	27.86	Peak	358.90	100	Horizontal	Pass
6	11627.312	50.34	17.60	74.0	23.66	Peak	103.20	100	Horizontal	Pass


A.2 Conducted Emission

Test Data and Plots

The Print Test Mode


Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

A.2.1 L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.182	36.4	10.46	64.4	28.00	Peak	L Line	Pass
1**	0.182	26.1	10.46	54.4	28.30	AV	L Line	Pass
2	0.216	35.1	10.82	63.0	27.90	Peak	L Line	Pass
2**	0.216	25.2	10.82	53.0	27.80	AV	L Line	Pass
3	0.480	34.9	11.23	56.3	21.40	Peak	L Line	Pass
3**	0.480	25.4	11.23	46.3	20.90	AV	L Line	Pass
4	1.016	29.8	9.88	56.0	26.20	Peak	L Line	Pass
4**	1.016	16.4	9.88	46.0	29.60	AV	L Line	Pass
5	2.326	31.6	10.33	56.0	24.40	Peak	L Line	Pass
5**	2.326	18.5	10.33	46.0	27.50	AV	L Line	Pass
6	4.490	30.8	9.68	56.0	25.20	Peak	L Line	Pass
6**	4.490	19.7	9.68	46.0	26.30	AV	L Line	Pass

A.2.2 N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.158	36.7	10.41	65.6	28.90	Peak	N Line	Pass
1**	0.158	25.6	10.41	55.6	30.00	AV	N Line	Pass
2	0.214	33.1	10.30	63.0	29.90	Peak	N Line	Pass
2**	0.214	23.2	10.30	53.0	29.80	AV	N Line	Pass
3	0.480	38.0	11.23	56.3	18.30	Peak	N Line	Pass
3**	0.480	29.9	11.23	46.3	16.40	AV	N Line	Pass
4	1.376	29.7	10.02	56.0	26.30	Peak	N Line	Pass
4**	1.376	20.3	10.02	46.0	25.70	AV	N Line	Pass
5	2.604	31.4	10.74	56.0	24.60	Peak	N Line	Pass
5**	2.604	20.7	10.74	46.0	25.30	AV	N Line	Pass
6	3.490	32.0	10.36	56.0	24.00	Peak	N Line	Pass
6**	3.490	19.6	10.36	46.0	26.40	AV	N Line	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ1750340-AE.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1750340-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ1750340-AI.PDF".

--END OF REPORT--