



TEST REPORT

Applicant: Thermor Ltd.

Address of Applicant: 16975 Leslie St., Newmarket, ON, L3Y 9A1, Canada

Equipment Under Test (EUT)

Product Name: HOME WEATHER STATION WITH WIND SPEED

Model No.: 348NC, 348BC, 348BU, 348NU

FCC ID: VX5-348RX

Applicable standards: FCC CFR Title 47 Part 15 Subpart B:2010

Date of sample receipt: May 29, 2012

Date of Test: May 30-31, 2012

Date of report issued: June 01, 2012

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	June 01, 2012	Original

Prepared by:

Oscar. Li

Date:

June 01, 2012

Project Engineer

Reviewed by:

Hans. Hu

Date:

June 01, 2012

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE AND VOLTAGE	5
5.4 TEST FACILITY.....	5
5.5 TEST LOCATION	6
5.6 DESCRIPTION OF SUPPORT UNITS	6
5.7 DEVIATION FROM STANDARDS.....	6
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA.....	8
7.1 RADIATED EMISSION	8
8 TEST SETUP PHOTO	14
9 EUT CONSTRUCTIONAL DETAILS	15

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	N/A
Radiated Emissions	Part15.109	PASS

PASS: The EUT complies with the essential requirements in the standard.

N/A: not applicable

5 General Information

5.1 Client Information

Applicant:	Thermor Ltd.
Address of Applicant:	16975 Leslie St., Newmarket, ON, L3Y 9A1, Canada

5.2 General Description of E.U.T.

Product Name:	HOME WEATHER STATION WITH WIND SPEED
Model No.:	348NC, 348BC, 348BU, 348NU
Power supply:	DC 4.5V(3*1.5V("AA" Size battery))
Remark:	Only the model 348NC was tested. 348BC, 348BU, 348NU and 348NC are identical in the same PCB layout, interior structure and electrical circuits. The only differences are the model name and appearance color for commercial purpose.

5.3 Test mode and voltage

Test mode:	
Receive mode	Keep the EUT in receive the weather data.

5.4 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none">● FCC —Registration No.: 600491 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, July 20, 2010.● Industry Canada (IC) The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-1.
--

5.5 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China Tel: 0755-27798480 Fax: 0755-27798960

5.6 Description of Support Units

None.

5.7 Deviation from Standards

Biconical, log.per. antenna and horn antenna were used instead of dipole antenna. Semi-anechoic Chamber was used as alternation of open air test sites, and all test suites were performed with radiated method in it.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 30 2011	Mar. 29 2013
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 04 2011	Jul. 03 2012
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 26 2012	Feb. 25 2013
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	Mar. 10 2012	Mar. 09 2013
6	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 04 2011	Jul. 03 2012
7	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 04 2011	Jul. 03 2012
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial cable	GTS	N/A	GTS210	Jul. 04 2011	Jul. 03 2012
10	Coaxial Cable	GTS	N/A	GTS211	Jul. 04 2011	Jul. 03 2012

7 Test results and Measurement Data

7.1 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																							
Test Method:	ANSI C63.4:2003																							
Test Frequency Range:	30MHz to 3000MHz																							
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																							
Receiver setup:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>120kHz</td> <td>300kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td> <td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>				Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value	
Frequency	Detector	RBW	VBW	Remark																				
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value																				
Above 1GHz	Peak	1MHz	3MHz	Peak Value																				
	Peak	1MHz	10Hz	Average Value																				
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Limit (dBuV/m @3m)</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td> <td>40.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>88MHz-216MHz</td> <td>43.50</td> <td>Quasi-peak Value</td> </tr> <tr> <td>216MHz-960MHz</td> <td>46.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>960MHz-1GHz</td> <td>54.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td> <td>54.00</td> <td>Average Value</td> </tr> <tr> <td>74.00</td> <td>Peak Value</td> </tr> </tbody> </table>				Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.00	Quasi-peak Value	88MHz-216MHz	43.50	Quasi-peak Value	216MHz-960MHz	46.00	Quasi-peak Value	960MHz-1GHz	54.00	Quasi-peak Value	Above 1GHz	54.00	Average Value	74.00	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																						
30MHz-88MHz	40.00	Quasi-peak Value																						
88MHz-216MHz	43.50	Quasi-peak Value																						
216MHz-960MHz	46.00	Quasi-peak Value																						
960MHz-1GHz	54.00	Quasi-peak Value																						
Above 1GHz	54.00	Average Value																						
	74.00	Peak Value																						
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 																							
Test setup:	Below 1GHz																							

	<p>Above 1GHz</p>		
Test environment:	Temp.: 25 °C	Humid.: 52%	Press.: 1 012mbar
Measurement Record:	Uncertainty: ± 4.5dB		
Test Instruments:	Refer to section 6 for details		
Test mode:	Refer to section 5.3 for details.		
Test results:	Pass		

Note:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$Final\ Test\ Level = Receiver\ Reading + Antenna\ Factor + Cable\ Factor - Preamplifier\ Factor$$

Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163 -2012-05 HORIZONTAL
 Job No. : 553RF
 Test Mode : Receiving mode
 Test Engineer: Oscar

	ReadAntenna	Cable	Preamp	Limit	Over				
Freq	Level	Factor	Loss	Line	Limit	Remark			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m			
1	34.639	38.84	15.81	0.61	32.06	23.20	40.00	-16.80	QP
2	53.882	38.55	16.16	0.81	31.95	23.57	40.00	-16.43	QP
3	102.360	37.52	15.98	1.21	31.77	22.94	43.50	-20.56	QP
4	257.422	39.45	15.06	2.16	32.16	24.51	46.00	-21.49	QP
5	502.940	38.41	18.63	3.32	31.54	28.82	46.00	-17.18	QP
6	661.151	38.04	21.28	3.95	31.13	32.14	46.00	-13.86	QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163 -2012-05 VERTICAL
 Job No. : 553RF
 Test Mode : Receiveing mode
 Test Engineer: Osgcar

	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	46.178	37.99	16.55	0.73	32.00	23.27	40.00	-16.73 QP
2	60.492	37.97	15.65	0.86	31.94	22.54	40.00	-17.46 QP
3	94.428	37.66	15.88	1.15	31.74	22.95	43.50	-20.55 QP
4	155.910	40.01	11.58	1.60	32.00	21.19	43.50	-22.31 QP
5	235.816	39.75	14.93	2.05	32.16	24.57	46.00	-21.43 QP
6	631.688	37.87	20.91	3.84	31.09	31.53	46.00	-14.47 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120D ANT(>1GHZ) HORIZONTAL
 Job No. : 553RF
 Test Mode : Receiveing mode
 Test Engineer: Osccar

	Freq	Read	Antenna	Cable	Preamp	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1240.000	30.31	25.50	4.50	31.51	28.80	54.00	-25.20 Average
2	1240.000	43.16	25.50	4.50	31.51	41.65	74.00	-32.35 Peak
3	1534.000	31.50	25.14	4.70	31.70	29.64	54.00	-24.36 Average
4	1534.000	44.02	25.14	4.70	31.70	42.16	74.00	-31.84 Peak
5	2004.000	32.49	26.13	4.97	31.10	32.49	54.00	-21.51 Average
6	2004.000	44.83	26.13	4.97	31.10	44.83	74.00	-29.17 Peak
7	2380.000	32.49	27.63	5.37	31.69	33.80	54.00	-20.20 Average
8	2380.000	45.89	27.63	5.37	31.69	47.20	74.00	-26.80 Peak
9	2626.000	34.68	27.88	5.60	31.47	36.69	54.00	-17.31 Average
10	2626.000	48.03	27.88	5.60	31.47	50.04	74.00	-23.96 Peak
11	2864.000	33.79	28.40	5.81	30.79	37.21	54.00	-16.79 Average
12	2864.000	47.94	28.40	5.81	30.79	51.36	74.00	-22.64 Peak

Vertical:





Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120D ANT(>1GHZ) VERTICAL
 Job No. : 553RF
 Test Mode : Receiveing mode
 Test Engineer: Osccar

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1198.000	30.37	25.34	4.47	31.47	28.71	54.00	-25.29	Average
2	1198.000	42.97	25.34	4.47	31.47	41.31	74.00	-32.69	Peak
3	1604.000	31.48	24.97	4.75	31.60	29.60	54.00	-24.40	Average
4	1604.000	44.14	24.97	4.75	31.60	42.26	74.00	-31.74	Peak
5	2018.000	32.38	26.24	4.98	31.12	32.48	54.00	-21.52	Average
6	2018.000	44.54	26.24	4.98	31.12	44.64	74.00	-29.36	Peak
7	2326.000	32.36	27.84	5.32	31.61	33.91	54.00	-20.09	Average
8	2326.000	45.32	27.84	5.32	31.61	46.87	74.00	-27.13	Peak
9	2638.000	34.58	27.89	5.62	31.47	36.62	54.00	-17.38	Average
10	2638.000	47.87	27.89	5.62	31.47	49.91	74.00	-24.09	Peak
11	2950.000	33.49	28.43	5.88	30.57	37.23	54.00	-16.77	Average
12	2950.000	47.83	28.43	5.88	30.57	51.57	74.00	-22.43	Peak


8 Test Setup Photo


Radiated Emission






9 EUT Constructional Details



















----- End-----