



FCC TEST REPORT (PART 27)

REPORT NO.: RF970219H03

MODEL NO.: CPEi25750

RECEIVED: Jan. 11, 2008

TESTED: Jan. 24 to March 26, 2008

ISSUED: March 26, 2008

APPLICANT: Motorola Inc.

ADDRESS: 1475 W. Shure Drive, Arlington Heights, IL 60004 USA

ISSUED BY : Advance Data Technology Corporation

LAB LOCATION : No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien, Taiwan.

This test report consists of 62 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by any government agencies. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	6
3	GENERAL INFORMATION.....	7
3.1	GENERAL DESCRIPTION OF EUT.....	7
3.2	DESCRIPTION OF TEST MODES.....	8
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	9
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	11
3.4	DESCRIPTION OF SUPPORT UNITS	11
3.4.1	CONFIGURATION OF SYSTEM UNDER TEST	12
4	TEST TYPES AND RESULTS	13
4.1	OUTPUT POWER MEASUREMENT	13
4.1.1	LIMITS OF OUTPUT POWER MEASUREMENT	13
4.1.2	TEST INSTRUMENTS	13
4.1.3	TEST PROCEDURES.....	14
4.1.4	TEST SETUP.....	14
4.1.5	EUT OPERATING CONDITIONS.....	14
4.1.6	TEST RESULTS.....	15
4.2	FREQUENCY STABILITY MEASUREMENT.....	19
4.2.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT	19
4.2.2	TEST INSTRUMENTS	19
4.2.3	TEST PROCEDURE.....	20
4.2.4	TEST SETUP.....	20
4.2.5	TEST RESULTS.....	21
4.3	EMISSION BANDWIDTH MEASUREMENT.....	22
4.3.1	LIMITS OF EMISSION BANDWIDTH MEASUREMENT	22
4.3.2	TEST INSTRUMENTS	22
4.3.3	TEST SETUP.....	22
4.3.4	TEST PROCEDURES.....	23
4.3.5	TEST RESULTS.....	24
4.4	CHANNEL EDGE MEASUREMENT	28
4.4.1	LIMITS OF CHANNEL EDGE MEASUREMENT	28
4.4.2	TEST INSTRUMENTS	28
4.4.3	TEST SETUP	28
4.4.4	TEST PROCEDURES.....	29
4.4.5	EUT OPERATING CONDITION	29
4.4.6	TEST RESULTS.....	30
4.5	CONDUCTED SPURIOUS EMISSIONS	34



4.5.1	LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	34
4.5.2	TEST INSTRUMENTS	34
4.5.3	TEST PROCEDURE	35
4.5.4	TEST SETUP.....	35
4.5.5	EUT OPERATING CONDITIONS.....	35
4.5.6	TEST RESULTS.....	36
4.6	RADIATED EMISSION MEASUREMENT (BELOW 1GHz)	48
4.6.1	LIMITS OF RADIATED EMISSION MEASUREMENT	48
4.6.2	TEST INSTRUMENTS	48
4.6.3	TEST PROCEDURES.....	49
4.6.4	DEVIATION FROM TEST STANDARD	49
4.6.5	TEST SETUP.....	50
4.6.6	EUT OPERATING CONDITIONS.....	50
4.6.7	TEST RESULTS.....	51
4.7	RADIATED EMISSION MEASUREMENT (ABOVE 1GHz).....	52
4.7.1	LIMITS OF RADIATED EMISSION MEASUREMENT	52
4.7.2	TEST INSTRUMENTS	52
4.7.3	TEST PROCEDURES.....	53
4.7.4	DEVIATION FROM TEST STANDARD	53
4.7.5	TEST SETUP	54
4.7.6	EUT OPERATING CONDITIONS.....	54
4.7.7	TEST RESULTS.....	55
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	61
6	INFORMATION ON THE TESTING LABORATORIES	62

1 CERTIFICATION

PRODUCT: WiMax CPE B2 Blade 2.5GHz

MODEL: CPEi25750

APPLICANT: Motorola Inc.

TESTED: Jan. 24 to March 26, 2008

TEST SAMPLE: ENGINEERING SAMPLE

TEST STANDARDS: FCC 47 CFR Part 2

FCC 47 CFR Part 27, Subpart C & M

ANSI/TIA/EIA-603-C-2004

The above equipment (Model no.: CPEi25750) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Claire Kuan , **DATE:** March 26, 2008
(Claire Kuan, Specialist)

TECHNICAL ACCEPTANCE : Hank Chung , **DATE:** March 26, 2008
Responsible for RF (Hank Chung, Deputy Manager)

APPROVED BY : May Chen , **DATE:** March 26, 2008
(May Chen, Deputy Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 27 & Part 2			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
2.1046 27.50(h)(2)	Maximum Peak Output Power Limit: max. 2 watts conducted peak power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability Stay with the authorized bands of operation	PASS	Meet the requirement of limit.
2.1049 27.53(m)(6)	Emission Bandwidth	PASS	Meet the requirement of limit.
2.1051 27.53(m)(4)(6)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(m)(4)(6)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(m)(4)(6)	Radiated Spurious Emissions	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Radiated emissions (30MHz-1GHz)	3.94 dB
Radiated emissions (1GHz -18GHz)	2.33 dB
Radiated emissions (18GHz -40GHz)	2.55 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WiMax CPE B2 Blade 2.5GHz
MODEL NO.	CPEi25750
FCC ID	VYO-CPE25750
POWER SUPPLY	DC 12V from power adapter
MODULATION TYPE	BPSK-1/2, QPSK-1/2
MODULATION TECHNOLOGY	OFDMA
FREQUENCY RANGE	2505MHz ~ 2685MHz
CHANNEL BANDWIDTH	5MHz & 10MHz
NUMBER OF CHANNEL	128
MAX. CONDUCTED POWER	27.40dBm
ANTENNA TYPE	Slot antenna with 7.17dBi
DATA CABLE	NA
I/O PORTS	RJ-45 port x 1 RJ-11 port x 2
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT must be supplied with a power adapter as following:

Brand	Model No.	Spec.
Delta	EADP-24KB B	Input: 100-240V, 1A, 50-60Hz Output: 12VDC,2A

2. For the radiated test <below 1GHz> was pre-tested under the following modes:

Test Mode	Description
Mode A	Channel bandwidth: 5MHz
Mode B	Channel bandwidth: 10MHz

From the above modes, the worst emission level was found in **Mode A**. Therefore only the test data of the mode was recorded in this report individually.

3. The above EUT information was declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Three channels have been tested and presented.

Low channel (L): 2505MHz.

Middle channel (M): 2600MHz.

High channel (H): 2685MHz.

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO							DESCRIPTION
	OP	FS	EB	CE	CSE	RE<1G	RE ³ 1G	
-	√	√	√	√	√	√	√	-

Where **OP**: Output power **FS**: Frequency stability
EB: Emission bandwidth **CE**: Channel edge
CSE: Conducted spurious emissions **RE<1G**: Radiated emission below 1GHz
RE³1G: Radiated emission above 1GHz

OUTPUT POWER MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
L, M, H	OFDMA	QPSK-1/2

FREQUENCY STABILITY MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
L	OFDMA	QPSK-1/2

EMISSION BANDWIDTH MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
L, M, H	OFDMA	QPSK-1/2

CHANNEL EDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
L, M, H	OFDMA	QPSK-1/2

CONDUCTED SPURIOUS EMISSIONS MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
L, M, H	OFDMA	QPSK-1/2

RADIATED EMISSION MEASUREMENT (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
L	OFDMA	QPSK-1/2

RADIATED EMISSION MEASUREMENT (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
L, M, H	OFDMA	QPSK-1/2

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27, Subpart C & M

ANSI/TIA/EIA-603-C-2004

NOTE: All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP18L	6976685584	FCC DoC
2	WiMAX Regulatory	Agilent	E4438C	MY45091206	NA
3	Antenna (Horn)	Schwarzbeck	BBHA9120-D 1	D124	NA
4	TELEPHONE	HTT	HTT-806	9543663	FCC
5	TELEPHONE	HTT	HTT-806	9543716	FCC

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	NA
4	3.0 m Non shielded cable, RJ11 connector, w/o core.
5	3.0 m Non shielded cable, RJ11 connector, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).

3.4.1 CONFIGURATION OF SYSTEM UNDER TEST



4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

The radiated peak output power shall be according to the specific rule Part 27.50(h)(2) that “User stations are limited to 2 watts and 27.50(i) specific that “Peak transmit power must be measure over any interval of continuous transmission using instrumentation calibration in terms of rms-equivalent voltage.”

4.1.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
Agilent Spectrum Analyzer	E4440A	MY46185282	Jun.14,2008
HUBER+SUHNER	SUCOFLEX104	22076614	Nov. 13, 2008
JFW 10dB attenuation	50HF-010-SMA	N/A	N/A


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1.3 TEST PROCEDURES

- a. Set span to encompass the entire emission bandwidth (EBW) of the signal.
- b. Set RBW=100kHz, VBW=1MHz, Detector mode=Peak.
- c. Compute power by integrating the spectrum across the 26dB EBW of the signal.
- d. Record the power level.

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

- a. The Notebook controlled EUT to export rated output power under transmission mode and specific channel frequency.
- b. All telephones are calling to each other via EUT.


4.1.6 TEST RESULTS

CHANNEL BANDWIDTH: 5MHz


INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak
ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH 965hPa	TESTED BY	Rex Huang

CONDUCTED POWER			
CHANNEL	FREQUENCY (MHz)	PEAK POWER OUTPUT(mW)	PEAK POWER OUTPUT(dBm)
Low	2505	540.754	27.33
Middle	2600	496.592	26.96
High	2685	492.040	26.92


LOW CHANNEL



MIDDLE CHANNEL



HIGH CHANNEL




CHANNEL BANDWIDTH: 10MHz


INPUT POWER (SYSTEM)	120Vac, 60Hz	DETECTOR FUNCTION	Peak
ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH 965hPa	TESTED BY	Rex Huang

CONDUCTED POWER			
CHANNEL	FREQUENCY (MHz)	PEAK POWER OUTPUT(mW)	PEAK POWER OUTPUT(dBm)
Low	2505	518.800	27.15
Middle	2600	549.541	27.40
High	2685	510.505	27.08


LOW CHANNEL



MIDDLE CHANNEL



HIGH CHANNEL



4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

According to the FCC part 2.1055 shall be tested the frequency stability. The rule is defined that” The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.” The test extreme voltage is according to the 2.1055(d)(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment and the extreme temperature rule is comply with specification of EUT -30°C ~ 50°C.

4.2.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100037	Aug. 12, 2008
OVEN	MHU-225AU	911033	Dec. 04, 2008
HUBER+SUHNER	SUCOFLEX104	22076614	Nov. 13, 2008
AC POWER SOURCE	6205	1140503	N/A

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in ADT RF OVEN room.

4.2.3 TEST PROCEDURE

- a. Power must be removed when changing from one temperature to another or one voltage to another voltage. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the AC input power. The various Volts from the minimum 102 Volts to 138 Volts. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing.
- d. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

4.2.4 TEST SETUP



4.2.5 TEST RESULTS

CHANNEL BANDWIDTH: 5MHz & 10MHz

MODE	Low channel (2505MHz)	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH 965hPa	TESTED BY	Rex Huang

AFC FREQUENCY ERROR VS. VOLTAGE.		
VOLTAGE (Volts)	FREQUENCY (MHz)	FREQUENCY DRIFT (ppm)
102	2504.9981	-0.758
120	2504.9947	-2.116
138	2504.9977	-0.918

AFC FREQUENCY ERROR VS. TEMP.		
TEMP. (°C)	FREQUENCY (MHz)	FREQUENCY DRIFT (ppm)
50	2505.0023	0.918
40	2505.0049	1.956
30	2504.9989	-0.439
20	2504.9947	-2.116
10	2505.0028	1.118
0	2505.0053	2.116
-10	2504.9949	-2.036
-20	2504.9991	-0.359

NOTE: The EUT can't operate and without any TX signal at -30°C.

4.3 EMISSION BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF EMISSION BANDWIDTH MEASUREMENT


According to FCC 27.53(m)(6) specified that emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4440A	MY46185282	Jun.14,2008
HUBER+SUHNER	SUCOFLEX104	22076614	Nov. 13, 2008
JFW 10dB attenuation	50HF-010-SMA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST SETUP



4.3.4 TEST PROCEDURES


- a. The Notebook controlled EUT to export rated output power under transmission mode and specific channel frequency. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 26dB bandwidth is define as the total spectrum the power of which is higher than peak power minus 26dB.

4.3.5 TEST RESULTS


CHANNEL BANDWIDTH: 5MHz

FREQUENCY (MHz)	-26 dBc BANDWIDTH (MHz)
2505	5.288
2600	5.257
2685	5.346


LOW CHANNEL



MIDDLE CHANNEL




HIGH CHANNEL




CHANNEL BANDWIDTH: 10MHz

FREQUENCY (MHz)	-26 dBc BANDWIDTH (MHz)
2505	9.943
2600	9.859
2685	10.018


LOW CHANNEL



MIDDLE CHANNEL



HIGH CHANNEL



4.4 CHANNEL EDGE MEASUREMENT

4.4.1 LIMITS OF CHANNEL EDGE MEASUREMENT

According to FCC 27.53(m)(4) specified that power of any emission outside of the channel edge must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4440A	MY46185282	Jun.14,2008
HUBER+SUHNER	SUCOFLEX104	22076614	Nov. 13, 2008
JFW 10dB attenuation	50HF-010-SMA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST SETUP

Same as Item 4.3.3

4.4.4 TEST PROCEDURES

- a. The EUT was set up for the rated peak power . The power was measured with Spectrum Analyzer. All measurements were done at 3 channels: low, middle and high operational frequency range.
- b. For Channel bandwidth: 5 MHz:
The center frequency of spectrum is the band edge frequency and span is 20MHz. RB of the spectrum is 51kHz and VB of the spectrum is 160kHz.
- c. For Channel bandwidth: 10 MHz:
The center frequency of spectrum is the band edge frequency and span is 30MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz.
- d. Record the max trace plot into the test report.


4.4.5 EUT OPERATING CONDITION

- a. The Notebook controlled EUT to export rated output power under transmission mode and specific channel frequency.


4.4.6 TEST RESULTS

CHANNEL BANDWIDTH: 5MHZ


LOW CHANNEL



MIDDLE CHANNEL




HIGH CHANNEL




CHANNEL BANDWIDTH: 10MHZ


LOW CHANNEL



MIDDLE CHANNEL



HIGH CHANNEL



4.5 CONDUCTED SPURIOUS EMISSIONS

4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

In the FCC 27.53(m)(4), On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.

4.5.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4440A	MY46185282	Jun.14,2008
HUBER+SUHNER	SUCOFLEX104	22076614	Nov. 13, 2008
JFW 10dB attenuation	50HF-010-SMA	NA	NA
Wainwright Instruments High Pass Filter	WHK3.1/18G-10SS	ZZ-010091	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

- a. The EUT was set up for the rated peak power. The power was measured with Spectrum Analyzer. All measurements were done at 3 channels: low, middle and high operational frequency range.
- b. When the spectrum scanned from 30MHz to 1GHz, it shall be connected to the 10dB pad attenuated the carried frequency. The spectrum set RB = 1MHz, VB = 3MHz.
- c. When the spectrum scanned from 1GHz to 27GHz, it shall be connected to the high pass filter attenuated the carried frequency. The spectrum set RB = 1MHz, VB = 3MHz.

4.5.4 TEST SETUP




4.5.5 EUT OPERATING CONDITIONS

- a. The Notebook controlled EUT to export rated output power under transmission mode and specific channel frequency.


4.5.6 TEST RESULTS

CHANNEL BANDWIDTH: 5MHZ


LOW CHANNEL: 30MHz ~ 1GHz:




1GHz ~ 5GHz:




5GHz ~ 10GHz:




10GHz ~ 26.5GHz:




MIDDLE CHANNEL: 30MHz ~ 1GHz:




1GHz ~ 5GHz:




5GHz ~ 10GHz:




10GHz ~ 26.5GHz:




HIGH CHANNEL: 30MHz ~ 1GHz:




1GHz ~ 5GHz:



5GHz ~ 10GHz:




10GHz ~ 26.5GHz:




CHANNEL BANDWIDTH: 10MHZ


LOW CHANNEL: 30MHz ~ 1GHz:




1GHz ~ 5GHz:




5GHz ~ 10GHz:




10GHz ~ 26.5GHz:




MIDDLE CHANNEL: 30MHz ~ 1GHz:




1GHz ~ 5GHz:




5GHz ~ 10GHz:




10GHz ~ 26.5GHz:




HIGH CHANNEL: 30MHz ~ 1GHz:




1GHz ~ 5GHz:



5GHz ~ 10GHz:



10GHz ~ 26.5GHz:



4.6 RADIATED EMISSION MEASUREMENT (BELOW 1GHz)

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

In the FCC 27.53(m) (4), On any frequency outside a licensee's frequency block the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Spectrum Analyzer	FSP40	100060	April 20, 2008
HP Pre_Amplifier	8449B	3008A01922	Sep. 18, 2008
ROHDE & SCHWARZ Test Receiver	ESCS30	100375	Sep. 20, 2008
SCHWARZBECK TRILOG Broadband Antenna	VULB 9168	138	July 17, 2008
Schwarzbeck Horn_Antenna	BBHA9120	D124	Jan. 01, 2009
RF Switches (ARNITSU)	MP59B	6200283544	NA
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Nov. 14. 2008
RF Cable(RICHTEC)	9913-30M	STCCAB-30M-1 GHz-021	Aug. 13, 2008
Software	ADT_Radiated_V 7.6.15.8	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
*CHANCE MOST Turn Table	TT-100	0203	NA

- Note:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The horn antenna, HP preamplifier (model: 8449B) and Spectrum Analyzer (model: R3271A) are used only for the measurement of emission frequency above 1GHz if tested.
 3. The test was performed in ADT Open Site No. C.
 4. The FCC Site Registration No. is 656396.
 5. The VCCI Site Registration No. is R-1626.
 6. The CANADA Site Registration No. is IC 4824A-3.

4.6.3 TEST PROCEDURES


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the receiving antenna, which was mounted on antenna tower and its position at 0.8 m above the ground.
- c. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading and recorded the value.
- d. The EUT is replaced by a horn antenna connected to a signal generator tuned to the frequency of emission.
- e. The signal generator level has to be adjusted to have the same emission nature.
- f. The radiated power can be calculated via the factor and antenna gain.
- g. Repeat step a ~ f for horizontal polarization.

NOTE: The resolution bandwidth of spectrum analyzer is 1MHz and the video bandwidth is 3MHz.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.6.6 EUT OPERATING CONDITIONS

- a. The Notebook controlled EUT to export rated output power under transmission mode and specific channel frequency.

4.6.7 TEST RESULTS

CHANNEL BANDWIDTH: 5MHZ

MODE	Low channel	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH 965hPa
TESTED BY	Rex Huang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Power level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	125.00	-63.21	-13.00	-61.99	-1.21	28.69
2	200.00	-61.50	-13.00	-65.84	4.34	29.65
3	250.00	-61.49	-13.00	-65.38	3.89	29.58
4	300.00	-55.53	-13.00	-59.24	3.71	36.54
5	400.00	-64.26	-13.00	-67.59	3.33	30.25
6	500.00	-54.94	-13.00	-57.83	2.89	37.69
7	625.00	-55.59	-13.00	-57.36	1.77	37.45
8	750.00	-57.04	-13.00	-57.86	0.82	38.52
9	875.00	-55.41	-13.00	-56.17	0.76	40.52
10	875.00	-95.93	-13.00	-96.69	0.76	0.00

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Power Level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	62.03	-60.19	-13.00	-53.20	-6.99	30.14
2	125.00	-59.45	-13.00	-58.23	-1.21	32.45
3	132.96	-67.21	-13.00	-65.68	-1.53	30.28
4	250.00	-57.32	-13.00	-61.21	3.89	33.75
5	300.00	-53.28	-13.00	-56.99	3.71	38.79
6	400.00	-62.66	-13.00	-65.99	3.33	31.85
7	480.00	-54.80	-13.00	-57.65	2.86	38.96
8	500.00	-56.18	-13.00	-59.07	2.89	36.45
9	625.00	-52.52	-13.00	-54.29	1.77	40.52

REMARKS: 1. Power Value(dBm)=S.G Power Value (dBm) + Correction Factor(dB)

4.7 RADIATED EMISSION MEASUREMENT (ABOVE 1GHz)

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

In the FCC 27.53(m) (4), On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB.

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Spectrum Analyzer	FSP40	100060	April 20, 2008
HP Pre_Amplifier	8449B	3008A01922	Sep. 18, 2008
ROHDE & SCHWARZ Test Receiver	ESCS30	100375	Sep. 20, 2008
SCHWARZBECK TRILOG Broadband Antenna	VULB 9168	138	July 17, 2008
Schwarzbeck Horn_Antenna	BBHA9120	D124	Jan. 01, 2009
RF Switches (ARNITSU)	MP59B	6200283544	NA
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Nov. 14. 2008
RF Cable(RICHTEC)	9913-30M	STCCAB-30M-1 GHz-021	Aug. 13, 2008
Software	ADT_Radiated_V 7.6.15.8	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
*CHANCE MOST Turn Table	TT-100	0203	NA

- Note:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The horn antenna, HP preamplifier (model: 8449B) and Spectrum Analyzer (model: R3271A) are used only for the measurement of emission frequency above 1GHz if tested.
 3. The test was performed in ADT Open Site No. C.
 4. The FCC Site Registration No. is 656396.
 5. The VCCI Site Registration No. is R-1626.
 6. The CANADA Site Registration No. is IC 4824A-3.

4.7.3 TEST PROCEDURES


- h. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- i. The EUT was set 3 meters away from the receiving antenna, which was mounted on antenna tower and its position at 0.8 m above the ground.
- j. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading and recorded the value.
- k. The EUT is replaced by a horn antenna connected to a signal generator tuned to the frequency of emission.
- l. The signal generator level has to be adjusted to have the same emission nature.
- m. The radiated power can be calculated via the factor and antenna gain.
- n. Repeat step a ~ f for horizontal polarization.

NOTE: The resolution bandwidth of spectrum analyzer is 1MHz and the video bandwidth is 3MHz.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITIONS

- a. The Notebook controlled EUT to export rated output power under transmission mode and specific channel frequency.

4.7.7 TEST RESULTS

CHANNEL BANDWIDTH: 5MHZ

MODE	Low channel	FREQUENCY RANGE	Above 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH, 965hPa
TESTED BY	Rex Huang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Power level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5010.00	-27.98 PK	-13.00	-35.00	7.01	69.25
2	7515.00	-32.83 PK	-13.00	-37.36	4.53	65.26
3	10020.00	-34.69 PK	-13.00	-38.71	4.02	62.87

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5010.00	-31.53 PK	-13.00	-38.55	7.01	65.70
2	7515.00	-32.31 PK	-13.00	-36.84	4.53	65.78
3	10020.00	-32.54 PK	-13.00	-36.56	4.02	65.02

REMARKS: 1. Power Value(dBm)=S.G Power Value (dBm) + Correction Factor(dB)

MODE	Middle channel	FREQUENCY RANGE	Above 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH, 965hPa
TESTED BY	Rex Huang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Power level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5200.00	-30.28 PK	-13.00	-37.33	7.05	67.19
2	7800.00	-38.80 PK	-13.00	-43.09	4.29	59.53
3	10400.00	-34.24 PK	-13.00	-37.91	3.66	64.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5200.00	-33.82 PK	-13.00	-40.87	7.05	63.65
2	7800.00	-28.49 PK	-13.00	-32.78	4.29	69.84
3	10400.00	-33.23 PK	-13.00	-36.90	3.66	65.11

REMARKS: 1. Power Value(dBm)=S.G Power Value (dBm) + Correction Factor(dB)

MODE	High channel	FREQUENCY RANGE	Above 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH, 965hPa
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Power level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5370.00	-29.95 PK	-13.00	-37.05	7.09	67.74
2	8050.00	-41.78 PK	-13.00	-45.91	4.13	56.71
3	10735.00	-42.79 PK	-13.00	-46.13	3.35	55.72

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5370.00	-37.43 PK	-13.00	-44.53	7.09	60.26
2	8050.00	-40.48 PK	-13.00	-44.61	4.13	58.01
3	10735.00	-41.36 PK	-13.00	-44.70	3.35	57.15

REMARKS: 1. Power Value(dBm)=S.G Power Value (dBm) + Correction Factor(dB)

CHANNEL BANDWIDTH: 10MHZ

MODE	Low channel	FREQUENCY RANGE	Above 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH, 965hPa
TESTED BY	Rex Huang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Power level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5010.00	-32.37 PK	-13.00	-39.39	7.01	64.86
2	7515.00	-39.05 PK	-13.00	-43.58	4.53	59.04
3	10020.00	-40.38 PK	-13.00	-44.40	4.02	57.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5010.00	-37.53 PK	-13.00	-44.55	7.01	59.70
2	7515.00	-38.83 PK	-13.00	-43.36	4.53	59.26
3	10020.00	-37.43 PK	-13.00	-41.45	4.02	60.13

REMARKS: 1. Power Value(dBm)=S.G Power Value (dBm) + Correction Factor(dB)

MODE	Middle channel	FREQUENCY RANGE	Above 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH, 965hPa
TESTED BY	Rex Huang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Power level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5200.00	-33.57 PK	-13.00	-40.62	7.05	63.90
2	7800.00	-41.97 PK	-13.00	-46.26	4.29	56.36
3	10400.00	-41.28 PK	-13.00	-44.95	3.66	57.06

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5200.00	-39.16 PK	-13.00	-46.21	7.05	58.31
2	7800.00	-36.28 PK	-13.00	-40.57	4.29	62.05
3	10400.00	-39.53 PK	-13.00	-43.20	3.66	58.81

REMARKS: 1. Power Value(dBm)=S.G Power Value (dBm) + Correction Factor(dB)

MODE	High channel	FREQUENCY RANGE	Above 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60Hz	ENVIRONMENTAL CONDITIONS	20deg°C, 60%RH, 965hPa
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Power level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5370.00	-35.29 PK	-13.00	-42.34	7.05	62.18
2	8050.00	-43.64 PK	-13.00	-47.93	4.29	54.69
3	10735.00	-42.38 PK	-13.00	-46.05	3.66	55.96

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBm)	Limit (dBm)	S.G level (dBm)	C.F. (dB)	Emission Level (dBuV/m)
1	5370.00	-40.69 PK	-13.00	-47.74	7.05	56.78
2	8050.00	-43.09 PK	-13.00	-47.38	4.29	55.24
3	10735.00	-41.53 PK	-13.00	-45.20	3.66	56.81

REMARKS: 1. Power Value(dBm)=S.G Power Value (dBm) + Correction Factor(dB)

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
GERMANY	TUV Rheinland
JAPAN	VCCI
NORWAY	NEMKO
CANADA	INDUSTRY CANADA , CSA
R.O.C.	TAF, BSMI, NCC
NETHERLANDS	Telefication
SINGAPORE	GOST-ASIA (MOU)
RUSSIA	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab: Web Site: www.adt.com.tw

Tel: 886-3-3183232

Fax: 886-3-3185050

The address and road map of all our labs can be found in our web site also.