

# TEST REPORT

**Product Name** : Wi-Fi&BT module  
**Brand Mark** : N/A  
**Model No.** : RW6852S-50B2  
**Extension model** : RW6852S-50  
**Report Number** : BLA-EMC-202209-A6404  
**FCC ID** : VYV-RW6852S- 50B2  
**Date of Sample Receipt** : 2022/9/26  
**Date of Test** : 2022/9/26 to 2022/11/15  
**Date of Issue** : 2022/11/15  
**Test Standard** : 47 CFR Part 15, Subpart C 15.247  
**Test Result** : Pass

Prepared for:

**Iton Technology Corp.**

**Room 1302, Block A, Building 4, Tianan Cyber Park, Huangge Road,  
Longgang District, Shenzhen City, Guangdong Province, China**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**

**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,  
Shenzhen, Guangdong Province, China**

**TEL: +86-755-23059481**

Compiled by:

*Jozu*

Approved by:

*Bluezheng*

Review by:

*Sueels*

Date:

2022/11/15



**REPORT REVISE RECORD**

<b>Version No.</b>	<b>Date</b>	<b>Description</b>
00	2022/11/15	Original

BlueAsia

## TABLE OF CONTENTS

<b>1</b>	<b>TEST SUMMARY .....</b>	<b>5</b>
<b>2</b>	<b>GENERAL INFORMATION .....</b>	<b>6</b>
<b>3</b>	<b>GENERAL DESCRIPTION OF E.U.T. ....</b>	<b>6</b>
<b>4</b>	<b>TEST ENVIRONMENT .....</b>	<b>8</b>
<b>5</b>	<b>TEST MODE .....</b>	<b>8</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>7</b>	<b>DESCRIPTION OF SUPPORT UNIT .....</b>	<b>9</b>
<b>8</b>	<b>LABORATORY LOCATION .....</b>	<b>9</b>
<b>9</b>	<b>TEST INSTRUMENTS LIST .....</b>	<b>10</b>
<b>10</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>12</b>
10.1	CONCLUSION .....	12
<b>11</b>	<b>RADIATED SPURIOUS EMISSIONS .....</b>	<b>14</b>
11.1	LIMITS .....	14
11.2	BLOCK DIAGRAM OF TEST SETUP .....	15
11.3	PROCEDURE .....	15
11.4	TEST DATA .....	17
<b>12</b>	<b>RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....</b>	<b>25</b>
12.1	LIMITS .....	25
12.2	BLOCK DIAGRAM OF TEST SETUP .....	26
12.3	PROCEDURE .....	26
12.4	TEST DATA .....	28
<b>13</b>	<b>CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>44</b>
13.1	LIMITS .....	44
13.2	BLOCK DIAGRAM OF TEST SETUP .....	44
13.3	TEST DATA .....	45
<b>14</b>	<b>CONDUCTED BAND EDGES MEASUREMENT .....</b>	<b>46</b>
14.1	LIMITS .....	46
14.2	BLOCK DIAGRAM OF TEST SETUP .....	46
14.3	TEST DATA .....	47

<b>15</b>	<b>MINIMUM 6DB BANDWIDTH .....</b>	<b>48</b>
15.1	LIMITS .....	48
15.2	BLOCK DIAGRAM OF TEST SETUP .....	48
15.3	TEST DATA .....	48
<b>16</b>	<b>POWER SPECTRUM DENSITY .....</b>	<b>49</b>
16.1	LIMITS .....	49
16.2	BLOCK DIAGRAM OF TEST SETUP .....	49
16.3	TEST DATA .....	49
<b>17</b>	<b>CONDUCTED PEAK OUTPUT POWER .....</b>	<b>50</b>
17.1	LIMITS .....	50
17.2	BLOCK DIAGRAM OF TEST SETUP .....	50
17.3	TEST DATA .....	51
<b>18</b>	<b>CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) .....</b>	<b>52</b>
18.1	LIMITS .....	52
18.2	BLOCK DIAGRAM OF TEST SETUP .....	52
18.3	PROCEDURE .....	52
18.1	TEST DATA .....	54
<b>19</b>	<b>APPENDIX .....</b>	<b>56</b>
	<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>194</b>
	<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>196</b>

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5 & Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(1) & 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	Iton Technology Corp.
<b>Address</b>	Room 1302, Block A, Building 4, Tianan Cyber Park, Huangge Road, Longgang District, Shenzhen City, Guangdong Province, China
<b>Manufacturer</b>	Iton Technology Corp.
<b>Address</b>	7th Floor, Building C, Shenzhen International Innovation Center (Futian Science and Technology Plaza), 1006 Shennan Road, Huafu Street, Futian District, Shenzhen City, Guangdong Province, China
<b>Factory</b>	Iton Technology Corp., Longgang Branch
<b>Address</b>	2~3 Floor, East Wing, Building A, Weixinda Technology Park, No.95 Ainan Road, Longgang District, Shenzhen City, Guangdong Province, China.
<b>Product Name</b>	Wi-Fi&BT module
<b>Test Model No.</b>	RW6852S-50B2
<b>Extension model</b>	RW6852S-50
<b>Note</b>	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	V2.1
<b>Software Version</b>	V1.0.35
<b>Operation Frequency:</b>	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
<b>Modulation Type:</b>	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
<b>Channel Spacing:</b>	5MHz
<b>Number of Channels:</b>	802.11b/g/n(HT20):11 802.11n(HT40):7
<b>Antenna Type:</b>	External Antenna
<b>Antenna Gain:</b>	ANT1:3.3dBi ; ANT2:3.3dBi (Provided by the applicant)
<b>Note:</b>	Antenna number : 2 SISO mode: 802.11b, 802.11g MIMO mode: 802.11n(HT20)/ 802.11n(HT40) Directional gain of MIMO mode:3.3+10log2=6.31dBi

Remark:The Antenna Gain is supplied by the customer.BlueAsia is not responsible for this data

Note: if transmitting antennas of directional gain greater than 6 dBi are used, then the limit should be reduced.

Because the directional gain = 6.31dB > 6.0 dBi, the limit should be calculated as below:

Power:

$$\begin{aligned} \text{Limit} &= 30 \text{ dBm} - (\text{ANT Gain} + 10 \cdot \log(N=2) - 6 \text{ dBi}) \\ &= 30 \text{ dBm} - (3.3 + 3.01 - 6) \text{ dBi} = 29.69 \text{ dBm} \end{aligned}$$

P.S.D:

$$\begin{aligned} \text{Limit} &= 8 \text{ dBm} - (\text{ANT Gain} + 10 \cdot \log(N=2) - 6 \text{ dBi}) \\ &= 8 \text{ dBm} - (3.3 + 3.01 - 6) \text{ dBi} = 7.69 \text{ dBm} \end{aligned}$$

BlueAsia

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	3.3Vdc

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (The duty cycle is greater than 98%)
Remark: Full battery is used during all test except ac conducted emission, 802.11b/g/n(HT20) and 802.11n(HT40) all have been tested, During the radiated spurious emission test, 802.11b/11g/11nH20/11nH40 modulations all have been tested,only worse case 802.11b is reported.	

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Unwanted Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Unwanted Radiated Emission (1GHz ~ 18GHz)	±4.44 dB



## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	HASEE	K610D	N/A	N/A

## 8 LABORATORY LOCATION

All tests were performed at:  
BlueAsia of Technical Services(Shenzhen) Co., Ltd.  
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province,  
China  
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673  
No tests were sub-contracted.

## 9 TEST INSTRUMENTS LIST

Test Equipment Of RF Conducted Test					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2022/09/15	2023/09/14
Spectrum	Agilent	N9020A	MY49100060	2022/09/07	2023/09/06
Spectrum	KEYSIGHT	N9030A	MY52350152	2022/07/01	2023/06/30
Spectrum	KEYSIGHT	N9010A	MY54330814	2022/07/01	2023/06/30
Signal Generator	Agilent	N5182A	MY47420955	2022/09/07	2023/09/06
Signal Generator	Agilent	E8257D	MY44320250	2022/07/01	2023/06/30
Signal Generator	Agilent	N5181A	MY46240904	2022/08/02	2023/08/01
Signal Generator	R&S	CMW500	132429	2022/09/07	2023/09/06
BluetoothTester	Anritsu	MT8852B	06262047872	2022/09/07	2023/09/06
Power probe	DARE	RPR3006W	14I00889SN042	2022/09/07	2023/09/06
DCPowersupply	zhaoxin	KXN-305D	20K305D1221363	2022/09/14	2023/09/13
DCPowersupply	zhaoxin	RXN-1505D	19R1505D050168	2022/09/14	2023/09/13

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber 1	SKET	966	N/A	2020/11/10	2023/11/9
Chamber 2	SKET	966	N/A	2021/07/20	2024/07/19
Spectrum	R&S	FSP40	100817	2022/09/15	2023/09/14
Receiver	R&S	ESR7	101199	2022/09/15	2023/09/14
Receiver	R&S	ESPI7	101477	2022/07/16	2023/07/15
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2022/09/15	2023/09/14
Horn Antenna	Schwarzbeck	BBHA9120D	01892 P:00331	2022/09/13	2025/09/12
Amplifier	SKET	LNPA_30M01G-30	SK2021060801	2022/07/16	2023/07/15
Amplifier	SKET	PA-000318G-45	N/A	2022/09/13	2023/09/12
Amplifier	SKET	LNPA_18G40G-50	SK2022071301	2022/07/14	2023/07/13
Filter group	SKET	2.4G/5G Filter group r	N/A	2022/07/16	2023/07/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2022/9/14	2025/9/13

Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

BlueAsia

## 10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


### 10.1 CONCLUSION


Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The best case gain of the antenna is 3.3dBi.





Blue

## 11 RADIATED SPURIOUS EMISSIONS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 11.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 11.2 BLOCK DIAGRAM OF TEST SETUP



## 11.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



### 11.4 TEST DATA


[TestMode: TX below 1G]; [Polarity: Horizontal]



\*:Maximum data    x:Over limit    !:over margin

**Test Result: Pass**

[TestMode: TX below 1G]; [Polarity: Vertical]



Site:      Polarization: **Vertical**      Temperature: (C)  
 Limit: FCC Part15 Class B      Power:      Humidity: %RH  
 EUT: WIFI Module  
 M/N: 852S-50B2  
 Mode: 2.4WIFI mode  
 Note:


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	54.8348	26.76	-6.42	20.34	40.00	-19.66	QP	P	
2	87.7246	30.79	-10.72	20.07	40.00	-19.93	QP	P	
3	147.4036	22.46	-6.21	16.25	43.50	-27.25	QP	P	
4	279.0436	20.40	-6.89	13.51	46.00	-32.49	QP	P	
5	451.1350	21.60	-1.90	19.70	46.00	-26.30	QP	P	
6 *	900.1474	20.71	5.72	26.43	46.00	-19.57	QP	P	

\*:Maximum data    x:Over limit    !:over margin

**Test Result: Pass**

Remark: During the test, pre-scan the 802.11b/g/n mode, and found the 802.11b mode which it is worse case.

[TestMode: TX low channel]; [Polarity: Horizontal]




Site	Polarization: <b>Horizontal</b>	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: wireless headphones		
M/N: Capsule3 Pro		
Mode: 2.4GWIFI-11B-TX-L		
Note:		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		1998.750	51.97	-4.47	47.50	74.00	-26.50	peak	
2		4824.000	39.12	4.13	43.25	74.00	-30.75	peak	
3		7326.000	37.91	8.21	46.12	74.00	-27.88	peak	
4		8238.000	40.68	9.00	49.68	74.00	-24.32	peak	
5		9648.000	37.45	11.01	48.46	74.00	-25.54	peak	
6	*	11457.500	38.81	13.66	52.47	74.00	-21.53	peak	

**Test Result: Pass**

[TestMode: TX low channel]; [Polarity: Vertical]




Site:      Polarization: **Vertical**      Temperature: (C)  
 Limit: FCC Part15 (PK)      Power:      Humidity: %RH  
 EUT: wireless headphones  
 M/N: Capsule3 Pro  
 Mode: 2.4GWIFI-11B-TX-L  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2492.250	48.73	-2.17	46.56	74.00	-27.44	peak	
2		4824.000	38.81	4.13	42.94	74.00	-31.06	peak	
3		7326.000	38.16	8.21	46.37	74.00	-27.63	peak	
4		8026.500	41.06	8.91	49.97	74.00	-24.03	peak	
5		9648.000	37.91	11.01	48.92	74.00	-25.08	peak	
6	*	11316.500	39.02	13.59	52.61	74.00	-21.39	peak	

**Test Result: Pass**

[TestMode: TX mid channel]; [Polarity: Horizontal]




Site:      Polarization: **Horizontal**      Temperature: (C)  
 Limit: FCC Part15 (PK)      Power:      Humidity: %RH  
 EUT: wireless headphones  
 M/N: Capsule3 Pro  
 Mode: 2.4GWIFI-11B-TX-M  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		1246.750	55.80	-8.02	47.78	74.00	-26.22	peak	
2		4874.000	40.50	4.32	44.82	74.00	-29.18	peak	
3		7311.000	40.03	8.18	48.21	74.00	-25.79	peak	
4		8261.500	39.77	9.02	48.79	74.00	-25.21	peak	
5		9748.000	38.50	11.26	49.76	74.00	-24.24	peak	
6	*	11774.750	39.22	13.80	53.02	74.00	-20.98	peak	

**Test Result: Pass**

[TestMode: TX mid channel]; [Polarity: Vertical]




Site:      Polarization: **Vertical**      Temperature: (C)  
 Limit: FCC Part15 (PK)      Power:      Humidity: %RH  
 EUT: wireless headphones  
 M/N: Capsule3 Pro  
 Mode: 2.4GWIFI-11B-TX-M  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2492.250	49.50	-2.17	47.33	74.00	-26.67	peak	
2		4874.000	40.09	4.32	44.41	74.00	-29.59	peak	
3		7311.000	38.39	8.18	46.57	74.00	-27.43	peak	
4		8167.500	40.28	8.98	49.26	74.00	-24.74	peak	
5		9748.000	38.26	11.26	49.52	74.00	-24.48	peak	
6	*	11669.000	39.37	13.75	53.12	74.00	-20.88	peak	

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Horizontal]




Site:      Polarization: **Horizontal**      Temperature: (C)  
 Limit: FCC Part15 (PK)      Power:      Humidity: %RH  
 EUT: wireless headphones  
 M/N: Capsule3 Pro  
 Mode: 2.4GWIFI-11B-TX-H  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2433.500	49.33	-1.52	47.81	74.00	-26.19	peak	
2		4824.000	38.54	4.13	42.67	74.00	-31.33	peak	
3		7386.000	38.96	8.36	47.32	74.00	-26.68	peak	
4		8214.500	40.49	9.00	49.49	74.00	-24.51	peak	
5		9848.000	36.87	11.52	48.39	74.00	-25.61	peak	
6	*	11868.750	39.09	13.84	52.93	74.00	-21.07	peak	

**Test Result: Pass**

[TestMode: TX high channel]; [Polarity: Vertical]



Site:      Polarization: **Vertical**      Temperature: (C)  
 Limit: FCC Part15 (PK)      Power:      Humidity: %RH  
 EUT: wireless headphones  
 M/N: Capsule3 Pro  
 Mode: 2.4GWIFI-11B-TX-H  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2245.500	51.72	-3.35	48.37	74.00	-25.63	peak	
2		4924.000	39.54	4.82	44.36	74.00	-29.64	peak	
3		7386.000	38.55	8.36	46.91	74.00	-27.09	peak	
4		8179.250	40.37	8.98	49.35	74.00	-24.65	peak	
5		9848.000	36.72	11.52	48.24	74.00	-25.76	peak	
6	*	11751.250	39.32	13.79	53.11	74.00	-20.89	peak	

**Test Result: Pass**



## 12 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25°C
<b>Humidity</b>	60%

### 12.1 LIMITS

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 12.2 BLOCK DIAGRAM OF TEST SETUP



## 12.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1:  $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamp\ Factor$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

### 12.4 TEST DATA

[TestMode: TX b low channel]; [Polarity: Horizontal]




Site	Polarization: <b>Horizontal</b>	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: wireless headphones		
M/N: Capsule3 Pro		
Mode: 2.4GWIFI-11B-TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		2310.000	43.28	-4.27	39.01	74.00	-34.99	peak	
2	*	2390.000	45.88	-3.82	42.06	74.00	-31.94	peak	

**Test Result: Pass**

[TestMode: TX b low channel]; [Polarity: Vertical]



Site:      Polarization: **Vertical**      Temperature: (C)

Limit: FCC Part15 (PK)      Power:      Humidity: %RH

EUT: wireless headphones

M/N: Capsule3 Pro

Mode: 2.4GWIFI-11B-TX-L


Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	2310.000	45.03	-4.27	40.76	74.00	-33.24	peak	
2 *	2390.000	53.50	-3.82	49.68	74.00	-24.32	peak	

**Test Result: Pass**

[TestMode: TX b high channel]; [Polarity: Vertical]

**Radiated Emission Measurement**



Site	Polarization: <b>Horizontal</b>	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: wireless headphones		
M/N: Capsule3 Pro		
Mode: 2.4GWIFI-11B-TX-H		
Note:		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2483.500	44.12	-3.96	40.16	74.00	-33.84	peak	
2	*	2500.000	52.16	-4.00	48.16	74.00	-25.84	peak	

**Test Result: Pass**