

FCC 47 CFR PART 15 SUBPART E

CERTIFICATION TEST REPORT

For

WIFI module

MODEL No.: BW2569-14P

FCC ID: VYVBW2569-14P

Trade Mark: N/A

REPORT NO.: ES160321036E4

ISSUE DATE: June 30, 2016

Prepared for

Iton Technology Crop.

Room 1302, Block A, Building 4, Tianan Cyber Park, HuanggeRoad, Longgang District, Shenzhen, China.

Prepared by

EMTEK(SHENZHEN) CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China TEL: 86-755-26954280 FAX: 86-755-26954282



1 TEST RESULT CERTIFICATION

Applicant:	Iton Technology Crop. Room 201,2nd Floor, Building 20, No 1006 Yitian Road, Futian District, Shenzhen,China
Manufacturer:	Iton Technology Crop. Room 201,2nd Floor, Building 20, No 1006 Yitian Road, Futian District, Shenzhen,China
Product Description:	WIFI module
Model Number:	BW2569-14P
File Number:	ES160321036E4
Date of Test:	May 16, 2016 to June 30, 2016

Measurement Procedure Used:

APPLICABLE STANDARDS			
STANDARD TEST RESULT			
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart E	PASS		

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD.. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.407

The test results of this report relate only to the tested sample identified in this report.

Date of Test :	May 16, 2016 to June 29, 2016
Prepared by :	Joanna Jiao/Editor
Reviewer :	Joe Xia /Supervisor
Approve & Authorized Signer :	Lisa Wang/Manager



TABLE OF CONTENTS

TES	T RESULT CERTIFICATION	2
EUT	TECHNICAL DESCRIPTION	4
SUN	IMARY OF TEST RESULT	6
TES	T METHODOLOGY	7
4.1 4.2 4.3	MEASUREMENT EQUIPMENT USED	7
FAC	CILITIES AND ACCREDITATIONS	13
5.1 5.2	FACILITIES LABORATORY ACCREDITATIONS AND LISTINGS	
TES	ST SYSTEM UNCERTAINTY	14
SET	UP OF EQUIPMENT UNDER TEST	15
7.1 7.2 7.3 7.4 7.5	RADIO FREQUENCY TEST SETUP CONDUCTED EMISSION TEST SETUP BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM SUPPORT EQUIPMENT	
TES		
8.1 8.2 8.3 8.4 8.5 8.6 8.7	MAXIMUM CONDUCTED OUTPUT POWER MAXIMUM PEAK POWER DENSITY FREQUENCY STABILITY UNDESIRABLE RADIATED SPURIOUS EMISSION	
	EUT SUM TES 4.1 4.2 4.3 FAC 5.1 5.2 TES 5.1 5.2 TES 5.1 7.1 7.2 7.3 7.4 7.5 TES 3.1 3.2 3.3 3.4 3.5 3.6	 4.2 MEASUREMENT EQUIPMENT USED. 4.3 DESCRIPTION OF TEST MODES. FACILITIES AND ACCREDITATIONS



Characteristics	Description						
Device Type	Wifi 5G Device						
IEEE 802.11 WLAN Mode Supported	⊠802.11n(2 ⊠802.11n(4 ⊠802.11ac(⊠802.11ac(■ 802.11a(20MHz channel bandwidth) ■ 802.11n(20MHz channel bandwidth) ■ 802.11n(40MHz channel bandwidth) ■ 802.11ac(20MHz channel bandwidth) ■ 802.11ac(40MHz channel bandwidth) ■ 802.11ac(40MHz channel bandwidth) ■ 802.11ac(80MHz channel bandwidth) ■ 802.11ac(80MHz channel bandwidth) 					
Data Rate	⊠802.11n(H ⊠802.11n(H ⊠802.11ac(⊠802.11ac(⊠802.11a:6, 9, 12, 18, 24, 36, 48, 54Mbps; ⊠802.11n(HT20): MCS0-MCS15; ⊠802.11ac(HT20): MCS0-MCS15; ⊠802.11ac(HT40): MCS0-MCS15; ⊠802.11ac(HT40):MCS0-MCS19; ⊠802.11ac(VHT80):MCS0-MCS19;					
MIMO Mode	2TX2RX						
Modulation		th BPSK/QPSK/16QAM/64QAM th BPSK/QPSK/16QAM/64QAM					
	Band	Mode	Frequency Range(MHz)	Number of channels			
		802.11a/n(HT20)/ac(VHT20)	5180-5240	4			
	UNII Band I	802.11n(HT40)/ac(VHT40)	5190-5230	2			
	Danu	802.11 ac(VHT80)	5210MHz	1			
		802.11a/n(HT20)/ac(VHT20)	5260-5320	4			
Operating Frequency	UNII Band II-A	802.11n(HT40)/ac(VHT40)	5270-5310	2			
Range	Dana II /	802.11 ac(VHT80)	5290	1			
		802.11a/n(HT20)/ac(VHT20)	5500-5700	11			
	UNII Band II-C	802.11n(HT40)/ac(VHT40)	5510-5670	5			
		802.11 ac(VHT80)	5530-5610	2			
		802.11a/n(HT20)/ac(VHT20)	5745-5825	5			
	UNII Band III	802.11n(HT40)/ac(VHT40)	5755-5795	2			
	Bung III	802.11 ac(VHT80)	5775	1			
Transmit Power Max	UNII Band I for 19.11dBm UNII Band II-A for 19.26dBm UNII Band II-C for 16.31dBm UNII Band III for 14.18dBm						
Antenna Type	Monolithic S	MD Antenna					
Smart system	□SISO for 802.11a/n ⊠MIMO for 802.11n/ac						
Antenna Gain	5dBi						

2 EUT TECHNICAL DESCRIPTION



Array Gain	8dBi
	DC supply: DC 3.3V
Power supply	Adapter supply: N/A

Note: for more details, please refer to the User's manual of the EUT.



3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark			
15.407 (a) 15.407 (e)	99% , 6dB and 26dB Bandwidth	PASS				
15.407 (a)	Maximum Conducted Output Power	PASS				
15.407 (a)	Peak Power Spectral Density	PASS				
15.407 (b)	Radiated Spurious Emission	PASS				
15.407(g)	Frequency Stability	PASS				
15.407 (b)(6) 15.207	Power Line Conducted Emission	PASS				
15.407(a) 15.203	Antenna Application	PASS				
15.203 Image: Construction of the second						

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: VYVBW2569-14P filing to comply with Section 15.247 of the FCC Part 15, Subpart E Rules.



4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards: FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart E

FCC KDB 789003 D2 General UNII Test Procedures New Rules v01r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT	MFR	MODEL	SERIAL	LAST	
TYPE		NUMBER	NUMBER	CAL.	
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/15/2016	
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/15/2016	
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/15/2016	
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/15/2016	
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/15/2016	

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/15/2016
Pre-Amplifier	HP	8447D	2944A07999	05/15/2016
Bilog Antenna	Schwarzbeck	VULB9163	142	05/15/2016
Loop Antenna	ARA	PLA-1030/B	1029	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/15/2016
Cable	Schwarzbeck	AK9513	ACRX1	05/15/2016
Cable	Rosenberger	N/A	FP2RX2	05/15/2016
Cable	Schwarzbeck	AK9513	CRPX1	05/15/2016
Cable	Schwarzbeck	AK9513	CRRX2	05/15/2016

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/15/2016
Signal Analyzer	Agilent	N9010A	My53470879	05/15/2016
Power meter	Anritsu	ML2495A	0824006	05/15/2016
Power sensor	Anritsu	MA2411B	0738172	05/15/2016

Remark: Each piece of equipment is scheduled for calibration once a year.



4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (⊠802.11a: 6 Mbps; ⊠802.11n (HT20): MCS0; ⊠802.11n (HT20): MCS15; ⊠802.11n (HT40): MCS0; ⊠802.11n (HT40): MCS15; ⊠802.11ac (HT20): MCS0; ⊠802.11ac (HT20): MCS15; ⊠ 802.11ac (HT40): MCS0; ⊠802.11ac (HT40): MCS19; ⊠802.11ac (HT80): MCS0; ⊠802.11ac (HT80): MCS19;) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.



Wifi 5G with UNII Band I

Frequency and Channel list for 802.11a/n(HT20)/ac(VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220		
40	5200	48	5240		

Frequency and Channel list for 802.11n(HT40)/ac(VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190				
46	5230				

Frequency and Channel list for 802.11ac(VHT80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210				

Test Frequency and Channel for 802.11a/n(HT20)/ac(VHT20):

Lowest Frequency		Middle F	requency	Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	40	5200	48	5240

Test Frequency and channel for 802.11n(VHT40)/ac(VHT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	N/A	N/A	46	5230

Test Frequency and channel for 802.11ac(HT80):

Lowest F	Lowest Frequency		Frequency	Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	N/A	N/A	N/A	N/A



Wifi 5G with UNII Band II-A

Frequency and Channel list for 802.11a/n(HT20)/ac(VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300		
56	5280	64	5320		

Frequency and Channel list for 802.11n(VHT40)/ac(VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
54	5270				
62	5310				

Frequency and Channel list for 802.11ac(VHT80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
58	5290				

Test Frequency and Channel for 802.11a/n(HT20)/ac(VHT20):

Lowest Frequency		Middle F	requency	Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	56	5280	64	5320

Test Frequency and channel for 802.11n(HT40)/ac(VHT40):

Lowest Frequency		Middle F	Middle Frequency		st Frequency
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
54	5270	N/A	N/A	62	5310

Test Frequency and channel for 802.11ac(VHT80):

Lowest F	Lowest Frequency		Frequency	Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
58	5290	N/A	N/A	N/A	N/A



Wifi 5G with UNII Band II-C

Frequency and Channel list for 802.11a/n(HT20)/ac(VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	116	5580	132	5660
104	5520	120	5600	136	5680
108	5540	124	5620	140	5700
112	5560	128	5640		

Frequency and Channel list for 802.11n(VHT40)/ac(VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
102	5510	126	5630		
110	5550	134	5670		
118	5590				

Frequency and Channel list for 802.11ac(VHT80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
106	5530				
122	5610				

Test Frequency and Channel for 802.11a/n(HT20)/ac(VHT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	120	5600	140	5700

Test Frequency and channel for 802.11n(VHT40)/ac(VHT40):

Lowest F	requency	Middle F	requency	Highes	st Frequency
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
102	5510	118	5590	134	5670

Test Frequency and channel for 802.11ac(VHT80):

Lowest F	requency	Middle F	Frequency	Highes	st Frequency
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
106	5530	N/A	N/A	122	5610



⊠ Wifi 5G with UNII Band III

Frequency and Channel list for 802.11a/n(HT20)/ac(VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785	165	5825
153	5765	161	5805		

Frequency and Channel list for 802.11n(HT40)/ac(VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755				
159	5795				

Frequency and Channel list for 802.11ac(VHT80):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775				

Test Frequency and Channel for 802.11a/n(HT20)/ac(VHT20):

Lowest F	requency	Middle F	requency	Highes	st Frequency
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785	165	5825

Test Frequency and channel for 802.11n(HT40)/ac(VHT40):

Lowest F	requency	Middle F	Frequency	Highes	st Frequency
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	N/A	N/A	159	5795

Test Frequency and channel for 802.11ac(VHT80):

Lowest F	requency	Middle F	Frequency	Highes	st Frequency
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
155	5775				



5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description	
EMC Lab.	 Accredited by CNAS, 2013.10.29 The certificate is valid until 2016.10.28 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L2291.
	Accredited by TUV Rheinland Shenzhen 2015.4 The Laboratory has been assessed according to the requirements ISO/IEC 17025.
	Accredited by FCC, April 17, 2013 The Certificate Registration Number is 709623.
	Accredited by FCC, July 24, 2013 The Certificate Registration Number is 406365.
	Accredited by Industry Canada, November 29, 2012 The Certificate Registration Number is 4480A.
Name of Firm Site Location	 EMTEK(SHENZHEN) CO., LTD Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China



6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5°C
Humidity	±3%

Measurement Uncertainty for a level of Confidence of 95%



7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

(a) Radiated Emission Test Set-Up, Frequency Below 30MHz










(c) Radiated Emission Test Set-Up, Frequency above 1000MHz






7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.


Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.





7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	Notebook	Lenovo	WB0205140E	N/A	N/A	

Notes:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



8 TEST REQUIREMENTS

8.1 BANDWIDTH MEASUREMENT

8.1.1 Applicable Standard

According to FCC Part 15.407(a)(1) for UNII Band I According to FCC Part 15.407(a)(2) for UNII Band II-A and UNII Band II-C According to FCC Part 15.407(a)(3) for UNII Band III According to FCC Part 15.407(e) for UNII Band III According to 789033 D02 Section II(C) According to 789033 D02 Section II(D)

8.1.2 Conformance Limit

No limit requirement. The minimum 6 dB emission bandwidth of at least 500 KHz for the UNII Band III.

8.1.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.1.4 Test Procedure

Connect the antenna port(s) to the spectrum analyzer input. Using the spectrum analyzer Channel Bandwidth mode, configure the spectrum analyzer as shown below

■ The following procedure shall be used for measuring (26 dB) power bandwidth:

Center Frequency: test Frequency

Set RBW = approximately 1% of the emission bandwidth.

Set the VBW > RBW.

Detector = Peak.

Trace mode = max hold.

X dB Bandwidth: 26 dB

Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until

the RBW/EBW ratio is approximately 1%. ■ Minimum Emission Bandwidth for the UNII Band III

Center Frequency: test Frequency

Set RBW = 100 kHz

Set VBW ≥ 3 · RBW

Detector = Peak

Trace mode = max hold

Sweep = auto couple

X dB Bandwidth: 6 dB

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

The following procedure shall be used for measuring (99 %) power bandwidth:

Set center frequency to the nominal EUT channel center frequency.

Set span = 1.5 times to 5.0 times the OBW.

Set RBW = 1 % to 5 % of the OBW

Set VBW ≥ 3 · RBW

Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.

Use the 99 % power bandwidth function of the instrument (if available).

If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



8.1.5 Test Results

7	-			a mode	-			
Temperature	: 28 ℃		Test Date :		June 23, 2016			
Humidity :	65 %		Test By:		King Ko	ong		
Band	Channel	Channel	26dB	EBW	99% OBW		Limit	Verdict
	Number	Freq. (MHz)	Ant0	Ant1	Ant0	Ant1	(MHz)	veruici
UNII	CH36	5180	21.40	21.51	16.816	16.821	N/A	N/A
Band I	CH40	5200	21.47	21.63	16.774	16.747	N/A	N/A
Danu i	CH48	5240	21.36	21.45	16.783	16.801	N/A	N/A
	CH52	5260	21.33	21.46	16.754	16.778	N/A	N/A
UNII Band II-A	CH56	5280	21.39	21.67	16.793	16.823	N/A	N/A
Danu II-A	CH64	5320	21.47	21.55	16.804	16.787	N/A	N/A
UNII	CH100	5500	21.35	21.50	16.793	16.759	N/A	N/A
Band II-C	CH120	5600	21.57	21.50	16.827	16.840	N/A	N/A
Danu II-C	CH140	5700	21.53	21.44	16.801	16.758	N/A	N/A
UNII	CH149	5745	21.38	21.25	16.789	16.802	N/A	N/A
Band III	CH157	5785	21.52	21.48	16.799	16.784	N/A	N/A
Danu III	CH165	5825	21.35	21.45	16.792	16.805	N/A	N/A
Note: N/A (Not Ap	plicable)							

⊠ 802.11n(VHT20) mode								
Temperature : 28℃			Test Dat	Test Date :		June 23, 2016		
Humidity :	65 %		Test By:		King Ko	ong		
Band	Channel	Channel	26dB	26dB EBW		OBW	Limit	Verdict
	Number	Freq. (MHz)	Ant0	Ant1	Ant0	Ant1	(MHz)	verdict
	CH36	5180	21.61	21.73	17.947	17.896	N/A	N/A
UNII Band I	CH40	5200	21.59	21.57	17.915	17.892	N/A	N/A
Dallu I	CH48	5240	21.80	21.72	17.870	17.918	N/A	N/A
UNII	CH52	5260	21.68	21.76	17.901	17.916	N/A	N/A
Band II-A	CH56	5280	21.64	21.84	17.917	17.904	N/A	N/A
Dallu II-A	CH64	5320	21.71	21.49	17.936	17.906	N/A	N/A
UNII	CH100	5500	21.52	21.76	17.918	17.917	N/A	N/A
Band II-C	CH120	5600	21.71	21.57	17.947	17.926	N/A	N/A
Danu II-C	CH140	5700	21.65	21.76	17.904	17.929	N/A	N/A
UNII	CH149	5745	21.70	21.54	17.851	17.939	N/A	N/A
Band III	CH157	5785	21.66	21.60	17.931	17.957	N/A	N/A
Dariu III	CH165	5825	21.81	21.85	17.924	17.920	N/A	N/A
Note: N/A (Not Ap	plicable)							



⊠ 802.11ac(VHT20) mode								
Temperature : 28℃			Test Date :		June 23, 2016			
Humidity :	65 %		Test By:		King Ko	ong		
Band	Channel	Channel	26dB	3 EBW 99%		99% OBW		
	Number	Freq. (MHz)	Ant0	Ant1	Ant0	Ant1	(MHz)	Verdict
	CH36	5180	21.66	21.79	17.935	17.940	N/A	N/A
UNII Band I	CH40	5200	21.44	21.66	17.921	17.909	N/A	N/A
Danu i	CH48	5240	21.46	21.64	17.923	17.909	N/A	N/A
UNII	CH52	5260	21.69	21.70	17.908	17.896	N/A	N/A
Band II-A	CH56	5280	21.94	21.67	17.931	17.903	N/A	N/A
Dallu II-A	CH64	5320	21.53	21.75	17.876	17.858	N/A	N/A
UNII	CH100	5500	21.68	21.62	17.888	17.911	N/A	N/A
Band II-C	CH120	5600	21.74	21.65	17.925	17.925	N/A	N/A
Danu II-C	CH140	5700	21.57	21.66	17.928	17.934	N/A	N/A
UNII	CH149	5745	21.56	21.67	17.915	17.918	N/A	N/A
Band III	CH157	5785	21.88	21.54	17.894	17.900	N/A	N/A
Dariu III	CH165	5825	21.74	21.62	17.920	17.915	N/A	N/A
Note: N/A (Not Ap	plicable)							

🛛 802.11n(VHT40) mode								
Temperature : 28℃		Test Date :		June 23, 2016				
Humidity :	65 %		Test By:		King Ko	ong		
Band	Channel	Channel	26dB	26dB EBW		OBW	Limit	Verdict
	Number	Freq. (MHz)	Ant0	Ant1	Ant0	Ant1	(MHz)	verdict
UNII	CH38	5190	40.28	40.28	36.356	36.323	N/A	N/A
Band I	CH46	5230	40.13	40.12	36.346	36.351	N/A	N/A
UNII	CH54	5270	40.01	39.93	36.348	36.341	N/A	N/A
Band II-A	CH62	5310	40.04	40.14	36.338	36.323	N/A	N/A
UNII	CH102	5510	40.10	39.97	36.339	36.314	N/A	N/A
Band II-C	CH118	5590	40.09	40.14	36.347	36.353	N/A	N/A
Danu II-C	CH134	5670	39.82	40.27	36.334	36.374	N/A	N/A
UNII	CH151	5755	39.65	39.95	36.299	36.308	N/A	N/A
Band III	CH159	5795	40.20	40.11	36.375	36.366	N/A	N/A
Note:								
N/A (Not Ap	plicable)							

Temperature :28℃Humidity :65 %		⊠ 802.11ac(VHT40) mo Test Date : Test By:			de June 23, 2016 King Kong			
Band	Channel	Channel	26dB	EBW	99%	99% OBW		Verdict
	Number	Freq. (MHz)	Ant0	Ant1	Ant0	Ant1	(MHz)	Vertice
UNII	CH38	5190	40.19	40.05	36.391	36.388	N/A	N/A
Band I	CH46	5230	40.26	40.09	36.353	36.336	N/A	N/A
UNII	CH54	5270	39.62	39.91	36.393	36.365	N/A	N/A
Band II-A	CH62	5310	39.93	39.84	36.324	36.329	N/A	N/A
UNII	CH102	5510	39.70	40.28	36.358	36.346	N/A	N/A
Band II-C	CH118	5590	40.05	40.03	36.322	36.345	N/A	N/A
Danu II-C	CH134	5670	39.93	40.01	36.325	36.360	N/A	N/A
UNII	CH151	5755	40.24	40.18	36.343	36.370	N/A	N/A
Band III	CH159	5795	40.03	40.14	36.325	36.365	N/A	N/A
Note: N/A (Not Ap	plicable)							



Temperature :28 ℃Humidity :65 %		⊠ 802.11ac(VHT80) mo Test Date : Test By:			de June 23, 2016 King Kong			
Band	Channel	Channel	26dB	EBW	99% OBW		Limit	Verdict
	Number	Freq. (MHz)	Ant0	Ant1	Ant0	Ant1	(MHz)	Voraiot
UNII Band I	CH42	5210	82.25	81.93	75.860	75.900	N/A	N/A
UNII Band II-A	CH58	5290	81.68	81.65	75.840	75.949	N/A	N/A
UNII	CH106	5530	82.01	81.56	75.830	75.709	N/A	N/A
Band II-C	CH122	5610	81.85	81.94	75.748	75.847	N/A	N/A
UNII Band III	CH155	5775	81.51	82.18	75.730	75.805	N/A	N/A
Note: N/A (Not Ap	plicable)							

- <i>i</i>			UNII Band III			
Temperature			Test Date :	June 23, 2016		
Humidity :	65 %		Test By:	King Kong		
Operation	Channel	Channel	6dB	6dB EBW		
Mode	Number	Freq. (MHz)	Ant0	Ant1	(MHz)	Verdict
	CH149	5745	16.39	16.42	500	PASS
802.11a	CH157	5785	16.41	16.41	500	PASS
	CH165	5825	16.40	16.41	500	PASS
802.11n	CH149	5745	17.62	17.63	500	PASS
(VHT20)	CH157	5785	17.63	17.63	500	PASS
(11120)	CH165	5825	17.63	17.64	500	PASS
802.11ac	CH149	5745	17.62	17.61	500	PASS
(VHT20)	CH157	5785	17.61	17.62	500	PASS
(11120)	CH165	5825	17.61	17.62	500	PASS
802.11n	CH151	5755	36.37	36.38	500	PASS
(VHT40)	CH159	5795	36.36	36.42	500	PASS
802.11ac	CH151	5755	36.41	36.42	500	PASS
(VHT40)	CH159	5795	36.34	36.40	500	PASS
802.11ac (VHT80)	CH155	5775	75.52	75.83	500	PASS
Note: N/A (Not Ap	plicable)					




 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11a
 Frequency(MHz)
 5180

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11a
 Frequency(MHz)
 5200

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0









 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11a
 Frequency(MHz)
 5240

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0







Emission Bandwidth&99% Occupied BandwidthUNII Band II-ATest Model802.11aFrequency(MHz)5260Ant0ContemporationContemporation







Emission Bandwidth&99% Occupied BandwidthUNII Band II-ATest Model802.11aFrequency(MHz)5280Ant0Ant0Ant0Ant0Ant0







Emission Bandwidth&99% Occupied BandwidthUNII Band II-ATest Model802.11aFrequency(MHz)5320Ant0







Emission Bandwidth&99% Occupied Bandwidth UNII Band II-C Test Model 802.11a Frequency(MHz) 5500 Ant0







Emission Bandwidth&99% Occupied BandwidthUNII Band II-CTest Model802.11aFrequency(MHz)5600Ant0








Emission Bandwidth&99% Occupied BandwidthUNII Band II-CTest Model802.11aFrequency(MHz)5700Ant0







Emission Bandwidth&99% Occupied BandwidthUNII Band IIITest Model802.11aFrequency(MHz)5745Ant0







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band III

 Test Model
 802.11a
 Frequency(MHz)
 5785

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0









 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band III

 Test Model
 802.11a
 Frequency(MHz)
 5825

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0








 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5180

 Ant0
 Ant0
 Ant0
 Ant0







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5200

 Ant0
 5200
 5200







Emission Bandwidth&99% Occupied Bandwidth UNII Band I Test Model 802.11n(VHT20) mode Frequency(MHz) 5240 Ant0








 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band II-A

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5260

 Ant0
 5260
 5260







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band II-A

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5280

 Ant0
 5280
 5280







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band II-A

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5320


 Ant0
 5320
 5320







Emission Bandwidth&99% Occupied Bandwidth UNII Band II-C Test Model 802.11n(VHT20) mode Frequency(MHz) 5500 Ant0







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band II-C

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5600

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0








 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band II-C

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5700

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0








 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band III

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5745

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0








 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band III

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5785

 Ant0
 5785
 5785









 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band III

 Test Model
 802.11n(VHT20) mode
 Frequency(MHz)
 5825

 Ant0
 5825
 5825







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11ac(VHT20) mode
 Frequency(MHz)
 5180

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11ac(VHT20) mode
 Frequency(MHz)
 5200

 Ant0
 5200
 5200







 Emission Bandwidth&99% Occupied Bandwidth
 UNII Band I

 Test Model
 802.11ac(VHT20) mode
 Frequency(MHz)
 5240

 Ant0
 Ant0
 Ant0
 Ant0
 Ant0



