

Test Laboratory: Compliance Certification Services Inc.

## **D2450V2 SN-728 Body**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:728**

Communication System: CW2450; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW,d=10mm/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 14.1 mW/g

**Pin=250mW,d=10mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.5 V/m; Power Drift = -0.025 dB

Peak SAR (extrapolated) = 27.0 W/kg



**SAR(1 g) = 13.0 mW/g; SAR(10 g) = 6.06 mW/g**

Maximum value of SAR (measured) = 19.1 mW/g

**Pin=250mW,d=10mm/Z Scan (1x1x21):** Measurement grid: dx=20mm,

dy=20mm, dz=5mm

Maximum value of SAR (measured) = 19.8 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **D2450V2 SN-728 Body**

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:728**

Communication System: CW2450; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Pin=250mW,d=10mm/Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 10.2 mW/g

**Pin=250mW,d=10mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.6 V/m; Power Drift = -0.068 dB



Peak SAR (extrapolated) = 30.5 W/kg

**SAR(1 g) = 13.3 mW/g; SAR(10 g) = 6.19 mW/g**

Maximum value of SAR (measured) = 15.9 mW/g

**Pin=250mW,d=10mm/Z Scan (1x1x21):** Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 16.1 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Down mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.278 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 6.95 V/m; Power Drift = -0.048 dB



Peak SAR (extrapolated) = 0.582 W/kg

**SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.139 mW/g**

Maximum value of SAR (measured) = 0.404 mW/g

**High CH Rate 1M/Z Scan (1x1x11):** Measurement grid: dx=20mm, dy=20mm, dz=10mm

Maximum value of SAR (measured) = 0.413 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Down mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**10mm High CH Rate 1M/Area Scan (14x10x1):** Measurement grid:

$dx=15$ mm,  $dy=15$ mm

Maximum value of SAR (measured) = 0.095 mW/g

**10mm High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement


grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=3$ mm

Reference Value = 3.03 V/m; Power Drift = -0.082 dB

Peak SAR (extrapolated) = 0.266 W/kg

**SAR(1 g) = 0.125 mW/g; SAR(10 g) = 0.063 mW/g**

Maximum value of SAR (measured) = 0.133 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Down mode WiQueen-U23n 180

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (5x20x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.315 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 6.35 V/m; Power Drift = -0.068 dB

Peak SAR (extrapolated) = 0.478 W/kg

**SAR(1 g) = 0.236 mW/g; SAR(10 g) = 0.115 mW/g**

Maximum value of SAR (measured) = 0.332 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Down mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.309 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 5.16 V/m; Power Drift = -0.093 dB

Peak SAR (extrapolated) = 0.540 W/kg

**SAR(1 g) = 0.278 mW/g; SAR(10 g) = 0.136 mW/g**

Maximum value of SAR (measured) = 0.382 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211b Horizontal Down mode WiQueen-U23n up 90**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (5x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.038 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 2.98 V/m; Power Drift = -0.103 dB

Peak SAR (extrapolated) = 0.061 W/kg

**SAR(1 g) = 0.032 mW/g; SAR(10 g) = 0.020 mW/g**

Maximum value of SAR (measured) = 0.043 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Down mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (7x7x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.013 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 1.69 V/m; Power Drift = -0.132 dB  
Peak SAR (extrapolated) = 0.019 W/kg  
**SAR(1 g) = 0.010 mW/g; SAR(10 g) = 0.00614 mW/g**  
Maximum value of SAR (measured) = 0.013 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 1.69 V/m; Power Drift = -0.132 dB  
Peak SAR (extrapolated) = 0.019 W/kg  
**SAR(1 g) = 0.010 mW/g; SAR(10 g) = 0.0062 mW/g**  
Maximum value of SAR (measured) = 0.013 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Down mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.160 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 5.15 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.325 W/kg

**SAR(1 g) = 0.165 mW/g; SAR(10 g) = 0.082 mW/g**

Maximum value of SAR (measured) = 0.228 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Down mode WiQueen-U23n 180

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (5x20x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.177 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 4.80 V/m; Power Drift = -0.048 dB

Peak SAR (extrapolated) = 0.271 W/kg

**SAR(1 g) = 0.135 mW/g; SAR(10 g) = 0.067 mW/g**

Maximum value of SAR (measured) = 0.184 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Down mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.174 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 4.02 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 0.310 W/kg

**SAR(1 g) = 0.159 mW/g; SAR(10 g) = 0.079 mW/g**

Maximum value of SAR (measured) = 0.217 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Down mode WiQueen-U23n up 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (5x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.024 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.57 V/m; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 0.050 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.027 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Down mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (7x7x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.008 mW/g

**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 1.86 V/m; Power Drift = -0.122 dB  
Peak SAR (extrapolated) = 0.024 W/kg  
**SAR(1 g) = 0.00677 mW/g; SAR(10 g) = 0.00361 mW/g**  
Maximum value of SAR (measured) = 0.010 mW/g

**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 1.86 V/m; Power Drift = -0.122 dB  
Peak SAR (extrapolated) = 0.012 W/kg  
**SAR(1 g) = 0.00498 mW/g; SAR(10 g) = 0.0025 mW/g**  
Maximum value of SAR (measured) = 0.010 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.161 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.57 V/m; Power Drift = -0.085 dB

Peak SAR (extrapolated) = 0.237 W/kg

**SAR(1 g) = 0.121 mW/g; SAR(10 g) = 0.061 mW/g**

Maximum value of SAR (measured) = 0.167 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n 180 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (5x20x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.131 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.77 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.204 W/kg

**SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.052 mW/g**

Maximum value of SAR (measured) = 0.140 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n 270 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.135 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.79 V/m; Power Drift = -0.086 dB

Peak SAR (extrapolated) = 0.240 W/kg

**SAR(1 g) = 0.125 mW/g; SAR(10 g) = 0.063 mW/g**

Maximum value of SAR (measured) = 0.170 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Down mode WiQueen-U23n up 90 HT20

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (6x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.012 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.08 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 0.028 W/kg

**SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00898 mW/g**

Maximum value of SAR (measured) = 0.013 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.08 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 0.019 W/kg

**SAR(1 g) = 0.010 mW/g; SAR(10 g) = 0.00914 mW/g**

Maximum value of SAR (measured) = 0.013 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n down 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (8x8x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.007 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.57 V/m; Power Drift = -0.046 dB

Peak SAR (extrapolated) = 0.025 W/kg

**SAR(1 g) = 0.00508 mW/g; SAR(10 g) = 0.00313 mW/g**

Maximum value of SAR (measured) = 0.008 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n 90 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.187 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.62 V/m; Power Drift = -0.087 dB

Peak SAR (extrapolated) = 0.275 W/kg

**SAR(1 g) = 0.140 mW/g; SAR(10 g) = 0.070 mW/g**

Maximum value of SAR (measured) = 0.192 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n 180 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (5x20x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.125 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.44 V/m; Power Drift = -0.080 dB

Peak SAR (extrapolated) = 0.182 W/kg

**SAR(1 g) = 0.094 mW/g; SAR(10 g) = 0.048 mW/g**

Maximum value of SAR (measured) = 0.127 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n 270 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.163 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.03 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 0.288 W/kg

**SAR(1 g) = 0.149 mW/g; SAR(10 g) = 0.075 mW/g**

Maximum value of SAR (measured) = 0.202 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Down mode WiQueen-U23n up 90 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (8x8x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.011 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.07 V/m; Power Drift = -0.067 dB

Peak SAR (extrapolated) = 0.017 W/kg

**SAR(1 g) = 0.00906 mW/g; SAR(10 g) = 0.00855 mW/g**

Maximum value of SAR (measured) = 0.012 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Down mode WiQueen-U23n down 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (8x8x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.007 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.58 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 0.022 W/kg

**SAR(1 g) = 0.00498 mW/g; SAR(10 g) = 0.00287 mW/g**

Maximum value of SAR (measured) = 0.007 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.58 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 0.017 W/kg

**SAR(1 g) = 0.00544 mW/g; SAR(10 g) = 0.00272 mW/g**

Maximum value of SAR (measured) = 0.007 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Up mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.136 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.75 V/m; Power Drift = -0.112 dB

Peak SAR (extrapolated) = 0.193 W/kg

**SAR(1 g) = 0.097 mW/g; SAR(10 g) = 0.047 mW/g**

Maximum value of SAR (measured) = 0.133 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Up mode WiQueen-U23n 180

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.128 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 3.54 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 0.186 W/kg

**SAR(1 g) = 0.092 mW/g; SAR(10 g) = 0.044 mW/g**

Maximum value of SAR (measured) = 0.129 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Up mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.121 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.54 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 0.195 W/kg

**SAR(1 g) = 0.098 mW/g; SAR(10 g) = 0.047 mW/g**

Maximum value of SAR (measured) = 0.135 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Up mode WiQueen-U23n up 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan 2 (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.027 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.56 V/m; Power Drift = -0.150 dB

Peak SAR (extrapolated) = 0.042 W/kg

**SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.0098 mW/g**

Maximum value of SAR (measured) = 0.029 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.56 V/m; Power Drift = -0.150 dB

Peak SAR (extrapolated) = 0.034 W/kg

**SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.00842 mW/g**

Maximum value of SAR (measured) = 0.025 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Horizontal Up mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (9x7x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.024 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 3.26 V/m; Power Drift = -0.099 dB  
Peak SAR (extrapolated) = 0.027 W/kg  
**SAR(1 g) = 0.025 mW/g; SAR(10 g) = 0.023 mW/g**  
Maximum value of SAR (measured) = 0.027 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 3.26 V/m; Power Drift = -0.099 dB  
Peak SAR (extrapolated) = 0.025 W/kg  
**SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.021 mW/g**  
Maximum value of SAR (measured) = 0.025 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.060 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.86 V/m; Power Drift = -0.134 dB

Peak SAR (extrapolated) = 0.111 W/kg

**SAR(1 g) = 0.055 mW/g; SAR(10 g) = 0.026 mW/g**

Maximum value of SAR (measured) = 0.076 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n 180

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.074 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 2.60 V/m; Power Drift = -0.121 dB

Peak SAR (extrapolated) = 0.109 W/kg

**SAR(1 g) = 0.054 mW/g; SAR(10 g) = 0.026 mW/g**

Maximum value of SAR (measured) = 0.074 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.068 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.63 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 0.108 W/kg

**SAR(1 g) = 0.058 mW/g; SAR(10 g) = 0.031 mW/g**

Maximum value of SAR (measured) = 0.077 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n up 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.014 mW/g

**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.25 V/m; Power Drift = -0.097 dB

Peak SAR (extrapolated) = 0.018 W/kg

**SAR(1 g) = 0.00907 mW/g; SAR(10 g) = 0.00368 mW/g**

Maximum value of SAR (measured) = 0.013 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.25 V/m; Power Drift = -0.097 dB

Peak SAR (extrapolated) = 0.024 W/kg

**SAR(1 g) = 0.013 mW/g; SAR(10 g) = 0.00564 mW/g**

Maximum value of SAR (measured) = 0.018 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 51.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (9x7x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.020 mW/g

**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.18 V/m; Power Drift = -0.145 dB

Peak SAR (extrapolated) = 0.022 W/kg

**SAR(1 g) = 0.019 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.022 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.18 V/m; Power Drift = -0.145 dB

Peak SAR (extrapolated) = 0.022 W/kg

**SAR(1 g) = 0.019 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.022 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Up mode WiQueen-U23n 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.042 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.929 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 0.076 W/kg

**SAR(1 g) = 0.038 mW/g; SAR(10 g) = 0.018 mW/g**

Maximum value of SAR (measured) = 0.052 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Up mode WiQueen-U23n 180 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.050 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.80 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.081 W/kg

**SAR(1 g) = 0.040 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.056 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n 270 HT20

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.048 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.31 V/m; Power Drift = -0.039 dB

Peak SAR (extrapolated) = 0.074 W/kg

**SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.022 mW/g**

Maximum value of SAR (measured) = 0.051 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Up mode WiQueen-U23n up 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.017 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.57 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 0.018 W/kg

**SAR(1 g) = 0.0146 mW/g; SAR(10 g) = 0.0057 mW/g**

Maximum value of SAR (measured) = 0.016 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Up mode WiQueen-U23n down 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (9x7x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.021 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.90 V/m; Power Drift = -0.082 dB

Peak SAR (extrapolated) = 0.023 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.023 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.042 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.13 V/m; Power Drift = -0.027 dB

Peak SAR (extrapolated) = 0.077 W/kg

**SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.054 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Up mode WiQueen-U23n 180 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.057 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.73 V/m; Power Drift = -0.131 dB

Peak SAR (extrapolated) = 0.084 W/kg

**SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.021 mW/g**

Maximum value of SAR (measured) = 0.060 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **80211g Horizontal Up mode WiQueen-U23n 270 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.053 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.99 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.081 W/kg

**SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.024 mW/g**

Maximum value of SAR (measured) = 0.060 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n up 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.015 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.32 V/m; Power Drift = -0.146 dB

Peak SAR (extrapolated) = 0.018 W/kg

**SAR(1 g) = 0.0134 mW/g; SAR(10 g) = 0.0049 mW/g**

Maximum value of SAR (measured) = 0.015 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Horizontal Up mode WiQueen-U23n down 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.96$  mho/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.6 deg C; Liquid Temperature: 23.6 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (9x7x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.021 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.11 V/m; Power Drift = -0.125 dB

Peak SAR (extrapolated) = 0.024 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.020 mW/g**

Maximum value of SAR (measured) = 0.023 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.11 V/m; Power Drift = -0.125 dB

Peak SAR (extrapolated) = 0.024 W/kg

**SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.020 mW/g**

Maximum value of SAR (measured) = 0.024 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Front mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.102 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.34 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.167 W/kg

**SAR(1 g) = 0.085 mW/g; SAR(10 g) = 0.043 mW/g**

Maximum value of SAR (measured) = 0.114 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **80211b Vertical Front mode WiQueen-U23n 180**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.058 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 1.35 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 0.091 W/kg

**SAR(1 g) = 0.045 mW/g; SAR(10 g) = 0.023 mW/g**

Maximum value of SAR (measured) = 0.062 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Front mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.045 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.20 V/m; Power Drift = -0.117 dB

Peak SAR (extrapolated) = 0.070 W/kg

**SAR(1 g) = 0.036 mW/g; SAR(10 g) = 0.018 mW/g**

Maximum value of SAR (measured) = 0.049 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Front mode WiQueen-U23n up 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.020 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.52 V/m; Power Drift = -0.072 dB

Peak SAR (extrapolated) = 0.033 W/kg

**SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00784 mW/g**

Maximum value of SAR (measured) = 0.022 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.52 V/m; Power Drift = -0.072 dB

Peak SAR (extrapolated) = 0.024 W/kg

**SAR(1 g) = 0.012 mW/g; SAR(10 g) = 0.00586 mW/g**

Maximum value of SAR (measured) = 0.018 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Front mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.007 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.17 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.026 W/kg

**SAR(1 g) = 0.00542 mW/g; SAR(10 g) = 0.00235 mW/g**

Maximum value of SAR (measured) = 0.008 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.17 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.011 W/kg

**SAR(1 g) = 0.00518 mW/g; SAR(10 g) = 0.00253 mW/g**

Maximum value of SAR (measured) = 0.008 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.062 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.46 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.086 W/kg

**SAR(1 g) = 0.046 mW/g; SAR(10 g) = 0.024 mW/g**

Maximum value of SAR (measured) = 0.063 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n 180

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.034 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 1.22 V/m; Power Drift = -0.100 dB

Peak SAR (extrapolated) = 0.053 W/kg

**SAR(1 g) = 0.026 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.037 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.026 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.726 V/m; Power Drift = -0.075 dB

Peak SAR (extrapolated) = 0.037 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.011 mW/g**

Maximum value of SAR (measured) = 0.028 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n up 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg


DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.010 mW/g

**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 1.65 V/m; Power Drift = -0.115 dB  
Peak SAR (extrapolated) = 0.051 W/kg  
**SAR(1 g) = 0.00814 mW/g; SAR(10 g) = 0.00351 mW/g**  
Maximum value of SAR (measured) = 0.012 mW/g

**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm  
Reference Value = 1.65 V/m; Power Drift = -0.115 dB  
Peak SAR (extrapolated) = 0.014 W/kg  
**SAR(1 g) = 0.00594 mW/g; SAR(10 g) = 0.0025 mW/g**  
Maximum value of SAR (measured) = 0.009 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (8x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.005 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.936 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.012 W/kg

**SAR(1 g) = 0.00272 mW/g; SAR(10 g) = 0.00113 mW/g**

Maximum value of SAR (measured) = 0.005 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.936 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.014 W/kg

**SAR(1 g) = 0.00203 mW/g; SAR(10 g) = 0.000732 mW/g**

Maximum value of SAR (measured) = 0.005 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Front mode WiQueen-U23n 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.015 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.732 V/m; Power Drift = -0.156 dB

Peak SAR (extrapolated) = 0.023 W/kg

**SAR(1 g) = 0.012 mW/g; SAR(10 g) = 0.00631 mW/g**

Maximum value of SAR (measured) = 0.016 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n 180 HT20

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.055 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.43 V/m; Power Drift = -0.110 dB

Peak SAR (extrapolated) = 0.087 W/kg

**SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.022 mW/g**

Maximum value of SAR (measured) = 0.059 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n 270 HT20

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.020 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.574 V/m; Power Drift = -0.135 dB

Peak SAR (extrapolated) = 0.031 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.0074 mW/g**

Maximum value of SAR (measured) = 0.020 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Front mode WiQueen-U23n up 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.002 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.688 V/m; Power Drift = -0.151 dB

Peak SAR (extrapolated) = 0.005 W/kg

**SAR(1 g) = 0.00195 mW/g; SAR(10 g) = 0.000232 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n down 90 HT20

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (8x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.002 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.200 V/m; Power Drift = -0.133 dB

Peak SAR (extrapolated) = 0.009 W/kg

**SAR(1 g) = 0.00104 mW/g; SAR(10 g) = 0.00083 mW/g**

Maximum value of SAR (measured) = 0.002 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.200 V/m; Power Drift = -0.133 dB

Peak SAR (extrapolated) = 0.006 W/kg

**SAR(1 g) = 0.000817 mW/g; SAR(10 g) = 0.000425 mW/g**

Maximum value of SAR (measured) = 0.002 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.016 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.12 V/m; Power Drift = -0.126 dB

Peak SAR (extrapolated) = 0.024 W/kg

**SAR(1 g) = 0.013 mW/g; SAR(10 g) = 0.00673 mW/g**

Maximum value of SAR (measured) = 0.017 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Front mode WiQueen-U23n 180 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.034 mW/g


**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.896 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.055 W/kg

**SAR(1 g) = 0.027 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.037 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n 270 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.025 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.917 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 0.044 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.010 mW/g**

Maximum value of SAR (measured) = 0.028 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n up 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.002 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.792 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.005 W/kg

**SAR(1 g) = 0.00109 mW/g; SAR(10 g) = 0.000803 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.792 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.005 W/kg

**SAR(1 g) = 0.000882 mW/g; SAR(10 g) = 0.000495 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Front mode WiQueen-U23n up 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (7x11x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.002 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.792 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.005 W/kg

**SAR(1 g) = 0.00089 mW/g; SAR(10 g) = 0.000303 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.792 V/m; Power Drift = -0.132 dB

Peak SAR (extrapolated) = 0.005 W/kg

**SAR(1 g) = 0.000482 mW/g; SAR(10 g) = 9.2e-005 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Back mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.147 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.95 V/m; Power Drift = -0.119 dB

Peak SAR (extrapolated) = 0.243 W/kg

**SAR(1 g) = 0.128 mW/g; SAR(10 g) = 0.066 mW/g**

Maximum value of SAR (measured) = 0.173 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Back mode WiQueen-U23n 180

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.058 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 3.77 V/m; Power Drift = -0.078 dB

Peak SAR (extrapolated) = 0.089 W/kg

**SAR(1 g) = 0.047 mW/g; SAR(10 g) = 0.024 mW/g**

Maximum value of SAR (measured) = 0.064 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Back mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.086 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.97 V/m; Power Drift = 0.082 dB

Peak SAR (extrapolated) = 0.126 W/kg

**SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.033 mW/g**

Maximum value of SAR (measured) = 0.088 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Back mode WiQueen-U23n up 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.030 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 1.75 V/m; Power Drift = -0.069 dB

Peak SAR (extrapolated) = 0.044 W/kg

**SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.011 mW/g**

Maximum value of SAR (measured) = 0.030 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211b Vertical Back mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11b WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 1M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.007 mW/g

**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.639 V/m; Power Drift = -0.089 dB

Peak SAR (extrapolated) = 0.011 W/kg

**SAR(1 g) = 0.00542 mW/g; SAR(10 g) = 0.00246 mW/g**

Maximum value of SAR (measured) = 0.008 mW/g


**High CH Rate 1M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.639 V/m; Power Drift = -0.089 dB

Peak SAR (extrapolated) = 0.031 W/kg

**SAR(1 g) = 0.00345 mW/g; SAR(10 g) = 0.000969 mW/g**

Maximum value of SAR (measured) = 0.006 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.082 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.90 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 0.140 W/kg

**SAR(1 g) = 0.073 mW/g; SAR(10 g) = 0.037 mW/g**

Maximum value of SAR (measured) = 0.097 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n 180

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.036 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 2.73 V/m; Power Drift = -0.097 dB

Peak SAR (extrapolated) = 0.053 W/kg

**SAR(1 g) = 0.027 mW/g; SAR(10 g) = 0.014 mW/g**

Maximum value of SAR (measured) = 0.037 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n 270

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.048 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.31 V/m; Power Drift = -0.014 dB

Peak SAR (extrapolated) = 0.071 W/kg

**SAR(1 g) = 0.036 mW/g; SAR(10 g) = 0.018 mW/g**

Maximum value of SAR (measured) = 0.049 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n up 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.019 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm,  
dy=5mm, dz=3mm

Reference Value = 0.940 V/m; Power Drift = -0.148 dB

Peak SAR (extrapolated) = 0.032 W/kg

**SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00626 mW/g**

Maximum value of SAR (measured) = 0.020 mW/g





Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n down 90

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 50.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**High CH Rate 6M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.005 mW/g

**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.585 V/m; Power Drift = -0.099 dB

Peak SAR (extrapolated) = 0.013 W/kg

**SAR(1 g) = 0.00277 mW/g; SAR(10 g) = 0.00108 mW/g**

Maximum value of SAR (measured) = 0.004 mW/g


**High CH Rate 6M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.585 V/m; Power Drift = -0.099 dB

Peak SAR (extrapolated) = 0.008 W/kg

**SAR(1 g) = 0.00225 mW/g; SAR(10 g) = 0.000778 mW/g**

Maximum value of SAR (measured) = 0.004 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n 90 HT20

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.061 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.15 V/m; Power Drift = -0.089 dB

Peak SAR (extrapolated) = 0.100 W/kg

**SAR(1 g) = 0.054 mW/g; SAR(10 g) = 0.028 mW/g**

Maximum value of SAR (measured) = 0.072 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Back mode WiQueen-U23n 180 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.056 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.09 V/m; Power Drift = -0.077 dB

Peak SAR (extrapolated) = 0.082 W/kg

**SAR(1 g) = 0.043 mW/g; SAR(10 g) = 0.022 mW/g**

Maximum value of SAR (measured) = 0.059 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Back mode WiQueen-U23n 270 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.034 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 1.75 V/m; Power Drift = -0.112 dB

Peak SAR (extrapolated) = 0.054 W/kg

**SAR(1 g) = 0.027 mW/g; SAR(10 g) = 0.013 mW/g**

Maximum value of SAR (measured) = 0.036 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Back mode WiQueen-U23n up 90 HT20**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

### **DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.009 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.488 V/m; Power Drift = -0.135 dB

Peak SAR (extrapolated) = 0.014 W/kg

**SAR(1 g) = 0.00584 mW/g; SAR(10 g) = 0.00235 mW/g**

Maximum value of SAR (measured) = 0.009 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n down 90 HT20

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT20; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 6.5M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.002 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.467 V/m; Power Drift = -0.036 dB

Peak SAR (extrapolated) = 0.009 W/kg

**SAR(1 g) = 0.00108 mW/g; SAR(10 g) = 0.000474 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g

**Middle CH Rate 6.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.467 V/m; Power Drift = -0.036 dB

Peak SAR (extrapolated) = 0.010 W/kg

**SAR(1 g) = 0.000823 mW/g; SAR(10 g) = 0.000309 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Back mode WiQueen-U23n 90 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.075 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.29 V/m; Power Drift = -0.035 dB

Peak SAR (extrapolated) = 0.126 W/kg

**SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.033 mW/g**

Maximum value of SAR (measured) = 0.088 mW/g



Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Back mode WiQueen-U23n 180 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (5x18x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.067 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 3.08 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 0.095 W/kg

**SAR(1 g) = 0.050 mW/g; SAR(10 g) = 0.025 mW/g**

Maximum value of SAR (measured) = 0.067 mW/g





Test Laboratory: Compliance Certification Services Inc.

## **80211g Vertical Back mode WiQueen-U23n 270 HT40**

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (14x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.043 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=3mm

Reference Value = 2.03 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 0.065 W/kg

**SAR(1 g) = 0.033 mW/g; SAR(10 g) = 0.016 mW/g**

Maximum value of SAR (measured) = 0.045 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n up 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.009 mW/g


**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.539 V/m; Power Drift = -0.117 dB

Peak SAR (extrapolated) = 0.013 W/kg

**SAR(1 g) = 0.00623 mW/g; SAR(10 g) = 0.00272 mW/g**

Maximum value of SAR (measured) = 0.009 mW/g



Test Laboratory: Compliance Certification Services Inc.

## 80211g Vertical Back mode WiQueen-U23n down 90 HT40

**DUT: WiQueen-U23n; Type: 802.11n WLAN USB Adapter; Serial: N/A**

Communication System: IEEE 802.11g WLAN HT40; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 50.4$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Air Temperature: 24.4 deg C; Liquid Temperature: 23.4 deg C

Area Scan Find Secondary Maximum Within 2dB and with a peak SAR value greater than 0.0012W/kg

DASY4 Configuration:

- Probe: EX3DV4 - SN3554; ConvF(5.93, 5.93, 5.93);
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn558; Calibrated: 9/19/2008
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA; Serial: SN: 1052
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Middle CH Rate 13.5M/Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.003 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 0:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.361 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 0.011 W/kg

**SAR(1 g) = 0.000953 mW/g; SAR(10 g) = 0.000303 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g

**Middle CH Rate 13.5M/Zoom Scan (7x7x9)/Cube 1:** Measurement grid:

dx=5mm, dy=5mm, dz=3mm

Reference Value = 0.361 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 0.006 W/kg

**SAR(1 g) = 0.000366 mW/g; SAR(10 g) = 0.000104 mW/g**

Maximum value of SAR (measured) = 0.003 mW/g

