

FCC Test Report

Report No.: RF150409C11A

FCC ID: VZ9150002

Test Model: EAP330/OWL630

Received Date: Sep. 15, 2017

Test Date: Sep. 17, 2017 ~ Oct. 06, 2017

Issued Date: Oct. 17, 2017

Applicant: 4IPNET, INC.

Address: 5F., NO.367, FUXING N. RD., SONGSHAN DIST., TAIPEI CITY 105,
TAIWAN (R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results.....	6
2.1 Measurement Uncertainty.....	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes.....	8
3.2.1 Test Mode Applicability and Tested Channel Detail.....	9
3.3 Duty Cycle of Test Signal	11
3.4 Description of Support Units	15
3.4.1 Configuration of System under Test	15
3.5 General Description of Applied Standards.....	16
4 Test Types and Results	17
4.1 Radiated Emission and Bandedge Measurement	17
4.1.1 Limits of Radiated Emission and Bandedge Measurement	17
4.1.2 Test Instruments	18
4.1.3 Test Procedures.....	20
4.1.4 Deviation from Test Standard	20
4.1.5 Test Set Up	21
4.1.6 EUT Operating Conditions.....	22
4.1.7 Test Results	23
4.2 Conducted Emission Measurement.....	49
4.2.1 Limits of Conducted Emission Measurement	49
4.2.2 Test Instruments	49
4.2.3 Test Procedures.....	50
4.2.4 Deviation from Test Standard	50
4.2.5 Test Setup.....	50
4.2.6 EUT Operating Conditions.....	50
4.2.7 Test Results	51
4.3 6 dB Bandwidth Measurement.....	55
4.3.1 Limits of 6 dB Bandwidth Measurement.....	55
4.3.2 Test Setup.....	55
4.3.3 Test Instruments	55
4.3.4 Test Procedure	55
4.3.5 Deviation from Test Standard	55
4.3.6 EUT Operating Conditions.....	55
4.3.7 Test Result	56
4.4 Occupied Bandwidth Measurement.....	62
4.4.1 Test Setup.....	62
4.4.2 Test Instruments	62
4.4.3 Test Procedure	62
4.4.4 Deviation from Test Standard	62
4.4.5 EUT Operating Conditions.....	62
4.4.6 Test Results	63
4.5 Conducted Output Power Measurement	69
4.5.1 Limits of Conducted Output Power Measurement.....	69
4.5.2 Test Setup.....	69
4.5.3 Test Instruments	69
4.5.4 Test Procedures.....	69
4.5.5 Deviation from Test Standard	69
4.5.6 EUT Operating Conditions.....	69
4.5.7 Test Results	70

4.6 Power Spectral Density Measurement	74
4.6.1 Limits of Power Spectral Density Measurement.....	74
4.6.2 Test Setup.....	74
4.6.3 Test Instruments	74
4.6.4 Test Procedure	74
4.6.5 Deviation from Test Standard	74
4.6.6 EUT Operating Condition	74
4.6.7 Test Results	75
4.7 Conducted Out of Band Emission Measurement	83
4.7.1 Limits of Conducted Out of Band Emission Measurement.....	83
4.7.2 Test Setup.....	83
4.7.3 Test Instruments	83
4.7.4 Test Procedure	83
4.7.5 Deviation from Test Standard	83
4.7.6 EUT Operating Condition	83
4.7.7 Test Results	84
5 Pictures of Test Arrangements.....	140
Appendix – Information on the Testing Laboratories	141

Release Control Record

Issue No.	Description	Date Issued
RF150409C11A	Original Release	Oct. 17, 2017

1 Certificate of Conformity

Product: Enterprise Access Point

Brand: 4ipnet

Test Model: EAP330/OWL630

Sample Status: Production Unit

Applicant: 4IPNET, INC.


Test Date: Sep. 17, 2017 ~ Oct. 06, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



, **Date:**

Oct. 17, 2017

Rona Chen / Specialist

Approved by :



, **Date:**

Oct. 17, 2017

Dylan Chiou / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -0.15 dB at 0.49737 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -1.52 dB at 2484 MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	Pass	Reference only
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Refer to section 3.1 Note 2 of this report.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Enterprise Access Point
Brand	4ipnet
Test Model	EAP330/OWL630
Status of EUT	Production Unit
Power Supply Rating	12.0Vdc (Adapter or DC Power Supply)
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7
Operating Frequency	2412 ~ 2462 MHz
Number of Channel	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
Output Power	564.585mW
Antenna Type	Dipole antenna with 5.03 dBi gain
Antenna Connector	Refer to Note as below
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

Note:

1. The EUT incorporates a MIMO function. Physically, the EUT provides 3 completed transmitters and 3 receivers.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	3TX
802.11n (40MHz)	3TX

2. All models are listed as below.

Brand	Model	Difference	
		Power Supply	Antenna Connector
4ipnet	EAP330	Adatper & POE	SMA type
	OWL630	POE & DC Power	N type

3. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	APD	WA-30B12	I/P: 100-240Vac, 0.8A O/P: 12Vdc, 2.5A
Antenna	Cortec	AN2450-5003BRS	--

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

7 channels are provided for 802.11n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	√	EAP330
B	√	√	√	√	OWL630

Where RE≥1G: Radiated Emission above 1 GHz RE<1G: Radiated Emission below 1 GHz
 PLC: Power Line Conducted Emission APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A, B	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11n (HT40)	3 to 9	9	OFDM	BPSK	MCS0
B	802.11n (HT40)	3 to 9	3	OFDM	BPSK	MCS0

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11n (HT40)	3 to 9	9	OFDM	BPSK	MCS0
B	802.11n (HT40)	3 to 9	3	OFDM	BPSK	MCS0

Bandedge Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A, B	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
	802.11n (HT20)	1 to 11	1, 11	OFDM	BPSK	MCS0
	802.11n (HT40)	3 to 9	3, 9	OFDM	BPSK	MCS0

Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A, B	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	MCS0

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120Vac, 60Hz (Mode A) 12Vdc (Mode B)	Karl Lee
RE<1G	25 deg. C, 65 % RH	120Vac, 60Hz (Mode A) 12Vdc (Mode B)	Karl Lee
PLC	25 deg. C, 65 % RH	120Vac, 60Hz (Mode A) 12Vdc (Mode B)	Anson Lin
APCM	25 deg. C, 65 % RH	12Vdc	Wayne Lin

3.3 Duty Cycle of Test Signal

Mode A


1Tx

802.11b: Duty cycle of test signal is 100 %, duty factor is not required.

802.11g: Duty cycle = $2.019/2.075 = 0.973$, Duty factor = $10 * \log(1/0.973) = 0.12$

802.11n (20MHz): Duty cycle = $1.885/1.941 = 0.971$, Duty factor = $10 * \log(1/0.971) = 0.13$


802.11n (40MHz): Duty cycle = $0.893/0.965 = 0.925$, Duty factor = $10 * \log(1/0.925) = 0.34$



2Tx

802.11n (20MHz): Duty cycle = $1.875/1.939 = 0.967$, Duty factor = $10 * \log(1/0.967) = 0.15$


802.11n (40MHz): Duty cycle = $0.900/0.965 = 0.932$, Duty factor = $10 * \log(1/0.932) = 0.31$



3Tx

802.11n (20MHz): Duty cycle = $1.883/1.947 = 0.967$, Duty factor = $10 * \log(1/0.967) = 0.15$

802.11n (40MHz): Duty cycle = $0.889/0.978 = 0.910$, Duty factor = $10 * \log(1/0.910) = 0.41$



Mode B


1Tx

802.11b: Duty cycle of test signal is 100 %, duty factor is not required.

802.11g: Duty cycle = $2.023/2.079 = 0.973$, Duty factor = $10 * \log(1/0.973) = 0.12$

802.11n (20MHz): Duty cycle = $1.879/1.943 = 0.967$, Duty factor = $10 * \log(1/0.967) = 0.15$


802.11n (40MHz): Duty cycle = $0.904/0.968 = 0.934$, Duty factor = $10 * \log(1/0.934) = 0.30$



2Tx

802.11n (20MHz): Duty cycle = $1.883/1.947 = 0.967$, Duty factor = $10 * \log(1/0.967) = 0.15$


802.11n (40MHz): Duty cycle = $0.906/0.970 = 0.934$, Duty factor = $10 * \log(1/0.934) = 0.30$



3Tx

802.11n (20MHz): Duty cycle = $1.867/1.939 = 0.963$, Duty factor = $10 * \log(1/0.963) = 0.17$

802.11n (40MHz): Duty cycle = $0.902/0.966 = 0.934$, Duty factor = $10 * \log(1/0.934) = 0.30$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	DC Power Supply	Topward	33010D	807748	N/A


No.	Signal Cable Description Of The Above Support Units
1.	N/S

Note:


1. All power cords of the above support units are non-shielded (1.8m).

3.4.1 Configuration of System under Test

Mode A



Mode B



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v04

662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).

The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Feb. 17, 2017	Feb. 16, 2018
Spectrum Analyzer Agilent	N9010A	MY52220314	Dec. 16, 2016	Dec. 15, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 13, 2016	Dec. 12, 2017
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 26, 2016	Dec. 27, 2017
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Dec. 12, 2016	Dec. 13, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 14, 2016	Dec. 13, 2017
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 17, 2017	Apr. 16, 2018
Loop Antenna	HLA 6121	45745	May 19, 2017	May 18, 2018
Preamplifier EMCI	EMC001340	980201	Nov. 02, 2016	Nov. 01, 2017
Bluetooth Tester	CBT	100946	Jul. 29, 2016	Jul. 28, 2018
Preamplifier EMCI	EMC 012645	980115	Oct. 21, 2016	Oct. 20, 2017
Preamplifier EMCI	EMC 184045	980116	Oct. 21, 2016	Oct. 20, 2017
Preamplifier EMCI	EMC 330H	980112	Oct. 21, 2016	Oct. 20, 2017
Power Meter Anritsu	ML2495A	1145013	Mar. 07, 2017	Mar. 06, 2018
Power Sensor Anritsu	MA2411B	1126085	Mar. 07, 2017	Mar. 06, 2018
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 21, 2016	Oct. 20, 2017
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 21, 2016	Oct. 20, 2017
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 21, 2016	Oct. 20, 2017
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Temperature & Humidity Chamber	GTH-120-40-CP-A R	MAA1306-019	Sep. 08, 2017	Sep. 07, 2018
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jun. 30, 2017	Jun. 29, 2018

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 10.
 3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.
 4. The FCC Designation Number is TW0003. The number will be varied with the Lab location and scope as attached.
 5. The IC Site Registration No. is IC7450F-10.

4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz & 360 KHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1/T for Average (Duty cycle < 98 %) detection at frequency above 1 GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up


<Radiated emission below 30 MHz>



<Frequency Range below 1 GHz>



<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

Above 1 GHz Data :

Mode A_1Tx

802.11b

EUT Test Condition		Measurement Detail					
Channel		Channel 1			Frequency Range		1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2372	42.94	41.28	54	-11.06	31.78	5.37	35.49	334	336	Average
2372	57.04	55.38	74	-16.96	31.78	5.37	35.49	334	336	Peak
2412	105.12	103.35			31.81	5.43	35.47	334	336	Average
2412	108.19	106.42			31.81	5.43	35.47	334	336	Peak
2490	40.23	38.22	54	-13.77	31.9	5.53	35.42	334	336	Average
2490	56.23	54.22	74	-17.77	31.9	5.53	35.42	334	336	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2332	51.14	49.6	54	-2.86	31.73	5.33	35.52	102	299	Average
2332	63.57	62.03	74	-10.43	31.73	5.33	35.52	102	299	Peak
2412	113.18	111.41			31.81	5.43	35.47	102	299	Average
2412	116.17	114.4			31.81	5.43	35.47	102	299	Peak
2492	42.83	40.81	54	-11.17	31.9	5.53	35.41	102	299	Average
2492	57.74	55.72	74	-16.26	31.9	5.53	35.41	102	299	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2356	41.57	39.94	54	-12.43	31.76	5.37	35.5	124	18	Average
2356	57.95	56.32	74	-16.05	31.76	5.37	35.5	124	18	Peak
2437	104.84	102.99			31.85	5.46	35.46	124	18	Average
2437	107.72	105.87			31.85	5.46	35.46	124	18	Peak
2496	40.55	38.53	54	-13.45	31.9	5.53	35.41	124	18	Average
2496	55.89	53.87	74	-18.11	31.9	5.53	35.41	124	18	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2358	46.03	44.4	54	-7.97	31.76	5.37	35.5	117	298	Average
2358	64.59	62.96	74	-9.41	31.76	5.37	35.5	117	298	Peak
2437	112.3	110.45			31.85	5.46	35.46	117	298	Average
2437	115.4	113.55			31.85	5.46	35.46	117	298	Peak
2486	42.96	40.97	54	-11.04	31.88	5.53	35.42	117	298	Average
2486	58.03	56.04	74	-15.97	31.88	5.53	35.42	117	298	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 11			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	40.57	38.84	54	-13.43	31.8	5.4	35.47	116	178	Average
2390	56.26	54.53	74	-17.74	31.8	5.4	35.47	116	178	Peak
2462	104.87	102.94			31.87	5.5	35.44	116	178	Average
2462	107.97	106.04			31.87	5.5	35.44	116	178	Peak
2486	41.17	39.18	54	-12.83	31.88	5.53	35.42	116	178	Average
2486	56.02	54.03	74	-17.98	31.88	5.53	35.42	116	178	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2384	46.07	44.38	54	-7.93	31.78	5.4	35.49	100	299	Average
2384	64.98	63.29	74	-9.02	31.78	5.4	35.49	100	299	Peak
2462	112.79	110.86			31.87	5.5	35.44	100	299	Average
2462	116.01	114.08			31.87	5.5	35.44	100	299	Peak
2490	49.3	47.29	54	-4.7	31.9	5.53	35.42	100	299	Average
2490	60.21	58.2	74	-13.79	31.9	5.53	35.42	100	299	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

802.11g

EUT Test Condition			Measurement Detail						
Channel		Channel 1			Frequency Range		1 GHz ~ 25 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	44.32	42.59	54	-9.68	31.8	5.4	35.47	334	332	Average
2390	56.84	55.11	74	-17.16	31.8	5.4	35.47	334	332	Peak
2412	95.48	93.71			31.81	5.43	35.47	334	332	Average
2412	102.96	101.19			31.81	5.43	35.47	334	332	Peak
2496	41.03	39.01	54	-12.97	31.9	5.53	35.41	334	332	Average
2496	55.54	53.52	74	-18.46	31.9	5.53	35.41	334	332	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	52.35	50.62	54	-1.65	31.8	5.4	35.47	102	299	Average
2390	68.88	67.15	74	-5.12	31.8	5.4	35.47	102	299	Peak
2412	102.15	100.38			31.81	5.43	35.47	102	299	Average
2412	110.75	108.98			31.81	5.43	35.47	102	299	Peak
2488	43.56	41.55	54	-10.44	31.9	5.53	35.42	102	299	Average
2488	56.45	54.44	74	-17.55	31.9	5.53	35.42	102	299	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2354	41.85	40.26	54	-12.15	31.76	5.33	35.5	124	18	Average
2354	56.58	54.99	74	-17.42	31.76	5.33	35.5	124	18	Peak
2437	94.74	92.89			31.85	5.46	35.46	124	18	Average
2437	102.98	101.13			31.85	5.46	35.46	124	18	Peak
2498	41.5	39.48	54	-12.5	31.9	5.53	35.41	124	18	Average
2498	56.91	54.89	74	-17.09	31.9	5.53	35.41	124	18	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2360	46.24	44.61	54	-7.76	31.76	5.37	35.5	117	298	Average
2360	61.86	60.23	74	-12.14	31.76	5.37	35.5	117	298	Peak
2437	102.3	100.45			31.85	5.46	35.46	117	298	Average
2437	110.8	108.95			31.85	5.46	35.46	117	298	Peak
2484	43.58	41.62	54	-10.42	31.88	5.5	35.42	117	298	Average
2484	58.21	56.25	74	-15.79	31.88	5.5	35.42	117	298	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 11			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2378	41.2	39.54	54	-12.8	31.78	5.37	35.49	116	178	Average
2378	56.12	54.46	74	-17.88	31.78	5.37	35.49	116	178	Peak
2462	94.01	92.08			31.87	5.5	35.44	116	178	Average
2462	102.21	100.28			31.87	5.5	35.44	116	178	Peak
2484	41.71	39.75	54	-12.29	31.88	5.5	35.42	116	178	Average
2484	56.15	54.19	74	-17.85	31.88	5.5	35.42	116	178	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2376	45.69	44.03	54	-8.31	31.78	5.37	35.49	100	299	Average
2376	61.39	59.73	74	-12.61	31.78	5.37	35.49	100	299	Peak
2462	102.21	100.28			31.87	5.5	35.44	100	299	Average
2462	110.87	108.94			31.87	5.5	35.44	100	299	Peak
2486	48.32	46.33	54	-5.68	31.88	5.53	35.42	100	299	Average
2486	67.64	65.65	74	-6.36	31.88	5.53	35.42	100	299	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

Mode A_3Tx
802.11n (HT20)

EUT Test Condition		Measurement Detail						
Channel	Channel 1	Frequency Range				1 GHz ~ 25 GHz		
Input Power	120 Vac, 60 Hz	Detector Function				Peak (PK) Average (AV)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By				Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2336	43.79	42.24	54	-10.21	31.74	5.33	35.52	100	347	Average
2336	56.62	55.07	74	-17.38	31.74	5.33	35.52	100	347	Peak
2412	98.88	97.11			31.81	5.43	35.47	100	347	Average
2412	106.74	104.97			31.81	5.43	35.47	100	347	Peak
2488	42.22	40.21	54	-11.78	31.9	5.53	35.42	100	347	Average
2488	56.23	54.22	74	-17.77	31.9	5.53	35.42	100	347	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	52.26	50.53	54	-1.74	31.8	5.4	35.47	132	260	Average
2390	64.52	62.79	74	-9.48	31.8	5.4	35.47	132	260	Peak
2412	106.86	105.09			31.81	5.43	35.47	133	261	Average
2412	114.27	112.5			31.81	5.43	35.47	133	261	Peak
2498	45.81	43.79	54	-8.19	31.9	5.53	35.41	133	261	Average
2498	59.6	57.58	74	-14.4	31.9	5.53	35.41	133	261	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
 Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2354	43.54	41.95	54	-10.46	31.76	5.33	35.5	116	347	Average
2354	57.63	56.04	74	-16.37	31.76	5.33	35.5	116	347	Peak
2437	98.66	96.81			31.85	5.46	35.46	116	347	Average
2437	106.06	104.21			31.85	5.46	35.46	116	347	Peak
2496	41.99	39.97	54	-12.01	31.9	5.53	35.41	116	347	Average
2496	56.82	54.8	74	-17.18	31.9	5.53	35.41	116	347	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2350	48.04	46.47	54	-5.96	31.74	5.33	35.5	132	297	Average
2350	60.7	59.13	74	-13.3	31.74	5.33	35.5	132	297	Peak
2437	106.48	104.63			31.85	5.46	35.46	132	297	Average
2437	114.31	112.46			31.85	5.46	35.46	132	297	Peak
2498	45.41	43.39	54	-8.59	31.9	5.53	35.41	132	297	Average
2498	57.43	55.41	74	-16.57	31.9	5.53	35.41	132	297	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 11			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2380	43.08	41.42	54	-10.92	31.78	5.37	35.49	114	347	Average
2380	56.78	55.12	74	-17.22	31.78	5.37	35.49	114	347	Peak
2462	98.41	96.48			31.87	5.5	35.44	114	347	Average
2462	106.07	104.14			31.87	5.5	35.44	114	347	Peak
2484	42.88	40.92	54	-11.12	31.88	5.5	35.42	114	347	Average
2484	55.8	53.84	74	-18.2	31.88	5.5	35.42	114	347	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2382	48.34	46.65	54	-5.66	31.78	5.4	35.49	101	304	Average
2382	61.04	59.35	74	-12.96	31.78	5.4	35.49	101	304	Peak
2462	106.2	104.27			31.87	5.5	35.44	101	304	Average
2462	114.64	112.71			31.87	5.5	35.44	101	304	Peak
2484	49.36	47.4	54	-4.64	31.88	5.5	35.42	100	257	Average
2484	62.54	60.58	74	-11.46	31.88	5.5	35.42	100	257	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

802.11n (HT40)

EUT Test Condition			Measurement Detail						
Channel		Channel 3			Frequency Range		1 GHz ~ 25 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	44.68	42.95	54	-9.32	31.8	5.4	35.47	131	346	Average
2390	57.38	55.65	74	-16.62	31.8	5.4	35.47	131	346	Peak
2422	92.83	91.03			31.83	5.43	35.46	131	346	Average
2422	100.14	98.34			31.83	5.43	35.46	131	346	Peak
2492	41.9	39.88	54	-12.1	31.9	5.53	35.41	131	346	Average
2492	56.03	54.01	74	-17.97	31.9	5.53	35.41	131	346	Peak

Antennal Polarity & Test Distance: Vertical at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	52.37	50.64	54	-1.63	31.8	5.4	35.47	133	252	Average
2390	66.27	64.54	74	-7.73	31.8	5.4	35.47	133	252	Peak
2422	100.71	98.91			31.83	5.43	35.46	133	261	Average
2422	108.56	106.76			31.83	5.43	35.46	133	261	Peak
2488	45.48	43.47	54	-8.52	31.9	5.53	35.42	133	261	Average
2488	58.08	56.07	74	-15.92	31.9	5.53	35.42	133	261	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2422 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 6		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	44.68	42.95	54	-9.32	31.8	5.4	35.47	116	347	Average
2390	57.57	55.84	74	-16.43	31.8	5.4	35.47	116	347	Peak
2437	93.01	91.16			31.85	5.46	35.46	116	347	Average
2437	101.4	99.55			31.85	5.46	35.46	116	347	Peak
2498	42.41	40.39	54	-11.59	31.9	5.53	35.41	116	347	Average
2498	56.77	54.75	74	-17.23	31.9	5.53	35.41	116	347	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	50.56	48.83	54	-3.44	31.8	5.4	35.47	137	257	Average
2390	61.78	60.05	74	-12.22	31.8	5.4	35.47	137	257	Peak
2437	101.89	100.04			31.85	5.46	35.46	132	297	Average
2437	109.86	108.01			31.85	5.46	35.46	132	297	Peak
2484	46.36	44.4	54	-7.64	31.88	5.5	35.42	132	297	Average
2484	59.3	57.34	74	-14.7	31.88	5.5	35.42	132	297	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 9		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2360	43.16	41.53	54	-10.84	31.76	5.37	35.5	114	347	Average
2360	57.11	55.48	74	-16.89	31.76	5.37	35.5	114	347	Peak
2452	93.46	91.59			31.85	5.46	35.44	114	347	Average
2452	100.5	98.63			31.85	5.46	35.44	114	347	Peak
2484	45.23	43.27	54	-8.77	31.88	5.5	35.42	114	347	Average
2484	60.01	58.05	74	-13.99	31.88	5.5	35.42	114	347	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386	49.85	48.14	54	-4.15	31.8	5.4	35.49	101	241	Average
2386	60.02	58.31	74	-13.98	31.8	5.4	35.49	101	241	Peak
2452	100.52	98.65			31.85	5.46	35.44	101	241	Average
2452	108.16	106.29			31.85	5.46	35.44	101	241	Peak
2484	52.48	50.52	54	-1.52	31.88	5.5	35.42	105	235	Average
2484	68.67	66.71	74	-5.33	31.88	5.5	35.42	105	235	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2452 MHz: Fundamental frequency.

Mode B_1Tx
802.11b

EUT Test Condition		Measurement Detail					
Channel	Channel 1	Frequency Range			1 GHz ~ 25 GHz		
Input Power	120 Vac, 60 Hz	Detector Function			Peak (PK) Average (AV)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By			Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2332	48.55	47.01	54	-5.45	31.73	5.33	35.52	148	152	Average
2332	64.64	63.1	74	-9.36	31.73	5.33	35.52	148	152	Peak
2412	112.03	110.26			31.81	5.43	35.47	148	152	Average
2412	115.28	113.51			31.81	5.43	35.47	148	152	Peak
2492	41.22	39.2	54	-12.78	31.9	5.53	35.41	148	152	Average
2492	58.03	56.01	74	-15.97	31.9	5.53	35.41	148	152	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2332	50.27	48.73	54	-3.73	31.73	5.33	35.52	241	159	Average
2332	61.64	60.1	74	-12.36	31.73	5.33	35.52	241	159	Peak
2412	114.08	112.31			31.81	5.43	35.47	241	159	Average
2412	117.03	115.26			31.81	5.43	35.47	241	159	Peak
2492	41.31	39.29	54	-12.69	31.9	5.53	35.41	241	159	Average
2492	57.96	55.94	74	-16.04	31.9	5.53	35.41	241	159	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2358	44.18	42.55	54	-9.82	31.76	5.37	35.5	148	151	Average
2358	65.21	63.58	74	-8.79	31.76	5.37	35.5	148	151	Peak
2437	113.96	112.11			31.85	5.46	35.46	148	151	Average
2437	116.76	114.91			31.85	5.46	35.46	148	151	Peak
2496	41.05	39.03	54	-12.95	31.9	5.53	35.41	148	151	Average
2496	56.63	54.61	74	-17.37	31.9	5.53	35.41	148	151	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2360	41.87	40.24	54	-12.13	31.76	5.37	35.5	194	158	Average
2360	60.64	59.01	74	-13.36	31.76	5.37	35.5	194	158	Peak
2437	115.66	113.81			31.85	5.46	35.46	194	158	Average
2437	118.5	116.65			31.85	5.46	35.46	194	158	Peak
2496	41.8	39.78	54	-12.2	31.9	5.53	35.41	194	158	Average
2496	56.06	54.04	74	-17.94	31.9	5.53	35.41	194	158	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 11		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2384	45.24	43.55	54	-8.76	31.78	5.4	35.49	146	151	Average
2384	63	61.31	74	-11	31.78	5.4	35.49	146	151	Peak
2462	110.4	108.47			31.87	5.5	35.44	146	151	Average
2462	113.34	111.41			31.87	5.5	35.44	146	151	Peak
2490	44.63	42.62	54	-9.37	31.9	5.53	35.42	146	151	Average
2490	57.84	55.83	74	-16.16	31.9	5.53	35.42	146	151	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2382	44.1	42.41	54	-9.9	31.78	5.4	35.49	214	157	Average
2382	59.29	57.6	74	-14.71	31.78	5.4	35.49	214	157	Peak
2462	113.38	111.45			31.87	5.5	35.44	214	157	Average
2462	116.37	114.44			31.87	5.5	35.44	214	157	Peak
2484	46.49	44.53	54	-7.51	31.88	5.5	35.42	214	157	Average
2484	58.89	56.93	74	-15.11	31.88	5.5	35.42	214	157	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

802.11g

EUT Test Condition			Measurement Detail						
Channel		Channel 1			Frequency Range		1 GHz ~ 25 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	50.37	48.64	54	-3.63	31.8	5.4	35.47	148	152	Average
2390	64.48	62.75	74	-9.52	31.8	5.4	35.47	148	152	Peak
2412	99.8	98.03			31.81	5.43	35.47	148	152	Average
2412	107.81	106.04			31.81	5.43	35.47	148	152	Peak
2488	42.1	40.09	54	-11.9	31.9	5.53	35.42	148	152	Average
2488	57	54.99	74	-17	31.9	5.53	35.42	148	152	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	51.69	49.96	54	-2.31	31.8	5.4	35.47	241	159	Average
2390	65.57	63.84	74	-8.43	31.8	5.4	35.47	241	159	Peak
2412	102.17	100.4			31.81	5.43	35.47	241	159	Average
2412	109.69	107.92			31.81	5.43	35.47	241	159	Peak
2500	42.41	40.39	54	-11.59	31.9	5.53	35.41	241	159	Average
2500	56.73	54.71	74	-17.27	31.9	5.53	35.41	241	159	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2364	44.07	42.44	54	-9.93	31.76	5.37	35.5	148	151	Average
2364	61.59	59.96	74	-12.41	31.76	5.37	35.5	148	151	Peak
2437	101.51	99.66			31.85	5.46	35.46	148	151	Average
2437	109.62	107.77			31.85	5.46	35.46	148	151	Peak
2488	41.8	39.79	54	-12.2	31.9	5.53	35.42	148	151	Average
2488	56.12	54.11	74	-17.88	31.9	5.53	35.42	148	151	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2356	42.09	40.46	54	-11.91	31.76	5.37	35.5	194	157	Average
2356	56.84	55.21	74	-17.16	31.76	5.37	35.5	194	157	Peak
2437	103.58	101.73			31.85	5.46	35.46	194	157	Average
2437	111.1	109.25			31.85	5.46	35.46	194	157	Peak
2484	42.75	40.79	54	-11.25	31.88	5.5	35.42	194	157	Average
2484	56.4	54.44	74	-17.6	31.88	5.5	35.42	194	157	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 11		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2382	43.8	42.11	54	-10.2	31.78	5.4	35.49	146	151	Average
2382	59.78	58.09	74	-14.22	31.78	5.4	35.49	146	151	Peak
2462	98.87	96.94			31.87	5.5	35.44	146	151	Average
2462	107.36	105.43			31.87	5.5	35.44	146	151	Peak
2484	45.67	43.71	54	-8.33	31.88	5.5	35.42	146	151	Average
2484	62.01	60.05	74	-11.99	31.88	5.5	35.42	146	151	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386	42.77	41.06	54	-11.23	31.8	5.4	35.49	214	157	Average
2386	57.71	56	74	-16.29	31.8	5.4	35.49	214	157	Peak
2462	101.62	99.69			31.87	5.5	35.44	214	157	Average
2462	109.79	107.86			31.87	5.5	35.44	214	157	Peak
2484	48.17	46.21	54	-5.83	31.88	5.5	35.42	214	157	Average
2484	63.75	61.79	74	-10.25	31.88	5.5	35.42	214	157	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

Mode B_3Tx
802.11n (HT20)

EUT Test Condition		Measurement Detail					
Channel	Channel 1	Frequency Range				1 GHz ~ 25 GHz	
Input Power	120 Vac, 60 Hz	Detector Function				Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By				Karl Lee	

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	49.95	48.22	54	-4.05	31.8	5.4	35.47	113	326	Average
2390	66.48	64.75	74	-7.52	31.8	5.4	35.47	113	326	Peak
2412	101.25	99.48			31.81	5.43	35.47	113	326	Average
2412	109.47	107.7			31.81	5.43	35.47	113	326	Peak
2492	41.76	39.74	54	-12.24	31.9	5.53	35.41	113	326	Average
2492	56.25	54.23	74	-17.75	31.9	5.53	35.41	113	326	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	50.79	49.06	54	-3.21	31.8	5.4	35.47	220	160	Average
2390	66.23	64.5	74	-7.77	31.8	5.4	35.47	220	160	Peak
2412	103.4	101.63			31.81	5.43	35.47	241	179	Average
2412	111.41	109.64			31.81	5.43	35.47	241	179	Peak
2494	41.97	39.95	54	-12.03	31.9	5.53	35.41	241	179	Average
2494	56.55	54.53	74	-17.45	31.9	5.53	35.41	241	179	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2356	42.02	40.39	54	-11.98	31.76	5.37	35.5	226	221	Average
2356	57.82	56.19	74	-16.18	31.76	5.37	35.5	226	221	Peak
2437	102.88	101.03			31.85	5.46	35.46	226	221	Average
2437	110.51	108.66			31.85	5.46	35.46	226	221	Peak
2496	41.31	39.29	54	-12.69	31.9	5.53	35.41	226	221	Average
2496	55.46	53.44	74	-18.54	31.9	5.53	35.41	226	221	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2360	45.35	43.72	54	-8.65	31.76	5.37	35.5	308	0	Average
2360	57.77	56.14	74	-16.23	31.76	5.37	35.5	308	0	Peak
2437	104.82	102.97			31.85	5.46	35.46	308	0	Average
2437	112.7	110.85			31.85	5.46	35.46	308	0	Peak
2494	43.4	41.38	54	-10.6	31.9	5.53	35.41	308	0	Average
2494	56.6	54.58	74	-17.4	31.9	5.53	35.41	308	0	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 11		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2378	42.95	41.29	54	-11.05	31.78	5.37	35.49	202	330	Average
2378	60.15	58.49	74	-13.85	31.78	5.37	35.49	202	330	Peak
2462	99.78	97.85			31.87	5.5	35.44	202	330	Average
2462	108.23	106.3			31.87	5.5	35.44	202	330	Peak
2498	41.7	39.68	54	-12.3	31.9	5.53	35.41	202	330	Average
2498	56.11	54.09	74	-17.89	31.9	5.53	35.41	202	330	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2378	45.42	43.76	54	-8.58	31.78	5.37	35.49	274	346	Average
2378	58.21	56.55	74	-15.79	31.78	5.37	35.49	274	346	Peak
2462	102.59	100.66			31.87	5.5	35.44	274	346	Average
2462	110.18	108.25			31.87	5.5	35.44	274	346	Peak
2484	48.3	46.34	54	-5.7	31.88	5.5	35.42	227	15	Average
2484	66.89	64.93	74	-7.11	31.88	5.5	35.42	227	15	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2462 MHz: Fundamental frequency.

802.11n (HT40)

EUT Test Condition			Measurement Detail						
Channel		Channel 3			Frequency Range		1 GHz ~ 25 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Average (AV)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	46.14	44.41	54	-7.86	31.8	5.4	35.47	308	342	Average
2390	61	59.27	74	-13	31.8	5.4	35.47	308	342	Peak
2422	97.53	95.73			31.83	5.43	35.46	308	342	Average
2422	105.15	103.35			31.83	5.43	35.46	308	342	Peak
2488	42.05	40.04	54	-11.95	31.9	5.53	35.42	308	342	Average
2488	56.52	54.51	74	-17.48	31.9	5.53	35.42	308	342	Peak

Antennal Polarity & Test Distance: Vertical at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	52.47	50.74	54	-1.53	31.8	5.4	35.47	247	198	Average
2390	68.38	66.65	74	-5.62	31.8	5.4	35.47	247	198	Peak
2422	99.38	97.58			31.83	5.43	35.46	241	159	Average
2422	107.22	105.42			31.83	5.43	35.46	241	159	Peak
2492	41.76	39.74	54	-12.24	31.9	5.53	35.41	241	159	Average
2492	55.43	53.41	74	-18.57	31.9	5.53	35.41	241	159	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2422 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail			
Channel		Channel 6			Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz			Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH			Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2366	43.44	41.8	54	-10.56	31.76	5.37	35.49	113	326	Average
2366	57.13	55.49	74	-16.87	31.76	5.37	35.49	113	326	Peak
2437	99.43	97.58			31.85	5.46	35.46	113	326	Average
2437	107.12	105.27			31.85	5.46	35.46	113	326	Peak
2484	45.66	43.7	54	-8.34	31.88	5.5	35.42	113	326	Average
2484	56.32	54.36	74	-17.68	31.88	5.5	35.42	113	326	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2390	44.37	42.64	54	-9.63	31.8	5.4	35.47	241	198	Average
2390	57.2	55.47	74	-16.8	31.8	5.4	35.47	241	198	Peak
2437	101.3	99.45			31.85	5.46	35.46	241	198	Average
2437	109.46	107.61			31.85	5.46	35.46	241	198	Peak
2490	42.09	40.08	54	-11.91	31.9	5.53	35.42	241	198	Average
2490	56.53	54.52	74	-17.47	31.9	5.53	35.42	241	198	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2437 MHz: Fundamental frequency.

EUT Test Condition			Measurement Detail		
Channel		Channel 9		Frequency Range	1 GHz ~ 25 GHz
Input Power		120 Vac, 60 Hz		Detector Function	Peak (PK) Average (AV)
Environmental Conditions		25 deg. C, 65 % RH		Tested By	Karl Lee

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2376	41.99	40.33	54	-12.01	31.78	5.37	35.49	111	326	Average
2376	56.03	54.37	74	-17.97	31.78	5.37	35.49	111	326	Peak
2452	96.2	94.33			31.85	5.46	35.44	111	326	Average
2452	104.75	102.88			31.85	5.46	35.44	111	326	Peak
2484	44.31	42.35	54	-9.69	31.88	5.5	35.42	111	326	Average
2484	57.64	55.68	74	-16.36	31.88	5.5	35.42	111	326	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2376	43.43	41.77	54	-10.57	31.78	5.37	35.49	241	204	Average
2376	56.24	54.58	74	-17.76	31.78	5.37	35.49	241	204	Peak
2452	99.53	97.66			31.85	5.46	35.44	241	204	Average
2452	106.86	104.99			31.85	5.46	35.44	241	204	Peak
2484	49.43	47.47	54	-4.57	31.88	5.5	35.42	301	16	Average
2484	64.47	62.51	74	-9.53	31.88	5.5	35.42	301	16	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2452 MHz: Fundamental frequency.

9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz Worst-Case Data:

Mode A

802.11n (HT40)

EUT Test Condition		Measurement Detail					
Channel	Channel 9	Frequency Range			30 MHz ~ 1 GHz		
Input Power	120 Vac, 60 Hz	Detector Function			Peak (PK) Quasi-peak (QP)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By			Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
32.16	27.95	43.26	40	-12.05	16.21	0.74	32.26	165	274	Peak
192.81	26.74	46.89	43.5	-16.76	10.51	1.61	32.27	132	127	Peak
278.4	26.51	42.86	46	-19.49	13.74	2.03	32.12	175	142	Peak
599.6	28.46	36.68	46	-17.54	21.1	2.87	32.19	108	271	Peak
785.1	29.85	34.79	46	-16.15	23.87	3.27	32.08	135	217	Peak
899.9	33.67	36.66	46	-12.33	25	3.49	31.48	138	304	Peak
Antennal Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
43.5	34.93	56.32	40	-5.07	9.93	0.9	32.22	116	127	Peak
193.35	20.58	40.67	43.5	-22.92	10.57	1.61	32.27	134	271	Peak
274.89	21.89	38.37	46	-24.11	13.7	1.94	32.12	194	212	Peak
599.6	28.03	36.25	46	-17.97	21.1	2.87	32.19	139	237	Peak
750.8	29.17	34.89	46	-16.83	23.2	3.22	32.14	175	247	Peak
899.9	33.39	36.38	46	-12.61	25	3.49	31.48	117	123	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value

Mode B
802.11n (HT40)

EUT Test Condition			Measurement Detail						
Channel		Channel 3			Frequency Range		30 MHz ~ 1 GHz		
Input Power		120 Vac, 60 Hz			Detector Function		Peak (PK) Quasi-peak (QP)		
Environmental Conditions		25 deg. C, 65 % RH			Tested By		Karl Lee		

Antennal Polarity & Test Distance: Horizontal at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
47.01	13.83	36.41	40	-26.17	8.74	0.9	32.22	114	201	Peak
193.08	25.25	45.4	43.5	-18.25	10.51	1.61	32.27	139	287	Peak
300	34.94	51.15	46	-11.06	13.9	2.03	32.14	145	284	Peak
599.6	28.06	36.28	46	-17.94	21.1	2.87	32.19	100	128	Peak
826.4	31.12	36.11	46	-14.88	23.55	3.38	31.92	139	328	Peak
899.9	32.63	35.62	46	-13.37	25	3.49	31.48	174	245	Peak

Antennal Polarity & Test Distance: Vertical at 3 m

Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
31.89	25.78	40.97	40	-14.22	16.33	0.74	32.26	139	184	Peak
192	19.32	39.51	43.5	-24.18	10.46	1.61	32.26	108	210	Peak
300	26.64	42.85	46	-19.36	13.9	2.03	32.14	139	317	Peak
599.6	28.42	36.64	46	-17.58	21.1	2.87	32.19	103	284	Peak
675.9	30.25	35.96	46	-15.75	23.36	3.05	32.12	196	230	Peak
899.9	31.78	34.77	46	-14.22	25	3.49	31.48	145	210	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 21, 2016	Nov. 20, 2017
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2017	Sep. 04, 2018
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 10, 2017	Mar. 09, 2018
LISN/AMN ROHDE & SCHWARZ (Peripheral)	ENV216	101196	Apr. 20, 2017	Apr. 19, 2018
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

- Placed the EUT on a testing table.
- Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.2.7 Test Results


Mode A

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/10/6

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19367	10.39	35.16	23.69	45.55	34.08	63.88	53.88	-18.33	-19.80
2	0.25338	10.40	32.12	22.78	42.52	33.18	61.65	51.65	-19.13	-18.47
3	0.32203	10.40	33.13	20.88	43.53	31.28	59.65	49.65	-16.12	-18.37
4	0.42600	10.41	35.62	23.55	46.03	33.96	57.33	47.33	-11.30	-13.37
5	0.65800	10.41	29.97	17.55	40.38	27.96	56.00	46.00	-15.62	-18.04
6	1.19800	10.43	27.94	17.71	38.37	28.14	56.00	46.00	-17.63	-17.86

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/10/6

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18180	10.16	34.29	25.50	44.45	35.66	64.40	54.40	-19.95	-18.74
2	0.25405	10.16	30.62	20.02	40.78	30.18	61.62	51.62	-20.84	-21.44
3	0.31365	10.17	31.00	20.70	41.17	30.87	59.87	49.87	-18.70	-19.00
4	0.37000	10.17	29.37	18.78	39.54	28.95	58.50	48.50	-18.96	-19.55
5	0.41799	10.17	35.40	24.01	45.57	34.18	57.49	47.49	-11.92	-13.31
6	0.65400	10.18	27.25	15.80	37.43	25.98	56.00	46.00	-18.57	-20.02

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode B

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	12 Vdc	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/10/6

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15400	0.27	50.24	50.48	50.51	50.75	65.78	55.78	-15.27	-5.03
2	0.49737	0.22	49.29	45.67	49.51	45.89	56.04	46.04	-6.53	-0.15
3	0.99800	0.22	43.71	43.57	43.93	43.79	56.00	46.00	-12.07	-2.21
4	1.49800	0.23	38.35	38.42	38.58	38.65	56.00	46.00	-17.42	-7.35
5	3.66600	0.28	42.97	42.27	43.25	42.55	56.00	46.00	-12.75	-3.45
6	4.66917	0.30	45.49	45.35	45.79	45.65	56.00	46.00	-10.21	-0.35

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	12 Vdc	Environmental Conditions	25°C, 65%RH
Tested by	Getaz Yang	Test Date	2017/10/6

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15400	0.20	51.08	51.32	51.28	51.52	65.78	55.78	-14.50	-4.26
2	0.50000	0.15	49.83	45.53	49.98	45.68	56.00	46.00	-6.02	-0.32
3	1.00239	0.16	43.94	43.68	44.10	43.84	56.00	46.00	-11.90	-2.16
4	1.50600	0.17	38.58	38.53	38.75	38.70	56.00	46.00	-17.25	-7.30
5	4.01000	0.22	42.66	39.76	42.88	39.98	56.00	46.00	-13.12	-6.02
6	4.67800	0.24	45.71	44.23	45.95	44.47	56.00	46.00	-10.05	-1.53

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6 dB Bandwidth Measurement

4.3.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100 kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

Mode A

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	7.11	0.5	Pass
6	2437	7.05	0.5	Pass
11	2462	7.11	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.38	0.5	Pass
6	2437	16.40	0.5	Pass
11	2462	16.38	0.5	Pass

802.11n (20MHz)

1Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	17.61	0.5	Pass
6	2437	17.37	0.5	Pass
11	2462	17.62	0.5	Pass

2Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	17.57	17.61	0.5	Pass
6	2437	17.63	17.61	0.5	Pass
11	2462	17.65	17.64	0.5	Pass

3Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	17.60	17.62	17.62	0.5	Pass
6	2437	17.62	17.62	17.62	0.5	Pass
11	2462	17.62	17.64	17.65	0.5	Pass

802.11n (40MHz)

1Tx


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
3	2422	35.84	0.5	Pass
6	2437	35.99	0.5	Pass
9	2452	36.12	0.5	Pass

2Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	36.40	36.10	0.5	Pass
6	2437	36.14	36.39	0.5	Pass
9	2452	35.89	36.14	0.5	Pass

3Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
3	2422	36.60	36.40	36.50	0.5	Pass
6	2437	35.99	36.39	36.33	0.5	Pass
9	2452	35.85	35.83	36.36	0.5	Pass



Mode B
802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	7.70	0.5	Pass
6	2437	7.11	0.5	Pass
11	2462	7.07	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.37	0.5	Pass
6	2437	16.41	0.5	Pass
11	2462	16.39	0.5	Pass

802.11n (20MHz)
1Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	17.61	0.5	Pass
6	2437	17.62	0.5	Pass
11	2462	17.62	0.5	Pass

2Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	17.62	17.62	0.5	Pass
6	2437	17.62	17.60	0.5	Pass
11	2462	17.63	17.64	0.5	Pass

3Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
1	2412	17.60	17.60	17.61	0.5	Pass
6	2437	17.58	17.63	17.62	0.5	Pass
11	2462	17.64	17.65	17.64	0.5	Pass

802.11n (40MHz)
1Tx


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
3	2422	36.15	0.5	Pass
6	2437	36.13	0.5	Pass
9	2452	36.12	0.5	Pass

2Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	36.05	36.40	0.5	Pass
6	2437	36.16	36.38	0.5	Pass
9	2452	36.37	35.10	0.5	Pass


3Tx

Channel	Frequency (MHz)	6dB Bandwidth (MHz)			Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2		
3	2422	36.34	36.40	36.41	0.5	Pass
6	2437	36.90	35.85	36.38	0.5	Pass
9	2452	36.37	36.13	36.37	0.5	Pass



4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.4.4 Deviation from Test Standard

No deviation.

4.4.5 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.6 Test Results

Mode A

802.11b

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
1	2412	12.70	Pass
6	2437	11.95	Pass
11	2462	12.10	Pass

802.11g

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
1	2412	17.70	Pass
6	2437	17.10	Pass
11	2462	17.70	Pass

802.11n (HT20)

1Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
1	2412	18.17	Pass
6	2437	18.15	Pass
11	2462	18.15	Pass

2Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)		Pass / Fail
		Chain 0	Chain 1	
1	2412	18.13	18.80	Pass
6	2437	18.15	18.10	Pass
11	2462	18.25	18.10	Pass

3Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			Pass / Fail
		Chain 0	Chain 1	Chain 2	
1	2412	18.13	18.13	18.80	Pass
6	2437	18.20	18.05	18.05	Pass
11	2462	18.15	18.10	18.10	Pass

802.11n (HT40)
1Tx


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
3	2422	37.18	Pass
6	2437	37.17	Pass
9	2452	37.33	Pass

2Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)		Pass / Fail
		Chain 0	Chain 1	
3	2422	37.18	37.18	Pass
6	2437	37.17	37.17	Pass
9	2452	37.33	37.00	Pass

3Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			Pass / Fail
		Chain 0	Chain 1	Chain 2	
3	2422	37.18	37.18	37.20	Pass
6	2437	37.50	37.17	37.00	Pass
9	2452	37.50	37.00	37.00	Pass



Mode A
802.11b

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
1	2412	12.20	Pass
6	2437	12.35	Pass
11	2462	11.85	Pass

802.11g

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
1	2412	17.70	Pass
6	2437	17.10	Pass
11	2462	17.10	Pass

802.11n (HT20)
1Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
1	2412	18.22	Pass
6	2437	18.20	Pass
11	2462	18.15	Pass

2Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)		Pass / Fail
		Chain 0	Chain 1	
1	2412	18.17	18.30	Pass
6	2437	18.15	18.10	Pass
11	2462	18.20	18.15	Pass

3Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			Pass / Fail
		Chain 0	Chain 1	Chain 2	
1	2412	18.17	18.80	18.30	Pass
6	2437	18.20	18.10	18.05	Pass
11	2462	18.20	18.05	18.05	Pass

802.11n (HT40)

1Tx


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	Pass / Fail
3	2422	37.34	Pass
6	2437	37.17	Pass
9	2452	37.50	Pass

2Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)		Pass / Fail
		Chain 0	Chain 1	
3	2422	37.18	37.20	Pass
6	2437	37.33	37.33	Pass
9	2452	37.33	37.00	Pass

3Tx

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			Pass / Fail
		Chain 0	Chain 1	Chain 2	
3	2422	37.18	37.20	37.18	Pass
6	2437	37.33	37.17	37.00	Pass
9	2452	37.17	37.17	37.17	Pass



4.5 Conducted Output Power Measurement

4.5.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;

Array Gain = $5 \log(NANT/NSS)$ dB or 3 dB, whichever is less for 20 MHz channel widths with NANT ≥ 5.

For power measurements on all other devices: Array Gain = $10 \log(NANT/NSS)$ dB.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Mode A

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	260.02	24.15	30	Pass
6	2437	208.93	23.20	30	Pass
11	2462	276.06	24.41	30	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	267.30	24.27	30	Pass
6	2437	226.99	23.56	30	Pass
11	2462	237.68	23.76	30	Pass

802.11n (HT20)

1Tx

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	271.64	24.34	30	Pass
6	2437	203.70	23.09	30	Pass
11	2462	199.99	23.01	30	Pass

2Tx

Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	22.26	23.47	390.598	25.92	30	Pass
6	2437	21.75	22.09	311.432	24.93	30	Pass
11	2462	20.42	22.31	280.370	24.48	30	Pass

3Tx

Channel	Frequency (MHz)	Peak Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	21.18	21.22	21.43	402.649	26.05	30	Pass
6	2437	20.18	20.15	20.38	316.890	25.01	30	Pass
11	2462	20.09	19.81	19.86	294.641	24.69	30	Pass

802.11n (HT40)

1Tx

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
3	2422	179.89	22.55	30	Pass
6	2437	261.22	24.17	30	Pass
9	2452	200.91	23.03	30	Pass

2Tx

Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	19.44	19.82	183.842	22.64	30	Pass
6	2437	20.90	22.61	305.416	24.85	30	Pass
9	2452	20.81	21.30	255.400	24.07	30	Pass

3Tx

Channel	Frequency (MHz)	Peak Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	17.73	17.99	17.93	184.330	22.66	30	Pass
6	2437	19.19	20.61	20.45	308.983	24.90	30	Pass
9	2452	18.86	19.67	19.51	258.927	24.13	30	Pass

Mode B
802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	353.18	25.48	30	Pass
6	2437	370.68	25.69	30	Pass
11	2462	313.33	24.96	30	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	314.05	24.97	30	Pass
6	2437	334.97	25.25	30	Pass
11	2462	276.69	24.42	30	Pass

802.11n (HT20)
1Tx

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
1	2412	321.37	25.07	30	Pass
6	2437	356.45	25.52	30	Pass
11	2462	269.77	24.31	30	Pass

2Tx

Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	23.55	23.69	460.348	26.63	30	Pass
6	2437	23.80	24.55	524.985	27.20	30	Pass
11	2462	21.83	22.24	319.900	25.05	30	Pass

3Tx

Channel	Frequency (MHz)	Peak Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
1	2412	22.22	22.27	22.50	513.208	27.10	30	Pass
6	2437	22.70	22.58	22.95	564.585	27.52	30	Pass
11	2462	20.53	20.23	20.29	325.324	25.12	30	Pass

802.11n (HT40)
1Tx

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
3	2422	234.42	23.70	30	Pass
6	2437	305.49	24.85	30	Pass
9	2452	185.78	22.69	30	Pass

2Tx

Channel	Frequency (MHz)	Peak Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	21.23	21.54	275.300	24.40	30	Pass
6	2437	22.32	22.25	338.489	25.30	30	Pass
9	2452	19.95	20.46	210.028	23.22	30	Pass

3Tx

Channel	Frequency (MHz)	Peak Power (dBm)			Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2				
3	2422	19.93	20.19	20.12	305.675	24.85	30	Pass
6	2437	20.44	21.18	21.03	368.648	25.67	30	Pass
9	2452	18.42	18.86	18.78	221.925	23.46	30	Pass

4.6 Power Spectral Density Measurement

4.6.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm.

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d. Set the VBW $\geq 3 \times \text{RBW}$.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 Test Results

Mode A

802.11b

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
1	2412	-1.40	8	Pass
6	2437	-2.25	8	Pass
11	2462	-1.67	8	Pass

802.11g

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
1	2412	-11.10	8	Pass
6	2437	-12.10	8	Pass
11	2462	-11.70	8	Pass

802.11n (HT20)
1Tx

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
1	2412	-14.37	8	Pass
6	2437	-15.58	8	Pass
11	2462	-15.64	8	Pass

2Tx

TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=2) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	1	2412	-13.98	3.01	-10.97	5.96	Pass
	6	2437	-16.12	3.01	-13.11	5.96	Pass
	11	2462	-16.63	3.01	-13.62	5.96	Pass
1	1	2412	-12.84	3.01	-9.83	5.96	Pass
	6	2437	-13.32	3.01	-10.31	5.96	Pass
	11	2462	-13.67	3.01	-10.66	5.96	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(2) = 8.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(8.04-6) = 5.96\text{dBm}$.

3Tx

TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=3) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	1	2412	-17.51	4.77	-12.74	4.2	Pass
	6	2437	-16.90	4.77	-12.13	4.2	Pass
	11	2462	-17.21	4.77	-12.44	4.2	Pass
1	1	2412	-14.41	4.77	-9.64	4.2	Pass
	6	2437	-15.60	4.77	-10.83	4.2	Pass
	11	2462	-16.34	4.77	-11.57	4.2	Pass
2	1	2412	-13.99	4.77	-9.22	4.2	Pass
	6	2437	-16.08	4.77	-11.31	4.2	Pass
	11	2462	-15.97	4.77	-11.20	4.2	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(3) = 9.8\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(9.8-6) = 4.2\text{dBm}$.

802.11n (HT40)
1Tx

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
3	2422	-16.27	8	Pass
6	2437	-12.90	8	Pass
9	2452	-18.49	8	Pass

2Tx


TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=2) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	3	2422	-20.35	3.01	-17.34	5.96	Pass
	6	2437	-18.35	3.01	-15.34	5.96	Pass
	9	2452	-16.91	3.01	-13.90	5.96	Pass
1	3	2422	-18.19	3.01	-15.18	5.96	Pass
	6	2437	-16.66	3.01	-13.65	5.96	Pass
	9	2452	-17.02	3.01	-14.01	5.96	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(2) = 8.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(8.04-6) = 5.96\text{dBm}$.

3Tx

TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=3) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	3	2422	-22.30	4.77	-17.53	4.2	Pass
	6	2437	-20.28	4.77	-15.51	4.2	Pass
	9	2452	-20.20	4.77	-15.43	4.2	Pass
1	3	2422	-21.53	4.77	-16.76	4.2	Pass
	6	2437	-18.02	4.77	-13.25	4.2	Pass
	9	2452	-19.81	4.77	-15.04	4.2	Pass
2	3	2422	-20.18	4.77	-15.41	4.2	Pass
	6	2437	-17.53	4.77	-12.76	4.2	Pass
	9	2452	-15.26	4.77	-10.49	4.2	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(3) = 9.8\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(9.8-6) = 4.2\text{dBm}$.



Mode B
802.11b

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
1	2412	0.73	8	Pass
6	2437	2.15	8	Pass
11	2462	0.52	8	Pass

802.11g

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
1	2412	-10.50	8	Pass
6	2437	-7.50	8	Pass
11	2462	-10.86	8	Pass

802.11n (HT20)
1Tx

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
1	2412	-11.11	8	Pass
6	2437	-8.62	8	Pass
11	2462	-11.04	8	Pass

2Tx

TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=2) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	1	2412	-14.15	3.01	-11.14	5.96	Pass
	6	2437	-11.17	3.01	-8.16	5.96	Pass
	11	2462	-14.65	3.01	-11.64	5.96	Pass
1	1	2412	-12.80	3.01	-9.79	5.96	Pass
	6	2437	-11.97	3.01	-8.96	5.96	Pass
	11	2462	-14.32	3.01	-11.31	5.96	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(2) = 8.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(8.04-6) = 5.96\text{dBm}$.

3Tx

TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=2) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	1	2412	-14.86	4.77	-10.09	4.2	Pass
	6	2437	-13.01	4.77	-8.24	4.2	Pass
	11	2462	-14.94	4.77	-10.17	4.2	Pass
1	1	2412	-15.42	4.77	-10.65	4.2	Pass
	6	2437	-13.76	4.77	-8.99	4.2	Pass
	11	2462	-15.73	4.77	-10.96	4.2	Pass
2	1	2412	-14.27	4.77	-9.50	4.2	Pass
	6	2437	-12.88	4.77	-8.11	4.2	Pass
	11	2462	-13.92	4.77	-9.15	4.2	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(3) = 9.8\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(9.8-6) = 4.2\text{dBm}$.

802.11n (HT40)
1Tx

Channel	Frequency (MHz)	PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
3	2422	-13.30	8	Pass
6	2437	-11.77	8	Pass
9	2452	-14.76	8	Pass

2Tx


TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=2) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	3	2422	-16.84	3.01	-13.83	5.96	Pass
	6	2437	-13.86	3.01	-10.85	5.96	Pass
	9	2452	-18.52	3.01	-15.51	5.96	Pass
1	3	2422	-18.80	3.01	-15.79	5.96	Pass
	6	2437	-15.66	3.01	-12.65	5.96	Pass
	9	2452	-18.16	3.01	-15.15	5.96	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(2) = 8.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(8.04-6) = 5.96\text{dBm}$.

3Tx

TX Chain	Channel	Freq. (MHz)	PSD (dBm/3 kHz)	10 log (N=3) dB	Total PSD (dBm/3 kHz)	Limit (dBm/3 kHz)	Pass / Fail
0	3	2422	-19.93	4.77	-15.16	4.2	Pass
	6	2437	-18.27	4.77	-13.50	4.2	Pass
	9	2452	-20.10	4.77	-15.33	4.2	Pass
1	3	2422	-19.82	4.77	-15.05	4.2	Pass
	6	2437	-18.76	4.77	-13.99	4.2	Pass
	9	2452	-20.66	4.77	-15.89	4.2	Pass
2	3	2422	-19.07	4.77	-14.30	4.2	Pass
	6	2437	-18.34	4.77	-13.57	4.2	Pass
	9	2452	-20.89	4.77	-16.12	4.2	Pass

NOTE: Directional gain = $5.03\text{dBi} + 10\log(3) = 9.8\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8-(9.8-6) = 4.2\text{dBm}$.




4.7 Conducted Out of Band Emission Measurement

4.7.1 Limits of Conducted Out of Band Emission Measurement

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.7.7 Test Results


The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement.

Mode A


802.11b






802.11g


CH 1




CH 6



CH 11







802.11n (20MHz)

1Tx


CH 1




CH 6




CH 11







2Tx


CHAIN 0






CHAIN 1
CH 1



A D T




A D T

CH 6



A D T




A D T







CH 11



A D T










A D T







3Tx
CHAIN 0
CH 1

CH 6

CH 11




CHAIN 1
CH 1

CH 6

CH 11






CHAIN 2
CH 1

CH 6

CH 11




802.11n (40MHz)


1Tx










2Tx

CHAIN 0







CHAIN 1
CH 3

CH 6

CH 9






3Tx







CHAIN 0










CHAIN 1




CHAIN 2
CH 3

CH 6

CH 9





Mode B
802.11b
CH 1

CH 6

CH 11





802.11g


CH 1




CH 6




CH 11






802.11n (20MHz)


1Tx







2Tx


CHAIN 0






CHAIN 1
CH 1



A D T




A D T

CH 6



A D T




A D T

CH 11


A D T





A D T










3Tx







CHAIN 0






CHAIN 1
CH 1

CH 6

CH 11






CHAIN 2
CH 1

CH 6

CH 11




802.11n (40MHz)


1Tx










2Tx


CHAIN 0










CHAIN 1
CH 3

CH 6

CH 9











3Tx
CHAIN 0




CHAIN 1
CH 3

CH 6

CH 9




CHAIN 2
CH 3

CH 6

CH 9




5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---