



# RF Exposure Evaluation

## REPORT

For

### **Guard RFID Solutions Inc.**

#140 – 766 Cliveden Place  
Delta, British Columbia  
V3M 6C7, Canada

Date: 24 August 2023  
Project No.: 22039  
FCC ID: VZKPT4  
IC ID.: 9937A-PT4  
Equipment: Patient Tag  
Model No.: PT-4

*Labtest Certification*

**ONE STOP GLOBAL CERTIFICATION SOLUTIONS**

ISO 17020 Accredited

ISO 17025 accredited

ISO 17065 Accredited

Unit 205 – 8291 92 ST., Delta, BC  
V4G 0A4, Canada  
Phone: 604-247-0444  
Fax: 604-247-0442  
[www.labtestcert.com](http://www.labtestcert.com)

## KDB 447498 D01

### General RF Exposure Guidance v06, section 4.3.1 (a)

For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

#### Calculation:

Information of the EUT is added in the below table.

Frequency (MHz)	Conducted Output Peak Power (dBm)	Conducted Output Peak Power (mW)	Min Test Separation Distance (mm)
2400-2483.5	5.53	3.57	5

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 1.125 \leq 3$

#### Conclusions

The SAR test exclusion thresholds are met.