

## MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### STANDARD APPLICABLE

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

### Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

\* = Plane-wave equipment power density

**MAXIMUM PERMISSIBLE EXPOSURE (MPE) EVALUATION**

**802.11b (Aux)**

		<b>Peak Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>1</b>	
<b>1</b>	<b>2412</b>	<b>24.76</b>	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	24.47	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2462</b>	24.73	<b>1 Watt = 30 dBm</b>

		<b>Average Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>1</b>	
<b>1</b>	<b>2412</b>	21.97	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	21.87	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2462</b>	<b>21.99</b>	<b>1 Watt = 30 dBm</b>

*\*Note: Measured by power meter, cable loss as 11dB that offsets on the power meter.*

**MPE Prediction (802.11b (Main) )**

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum average output power at antenna input	21.99	(dBm)
Maximum average output power at antenna input	158.1248039	(mW)
Duty cycle:	100	(%)
Maximum Pav :	158.1248039	(mW)
Antenna gain (typical):	2.36	(dBi)
Maximum antenna gain:	1.721868575	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2462	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.054194	(mW/cm <sup>2</sup> )

### Measurement Result

The predicted power density level at 20 cm is 0.05419mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1mW/cm<sup>2</sup> at 2462MHz.

**802.11g (Aux)**

		<b>Peak Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>6</b>	
<b>1</b>	<b>2412</b>	24.72	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	<b>24.83</b>	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2462</b>	24.64	<b>1 Watt = 30 dBm</b>

		<b>Average Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>6</b>	
<b>1</b>	<b>2412</b>	<b>14.86</b>	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	14.69	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2462</b>	14.50	<b>1 Watt = 30 dBm</b>

*\*Note: Measured by power meter, cable loss as 11dB that offsets on the power meter.*

### MPE Prediction (802.11g (Main) )

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum average output power at antenna input	14.86	(dBm)
Maximum average output power at antenna input	30.61963434	(mW)
Duty cycle:	100	(%)
Maximum Pav :	30.61963434	(mW)
Antenna gain (typical):	2.36	(dBi)
Maximum antenna gain:	1.721868575	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2412	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.010494	(mW/cm <sup>2</sup> )

### Measurement Result

The predicted power density level at 20 cm is 0.0105mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1mW/cm<sup>2</sup> at 2412MHz.

**802.11n\_20M (MIMO Chain 0+1)**

		<b>Peak Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>MCS8</b>	
<b>1</b>	<b>2412</b>	<b>26.69</b>	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	26.61	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2462</b>	26.42	<b>1 Watt = 30 dBm</b>

		<b>Average Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>MCS8</b>	
<b>1</b>	<b>2412</b>	<b>16.20</b>	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	16.13	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2462</b>	15.93	<b>1 Watt = 30 dBm</b>

*\*Note: Measured by power meter, cable loss as 14dB that offsets on the power meter.*

### MPE Prediction (802.11 n\_20M (MIMO Chain 0+1) )

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum average output power at antenna input	16.2	(dBm)
Maximum average output power at antenna input	41.68693835	(mW)
Duty cycle:	100	(%)
Maximum Pav :	41.68693835	(mW)
Antenna gain (typical):	4.7	(dBi)
Maximum antenna gain:	2.951209227	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2412	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.024488	(mW/cm <sup>2</sup> )

### Measurement Result

The predicted power density level at 20 cm is 0.0243mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1mW/cm<sup>2</sup> at 2412MHz.

**802.11n\_40M (MIMO Chain 0+1)**

		<b>Peak Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>MCS8</b>	
<b>1</b>	<b>2422</b>	<b>26.59</b>	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	26.49	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2452</b>	26.48	<b>1 Watt = 30 dBm</b>

		<b>Average Power Output (dBm)</b>	
<b>CH</b>	<b>Frequency (MHz)</b>	<b>Data Rate</b>	<b>Required Limit</b>
		<b>MCS8</b>	
<b>1</b>	<b>2422</b>	<b>15.91</b>	<b>1 Watt = 30 dBm</b>
<b>6</b>	<b>2437</b>	15.74	<b>1 Watt = 30 dBm</b>
<b>11</b>	<b>2452</b>	15.88	<b>1 Watt = 30 dBm</b>

*\*Note: Measured by power meter, cable loss as 14dB that offsets on the power meter.*



**MPE Prediction (802.11 n\_40M (MIMO Chain 0+1))**

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum average output power at antenna input	15.91	(dBm)
Maximum average output power at antenna input	38.99419867	(mW)
Duty cycle:	100	(%)
Maximum Pav :	38.99419867	(mW)
Antenna gain (typical):	4.7	(dBi)
Maximum antenna gain:	2.951209227	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2422	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.022906	(mW/cm <sup>2</sup> )

**Measurement Result**

The predicted power density level at 20 cm is 0.0229mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1mW/cm<sup>2</sup> at 2452MHz.