

## iSCAN™ User's Manual

### Background.

The iSCAN™ is 2.4GHz bi-directional radio transceiver equipped with a CCD barcode scan engine and status LCD screen. A User may configure the device to execute a number of commands based on the type and content of Code-128 or Code-39 encoded barcodes. The iSCAN™ may interact with iControl iTAG™ or iCHIME™ products through the Marine Asset Tag Tracking System (MATTs) communication protocol to build a sensor network, the purpose of which is to support tracking shipping containers in a worldwide supply chain. An iSCAN™ utilizes a low power, wireless, radio operating in the 2.4 GHz band as its primary mode of communication. The wireless radio operates in compliance with IEEE Standard 802.15.4-2006. The iSCAN™ utilizes the same radio, processor, and User interface software as iControl's iTAG™ and iCHIME™ products. The iSCAN™ also supports the same command list as iControl's iTAG™.

The iSCAN™ features two pushbuttons that cycle through and select menu options on the LCD screen, as well as a push-and-hold trigger to initiate a barcode scan. There are no other connections except the battery charging contacts. All iSCAN™s should use an iControl provided charger.



Figure 1 iSCAN™ and Related Device

## **iSCAN™ Radio Operation.**

This section intentionally blank for long-term confidentiality purposes.

## **Other Features.**

In addition to the wireless radio, the iSCAN™ provides other features for system integration and use.

1. Various LED indicators reveal status information to a User, such as power on, low battery, active radio communications, and good or bad barcode scan.
2. An LCD screen reveals in-depth information to a User, such as scanned device barcode ID for verification, warehouse location, battery level, barcode scan status.
3. A push button trigger on the bottom of the iSCAN™ activates the barcode scan beam. This beam is active as long as the trigger is held but will deactivate on successful barcode scan.
4. There is an onboard temperature sensor integrated with iSCAN™. The default iSCAN™ status data packet includes the device temperature, radio signal strength, and battery status.
5. The iSCAN™ has non-volatile on board data storage which may collect data for later upload.
6. iSCAN™ provides date time stamps for all data. The onboard clock for the iSCAN™ is set to UTC by readers in the network.


## Functional Block Diagram.

The iSCAN™ module integrates a low power microprocessor and a 2.4Ghz radio. The iSCAN™ includes a software user interface for radio control and data transmission.

Please note that the iSCAN™ uses the same command list as the iTAG™ command list. For iSCAN™ command and control, please refer to the *iTAG™ Command List* for a complete description of commands that control the iSCAN™ wireless barcode scanner.

The iSCAN™ is equipped with an integrated trace antenna rated at 3.5 dBi. All mobile applications will utilize either the integral antenna provided with the iSCAN™ or an internal omni-directional antenna rated on 4.4 dBi.

**NOTE: Users may not modify the antenna or its connection in anyway or risk violating radio law.**




**Figure 2 iSCAN™ Block Diagram**

## Absolute Maximum Ratings.

Under no circumstances must the absolute maximum ratings giving in this table be violated. Stress exceeding one or more of the limiting values may cause permanent damage to the device.

Parameter	Min	Max	Units	Condition
Charger Supply Voltage	4.5	6.3	V	Users must utilize an iControl provided charging cradle for the iSCAN™. Polarity protected. Onboard LI controller.
Voltage on any digital pin	-0.3	3.6	V	N/A
Input RF level		10	dBm	
Storage temperature range	-50	150	C	
Operating ambient temperature	-20	50	C	

Figure 3 Maximum Ratings



**Caution!** ESD sensitive device.  
Precaution should be used when handling  
the device in order to prevent permanent  
damage.

## General Characteristics.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Power mode 1 → active	Digital regulator on, 16-MHz RCOSC and 32-MHz crystal oscillator off. Start-up of 16-MHz RCOSC		4		μs
Power mode 2 or 3 → active	Digital regulator off, 16-MHz RCOSC and 32-MHz crystal oscillator off. Start-up of regulator and 16-MHz RCOSC		0.1		ms
Active → TX or RX	Initially running on 16-MHz RCOSC, with 32-MHz XOSC OFF		0.5		ms
	With 32-MHz XOSC initially on			192	μs
RX/TX and TX/RX turnaround				192	μs
<b>RADIO PART</b>					
RF frequency range (1)	Programmable in 1-MHz steps, 5 MHz between channels for compliance with [1]	2394		2507	MHz
Radio baud rate	As defined by [1]		250		kbps
Radio chip rate	As defined by [1]		2		MChip/s
Flash erase cycles				20	k cycles
Flash page size			2		KB

(1) Programmable in 5MHz steps starting at 2405MHz per IEEE 802.15.4

## iSCAN™ Radio Specification (Transmit).

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Nominal output power	Delivered to a single-ended 50-Ω load through a balun using maximum-recommended output-power setting [1] requires minimum -3 dBm	7.3	20	21.9	dBm
Programmable output power range			32		dB
Spurious emissions	Max recommended output power setting <sup>(1)</sup>				
Measured conducted according to stated regulations. Only largest spurious emission stated within each band.	25 MHz–1000 MHz (outside restricted bands)		-60		dBm
	25 MHz–2400 MHz (within FCC restricted bands)		-60		
	25 MHz–1000 MHz (within ETSI restricted bands)		-60		
	1800–1900 MHz (ETSI restricted band)		-57		
	5150–5300 MHz (ETSI restricted band)		-55		
	At $2 \times f_c$ and $3 \times f_c$ (FCC restricted band)		-42		
	At $2 \times f_c$ and $3 \times f_c$ (ETSI EN 300-440 and EN 300-328) <sup>(2)</sup>		-31		
1 GHz–12.75 GHz (outside restricted bands)		-53			
At 2483.5 MHz and above (FCC restricted band)					
	$f_c = 2480$ MHz <sup>(3)</sup>		-42		
Optimum load impedance	Differential impedance as seen from the RF port (RF_P and RF_N) towards the antenna		69 + j29		Ω
Parameter	Condition	Typical		Unit	
Emission with TXPOWER = 0xE5	Conducted 2•RF (FCC restricted band)	-51.8		dBm	
	Conducted 3•RF (FCC restricted band)	-49.5			
Max Error Vector Magnitude (EVM)	IEEE 802.15.4 requires max. 35% Measured as defined by IEEE 802.15.4	TXPOWER = 0xF5, f = IEEE 802.15.4 channels	17		%
		TXPOWER = 0xE5, f = IEEE 802.15.4 channels	12.5		
		TXPOWER = 0xD5, f = IEEE 802.15.4 channels	7.8		
		TXPOWER = 0xC5, f = IEEE 802.15.4 channels	4.4		

## iSCAN™ Radio Specification (Receive).

Parameter	Condition	Typical	Unit
Receive Sensitivity HGM	1 % PER, IEEE 802.15.4 requires -85 dBm	-99	dBm
Receive Sensitivity LGM	1 % PER, IEEE 802.15.4 requires -85 dBm	-95.5	
Saturation HGM	IEEE 802.15.4 requires -20 dBm	-2	
Saturation LGM	IEEE 802.15.4 requires -20 dBm	-1	

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Adjacent-channel rejection, 5-MHz channel spacing	Wanted signal -82 dBm, adjacent modulated channel at 5 MHz, PER = 1 %, as specified by [1]. [1] requires 0 dB		49		dB
Adjacent-channel rejection, -5-MHz channel spacing	Wanted signal -82 dBm, adjacent modulated channel at -5 MHz, PER = 1 %, as specified by [1]. [1] requires 0 dB		49		dB
Alternate-channel rejection, 10-MHz channel spacing	Wanted signal -82 dBm, adjacent modulated channel at 10 MHz, PER = 1%, as specified by [1] [1] requires 30 dB		57		dB
Alternate-channel rejection, -10-MHz channel spacing	Wanted signal -82 dBm, adjacent modulated channel at -10 MHz, PER = 1 %, as specified by [1] [1] requires 30 dB		57		dB
Channel rejection ≥ 20 MHz ≤ -20 MHz	Wanted signal at -82 dBm. Undesired signal is an IEEE 802.15.4 modulated channel, stepped through all channels from 2405 to 2480 MHz. Signal level for PER = 1%.		57 57		dB
Co-channel rejection	Wanted signal at -82 dBm. Undesired signal is 802.15.4 modulated at the same frequency as the desired signal. Signal level for PER = 1 %.		-3		dB
Blocking/desensitization 5 MHz from band edge 10 MHz from band edge 20 MHz from band edge 50 MHz from band edge -5 MHz from band edge -10 MHz from band edge -20 MHz from band edge -50 MHz from band edge	Wanted signal 3 dB above the sensitivity level, CW jammer, PER = 1%. Measured according to EN 300 440 class 2.		-33 -33 -32 -31 -35 -35 -34 -34		dBm
Spurious emission. Only largest spurious emission stated within each band. 30 MHz-1000 MHz 1 GHz-12.75 GHz	Conducted measurement with a 50-Ω single-ended load. Suitable for systems targeting compliance with EN 300 328, EN 300 440, FCC CFR47 Part 15 and ARIB STD-T-86.		< -80 -57		dBm
Frequency error tolerance <sup>(1)</sup>	[1] requires minimum 80 ppm		±150		ppm
Symbol rate error tolerance <sup>(2)</sup>	[1] requires minimum 80 ppm		±1000		ppm

(1) Difference between center frequency of the received RF signal and local oscillator frequency.

(2) Difference between incoming symbol rate and the internally generated symbol rate

## Module Unique Address Identification.

Each iSCAN™ is assigned a unique 8 byte MAC address by iControl Incorporated. The MAC address is used for radio network address identification. The MAC address can not be modified by the User and is located in protected flash memory. Figure 5 depicts the communication protocol between iControl iSCAN™ and the iGATE™ reader. The communication protocol utilizes a unique 8 byte MAC address defined by the IEEE 802.15.4 standard.

In Figure 5,

The iSCAN™ address is (0x0035A92300000002).

The iGATE™ address is (0x0035A9230A010203)

Time (us)	Length	Frame control field	Sequence number	Dest. PAN	Dest. Address	Source PAN	Source Address	Other Fields	LOI	FCS		
+14059534 =1623495352	10	Type Sec Pnd Ack req Intra PAN CMD 0 0 0 0 0	0x00	0x0A01	0xFFFF			Beacon request	76	OK		
+865690 =1624361042	22	Type Sec Pnd Ack req Intra PAN BCN 0 0 0 0 0	0x12	0x0203	0x0A01	0x0203	0x0A01	Superframe specification B0 S0 F.CAP BLE Coord Assoc 15 15 00 0 1 1	GTS fields Len Permit 0 0	Beacon payload 00 01 08 06 00 00 09 00 F0	LOI 112	FCS OK
+50141 =1624411183	21	Type Sec Pnd Ack req Intra PAN CMD 0 0 1 0 0	0x01	0x0203	0x0A01	0x0002	0x0035A92300000002	Association request Alt.coord FFD Power Idle RX Sec Alloc addr 0 0 1 0 0 1			LOI 76	FCS OK
+51111 =1624462294	29	Type Sec Pnd Ack req Intra PAN CMD 0 0 1 0 0	0x13	0x0203	0x0035A92300000002	0x0203	0x0035A9230A010203	Association response Short addr Assoc. status 0x0002 Successful			LOI 112	FCS OK
+965869 =1625428163	60	Type Sec Pnd Ack req Intra PAN DATA 0 0 0 0 0	0x02	0x0203	0x0A01	0x0203	0x0035A92300000002	MAC payload 70 0C 01 08 06 00 00 09 00 02 01 48 09 3A 09 49 09 72 09 CB 09 68 09 AE 09 6E 09 28 03 09 05 29 06 FF 07 06 6E 00 00 00 00			LOI 76	FCS F
+4062306 =1629490469	60	Type Sec Pnd Ack req Intra PAN DATA 0 0 0 0 0	0x03	0x0203	0x0A01	0x0203	0x0035A92300000002	MAC payload 70 0C 01 08 06 00 00 09 04 03 05 92 01 0F 04 86 05 52 06 7C 07 3D 08 B6 08 F1 08 25 03 0A 05 1D 06 FF 07 06 6A 00 00 00 00			LOI 76	FCS F

Figure 5

## FCC Compliance:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

## Troubleshooting:

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

1. Reorient or relocate the receiving antenna.
2. Increase the separation between the equipment and receiver.
3. Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
4. Consult the dealer or an experienced radio/TV technician.

## Conditions:

Operation is subject to the following two conditions:

1. This device may not cause harmful interference
2. This device must accept any interference received, including interference that may cause undesired operation.

## Markings:

To satisfy FCC exterior labeling requirements the following text must be placed on the exterior of the product. FCC ID: **FCC ID: W2E-ISCAN10**








Figure 2 iSCAN™ FCC Label Location

## FCC Warnings:

**Modifications:** Modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment under FCC Rules.

## Radio Frequency Exposure:

### Notes:

- 1) For mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculators indicate the MPE distance is less.
- 2) This equipment has been evaluated in accordance with the FCC bulletin 56 "Hazards of radio frequency and electromagnetic fields" and bulletin 65 " Human exposure to radio frequency and electromagnetic fields.

## NCC 警語

- 減少電磁波影響，請妥適使用

(For Reducing RF Influence, Use Properly)

- 為維護隱私權，請妥適使用

(For protect individual privacy, Use Properly)

- 本器材須經專業工程人員安裝及設定，始得設置使用，且不得直接販售給一般消費者。

(This device must be installed by expert and will not be sold directly to the general public through retail store)

- 低功率電波輻射性電機管理辦法

第十二條

經型式認證合格之低功率射頻電機，非經許可，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性及功能。

第十四條

低功率射頻電機之使用不得影響飛航安全及干擾合法通信；經發現有干擾現象時，應立即停用，並改善至無干擾時方得繼續使用。

前項合法通信，指依電信法規定作業之無線電通信。

低功率射頻電機須忍受合法通信或工業、科學及醫療用電波輻射性電機設備之干擾。

### WARNING

Administrative Regulations on Low Power Radio Waves Radiated Devices warning:

Article 12

Without permission granted by the NCC, any company, enterprise, or user is not allowed to change frequency, enhance transmitting power or alter original characteristic as well as performance to an approved low power radio-frequency devices.

Article 14

The low power radio-frequency devices shall not influence aircraft security and interfere legal communications; If found, the user shall cease operating immediately until no interference is achieved.

The said legal communications means radio communications is operated in compliance with the Telecommunications Act.

The low power radio-frequency devices must be susceptible with the interference from legal communications or ISM radio wave radiated devices.