



SAR TEST REPORT

Test Report No.: 11143373S-C

Applicant : FUJIFILM Corporation
Type of Equipment : Flat Panel Sensor
Model No. : RIC 24C (*. With built-in wireless LAN module)
FCC ID : W2Z-01000007
Test Standard : FCC 47CFR §2.1093
Test Result : Complied

Highest Reported SAR(1g) Value	SAR type	Operation Band [MHz]	Remarks
0.16 W/kg	Body	2412~2462	(DTS) Antenna#0, 2417MHz, 11g(6Mbps), Output power: 18.52 dBm
0.18 W/kg	Head		(DTS) Antenna#0, 2417MHz, 11g(6Mbps), Output power: 18.52 dBm
0.18 W/kg	Body	5180~5320, 5500~5700, 5745~5825	(UNII) Antenna#0, 5500 MHz, 11a (6Mbps), Output power: 15.99 dBm
0.19 W/kg	Head		(UNII) Antenna#0, 5500 MHz, 11a (6Mbps), Output power: 15.99 dBm

- *. **The highest reported SAR (1g) value across all exposure condition is "0.19 W/kg" = grant listing.**
- *. **Co-location was not considered, because the SLLSR (SAR to peak location separation ratio) was smaller than 0.04.**

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.
7. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)

Date of test: February 3~23, 2016

Test engineer: H. Naka
Hiroshi Naka
Engineer, Consumer Technology Division

Approved by: T. Imamura
Toyokazu Imamura
Leader, Consumer Technology Division

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
- There is no testing item of "Non-accreditation".



REVISION HISTORY

Revision	Test report No.	Date	Page revised	Contents
Original	11143373S-C	April 25, 2016	-	-
-r01	11143373S-C	July 13, 2017	p1,2,3	(p3) Corrected writing error.

*. By issue of new revision report, the report of an old revision becomes invalid.

CONTENTS

PAGE

REVISION HISTORY..... 2
CONTENTS 2
SECTION 1: Customer information 3
SECTION 2: Equipment under test (EUT)..... 3
 2.1 Identification of EUT 3
 2.2 Product Description (Wireless LAN module, antenna) 3
 2.3 Tx output power (typical) specification (antenna port terminal conducted)..... 4
 2.4 Maximum output power which may possible 5
SECTION 3: Test specification, procedures and results 6
 3.1 Test specification 6
 3.2 Exposure limit 6
 3.3 Procedure and result 6
 3.4 Test location 7
 3.5 Confirmation before SAR testing 7
 3.6 Confirmation after SAR testing 7
 3.7 Test setup of EUT and SAR measurement procedure 7
SECTION 4: Operation of EUT during SAR testing..... 9
SECTION 5: Uncertainty assessment (SAR measurement)..... 10
SECTION 6: Confirmation before testing 11
 6.1 Assessment for the antenna terminal port conducted power of EUT 11
SECTION 7: SAR Measurement results..... 14
 7.1 Liquid measurement 14
 7.2 SAR measurement results (Body) 15
 7.3 SAR measurement results (Head)..... 16

Contents of appendixes

APPENDIX 1: Photographs of test setup 17
 Appendix 1-1 Photograph of EUT and antenna position 17
 Appendix 1-2 Antenna position 18
 Appendix 1-3 EUT and support equipment..... 19
 Appendix 1-4 Photograph of SAR test setup 20
APPENDIX 2: SAR Measurement data..... 22
 Appendix 2-1 Evaluation procedure..... 22
 Appendix 2-2 Measurement data..... 23
APPENDIX 3: Test instruments..... 67
 Appendix 3-1 Equipment used 67
 Appendix 3-2 Configuration and peripherals 68
 Appendix 3-3 Test system specification..... 69
 Appendix 3-4 Simulated tissues composition and parameter confirmation 70
 Appendix 3-5 Daily check results 70
 Appendix 3-6 Daily check uncertainty 71
 Appendix 3-7 Daily check measurement data 72
 Appendix 3-8 Calibration certificate: E-Field Probe (EX3DV4) 77
 Appendix 3-9 Calibration certificate: Dipole (D2450V2)..... 88
 Appendix 3-10 Calibration certificate: Dipole (D5GHzV2) 96

SECTION 1: Customer information

Company Name	FUJIFILM Corporation
Address	9-7-3 Akasaka Minato-ku, Tokyo 107-0052, Japan
Telephone Number	81-3-6271-1654
Facsimile Number	81-3-6271-1189
Contact Person	Takao Ozaki

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

Type of Equipment	Flat Panel Sensor
Model Number	RIC 24C
Serial Number	#001
Condition of EUT	Engineering prototype (*. Not for sale. This sample is equivalent to mass-production items)
Receipt Date of Sample	February 1, 2016 (*. No modification by the Lab.) (*. The Wireless LAN Module (model: SX-PCEAN(FF-E)) that had been measured the SAR test reference power, was installed into the EUT by the Lab.)
Country of Mass-production	Taiwan
Rating	DC8V
Category Identified	Portable device (*. Since EUT may contact and/or very close to a human body and head during Wi-Fi operation, the partial-body SAR (1g) shall be observed.)
SAR Accessory	Any body-worn accessory was not applied.
Feature of EUT, SAR tested consideration	Model: RIC 24C (referred to as the EUT in this report) is a Flat Panel Sensor with a wireless function and used in the hospitality environment. Since the EUT is the medical device, this only used under the guidance of a doctor or a qualified person. The possibility of the maximum RF human exposure is only a body/head of the patient who comes in contact directly on the front surface side (patient side) of the EUT. Therefore, the SAR test was only considered to apply to the front surface (patient side) of the EUT.

2.2 Product Description (Wireless LAN module, antenna)

Equipment type	Transceiver						
Model	SX-PCEAN(FF-E)						
Frequency band	2.4GHz band		5GHz band				
			-	U-NII-1 (W52)	U-NII-2A (W53)	U-NII-2C (W56)	U-NII-3 (W58)
Frequency of operation (MHz) (*.ch.: channel)	11b.g, n(20HT)	2412-2462 (*.ch.1-11)	11a, n(20HT)	5180-5240 (*.ch.36-48)	5260-5320 (*.ch.52-64)	5500-5700 (*.ch.100-140)	5745-5825 (*.ch.149-165)
	n(40HT)	2422-2452 (*.ch.3-9)	n(40HT)	5190-5230 (*.ch.38-46)	5270-5310 (*.ch.54-62)	5510-5670 (*.ch.102-134)	5755, 5795 (*.ch.151,159)
Channel spacing (MHz)	5 (11b.g,n(20HT),n(40HT))		20 (11b.g,n(20HT)) / 40 (11n(40HT))				
Bandwidth (MHz)	20 (11b.g,n(20HT)) / 40 (11n(40HT))		20 (11b.g,n(20HT)) / 40 (11n(40HT))				
Type of modulation	DSSS: DBPSK, DQPSK, CCK (11b), OFDM: BPSK, QPSK, 16QAM, 64QAM (11g,a,n(20HT),n(40HT))						
Transmit power (typical, maximum channel and data rate) and tolerance (as manufacture variation) (dBm) (*.ch.: channel)	11b	13.5±2.5 (*.ch.1-11, 1-11Mbps)	11a:	12.5±2.5 (*.ch.36-48, 6-54Mbps)	12.5±2.5 (*.ch.52-64, 6-54Mbps)	15.0±2.5 (*.ch.100-140, 6-48Mbps)	15.0±2.5 (*.ch.149-165, 6-48Mbps)
	11g	17.0±2.5 (*.ch.2, 6-36Mbps)					
	n(20HT)	14.5±2.5 (*.ch.2, MCS0-4/8-12)	n(20HT)	11.0±2.5 (*.ch.36-48, MCS0-6/8-14)	11.0±2.5 (*.ch.52-64, MCS0-6/8-14)	13.5±2.5 (*.ch.100-140, MCS0-4/8-12)	13.5±2.5 (*.ch.149-165, MCS0-4/8-12)
	n(40HT)	13.5±2.5 (*.ch.4, MCS0-4/8-12)	n(40HT)	11.0±2.5 (*.ch.46, MCS0-7/8-15)	11.0±2.5 (*.ch.54, MCS0-7/8-15)	11.0±2.5 (*.ch.102-134, MCS0-5/8-13)	11.0±2.5 (*.ch.151,159, MCS0-5/8-13)
*. The value in a table shows the maximum power conditions of typical on each antenna. *. 3dBm is added to MIMO power. *. Refer to clause 2.3 for more detail. Refer to clause 2.4 for the maximum output power which may possible. *. The measured Tx output power (conducted) refers to section 6 in this report.							
Power supply	DC 3.3V (*. DC3.3V is supplied from the main unit via constant voltage circuit.)						
Antenna	antenna #0 (Bottom, short-side-ant#0)			antenna #1 (Side, long-side-ant#1)			
Antenna quantity	2 pcs. (*. Separation distance between the antenna #0 and the antenna #1: approx.315 mm) 11b.g.a: One selected Tx antenna operation. 11n(20HT),n(40HT): One selected Tx antenna operation (MCS0~7) / Two Tx antenna operation (MCS8~13)						
Antenna model	113Y120216 (cable length: 300 mm)			113Y120216 (cable length: 300 mm)			
Antenna type / connector type	Monopole antenna / Connector; PCB side: UFL, Antenna side: soldered						
Antenna gain (max.peak) (*.including cable loss)	-7.3 dBi (2.4GHz), -2.3 dBi (5GHz) (*.installed into the platform)			-6.5 dBi (2.4GHz), -0.3 dBi (5GHz) (*.installed into the platform)			

*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

2.3 Tx output power (typical) specification (antenna port terminal conducted)

		Target Power [dBm] (average)																																	
		11b				11g								11n(20HT)																					
[MHz]	CH	1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15						
2412	1	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5		
2417	2	13.5	13.5	13.5	13.5	17	17	17	17	17	17	16	15	14.5	14.5	14.5	14.5	14.5	14	13.5	13	13.5	13	17.5	17.5	17.5	17.5	17.5	17	16.5	16	16.5	16		
2422	3	13.5	13.5	13.5	13.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	15	14	14	14	14	14	13.5	13	12.5	17	17	17	17	17	17	16.5	16	15.5	15	15.5	15		
2427	4	13.5	13.5	13.5	13.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	15	13.5	13.5	13.5	13.5	13.5	13	12.5	12	16.5	16.5	16.5	16.5	16.5	16	15.5	15	15.5	15	15.5	15		
2432	5	13.5	13.5	13.5	13.5	16	16	16	16	16	16	15.5	15	13	13	13	13	13	12.5	12.5	12	16	16	16	16	16	15.5	15.5	15	15.5	15	15.5	15		
2437	6	13.5	13.5	13.5	13.5	16	16	16	16	16	16	15.5	15	12.5	12.5	12.5	12.5	12.5	12	12	11.5	15.5	15.5	15.5	15.5	15.5	15	15	14.5	14	14.5	14	14.5	14	
2442	7	13.5	13.5	13.5	13.5	15.5	15.5	15.5	15.5	15.5	15.5	15	15	12	12	12	12	12	12	11.5	11.5	15	15	15	15	15	15	14.5	14	14.5	14	14.5	14		
2447	8	13.5	13.5	13.5	13.5	15.5	15.5	15.5	15.5	15.5	15.5	15	15	11.5	11.5	11.5	11.5	11.5	11.5	11.5	11	14.5	14.5	14.5	14.5	14.5	14.5	14.5	14	14.5	14	14.5	14		
2452	9	13.5	13.5	13.5	13.5	15	15	15	15	15	15	15	15	11	11	11	11	11	11	11	11	14	14	14	14	14	14	14	14	14	14	14	14	14	
2457	10	13.5	13.5	13.5	13.5	15	15	15	15	15	15	15	15	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	
2462	11	13.5	13.5	13.5	13.5	15	15	15	15	15	15	15	15	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5

		Target Power [dBm] (average)																								
		11a				11n(20HT)																				
[MHz]	CH	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
5180	36	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5200	40	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5220	44	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5240	48	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5260	52	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5280	56	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5300	60	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5320	64	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	11	11	11	11	11	11	11	10.5	14	14	14	14	14	14	14	14	13.5
5500	100	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5520	104	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5540	108	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5560	112	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5580	116	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5600	120	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5620	124	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5640	128	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5660	132	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5680	136	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5700	140	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5745	149	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5765	153	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5785	157	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5805	161	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	
5825	165	15	15	15	15	15	15	15	14	13.5	13.5	13.5	13.5	13.5	12.5	10.5	8.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5	11.5	

		Target Power [dBm] (average)															
		11n(40HT)															
[MHz]	CH	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2422	3	6	6	6	6	6	6	6	6	9	9	9	9	9	9	9	9
2427	4	13.5	13.5	13.5	13.5	13.5	13	12.5	12	16.5	16.5	16.5	16.5	16.5	16	15.5	15
2432	5	12	12	12	12	12	11	11	11	15	15	15	15	15	14	14	14
2437	6	10.5	10.5	10.5	10.5	10.5	10.5	10	10	13.5	13.5	13.5	13.5	13.5	13.5	13	13
2442	7	9.5	9.5	9.5	9.5	9.5	9	9	9	12.5	12.5	12.5	12.5	12.5	12	12	12
2447	8	8	8	8	8	8	8	8	8	11	11	11	11	11	11	11	11
2452	9	7	7	7	7	7	7	7	7	10	10	10	10	10	10	10	10
5190	38	10	10	10	10	10	10	10	10	13	13	13	13	13	13	13	13
5230	46	11	11	11	11	11	11	11	11	14	14	14	14	14	14	14	14
5270	54	11	11	11	11	11	11	11	11	14	14	14	14	14	14	14	14
5310	62	10	10	10	10	10	10	10	10	13	13	13	13	13	13	13	13
5510	102	11	11	11	11	11	11	10	8	14	14	14	14	14	14	13	11
5550	110	11	11	11	11	11	11	10	8	14	14	14	14	14	14	13	11
5590	118	11	11	11	11	11	11	10	8	14	14	14	14	14	14	13	11
5630	126	11	11	11	11	11	11	10	8	14	14	14	14	14	14	13	11
5670	134	11	11	11	11	11	11	10	8	14	14	14	14	14	14	13	11
5755	151	11	11	11	11	11	11	10	8	14	14	14	14	14	14	13	11
5795	159	11	11	11	11	11	11	10	8	14	14	14	14	14	14	13	11

2.4. Maximum output power which may possible

		Maximum output power which may possible [dBm] (average)																												
		11b				11g								11n(20HT)																
[MHz]	CH	1	2	5.5	11	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15	
2412	1	16	16	16	16	16	16	16	16	16	16	16	16	13	13	13	13	13	13	13	13	16	16	16	16	16	16	16	16	
2417	2	16	16	16	16	19.5	19.5	19.5	19.5	19.5	19.5	19.5	18.5	17.5	17	17	17	17	17	16.5	16	15.5	20	20	20	20	20	19.5	19	18.5
2422	3	16	16	16	16	19	19	19	19	19	19	18	17.5	16.5	16.5	16.5	16.5	16.5	16	15.5	15	19.5	19.5	19.5	19.5	19.5	19	18.5	18	
2427	4	16	16	16	16	19	19	19	19	19	19	18	17.5	16	16	16	16	16	15.5	15	14.5	19	19	19	19	19	18.5	18	17.5	
2432	5	16	16	16	16	18.5	18.5	18.5	18.5	18.5	18.5	18	17.5	15.5	15.5	15.5	15.5	15.5	15	15	14.5	18.5	18.5	18.5	18.5	18.5	18	18	17.5	
2437	6	16	16	16	16	18.5	18.5	18.5	18.5	18.5	18.5	18	17.5	15	15	15	15	15	14.5	14.5	14	18	18	18	18	18	17.5	17.5	17	
2442	7	16	16	16	16	18	18	18	18	18	18	17.5	17.5	14.5	14.5	14.5	14.5	14.5	14.5	14	14	17.5	17.5	17.5	17.5	17.5	17.5	17	17	
2447	8	16	16	16	16	18	18	18	18	18	18	17.5	17.5	14	14	14	14	14	14	14	14	17.5	17.5	17.5	17.5	17.5	17	17	16.5	
2452	9	16	16	16	16	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5	
2457	10	16	16	16	16	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	13	13	13	13	13	13	13	13	16	16	16	16	16	16	16	16	
2462	11	16	16	16	16	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	13	13	13	13	13	13	13	13	16	16	16	16	16	16	16	16	

		Maximum output power which may possible [dBm] (average)																							
		11a								11n(20HT)															
[MHz]	CH	6	9	12	18	24	36	48	54	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
5180	36	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5200	40	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5220	44	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5240	48	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5260	52	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5280	56	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5300	60	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5320	64	15	15	15	15	15	15	15	15	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16
5500	100	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5520	104	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5540	108	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5560	112	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5580	116	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5600	120	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5620	124	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5640	128	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5660	132	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5680	136	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5700	140	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5745	149	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5765	153	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5785	157	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5805	161	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14
5825	165	17.5	17.5	17.5	17.5	17.5	17.5	17.5	16.5	16	16	16	16	16	15	13	11	19	19	19	19	19	18	16	14

		Maximum output power which may possible [dBm] (average)															
		11n(40HT)															
[MHz]	CH	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
2422	3	8.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	11.5	11.5	11.5	11.5	11.5	11.5	11.5	11.5
2427	4	16	16	16	16	16	15.5	15	14.5	19	19	19	19	18.5	18	17.5	
2432	5	14.5	14.5	14.5	14.5	14.5	13.5	13.5	13.5	17.5	17.5	17.5	17.5	17.5	16.5	16.5	16.5
2437	6	13	13	13	13	13	13	12.5	12.5	16	16	16	16	16	15.5	15.5	
2442	7	12	12	12	12	12	11.5	11.5	11.5	15	15	15	15	15	14.5	14.5	14.5
2447	8	10.5	10.5	10.5	10.5	10.5	10.5	10.5	10.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5
2452	9	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5
5190	38	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5
5230	46	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5
5270	54	13.5	13.5	13.5	13.5	13.5	13.5	13.5	13.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5	16.5
5310	62	12.5	12.5	12.5	12.5	12.5	12.5	12.5	12.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5	15.5
5510	102	13.5	13.5	13.5	13.5	13.5	13.5	12.5	10.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5
5550	110	13.5	13.5	13.5	13.5	13.5	13.5	12.5	10.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5
5590	118	13.5	13.5	13.5	13.5	13.5	13.5	12.5	10.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5
5630	126	13.5	13.5	13.5	13.5	13.5	13.5	12.5	10.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5
5670	134	13.5	13.5	13.5	13.5	13.5	13.5	12.5	10.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5
5755	151	13.5	13.5	13.5	13.5	13.5	13.5	12.5	10.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5
5795	159	13.5	13.5	13.5	13.5	13.5	13.5	12.5	10.5	16.5	16.5	16.5	16.5	16.5	16.5	15.5	13.5

SECTION 3: Test specification, procedures and results

3.1 Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. The device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling in accordance with the following measurement procedures..

KDB 447498 D01 (v06):	General RF exposure guidance
KDB 248227 D01 (v02r02):	SAR Guidance for IEEE 802.11 (Wi-Fi) transmitters
KDB 865664 D01 (v01r04):	SAR measurement 100MHz to 6GHz
IEEE Std. 1528-2013:	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

3.2 Exposure limit

Environments of exposure limit	Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
(A) Limits for Occupational /Controlled Exposure (W/kg)	0.4	8.0	20.0
(B) Limits for General population /Uncontrolled Exposure (W/kg)	0.08	1.6	4.0

*. **Occupational/Controlled Environments:** are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

*. **General Population/Uncontrolled Environments:** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is;

General population / uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: 1.6 W/kg

3.3 Procedures and Results

Test Procedure	Wi-Fi (DTS) (2412-2462MHz)		Wi-Fi (U-NII-1) (5180-5240MHz)(W52)		Wi-Fi (U-NII-2A) (5260-5320MHz)(W53)		Wi-Fi (U-NII-2C) (5500-5700MHz)(W56)		Wi-Fi (U-NII-3) (5745-5825MHz)(W58)	
	ant#0	ant#1	ant#0	ant#1	ant#0	ant#1	ant#0	ant#1	ant#0	ant#1
Category	SAR measurement; KDB 447498, KDB 248227, KDB 865664, IEEE Std.1528									
Category	FCC 47CFR §2.1093 (Portable device)									
Results (SAR(1g))	Complied		Complied		Complied		Complied		Complied	
Antenna#	ant#0	ant#1	ant#0	ant#1	ant#0	ant#1	ant#0	ant#1	ant#0	ant#1
Liquid type	Body liquid									
Reported SAR value	0.16 W/kg	0.11 W/kg	0.14 W/kg	0.10 W/kg	0.11 W/kg	0.06 W/kg	0.18 W/kg	0.16 W/kg	0.12 W/kg	0.15 W/kg
Measured SAR value	0.129 W/kg	0.0693 W/kg	0.103 W/kg	0.0683 W/kg	0.0781 W/kg	0.0424 W/kg	0.129 W/kg	0.117 W/kg	0.0808 W/kg	0.106 W/kg
Operation mode, frequency[MHz]	11g(6Mbps), 2417	11g(6Mbps), 2417	11a(6Mbps), 5180	11a(6Mbps), 5180	11a(6Mbps), 5260	11a(6Mbps), 5320	11a(6Mbps), 5500	11a(6Mbps), 5500	11a(6Mbps), 5785	11a(6Mbps), 5745
Duty cycle [%] (scaled factor)	99.8(×1.00)	99.8(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)
Output power [dBm] (max. power, scaled factor)	18.52dBm (19.5,×1.25)	17.63dBm (19.5,×1.54)	13.70dBm (15.0,×1.35)	13.50dBm (15.0,×1.41)	13.67dBm (15.0,×1.36)	13.84dBm (15.0,×1.31)	15.99dBm (17.5,×1.42)	16.18dBm (17.5,×1.36)	15.93dBm (17.5,×1.44)	15.91dBm (17.5,×1.44)
Liquid type	Head liquid (by Flat phantom)									
Reported SAR value	0.18 W/kg	0.11 W/kg	0.15 W/kg	0.12 W/kg	0.11 W/kg	0.07 W/kg	0.19 W/kg	0.18 W/kg	0.14 W/kg	0.17 W/kg
Measured SAR value	0.145 W/kg	0.0709 W/kg	0.113 W/kg	0.083 W/kg	0.0833 W/kg	0.0484 W/kg	0.135 W/kg	0.135 W/kg	0.0982 W/kg	0.118 W/kg
Operation mode, frequency[MHz]	11g(6Mbps), 2417	11g(6Mbps), 2417	11a(6Mbps), 5180	11a(6Mbps), 5180	11a(6Mbps), 5260	11a(6Mbps), 5300	11a(6Mbps), 5500	11a(6Mbps), 5500	11a(6Mbps), 5785	11a(6Mbps), 5745
Duty cycle [%] (scaled factor)	99.8(×1.00)	99.8(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)	99.7(×1.00)
Output power [dBm] (max. power, scaled factor)	18.52dBm (19.5,×1.25)	17.63dBm (19.5,×1.54)	13.70dBm (15.0,×1.35)	13.50dBm (15.0,×1.41)	13.67dBm (15.0,×1.36)	13.56dBm (15.0,×1.39)	15.99dBm (17.5,×1.42)	16.18dBm (17.5,×1.36)	15.93dBm (17.5,×1.44)	15.91dBm (17.5,×1.44)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. No addition, deviation nor exclusion has been made from standards

3.4 Test Location

No.7 shielded room (2.76m (Width) × 3.76m (Depth) × 2.4m (Height)) for SAR testing.

UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

3.5 Confirmation before SAR testing

3.5.1 Average power for SAR tests

Before SAR test, the RF wiring for the sample had been switched to the antenna conducted power measurement line from the antenna line and the average power was measured. The result is shown in Section 6.

*. The EUT transmission power was verified that it was within 2dB lower than the maximum tune-up tolerance limit when it was set the rated power. (Clause 4.1, KDB447498 D01 (v06))

Step.1 Data rate check (*. The EUT supported the following data rate in each operation mode.)

11b		11g		11a		11n(20HT)						11n(40HT)					
Mod (DSSS)	Data rate	Mod (OFDM)	Data rate	Mod (OFDM)	Data rate	MCS Index	Spatial Stream	Mod (OFDM)	MCS Index	Spatial Stream	Mod (OFDM)	MCS Index	Spatial Stream	Mod (OFDM)	MCS Index	Spatial Stream	Mod (OFDM)
DBPSK	1 Mbps	BPSK	6 Mbps	BPSK	6 Mbps	MCS0	1	BPSK	MCS8	2	BPSK	MCS0	1	BPSK	MCS8	2	BPSK
DQPSK	2 Mbps	BPSK	9 Mbps	BPSK	9 Mbps	MCS1	1	QPSK	MCS9	2	QPSK	MCS1	1	QPSK	MCS9	2	QPSK
CCK	5.5 Mbps	QPSK	12 Mbps	QPSK	12 Mbps	MCS2	1	QPSK	MCS10	2	QPSK	MCS2	1	QPSK	MCS10	2	QPSK
CCK	11 Mbps	QPSK	18 Mbps	QPSK	18 Mbps	MCS3	1	16QAM	MCS11	2	16QAM	MCS3	1	16QAM	MCS11	2	16QAM
*.Mod; Modulation	16QAM	24 Mbps	16QAM	24 Mbps	MCS4	1	16QAM	MCS12	2	16QAM	MCS4	1	16QAM	MCS12	2	16QAM	
	16QAM	36 Mbps	16QAM	36 Mbps	MCS5	1	64QAM	MCS13	2	64QAM	MCS5	1	64QAM	MCS13	2	64QAM	
	64QAM	48 Mbps	64QAM	48 Mbps	MCS6	1	64QAM	MCS14	2	64QAM	MCS6	1	64QAM	MCS14	2	64QAM	
	64QAM	54 Mbps	64QAM	54 Mbps	MCS7	1	64QAM	MCS15	2	64QAM	MCS7	1	64QAM	MCS15	2	64QAM	

Step.2 Consideration of SAR test channel

For the SAR test reference, on each operation band, the average output power was measured on the lower/middle/upper and specified channels with the worst data rate condition in step 1 in the above.

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within ±5% in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY5 system calculates the power drift by measuring the e-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

*. DASY5 system calculation Power drift value[dB] = 20log(Ea)/(Eb) (where, Before SAR testing: Eb[V/m] / After SAR testing: Ea[V/m])

Limit of power drift[W] = ±5%

Power drift limit (X) [dB] = 10log(P_drift)=10log(1.05/1)=10log(1.05)-10log(1)=0.21dB from E-filed relations with power.

$S = E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$ (η : Space impedance) → $P = (E^2 \times 4 \times \pi \times r^2) / \eta$

Therefore, The correlation of power and the E-filed

Power drift limit (X) dB = 10log(P_drift) = 10log(E_drift)^2 = 20log(E_drift)

From the above mentioned, **the calculated power drift of DASY5 system must be the less than ±0.21dB.**

3.7 Test setup of EUT and SAR measurement procedure

After considering the outline of Flat Panel Sensor, the SAR test was carried out on the following setup conditions.

Setup	Explanation of EUT setup position (* Refer to Appendix 1 for test setup photographs.)	antenna #0		antenna #1	
		Separation [mm]	SAR Tested /Reduced	Separation [mm]	SAR Tested /Reduced
Front	The front surface (patient side) of EUT was touched to the Flat phantom.	9.7	Tested (*1)	9.7	Tested (*1)
Back	The back surface (operator side) of EUT was touched to the Flat phantom.	2	Reduced (*1)	2	Reduced (*1)
Long side-ant#1 (antenna#1)	The long side edge surface (near antenna #1 side) of EUT was touched to the Flat phantom.	≈9	Tested (*1)	≈200	Reduced (>200 mm)
Long-side	The long side edge surface (near antenna #1 side) of EUT was touched to the Flat phantom.	≈28.7	Reduced (*1)	≈250	Reduced (>200 mm)
Short-side-ant#0 (antenna#0)	The short side edge surface (near antenna #0 side) of EUT was touched to the Flat phantom.	≈260	Reduced (>200 mm)	≈9	Tested (*1)
Short-side	The short side edge surface (opposite to antenna#0) of EUT was touched to the Flat phantom.	≈310	Reduced (>200 mm)	≈28.7	Reduced (*1)

*. Separation: Antenna separation distance. It is the distance from the antenna to the outer surface of Flat Panel Sensor form which a human may touch.

*. Size of EUT (Flat Panel Sensor, RIC 24C): 328 × 268 × 15 (thickness) [mm]

(cont'd)

(cont'd)

KDB 447498 D01 (v06) was taken into consideration to reduce SAR test.

Consideration of SAR test reduction by the antenna separation distance (100MHz~6GHz, ≤50mm)											
Band, Mode	Setup Position	Minimum distance		Max. power or upper frequency [GHz]	Max. tune-up power			Calculation of exclusion: ≤3.0(*2)	Standalone SAR Test Required? (If >3, -> Required)		Remarks
		[mm]	[mm] (rounded)		[dBm]	[mW]	[mW] (rounded)				
WLAN 2.4GHz 11g	Back (ant#0, ant#1)	2	2 (≤5)	2.417	19.5	89.1	89	27.7	>3.0	Required	->SAR test was reduced. (*1)
	Long-side-ant#1(ant#1), Short-side-ant#0(ant#0)	≈9	9	2.417	19.5	89.1	89	15.4	>3.0	Required	-
	Front (ant#0, ant#1)	9.7	10	2.417	19.5	89.1	89	13.8	>3.0	Required	-
	Long-side(ant#0), Short-side(ant#1)	≈28.7	29	2.417	19.5	89.1	89	4.8	>3.0	Required	-
WLAN W52&53 11a	Back (ant#0, ant#1)	2	2 (≤5)	5.32	15.0	31.6	32	14.8	>3.0	Required	->SAR test was reduced. (*1)
	Long-side-ant#1(ant#1), Short-side-ant#0(ant#0)	≈9	9	5.32	15.0	31.6	32	8.2	>3.0	Required	-
	Front (ant#0, ant#1)	9.7	10	5.32	15.0	31.6	32	7.4	>3.0	Required	-
	Long-side(ant#0), Short-side(ant#1)	≈28.7	29	5.32	15.0	31.6	32	2.5	≤3.0	Not required	-
WLAN W56 11a	Back (ant#0, ant#1)	2	2 (≤5)	5.7	17.5	56.2	56	26.7	>3.0	Required	->SAR test was reduced. (*1)
	Long-side-ant#1(ant#1), Short-side-ant#0(ant#0)	≈9	9	5.7	17.5	56.2	56	14.9	>3.0	Required	-
	Front (ant#0, ant#1)	9.7	10	5.7	17.5	56.2	56	13.4	>3.0	Required	-
	Long-side(ant#0), Short-side(ant#1)	≈28.7	29	5.7	17.5	56.2	56	4.6	>3.0	Required	-
WLAN W58 11a	Back (ant#0, ant#1)	2	2 (≤5)	5.825	17.5	56.2	56	27.0	>3.0	Required	->SAR test was reduced. (*1)
	Long-side-ant#1(ant#1), Short-side-ant#0(ant#0)	≈9	9	5.825	17.5	56.2	56	15.0	>3.0	Required	-
	Front (ant#0, ant#1)	9.7	10	5.825	17.5	56.2	56	13.5	>3.0	Required	-
	Long-side(ant#0), Short-side(ant#1)	≈28.7	29	5.825	17.5	56.2	56	4.7	>3.0	Required	-

*1. Since this EUT is the medical device, the EUT is only used under the guidance of a doctor or a qualified person. The possibility of the maximum RF human exposure is only a body/head of the patient who comes in contact directly on the front surface (patient side) of the EUT. Therefore, the SAR test was only considered to the front surface of the EUT. However, SAR value couldn't be measured at the front surface, so SAR was evaluated on the side edge.

*2. Parenthesis 1), Clause 4.3.1, KDB 447498 D01 (v06) gives the following formula to calculate the SAR(1g) test exclusion thresholds for 100MHz-6GHz at test separation distance ≤50mm.

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f}(\text{GHz})] \leq 3.0 \text{ (for SAR(1g))} \dots\dots\dots \text{formula (1)}$$
 If power is calculated from the upper formula (1);

$$[\text{SAR(1g) test exclusion thresholds, mW}] = 3 \times [\text{test separation distance, mm}] / [\sqrt{f}(\text{GHz})] \dots\dots\dots \text{formula (2)}$$

$$[\text{SAR(1g) test exclusion thresholds, mW}] = 3 \times 50 / \text{SQRT}(2.462) = 96\text{mW, where test separation distance} = 50\text{mm}$$

* **Simultaneous transmission evaluation**

Parenthesis 2) and 3), Clause 4.3.2, KDB 447498 D01 (v06) gives the following formula to calculate the simultaneous transmission SAR test exclusion limit (SPLSR: SAR to peak location separation ratio must be ≤0.04 for antenna pair.)

Mode	Data rate	Band	Position	Minimum distance		Max. power or Upper frequency	Max. power (with tune-up tolerance)	Estimate SAR(1g) [W/kg]				Ant#0<->#1 distance	SPLSR	Simultaneous SAR test apply?
				Ant#0	Ant#1			Ant#0	Ant#1	Ant#0+#1	Limit			
n20	MCS8	2.4GHz	Front (Patient side)	9.7 mm	9.7 mm	2.417GHz	17.0dBm (50mW)	1.07	1.07	2.14	1.6	315 mm	0.010	Reduced SPLSR: ≤0.04
n20	MCS8	W52/53				5.32GHz	13.5dBm (22mW)	0.70	0.70	1.40	1.6	315 mm	0.005	
n20	MCS8	W56				5.7GHz	16.0dBm (40mW)	1.31	1.31	2.62	1.6	315 mm	0.014	
n20	MCS8	W58				5.825GHz	16.0dBm (40mW)	1.33	1.33	2.66	1.6	315 mm	0.014	

*. Calculating formula: Estimate standalone SAR(1g) = [(max. power, mW) / (min. test separation distance, mm)] × [√f(GHz)] / [7.5]
 SPLSR (SAR to Peak Location Separation Ratio) = {(SAR_Ant#0, W/kg) + (SAR_Ant#1, W/kg)} ^1.5 / (Ant#0<->#1 distance, mm)

By the determined test setup shown above, the SAR test was applied in the following procedures.

Step 1	Change the operation mode on each antenna independently with highest output power channel.
Step 2	Repeat Step1 for other frequency band.

*. During SAR test, the radiated power is always monitored by Spectrum Analyzer.

SECTION 4: Operation of EUT during testing

4.1 Operating modes for SAR testing

This EUT has IEEE 802.11b, g, a, n(HT20) and n(HT40) continuous transmitting modes.


The frequency and the modulation used in the SAR testing are shown as a following.

Operation mode	g	b	n20(1Tx)	n20(2Tx)	n40(1Tx)	n40(2Tx)	a	n20(1Tx)	n20(2Tx)	n40(1Tx)	n40(2Tx)	
band	DTS						W52 (U-NII-1) (*1)					
Tx band [MHz]	2412~2462						2422~2452					
Bandwidth [MHz]	20	20	20	20	40	40	20	20	20	40	40	
Max.power [dBm]	19.5	16	17	20	16	19	15	13.5	16.5	13.5	16.5	
Modulation	OFDM	DSSS	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	
Data rate [Mbps]	6	1	MCS0	MCS8	MCS0	MCS8	6	MCS0	MCS8	MCS0	MCS8	
SAR Tested?	Tested	Tested	Reduced	Reduced	Tested	Reduced	Tested	Reduced	Reduced	Reduced	Reduced	
Frequency tested [MHz]	ant#0	2417, 2437, 2462	2412(*2)	-(*)2	-(*)3	2427(*2)	-(*)3	5180	-	-	-	
ant#1	2417, 2437, 2462	2412(*2)	-(*)2	-(*)3	2427(*2)	-(*)3	5180	-	-	-		

Operation mode	a	n20(1Tx)	n20(2Tx)	n40(1Tx)	n40(2Tx)	a	n20(1Tx)	n20(2Tx)	n40(1Tx)	n40(2Tx)	a	n20(1Tx)	n20(2Tx)	n40(1Tx)	n40(2Tx)	
band	W53 (U-NII-2A)					W56 (U-NII-2C)					W56 (U-NII-2C)					
Tx band [MHz]	5260~5320					5270~5310					5500~5700					
Bandwidth [MHz]	20	20	20	40	40	20	20	20	40	40	20	20	20	40	40	
Max.power [dBm]	15	13.5	16.5	13.5	16.5	17.5	16	19	13.5	16.5	17.5	16	19	13.5	16.5	
Modulation	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	OFDM	
Data rate [Mbps]	6	MCS0	MCS8	MCS0	MCS8	6	MCS0	MCS8	MCS0	MCS8	6	MCS0	MCS8	MCS0	MCS8	
SAR Tested?	Tested	Reduced	Reduced	Tested	Reduced	Tested	Reduced	Reduced	Tested	Reduced	Tested	Reduced	Reduced	Tested	Reduced	
Frequency tested [MHz]	ant#0	5260, 5300, 5320	-(*)2	-(*)3	-(*)2	-(*)3	5500, 5580, 5600, 5700	-(*)2	-(*)3	-(*)2	-(*)3	5745, 5785, 5825	-(*)2	-(*)3	-(*)2	-(*)3
ant#1	5260, 5300, 5320	-(*)2	-(*)3	5270 (*2)	-(*)3	5500, 5580, 5600, 5700	-(*)2	-(*)3	5550 (*2)	-(*)3	5745, 5785, 5825	-(*)2	-(*)3	5795 (*2)	-(*)3	

Controlled software

Tx Controlled software: ART v09 (Build 34)
 Mode: Continuous transmit mode.
 •Tx antenna chain:
 Ant#0=100, Ant#0=010, Ant#0+Ant#1(MIMO)=110.
 •Frequency: Selected the target frequency.
 •Data Rate: Selected the target data rate.
 •HT40: Selected when 11n(40HT) was tested.
 •Setting target power: Defaults were used, but when measurement power didn't enter 2dB from maximum power, it was adjusted (tuned-up).
 * As for parameters other than the above, the initial value was used.



Note: SAR test reduction consideration

Table A-1. Output power measured and SAR test channel selection

802.11 Modes	b	g	n	a	n(1Tx)
Ch. Bandwidth [MHz]	20	20	20	40	20
Lowest data rate [Mbps]	1	6	6.5	6.5	6
§15.247 (2.4GHz)	Ch.	1/6/11	1/2/6/11	-	-
	mW (ant#0)	32/29/31	29/71/51/41	lower power	-
	mW (ant#1)	33/31/30	29/58/53/39	lower power	-
U-NII-1 (W52)	Ch.	-	-	36/44/48	-
	mW (ant#0)	-	-	23/25/25	lower power
	mW (ant#1)	-	-	22/23/23	lower power
U-NII-2A (W53)	Ch.	-	-	52/60/64	-
	mW (ant#0)	-	-	23/25/24	lower power
	mW (ant#1)	-	-	22/23/23	lower power
U-NII-2C (W56)	Ch.	-	-	100/118/120/140	-
	mW (ant#0)	-	-	40/44/43/39	lower power
	mW (ant#1)	-	-	42/41/41/38	lower power
U-NII-3 (W58)	Ch.	-	-	149/157/165	-
	mW (ant#0)	-	-	39/39/40	lower power
	mW (ant#1)	-	-	39/40/44	lower power

Table A-2. Reported SAR(1g) and test reduction plan(Head)

b	g	n	a	n(1Tx)
20	20	20	40	20
1	6	6.5	6.5	6
1	1/2/6/11	-	-	-
0.08	0.18	lower power	-	-
0.04	0.11	lower power	-	-
-	-	-	36/44/48	-
-	-	-	0.15	lower power
-	-	-	0.12	lower power
-	-	-	52/60/64	-
-	-	-	0.10	lower power
-	-	-	0.07	lower power
-	-	-	100/118/120/140	-
-	-	-	0.19/0.07/0.05/0.07	lower power
-	-	-	0.18/0.12/0.11/0.14	lower power
-	-	-	149/157/165	-
-	-	-	0.11/0.14/0.09	lower power
-	-	-	0.17/0.17/0.17	lower power

- *1. (KDB248227 D01 (v02r02)) Since highest reported SAR(1g) of U-NII-2A was ≤ 1.2 W/kg, SAR measurement of U-NII-1 band was omitted. However, SAR test was applied to 5180MHz as lower frequency of U-NII-1 and U-NII-2A band.
- *2. (KDB248227 D01 (v02r02)) SAR test of other power mode was reduced, because the reported SAR(1g) of 11g, and 11a mode (highest power mode in each operation band) was ≤ 0.4 W/kg. However, in a representative frequency, 11b was evaluated for DSSS mode and 11n(40HT) mode was evaluated for BW=40MHz.
- *3. (KDB447498 D01 (v06)) Since SPLSR (SAR to peak location separation ratio) was enough smaller than 0.04, SAR test of MIMO mode was reduced.
- *. The SAR testing was applied to lower, middle and upper channels for the worst SAR condition in each operation band.

SECTION 5: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement (2.4-6GHz) (*.ε&σ:≤±5%, DAK3.5, Tx: ≈100% duty cycle) (v08)							1g SAR	10g SAR	
Combined measurement uncertainty of the measurement system (k=1)							± 13.7%	± 13.6%	
Expanded uncertainty (k=2)							± 27.4%	± 27.2%	
	Error Description (2.4-6GHz) (v08)	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g) (std. uncertainty)	ui (10g) (std. uncertainty)	Vi, veff
A	Measurement System (DASY5)								
1	Probe Calibration Error	±6.55 %	Normal	1	1	1	±6.55 %	±6.55 %	∞
2	Axial isotropy Error	±4.7 %	Rectangular	√3	√0.5	√0.5	±1.9 %	±1.9 %	∞
3	Hemispherical isotropy Error	±9.6 %	Rectangular	√3	√0.5	√0.5	±3.9 %	±3.9 %	∞
4	Linearity Error	±4.7 %	Rectangular	√3	1	1	±2.7 %	±2.7 %	∞
5	Probe modulation response	±2.4 %	Rectangular	√3	1	1	±1.4 %	±1.4 %	∞
6	Sensitivity Error (detection limit)	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
7	Boundary effects Error	±4.3 %	Rectangular	√3	1	1	±2.5 %	±2.5 %	∞
8	Readout Electronics Error(DAE)	±0.3 %	Rectangular	√3	1	1	±0.3 %	±0.3 %	∞
9	Response Time Error	±0.8 %	Normal	1	1	1	±0.8 %	±0.8 %	∞
10	Integration Time Error (≈100% duty cycle)	±0 %	Rectangular	√3	1	1	0 %	0 %	∞
11	RF ambient conditions-noise	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
12	RF ambient conditions-reflections	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
13	Probe positioner mechanical tolerance	±3.3 %	Rectangular	√3	1	1	±1.9 %	±1.9 %	∞
14	Probe Positioning with respect to phantom shell	±6.7 %	Rectangular	√3	1	1	±3.9 %	±3.9 %	∞
15	Max. SAR evaluation (Post-processing)	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
B	Test Sample Related								
16	Device Holder or Positioner Tolerance	±3.6 %	Normal	1	1	1	±3.6 %	±3.6 %	5
17	Test Sample Positioning Error	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	145
18	Power scaling	±0%	Rectangular	√3	1	1	±0 %	±0 %	∞
19	Drift of output power (measured, <0.2dB)	±2.3%	Rectangular	√3	1	1	±2.9 %	±2.9 %	∞
C	Phantom and Setup								
20	Phantom uncertainty (shape, thickness tolerances)	±7.5 %	Rectangular	√3	1	1	±4.3 %	±4.3 %	∞
21	Algorithm for correcting SAR (ε',σ: ≤5%)	±1.2 %	Normal	1	1	0.84	±1.2 %	±0.97 %	∞
22	Measurement Liquid Conductivity Error (DAK3.5)	±3.0 %	Normal	1	0.78	0.71	±2.3 %	±2.1 %	7
23	Measurement Liquid Permittivity Error (DAK3.5)	±3.1 %	Normal	1	0.23	0.26	±0.7 %	±0.8 %	7
24	Liquid Conductivity-temp.uncertainty (≤2deg.C.)	±5.3 %	Rectangular	√3	0.78	0.71	±2.4 %	±2.2 %	∞
25	Liquid Permittivity-temp.uncertainty (≤2deg.C.)	±0.9 %	Rectangular	√3	0.23	0.26	±0.1 %	±0.1 %	∞
	Combined Standard Uncertainty						±13.7 %	±13.6 %	733
	Expanded Uncertainty (k=2)						±27.4 %	±27.2 %	

*. Table of uncertainties are listed for ISO/IEC 17025.

*. This measurement uncertainty budget is suggested by IEEE Std.1528(2013) and determined by Schmid & Partner Engineering AG (DASY5 Uncertainty Budget). Per KDB 865664 D01 (v01r04) SAR Measurement 100 MHz to 6 GHz Section 2.8.1., when the highest measured SAR(1g) within a frequency band is < 1.5W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std.1528 (2013) is not required in SAR reports submitted for equipment approval.

SECTION 6: Confirmation before testing

6.1 Assessment for the antenna terminal port conducted power of EUT (Worst data rate, worst channel determination)

6.1.1 2.4GHz band

Mode	Freq. [MHz]	Data rate [Mbps]	Power spec.		Duty cycle			Antenna #0 (chain #0) power				Antenna #1 (chain #1) power				MIMO Ant.#0+Ant.#1 power			Power Tune-up?				
			Typical [dBm]	Max. [dBm]	duty cycle [%]	factor [dB]	scaled factor [-]	Set pwr. [dBm]	Ave. [dBm]	Δ Max. [dB]	Tune-up factor [-]	SAR Tested?	Set pwr. [dBm]	Ave. [dBm]	Δ Max. [dB]	Tune-up factor [-]	SAR Tested?	MIMO target [dBm]		MIMO max. [dBm]	SUM Ave. [dBm]	Δ Max. [dB]	
11b	2412	1	13.5	16.0	99.8	0.01	×1.00	13.5	14.13	-1.87	×1.54	-	13.5	13.92	-2.08	×1.61	-	-	-	-	-	-	
	2412	2	13.5	16.0	99.8	0.01	×1.00	13.5	14.13	-1.87	-	-	13.5	13.92	-2.08	-	-	-	-	-	-	-	
	2412	5.5	13.5	16.0	99.6	0.02	×1.00	13.5	14.13	-1.87	-	-	13.5	13.92	-2.08	-	-	-	-	-	-	-	
	2412	11	13.5	16.0	99.4	0.03	×1.01	13.5	14.13	-1.87	-	-	13.5	13.92	-2.08	-	-	-	-	-	-	-	
	2412	1	13.5	16.0	99.8	0.01	×1.00	15.0	14.99	-1.01	×1.26	Tested	15.0	15.20	-0.80	×1.20	Tested	-	-	-	-	tune-up	
	2437	1	13.5	16.0	99.8	0.01	×1.00	15.0	14.57	-1.43	×1.39	-	15.0	14.91	-1.09	×1.29	-	-	-	-	-	tune-up	
2462	1	13.5	16.0	99.8	0.01	×1.00	15.0	14.97	-1.03	×1.27	-	15.0	14.70	-1.30	×1.35	-	-	-	-	-	tune-up		
11g	2417	6	17.0	19.5	99.8	0.01	×1.00	17.0	17.44	-2.06	×1.61	-	17.0	17.63	-1.87	×1.54	Tested	-	-	-	-	-	
	2417	9	17.0	19.5	99.6	0.02	×1.00	17.0	17.37	-2.13	-	-	17.0	17.51	-1.99	-	-	-	-	-	-	-	
	2417	12	17.0	19.5	99.4	0.03	×1.01	17.0	17.31	-2.19	-	-	17.0	17.47	-2.03	-	-	-	-	-	-	-	
	2417	18	17.0	19.5	99.0	0.04	×1.01	17.0	17.30	-2.20	-	-	17.0	17.37	-2.13	-	-	-	-	-	-	-	
	2417	24	17.0	19.5	98.8	0.05	×1.01	17.0	17.20	-2.30	-	-	17.0	17.35	-2.15	-	-	-	-	-	-	-	
	2417	36	17.0	19.5	98.4	0.07	×1.02	17.0	17.21	-2.29	-	-	17.0	17.39	-2.11	-	-	-	-	-	-	-	
	2417	48	16.0	18.5	97.4	0.11	×1.03	16.0	15.92	-2.58	-	-	16.0	16.29	-2.21	-	-	-	-	-	-	-	
	2417	56	15.0	17.5	97.1	0.13	×1.03	15.0	15.02	-2.48	-	-	15.0	15.45	-2.05	-	-	-	-	-	-	-	
	2412	6	13.5	16.0	99.8	0.01	×1.00	13.5	14.57	-1.43	×1.39	-	13.5	14.63	-1.37	×1.37	-	-	-	-	-	-	
	2417	6	17.0	19.5	99.8	0.01	×1.00	18.0	18.52	-0.98	×1.25	Tested	-	-	-	-	-	-	-	-	-	tune-up	
	2437	6	15.5	18.0	99.8	0.01	×1.00	17.0	17.09	-1.41	×1.38	Tested	17.0	17.25	-1.25	×1.33	Tested	-	-	-	-	-	tune-up
	2462	6	15.0	17.5	99.8	0.01	×1.00	16.0	16.08	-1.42	×1.39	Tested	16.0	15.87	-1.63	×1.46	Tested	-	-	-	-	-	tune-up
11n (20HT) (1Tx)	2417	MCS0	14.5	17.0	99.6	0.02	×1.00	14.5	15.16	-1.84	×1.53	no(*1)	14.5	15.12	-1.88	×1.54	no(*1)	-	-	-	-	-	
	2417	MCS1	14.5	17.0	99.3	0.03	×1.01	14.5	14.87	-2.13	-	-	14.5	14.99	-2.01	-	-	-	-	-	-	-	
	2417	MCS2	14.5	17.0	98.8	0.05	×1.01	14.5	14.74	-2.26	-	-	14.5	14.80	-2.20	-	-	-	-	-	-	-	
	2417	MCS3	14.5	17.0	98.6	0.06	×1.01	14.5	14.72	-2.28	-	-	14.5	14.79	-2.21	-	-	-	-	-	-	-	
	2417	MCS4	14.5	17.0	97.9	0.09	×1.02	14.5	14.62	-2.38	-	-	14.5	14.78	-2.22	-	-	-	-	-	-	-	
	2417	MCS5	14.5	17.0	97.3	0.12	×1.03	14.0	14.39	-2.11	-	-	14.0	14.29	-2.21	-	-	-	-	-	-	-	
	2417	MCS6	14.5	17.0	96.8	0.14	×1.03	13.5	13.95	-2.05	-	-	13.5	13.83	-2.17	-	-	-	-	-	-	-	
	2417	MCS7	14.5	17.0	96.4	0.16	×1.04	13.0	13.54	-1.96	-	-	13.0	13.53	-1.97	-	-	-	-	-	-	-	
	2412	MCS0	10.5	13.0	99.6	0.02	×1.00	10.5	11.71	-1.29	×1.35	-	10.5	11.36	-1.64	×1.46	-	-	-	-	-	-	
	2437	MCS0	12.5	15.0	99.6	0.02	×1.00	13.5	13.73	-1.27	×1.34	-	13.5	14.04	-0.96	×1.25	-	-	-	-	-	-	
	2462	MCS0	10.5	13.0	99.6	0.02	×1.00	11.5	11.34	-1.66	×1.47	-	11.5	11.79	-1.21	×1.32	-	-	-	-	-	tune-up	
	11n (40HT) (1Tx)	2427	MCS0	13.5	16.0	99.3	0.03	×1.01	13.5	14.19	-1.81	×1.52	Tested	13.5	14.34	-1.66	×1.47	Tested	-	-	-	-	-
2427		MCS1	13.5	16.0	98.6	0.06	×1.01	13.5	13.99	-2.01	-	-	13.5	14.26	-1.74	-	-	-	-	-	-	-	
2427		MCS2	13.5	16.0	97.8	0.10	×1.02	13.5	14.00	-2.00	-	-	13.5	14.16	-1.84	-	-	-	-	-	-	-	
2427		MCS3	13.5	16.0	97.0	0.12	×1.03	13.5	14.05	-1.95	-	-	13.5	14.21	-1.79	-	-	-	-	-	-	-	
2427		MCS4	13.5	16.0	96.9	0.14	×1.03	13.5	13.98	-2.02	-	-	13.5	14.09	-1.91	-	-	-	-	-	-	-	
2427		MCS5	13.0	15.5	94.8	0.23	×1.05	13.0	13.52	-1.98	-	-	13.0	13.72	-1.78	-	-	-	-	-	-	-	
2427		MCS6	12.5	15.0	94.3	0.25	×1.06	12.5	12.94	-2.06	-	-	12.5	13.07	-1.93	-	-	-	-	-	-	-	
2427		MCS7	12.0	14.5	93.9	0.27	×1.06	12.0	12.59	-1.91	-	-	12.0	12.72	-1.78	-	-	-	-	-	-	-	
2422		MCS0	6.0	8.5	99.3	0.03	×1.01	6.0	7.29	-1.21	×1.32	-	6.0	6.79	-1.71	×1.48	-	-	-	-	-	-	
2437		MCS0	10.5	13.0	99.3	0.03	×1.01	10.5	10.57	-2.43	×1.75	-	10.5	11.24	-1.76	×1.50	-	-	-	-	-	-	
2452		MCS0	7.0	9.5	99.3	0.03	×1.01	7.0	7.54	-1.96	×1.57	-	7.0	7.69	-1.81	×1.52	-	-	-	-	-	-	
11n (20HT) (2Tx)		2417	MCS8	14.5	17.0	99.6	0.02	×1.00	14.5	15.02	-1.98	×1.58	no(*2)	14.5	15.16	-1.84	×1.53	no(*2)	17.5	20.0	18.10	-1.90	-
	2417	MCS9	14.5	17.0	99.3	0.03	×1.01	14.5	14.76	-2.24	-	-	14.5	14.93	-2.07	-	-	17.5	20.0	17.86	-2.14	-	
	2417	MCS10	14.5	17.0	98.8	0.05	×1.01	14.5	14.81	-2.19	-	-	14.5	14.86	-2.14	-	-	17.5	20.0	17.85	-2.15	-	
	2417	MCS11	14.5	17.0	98.4	0.06	×1.01	14.5	14.82	-2.18	-	-	14.5	14.77	-2.23	-	-	17.5	20.0	17.81	-2.19	-	
	2417	MCS12	14.5	17.0	97.9	0.09	×1.02	14.5	14.87	-2.13	-	-	14.5	14.74	-2.26	-	-	17.5	20.0	17.82	-2.18	-	
	2417	MCS13	14.0	16.5	97.3	0.12	×1.03	14.0	14.37	-2.13	-	-	14.0	14.19	-2.31	-	-	17.0	19.5	17.29	-2.21	-	
	2417	MCS14	13.5	16.0	96.8	0.14	×1.03	13.5	13.79	-2.21	-	-	13.5	13.73	-2.27	-	-	16.5	19.0	16.77	-2.23	-	
	2417	MCS15	13.0	15.5	96.4	0.16	×1.04	13.0	13.31	-2.19	-	-	13.0	13.26	-2.24	-	-	16.0	18.5	16.30	-2.20	-	
	2412	MCS8	10.5	13.0	99.6	0.02	×1.00	10.5	11.79	-1.21	×1.32	-	10.5	11.27	-1.73	×1.49	-	-	13.5	16.0	14.55	-1.45	-
	2437	MCS8	12.5	15.0	99.6	0.02	×1.00	13.5	13.66	-1.34	×1.36	-	13.5	14.00	-1.00	×1.26	-	-	15.5	18.0	16.84	-1.16	tune-up
	2462	MCS8	10.5	13.0	99.6	0.02	×1.00	11.5	11.50	-1.50	×1.41	-	11.5	11.70	-1.30	×1.35	-	-	13.5	16.0	14.61	-1.39	tune-up
	11n (40HT) (2Tx)	2427	MCS8	13.5	16.0	98.9	0.05	×1.01	13.5	14.18	-1.82	×1.52	no(*2)	13.5	14.26	-1.74	×1.49	no(*2)	16.5	19.0	17.23	-1.77	-
2427		MCS9	13.5	16.0	97.4	0.11	×1.03	13.5	14.04	-1.96	-	-	13.5	14.10	-1.90	-	-	16.5	19.0	17.08	-1.92	-	
2427		MCS10	13.5	16.0	96.3	0.16	×1.04	13.5	14.04	-1.96	-	-	13.5	14.11	-1.89	-	-	16.5	19.0	17.09	-1.91	-	
2427		MCS11	13.5	16.0	95.5	0.20	×1.05	13.5	13.99	-2.01	-	-	13.5	13.98	-2.02	-	-	16.5	19.0	16.99	-2.01	-	
2427		MCS12	13.5	16.0	93.8	0.28	×1.07	13.5	13.85	-2.15	-	-	13.5	13.90	-2.10	-	-	16.5	19.0	16.89	-2.11		

(cont'd) 6.12 5GHz band (cont'd)

Mode	Freq. [MHz]	Data rate [Mbps]	Power spec.		Duty cycle				Antenna #0 (chain #0) power				Antenna #1 (chain #1) power				MIMO Ant#0+Ant#1 power				Power Tune -up?		
			Typical [dBm]	Max. [dBm]	duty cycle [%]	factor [dB]	scaled factor [-]	Set pwr. [dBm]	Ave. [dBm]	Δ Max. [dB]	Tune-up factor [-]	SAR Tested?	Set pwr. [dBm]	Ave. [dBm]	Δ Max. [dB]	Tune-up factor [-]	SAR Tested?	MIMO target [dBm]	MIMO max. [dBm]	SUM Ave. [dBm]		Δ Max. [dB]	
11n (20HT) (2Tx)	5180	MCS8	11.0	13.5	99.3	0.03	×1.01	13.5	11.84	-1.66	×1.47	-	13.5	12.42	-1.08	×1.28	-	14.0	16.5	15.15	-1.35	tune-up	
	5220	MCS8	11.0	13.5	99.3	0.03	×1.01	13.5	12.32	-1.18	×1.31	-	13.5	12.43	-1.07	×1.28	-	14.0	16.5	15.39	-1.11	tune-up	
	5240	MCS8	11.0	13.5	99.3	0.03	×1.01	13.5	12.43	-1.07	×1.28	no(*1)	13.5	12.54	-0.96	×1.25	no(*1)	14.0	16.5	15.50	-1.00	tune-up	
	5260	MCS8	11.0	13.5	99.3	0.03	×1.01	13.5	12.54	-0.96	×1.25	-	13.5	12.68	-0.82	×1.21	-	14.0	16.5	15.62	-0.88	tune-up	
	5300	MCS8	11.0	13.5	99.3	0.03	×1.01	13.5	12.81	-0.69	×1.17	no(*1)	13.5	12.63	-0.87	×1.22	no(*1)	14.0	16.5	15.73	-0.77	tune-up	
	5320	MCS8	11.0	13.5	99.3	0.03	×1.01	13.5	12.92	-0.58	×1.14	-	13.5	12.40	-1.10	×1.29	-	14.0	16.5	15.68	-0.82	tune-up	
	5500	MCS8	13.5	16.0	99.3	0.03	×1.01	15.0	14.96	-1.04	×1.27	-	15.0	14.51	-1.49	×1.41	-	16.5	19.0	17.75	-1.25	tune-up	
	5580	MCS8	13.5	16.0	99.3	0.03	×1.01	15.0	15.00	-1.00	×1.26	-	15.0	14.69	-1.31	×1.35	-	16.5	19.0	17.86	-1.14	tune-up	
	5600	MCS8	13.5	16.0	99.3	0.03	×1.01	15.0	15.03	-0.97	×1.25	no(*1)	15.0	14.72	-1.28	×1.34	no(*1)	16.5	19.0	17.89	-1.11	tune-up	
	5700	MCS8	13.5	16.0	99.3	0.03	×1.01	15.0	14.77	-1.23	×1.33	-	15.0	14.54	-1.46	×1.40	-	16.5	19.0	17.67	-1.33	tune-up	
	5745	MCS8	13.5	16.0	99.3	0.03	×1.01	16.0	14.89	-1.11	×1.29	-	16.0	14.82	-1.18	×1.31	-	16.5	19.0	17.87	-1.13	tune-up	
	5785	MCS8	13.5	16.0	99.3	0.03	×1.01	16.0	14.85	-1.15	×1.30	-	16.0	15.13	-0.87	×1.22	-	16.5	19.0	18.00	-1.00	tune-up	
	5825	MCS8	13.5	16.0	99.3	0.03	×1.01	16.0	14.83	-1.17	×1.31	no(*1)	16.0	15.18	-0.82	×1.21	no(*1)	16.5	19.0	18.02	-0.98	tune-up	
	11n (40HT) (2Tx)	5510	MCS8	11.0	13.5	98.7	0.06	×1.01	11.0	10.88	-2.62	×1.83	-	11.0	10.69	-2.81	×1.91	-	14.0	16.5	13.80	-2.70	-
		5510	MCS9	11.0	13.5	98.0	0.09	×1.02	11.0	10.84	-2.66	-	-	11.0	10.56	-2.94	-	-	14.0	16.5	13.71	-2.79	-
5510		MCS10	11.0	13.5	96.8	0.14	×1.03	11.0	10.80	-2.70	-	-	11.0	10.22	-3.28	-	-	14.0	16.5	13.53	-2.97	-	
5510		MCS11	11.0	13.5	95.4	0.20	×1.05	11.0	10.83	-2.67	-	-	11.0	10.11	-3.39	-	-	14.0	16.5	13.50	-3.00	-	
5510		MCS12	11.0	13.5	93.6	0.29	×1.07	11.0	10.79	-2.71	-	-	11.0	10.22	-3.28	-	-	14.0	16.5	13.52	-2.98	-	
5510		MCS13	11.0	13.5	92.8	0.32	×1.08	11.0	10.63	-2.87	-	-	11.0	10.14	-3.36	-	-	14.0	16.5	13.40	-3.10	-	
5510		MCS14	10.0	12.5	91.8	0.37	×1.09	10.0	9.67	-2.83	-	-	10.0	9.55	-2.95	-	-	13.0	15.5	12.62	-2.88	-	
5510		MCS15	8.0	10.5	91.3	0.40	×1.10	8.0	7.99	-2.51	-	-	8.0	7.36	-3.14	-	-	11.0	13.5	10.70	-2.80	-	
5230		MCS8	11.0	13.5	98.7	0.06	×1.01	13.5	12.29	-1.21	×1.32	no(*1)	13.5	12.30	-1.20	×1.32	no(*1)	14.0	16.5	15.30	-1.20	tune-up	
5270		MCS8	11.0	13.5	98.7	0.06	×1.01	13.5	12.17	-1.33	×1.36	no(*1)	13.5	12.39	-1.11	×1.29	no(*1)	14.0	16.5	15.29	-1.21	tune-up	
5510		MCS8	11.0	13.5	98.7	0.06	×1.01	12.5	12.76	-0.74	×1.19	no(*1)	12.5	11.72	-1.78	×1.51	no(*1)	14.0	16.5	15.28	-1.22	tune-up	
5550		MCS8	11.0	13.5	98.7	0.06	×1.01	12.5	12.45	-1.05	×1.27	-	12.5	11.85	-1.65	×1.46	-	14.0	16.5	15.17	-1.33	tune-up	
5590		MCS8	11.0	13.5	98.7	0.06	×1.01	12.5	12.51	-0.99	×1.26	-	12.5	11.81	-1.69	×1.48	-	14.0	16.5	15.18	-1.32	tune-up	
5670		MCS8	11.0	13.5	98.7	0.06	×1.01	12.5	12.17	-1.33	×1.36	-	12.5	12.21	-1.29	×1.35	-	14.0	16.5	15.20	-1.30	tune-up	
5755		MCS8	11.0	13.5	98.7	0.06	×1.01	13.5	12.45	-1.05	×1.27	no(*1)	13.5	12.36	-1.14	×1.30	no(*1)	14.0	16.5	15.42	-1.08	tune-up	
5795	MCS8	11.0	13.5	98.7	0.06	×1.01	13.5	11.93	-1.57	×1.44	-	13.5	12.12	-1.38	×1.37	-	14.0	16.5	15.04	-1.46	tune-up		

* []: SAR test was applied. * xx.xx highlight is shown the maximum measured output power.

*1. (KDB447498 D01 (v06)) Since SPLSR (SAR to peak location separation ratio) was enough smaller than 0.04, SAR test of MIMO mode was reduced.

* Date measured February 3 and 4, 2016 / measured by: H. Naka (21 ± 2 deg.C / 50 ± 5 %RH, at preparation room of S/R#7)

(Common definition)

* Freq.: Frequency, Max.: Maximum, Power spec.: Power specification, Set pwr.: Setting power for the measurement, Ave.: Average

* Calculating formula: Average power (dBm) = (P/M Reading, dBm) + (Cable loss, dB) + (Attenuator, dB) + (duty factor, dB)

Duty cycle: (duty cycle, %) = (Tx on time, ms) / (1 cycle time, ms) × 100; Duty factor: (duty factor, dBm) = 10 × log (100/(duty cycle, %))

Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = 100% / (duty cycle, %)


ΔMax. (Deviation form maximum power, dB) = (results power (average, dBm)) - (Max.-specification output power (average, dBm))

Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = 1 / (10 ^ ("Deviation from max., dB" / 10))

* Date measured: February 3 and 4, 2016 / Measured by: Hiroshi Naka / Place: preparation room of No. 7 shielded room. (21 ± 1 deg.C / 45 ± 10 %RH)

* Uncertainty of antenna port conducted test; Power measurement uncertainty above 1GHz for this test was: (±) 0.76 dB.

* Uncertainty of antenna port conducted test; Duty cycle and time measurement: (±) 0.012 %.



SECTION 7: SAR Measurement results

Measurement date: February 16~19, 22 and 23, 2016

Measurement by: Hiroshi Naka

7.1 Liquid measurement

Target Frequency [MHz]	Liquid type	Liquid parameters (*a)						ASAR Coefficients(*c)		Date measured				
		Permittivity (εr) [-]			Conductivity [S/m]			Temp. [deg.C]	Depth [mm]		ASAR (1g) [%]	Correction required?		
		Target	Measured		Limit (*b)	Target	Measured						Limit (*b)	
5745	Head	35.36	34.97	-1.1	-5% ≤ εr-meas ≤ 0%	5.214	5.102	-2.1	-5% ≤ σ-meas ≤ +5%	22.9	149	+0.32	not required.	February 16, 2016 before SAR test
5785		35.32	34.98	-1.0		5.255	5.130	-2.4		+0.30	not required.			
5795		35.31	35.01	-0.8		5.265	5.129	-2.6		+0.28	not required.			
5825		35.27	34.88	-1.1		5.296	5.193	-1.9		+0.31	not required.			
5180		36.01	35.73	-0.8		4.635	4.538	-2.1		+0.21	not required.			
5260	Head	35.92	35.64	-0.8	-5% ≤ εr-meas ≤ 0%	4.717	4.610	-2.3	-5% ≤ σ-meas ≤ +5%	22.9	149	+0.22	not required.	February 17, 2016 before SAR test
5270		35.91	35.60	-0.9		4.727	4.617	-2.3		+0.24	not required.			
5300		35.87	35.66	-0.6		4.758	4.633	-2.6		+0.20	not required.			
5320		35.85	35.60	-0.7		4.778	4.645	-2.8		+0.23	not required.			
5500		35.64	35.36	-0.8		4.963	4.825	-2.8		+0.27	not required.			
5550		35.59	35.24	-1.0		5.014	4.885	-2.6		+0.31	not required.			
5580		35.55	35.24	-0.9		5.045	4.890	-3.1		+0.31	not required.			
5600		35.53	35.20	-0.9		5.065	4.945	-2.4		+0.29	not required.			
5700		35.41	35.02	-1.1		5.168	5.047	-2.3		+0.33	not required.			
5500		48.61	47.19	-2.9		-5% ≤ εr-meas ≤ 0%	5.650	5.859		+3.7	0% ≤ σ-meas ≤ +5%	22.6	147	
5580	48.50	47.06	-3.0	5.743	5.968		+3.9	+0.42	not required.					
5600	48.47	47.03	-3.0	5.766	6.003		+4.1	+0.41	not required.					
5700	48.34	46.95	-2.9	5.883	6.150		+4.5	+0.36	not required.					
5745	48.27	46.83	-3.0	5.936	6.192		+4.3	+0.40	not required.					
5785	48.22	46.83	-2.9	5.982	6.253		+4.5	+0.37	not required.					
5825	48.17	46.77	-2.9	6.029	6.306		+4.6	+0.37	not required.					
5180	49.04	47.81	-2.5	5.424	5.424		+2.8	+0.44	not required.					
5260	48.93	47.61	-2.7	5.369	5.559		+3.5	+0.44	not required.					
5300	48.88	47.56	-2.7	5.416	5.616		+3.7	+0.42	not required.					
5320	48.85	47.57	-2.6	5.439	5.608	+3.1	+0.42	not required.						
2412	Body	52.75	50.55	-4.2	-5% ≤ εr-meas ≤ 0%	1.914	1.949	+1.8	0% ≤ σ-meas ≤ +5%	22.4	153	+1.83	not required.	February 22, 2016 before SAR test
2417		52.74	50.51	-4.2		1.918	1.949	+1.6		+1.73	not required.			
2427		52.73	50.48	-4.3		1.928	1.969	+2.1		+1.99	not required.			
2437		52.72	50.39	-4.4		1.938	1.991	+2.7		+2.32	not required.			
2462		52.68	50.31	-4.5		1.967	2.017	+2.5		+2.22	not required.			
2412	Head	39.27	38.13	-2.9	-5% ≤ εr-meas ≤ 0%	1.766	1.808	+2.4	0% ≤ σ-meas ≤ +5%	23.8	151	+1.82	not required.	February 22-23, 2016 before SAR test (*1)
2417		39.26	38.10	-3.0		1.771	1.817	+2.6		+1.95	not required.			
2427		39.24	38.08	-3.0		1.780	1.834	+3.1		+2.16	not required.			
2437		39.22	38.01	-3.1		1.788	1.843	+3.1		+2.18	not required.			
2462		39.18	37.96	-3.1		1.813	1.877	+3.5		+2.39	not required.			

*1. It was within 24 hours from measurement on February 22, so measured parameters on February 22 were used on February 23.

*a. The target value is a parameter defined in Appendix A of KDB865664 D01 (v01r04), the dielectric parameters suggested for head and body tissue simulating liquid are given at 2000, 2450, 3000 and 5800MHz. (*The parameters of the head liquid are the same value as IEC 62209-2.) Parameters for the frequencies between 2000-3000, 3000-5800MHz were obtained using linear interpolation. Above 5800MHz were obtained using linear extrapolation.

*b. Refer to KDB865664 D01 (v01r04), item 4), Clause 2.6; "When nominal tissue dielectric parameters are recorded in the probe calibration data; for example, only target values and tolerance are reported, the measured εr and σ of the liquid used in routine measurements must be: ≤ the target εr and ≥ the target σ values and also within 5% of the required target dielectric parameters."

*c. Calculating formula: $ASAR(1g) = C_{\epsilon r} \times \Delta \epsilon r + C_{\sigma} \times \Delta \sigma$, $C_{\epsilon r} = 7.854E-4 \times f^3 + 9.402E-3 \times f^2 - 2.742E-2 \times f + 0.2026$ / $C_{\sigma} = 9.804E-3 \times f^3 - 8.661E-2 \times f^2 + 2.981E-2 \times f + 0.7829$

7.2 SAR measurement results (Body)

[Measured and Reported (Scaled) SAR results]

Mode	Freq. [MHz] (Channel)	Data rate [Mbps]	SAR measurement results						Reported SAR [W/kg]					Remarks (* Interpolated max.SAR in area scan result.)						
			EUT setup (*1)			SAR [W/kg]			Duty cycle correction		Output average power correction				SAR Corrected (Scaled) (*b)					
			Antenna *SAR measured	Position	Gap [mm]	Bty. ID	Max. value of multi-peak		SAR plot # in Appendix 2-2	Duty [%]	Duty scaled	Meas. [dBm]	Max. [dBm]			Tune-up factor				
ant#0	ant#1	Front (Patient)	Short-side -ant#0	Long-side -ant#1	Meas.	ΔSAR [%]	ΔSAR corrected													
Step 1: 2.4GHz Band (Body)																				
11g	2417(2)	6	ant#0	Front (Patient)	0	#2	too small	+1.73	n/a (*a)	Plot 1-3	99.8	×1.00	18.57	19.5	×1.25	n/a	(*0.0115W/kg)			
	2417(2)				0	#2	not detected	+1.73	n/a (*a)	Plot 1-4	99.8	×1.00	17.63	19.5	×1.54	n/a	(*0W/kg)			
11g	2417(2)	6	ant#0	Short-side -ant#0	0	#2	0.129	+1.73	n/a (*a)	Plot 1-1	99.8	×1.00	18.57	19.5	×1.25	0.161	ant#0-worst,body,2.4GHz			
	2437(6)				0	#2	0.109	+2.32	n/a (*a)	Plot 1-5	99.8	×1.00	17.09	18.0	×1.38	0.150	-			
	2462(11)				0	#2	0.072	+2.22	n/a (*a)	Plot 1-6	99.8	×1.00	16.08	17.5	×1.39	0.100	-			
11b	2412(1)	1			0	#2	0.059	+1.82	n/a (*a)	Plot 1-7	99.8	×1.00	14.99	16.0	×1.26	0.074	-			
n40HT	2427(4)	MCS0			0	#2	0.052	+2.16	n/a (*a)	Plot 1-8	99.3	×1.01	14.19	16.0	×1.52	0.079	-			
11g	2417(2)	6	ant#1	Long-side -ant#1	0	#3	0.069	+1.73	n/a (*a)	Plot 1-2	99.8	×1.00	17.63	19.5	×1.54	0.106	ant#1-worst,body,2.4GHz			
	2437(6)				0	#3	0.057	+2.32	n/a (*a)	Plot 1-9	99.8	×1.00	17.25	18.0	×1.33	0.076	-			
	2462(11)				0	#3	0.037	+2.22	n/a (*a)	Plot 1-10	99.8	×1.00	15.87	17.5	×1.46	0.054	-			
11b	2412(1)	1			0	#3	0.036	+1.82	n/a (*a)	Plot 1-11	99.8	×1.00	15.20	16.0	×1.20	0.043	-			
n40HT	2427(4)	MCS0			0	#3	0.030	+2.16	n/a (*a)	Plot 1-12	99.3	×1.01	14.34	16.0	×1.47	0.044	-			
Step 2: 5GHz Band (Body)																				
11a	5300(60)	6	ant#0	Front (Patient)	0	#3	not detected	+0.42	n/a (*a)	Plot 2-3	99.7	×1.00	13.88	15.0	×1.29	n/a	(*0.00834W/kg)			
	5580(118)				0	#3	not detected	+0.42	n/a (*a)	Plot 2-4	99.7	×1.00	16.38	17.5	×1.29	n/a	(*0.00218W/kg)			
	5825(165)				0	#3	too small	+0.37	n/a (*a)	Plot 2-5	99.7	×1.00	16.05	17.5	×1.40	n/a	(*0.0473W/kg)			
	5300(60)		ant#1	Short-side -ant#0	0	#3	not detected	+0.42	n/a (*a)	Plot 2-6	99.7	×1.00	13.56	15.0	×1.39	n/a	(*0.00117W/kg)			
	5580(116)				0	#3	not detected	+0.42	n/a (*a)	Plot 2-7	99.7	×1.00	16.14	17.5	×1.37	n/a	(*0.00162W/kg)			
	5825(165)				0	#3	not detected	+0.37	n/a (*a)	Plot 2-8	99.7	×1.00	16.39	17.5	×1.29	n/a	(*0.0642W/kg)			
5180(36)	6	ant#0	Short-side -ant#0	0	#2	0.103	+0.44	n/a (*a)	Plot 2-9	99.7	×1.00	13.70	15.0	×1.35	0.139	ant#0-worst,body,w52/53				
5260(52)				0	#2	0.078	+0.44	n/a (*a)	Plot 2-10	99.7	×1.00	13.67	15.0	×1.36	0.106	-				
5300(60)				0	#2	0.068	+0.42	n/a (*a)	Plot 2-11	99.7	×1.00	13.94	15.0	×1.28	0.087	-				
5320(64)				0	#2	0.071	+0.42	n/a (*a)	Plot 2-12	99.7	×1.00	13.88	15.0	×1.29	0.092	-				
5500(100)				0	#3	0.129	+0.43	n/a (*a)	Plot 2-1	99.7	×1.00	15.99	17.5	×1.42	0.183	ant#0-worst,body,w56				
5580(116)				0	#3	0.051	+0.42	n/a (*a)	Plot 2-13	99.7	×1.00	16.39	17.5	×1.29	0.066	-				
5600(120)				0	#3	0.037	+0.41	n/a (*a)	Plot 2-14	99.7	×1.00	16.38	17.5	×1.29	0.048	-				
5700(140)				0	#3	0.041	+0.36	n/a (*a)	Plot 2-15	99.7	×1.00	15.95	17.5	×1.43	0.059	-				
5745(149)				0	#3	0.067	+0.40	n/a (*a)	Plot 2-16	99.7	×1.00	15.95	17.5	×1.43	0.096	-				
5785(157)				0	#3	0.081	+0.37	n/a (*a)	Plot 2-17	99.7	×1.00	15.93	17.5	×1.44	0.117	ant#0-worst,body,w58				
5825(165)				0	#3	0.058	+0.37	n/a (*a)	Plot 2-18	99.7	×1.00	16.05	17.5	×1.40	0.081	-				
11a				5180(36)	6	ant#1	Long-side -ant#1	0	#2	0.068	+0.44	n/a (*a)	Plot 2-19	99.7	×1.00	13.50	15.0	×1.41	0.096	ant#0-worst,body,w52/53
				5260(52)				0	#2	0.039	+0.44	n/a (*a)	Plot 2-20	99.7	×1.00	13.55	15.0	×1.40	0.055	-
				5300(60)				0	#2	0.040	+0.42	n/a (*a)	Plot 2-21	99.7	×1.00	13.56	15.0	×1.39	0.056	-
	5320(64)	0	#2	0.042				+0.42	n/a (*a)	Plot 2-22	99.7	×1.00	13.84	15.0	×1.31	0.055	-			
	5500(100)	0	#2	0.117				+0.43	n/a (*a)	Plot 2-2	99.7	×1.00	16.18	17.5	×1.36	0.159	ant#1-worst,body,w56			
	5580(116)	0	#2	0.073				+0.42	n/a (*a)	Plot 2-23	99.7	×1.00	16.14	17.5	×1.37	0.100	-			
	5600(120)	0	#2	0.069				+0.41	n/a (*a)	Plot 2-24	99.7	×1.00	16.13	17.5	×1.37	0.095	-			
	5700(140)	0	#2	0.092				+0.36	n/a (*a)	Plot 2-25	99.7	×1.00	15.80	17.5	×1.48	0.136	-			
	5745(149)	0	#2	0.106				+0.40	n/a (*a)	Plot 2-26	99.7	×1.00	15.91	17.5	×1.44	0.153	ant#1-worst,body,w58			
	5785(157)	0	#2	0.100				+0.37	n/a (*a)	Plot 2-27	99.7	×1.00	15.99	17.5	×1.42	0.142	-			
5825(165)	0	#2	0.112	+0.37	n/a (*a)	Plot 2-28	99.7	×1.00	16.39	17.5	×1.29	0.144	-							

*1. Since this EUT is the medical device, the EUT is only used under the guidance of a doctor or a qualified person. The possibility of the maximum RF human exposure is only a body/head of the patient who comes in contact directly on the front surface (patient side) of the EUT. Therefore, the SAR test was only considered to the front surface of the EUT. However, SAR value couldn't be measured at the front surface, so SAR was evaluated on the side edge.

Notes: * Gap: It is the separation distance between the platform outer surface and the bottom outer surface of phantom; Freq.: Frequency; Bty.ID: Battery ID (Battery #2 and #3 were same model. Refer to Appendix 1 for more detail); Max.: Maximum; Meas.: Measured value; n/a: not applied.
* Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency	Probe calibration frequency	Validity	Conversion factor	Uncertainty
2412, 2417, 2427, 2437, 2462 MHz	2450 MHz	within ±50MHz of calibration frequency	7.17	±12.0%
5180, 5260, 5300, 5320 MHz	5250 MHz	within ±110 MHz of calibration frequency	4.53	±13.1 %
5500, 5580, 5600, 5700 MHz	5600 MHz	within ±110 MHz of calibration frequency	3.78	±13.1 %
5745, 5785, 5825 MHz	5750 MHz	within ±110 MHz of calibration frequency	4.06	±13.1 %

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

*a. Since the calculated ΔSAR values of the tested liquid had shown positive correction, the measured SAR was not converted by ΔSAR correction.

Calculating formula: ΔSAR corrected SAR (W/kg) = (Meas. SAR (W/kg)) × (100 - (ΔSAR(%))) / 100

*b. Calculating formula: Reported SAR (W/kg) = (Measured SAR (W/kg)) × (Duty scaled) × (Tune-up factor)
Duty scaled = Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = 100% / (duty cycle, %)
Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = 1 / (10 ^ ("Deviation from max., dB" / 10))

7.3 SAR measurement results (Head)

[Measured and Reported (Scaled) SAR results]

Mode	Freq. [MHz] (Channel)	Data rate [Mbps]	SAR measurement results						Reported SAR [W/kg]					Remarks (* Interpolated max.SAR in area scan result.)							
			EUT setup (*1)			SAR [W/kg]			Duty cycle correction		Output average power correction				SAR Corrected (Scaled) (*b)						
			Antenna *SAR measured	Position	Gap [mm]	Bty. ID	Max. value of multi-peak		SAR plot # in Appendix 2-2	Duty [%]	Duty scaled	Meas. [dBm]	Max. [dBm]			Tune-up factor					
				Meas.	ΔSAR [%]	ΔSAR corrected															
Step 3: 2.4GHz Band (Head)																					
11g	2417(2)	6	ant#0	Front (Patient)	0	#3	too small	+1.95	n/a (*a)	Plot 3-3	99.8	×1.00	18.57	19.5	×1.25	n/a	(*0.0152W/kg)				
	2417(2)		ant#1		0	#3	not detected	+1.95	n/a (*a)	Plot 3-4	99.8	×1.00	17.63	19.5	×1.54	n/a	(*0.000789W/kg)				
11g	2417(2)	6	ant#0	Short-side -ant#0	0	#3	0.145	+1.95	n/a (*a)	Plot 3-1	99.8	×1.00	18.57	19.5	×1.25	0.181	ant#0-worst,head,2.4GHz				
	2437(6)				0	#3	0.113	+2.18	n/a (*a)	Plot 3-5	99.8	×1.00	17.09	18.0	×1.38	0.156	-				
	2462(11)				0	#3	0.080	+2.39	n/a (*a)	Plot 3-6	99.8	×1.00	16.08	17.5	×1.39	0.111	-				
11b	2412(1)	1			0	#3	0.064	+1.82	n/a (*a)	Plot 3-7	99.8	×1.00	14.99	16.0	×1.26	0.081	-				
n40HT	2427(4)	MCS0			0	#2	0.056	+2.16	n/a (*a)	Plot 3-8	99.3	×1.01	14.19	16.0	×1.52	0.085	-				
11g	2417(2)	6	ant#1	Long-side -ant#1	0	#2	0.071	+1.95	n/a (*a)	Plot 3-2	99.8	×1.00	17.63	19.5	×1.54	0.109	ant#1-worst,head,2.4GHz				
	2437(6)				0	#2	0.058	+2.18	n/a (*a)	Plot 3-9	99.8	×1.00	17.25	18.0	×1.33	0.077	-				
	2462(11)				0	#2	0.037	+2.39	n/a (*a)	Plot 3-10	99.8	×1.00	15.87	17.5	×1.46	0.054	-				
11b	2412(1)	1			0	#2	0.037	+1.82	n/a (*a)	Plot 3-11	99.8	×1.00	15.20	16.0	×1.20	0.044	-				
n40HT	2427(4)	MCS0			0	#2	0.029	+2.16	n/a (*a)	Plot 3-12	99.3	×1.01	14.34	16.0	×1.47	0.043	-				
Step body-4: 5GHz Band (Head)																					
11a	5300(60)	6	ant#0	Front (Patient)	0	#3	not detected	+0.20	n/a (*a)	Plot 4-3	99.7	×1.00	13.88	15.0	×1.29	n/a	(*0.000645W/kg)				
	5580(118)				0	#3	too small	+0.31	n/a (*a)	Plot 4-4	99.7	×1.00	16.38	17.5	×1.29	n/a	(*0.0131W/kg)				
	5825(165)				0	#3	too small	+0.31	n/a (*a)	Plot 4-5	99.7	×1.00	16.05	17.5	×1.40	n/a	(*0.0554W/kg)				
	5300(60)		ant#1	Short-side -ant#0	0	#3	not detected	+0.20	n/a (*a)	Plot 4-6	99.7	×1.00	13.56	15.0	×1.39	n/a	(*0.000862W/kg)				
	5580(116)				0	#3	too small	+0.31	n/a (*a)	Plot 4-7	99.7	×1.00	16.14	17.5	×1.37	n/a	(*0.0174W/kg)				
	5825(165)				0	#3	too small	+0.31	n/a (*a)	Plot 4-8	99.7	×1.00	16.39	17.5	×1.29	n/a	(*0.0215W/kg)				
11a	5180(36)	6	ant#0	Short-side -ant#0	0	#2	0.113	+0.21	n/a (*a)	Plot 4-9	99.7	×1.00	13.70	15.0	×1.35	0.153	ant#0-worst,body,w52/53				
	5260(52)				0	#2	0.083	+0.22	n/a (*a)	Plot 4-10	99.7	×1.00	13.67	15.0	×1.36	0.113	-				
	5300(60)				0	#2	0.074	+0.20	n/a (*a)	Plot 4-11	99.7	×1.00	13.94	15.0	×1.28	0.095	-				
	5320(64)				0	#2	0.077	+0.23	n/a (*a)	Plot 4-12	99.7	×1.00	13.88	15.0	×1.29	0.099	-				
	5500(100)				0	#3	0.135	+0.27	n/a (*a)	Plot 4-1	99.7	×1.00	15.99	17.5	×1.42	0.192	ant#0-worst,body,w56				
	5580(116)				0	#3	0.051	+0.31	n/a (*a)	Plot 4-13	99.7	×1.00	16.39	17.5	×1.29	0.066	-				
	5600(120)				0	#3	0.039	+0.29	n/a (*a)	Plot 4-14	99.7	×1.00	16.38	17.5	×1.29	0.050	-				
	5700(140)				0	#3	0.046	+0.33	n/a (*a)	Plot 4-15	99.7	×1.00	15.95	17.5	×1.43	0.066	-				
	5745(149)				0	#3	0.075	+0.32	n/a (*a)	Plot 4-16	99.7	×1.00	15.95	17.5	×1.43	0.107	-				
	5785(157)				0	#3	0.098	+0.30	n/a (*a)	Plot 4-17	99.7	×1.00	15.93	17.5	×1.44	0.141	ant#0-worst,body,w58				
	5825(165)				0	#3	0.064	+0.31	n/a (*a)	Plot 4-18	99.7	×1.00	16.05	17.5	×1.40	0.090	-				
	11a				5180(36)	6	ant#1	Long-side -ant#1	0	#2	0.083	+0.21	n/a (*a)	Plot 4-19	99.7	×1.00	13.55	15.0	×1.40	0.117	ant#1-worst,body,w52/53
					5260(52)				0	#2	0.046	+0.22	n/a (*a)	Plot 4-20	99.7	×1.00	13.50	15.0	×1.41	0.064	-
					5300(60)				0	#2	0.048	+0.20	n/a (*a)	Plot 4-21	99.7	×1.00	13.56	15.0	×1.39	0.067	-
5320(64)		0	#2	0.050	+0.23				n/a (*a)	Plot 4-22	99.7	×1.00	13.84	15.0	×1.31	0.066	-				
5500(100)		0	#2	0.135	+0.27				n/a (*a)	Plot 4-2	99.7	×1.00	16.18	17.5	×1.36	0.184	ant#1-worst,body,w56				
5580(116)		0	#2	0.086	+0.31				n/a (*a)	Plot 4-23	99.7	×1.00	16.14	17.5	×1.37	0.118	-				
5600(120)		0	#2	0.078	+0.29				n/a (*a)	Plot 4-24	99.7	×1.00	16.13	17.5	×1.37	0.107	-				
5700(140)		0	#2	0.093	+0.33				n/a (*a)	Plot 4-25	99.7	×1.00	15.80	17.5	×1.48	0.138	-				
5745(149)		0	#2	0.118	+0.32				n/a (*a)	Plot 4-26	99.7	×1.00	15.91	17.5	×1.44	0.170	ant#1-worst,body,w58				
5785(157)		0	#2	0.118	+0.30				n/a (*a)	Plot 4-27	99.7	×1.00	15.99	17.5	×1.42	0.168	-				
n40HT	5270(54)	MCS0			0	#2	0.028	+0.24	n/a (*a)	Plot 2-29	99.3	×1.01	12.16	13.5	×1.36	0.038	-				
	5550(110)		0	#2	0.025	+0.31	n/a (*a)	Plot 2-30	99.3	×1.01	12.22	13.5	×1.34	0.034	-						
	5795(159)		0	#2	0.043	+0.28	n/a (*a)	Plot 2-31	99.3	×1.01	12.21	13.5	×1.35	0.058	-						

*1. Since this EUT is the medical device, the EUT is only used under the guidance of a doctor or a qualified person. The possibility of the maximum RF human exposure is only a body/head of the patient who comes in contact directly on the front surface (patient side) of the EUT. Therefore, the SAR test was only considered to the front surface of the EUT. However, SAR value couldn't be measured at the front surface, so SAR was evaluated on the side edge.

Notes: * Gap: It is the separation distance between the platform outer surface and the bottom outer surface of phantom; Freq.: Frequency; Bty.ID: Battery ID (Battery #2 and #3 were same model. Refer to Appendix 1 for more detail); Max.: Maximum, Meas.: Measured value; n/a: not applied.
* Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency	Probe calibration frequency	Validity	Conversion factor	Uncertainty
2412, 2417, 2427, 2437, 2462 MHz	2450 MHz	within ±50MHz of calibration frequency	7	±12.0%
5180, 5260, 5270, 5300, 5320 MHz	5250 MHz	within ±110 MHz of calibration frequency	5.04	±13.1 %
5500, 5550, 5580, 5600, 5700 MHz	5600 MHz	within ±110 MHz of calibration frequency	4.61	±13.1 %
5745, 5785, 5795, 5825 MHz	5750 MHz	within ±110 MHz of calibration frequency	4.66	±13.1 %

* The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

*a. Since the calculated ΔSAR values of the tested liquid had shown positive correction, the measured SAR was not converted by ΔSAR correction.

Calculating formula: ΔSAR corrected SAR (W/kg) = (Meas. SAR (W/kg)) × (100 - (ΔSAR(%))) / 100

*b. Calculating formula: Reported SAR (W/kg) = (Measured SAR (W/kg)) × (Duty scaled) × (Tune-up factor)

Duty scaled = Duty scaled factor: Duty cycle correction factor for obtained SAR value, Duty scaled factor [-] = 100% / (duty cycle, %)

Tune-up factor: Power tune-up factor for obtained SAR value, Tune-up factor [-] = 1 / (10 ^ ("Deviation from max., dB" / 10))

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400 / Facsimile: +81 463 50 6401